
**Connections for fluid power and
general use — Ports and stud ends
with ISO 261 metric threads and
O-ring sealing —**

Part 4:

**Dimensions, design, test methods and
requirements for external hex and
internal hex port plugs**

ISO 6149-4:2017
https://standards.iteh.ai/catalog/standards/sist/c4e11a05-d9bb-48a9-8040-79cdaceab1/iso-6149-4-2017
*Raccordements pour transmissions hydrauliques et applications
générales — Orifaces et éléments mâles à filetage métrique ISO 261 et
joint torique —*

*Partie 4: Dimensions, conception, méthodes d'essai et exigences des
bouchons d'orifice à six pans externes et à six pans internes*



iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 6149-4:2017

<https://standards.iteh.ai/catalog/standards/sist/c4e1fa05-d9bb-48a9-8040-e279cdaceab1/iso-6149-4-2017>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

	Page
Foreword.....	iv
Introduction.....	v
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	2
4 Dimensions.....	2
4.1 Plug dimensions.....	2
4.2 Hex tolerances.....	2
4.3 Screw threads.....	2
5 Requirements.....	2
5.1 Working pressures and working temperatures.....	2
5.2 Performance.....	3
6 O-rings.....	3
7 Test methods.....	3
8 Designation of port plugs.....	3
9 Identification.....	3
10 Manufacture.....	4
10.1 Construction.....	4
10.2 Workmanship.....	4
10.3 Finish.....	4
11 Procurement information.....	4
ISO 6149-4:2017	
12 Marking.....	4
https://standards.iteh.ai/catalog/standards/sist/c4e1fa05-d9bb-48a9-8040-e279cdaceab1/iso-6149-4-2017	
13 Identification statement (reference to this document).....	4
Bibliography.....	10

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html. (standards.iteh.ai)

This document was prepared by ISO/TC 131, *Fluid power systems, SC 4, Connectors and similar products and components*.

<https://standards.iteh.ai/catalog/standards/sist/c4e1fa05-d9bb-48a9-8040-739f18e0d701/iso-6149-4-2017>

This second edition cancels and replaces the first edition (ISO 6149-4:2006), of which it constitutes a minor revision.

The main change since last version is the addition of a warning statement about the hazards of intermixing of stud ends with the various port types.

Introduction

In fluid power systems, power is transmitted and controlled through a fluid (liquid or gas) under pressure within an enclosed circuit. In general applications, a fluid can be conveyed under pressure.

Components are connected through their threaded ports by stud ends on fluid conductor connectors to tubes and pipes or to hose fittings and hoses. Fluid ports are closed by inserting a plug in the port.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 6149-4:2017](https://standards.iteh.ai/catalog/standards/sist/c4e1fa05-d9bb-48a9-8040-e279cdaceab1/iso-6149-4-2017)

<https://standards.iteh.ai/catalog/standards/sist/c4e1fa05-d9bb-48a9-8040-e279cdaceab1/iso-6149-4-2017>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 6149-4:2017

<https://standards.iteh.ai/catalog/standards/sist/c4e1fa05-d9bb-48a9-8040-e279cdaceab1/iso-6149-4-2017>

Connections for fluid power and general use — Ports and stud ends with ISO 261 metric threads and O-ring sealing —

Part 4:

Dimensions, design, test methods and requirements for external hex and internal hex port plugs

1 Scope

This document specifies dimensions and performance requirements for external hex and internal hex port plugs for use with ISO 6149-1 ports.

Port plugs in accordance with this document can be used at working pressures up to 63 MPa (630 bar¹). The permissible working pressure depends upon the plug end size, materials, design, working conditions, application, etc.

Conformance to the dimensional information in this document does not guarantee rated performance. Each manufacturer is expected to perform testing according to the specification contained in this document to assure that components comply with the performance ratings.

WARNING — The use of stud ends conforming to this document with ports conforming to the relevant parts of ISO 1179, ISO 9974 and ISO 11926 could lead to a hazardous situation.

<https://standards.iteh.ai/catalog/standards/sist/c4e1fa05-d9bb-48a9-8040-e279cdaceab1/iso-6149-4-2017>

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 48, *Rubber, vulcanized or thermoplastic — Determination of hardness (hardness between 10 IRHD and 100 IHRD)*

ISO 261:1998, *ISO general purpose metric screw threads — General plan*

ISO 1629, *Rubber and latices — Nomenclature*

ISO 3601-3:2005, *Fluid power systems — O-rings — Part 3: Quality acceptance criteria*

ISO 4042, *Fasteners — Electroplated coatings*

ISO 4759-1:2000, *Tolerances for fasteners — Part 1: Bolts, screws, studs and nuts — Product grades A, B and C*

ISO 5598, *Fluid power systems and components — Vocabulary*

ISO 6149-1, *Connections for hydraulic fluid power and general use — Ports and stud ends with ISO 261 metric threads and O-ring sealing — Part 1: Ports with truncated housing for O-ring seal*

ISO 6149-2, *Connections for hydraulic fluid power and general use — Ports and stud ends with ISO 261 metric threads and O-ring sealing — Part 2: Dimensions, design, test methods and requirements for heavy-duty (S series) stud ends*

1) 1 bar = 0,1 MPa = 10⁵ Pa; 1 MPa = 1 N/mm².

ISO 7789, *Hydraulic fluid power — Two-, three- and four-port screw-in cartridge valves — Cavities*

ISO 9227, *Corrosion tests in artificial atmospheres — Salt spray tests*

ISO 10683, *Fasteners — Non-electrolytically applied zinc flake coatings*

ISO 19879, *Metallic tube connections for fluid power and general use — Test methods for hydraulic fluid power connections*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 5598 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— IEC Electropedia: available at <http://www.electropedia.org/>

— ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1 plug

stud end with no through hole for fluid passage, used to contain hydraulic fluid

4 Dimensions

4.1 Plug dimensions

iTeh STANDARD PREVIEW
(standards.iteh.ai)

External hex and internal hex plugs shall conform to the dimensions shown in [Figures 1](#) and [2](#) and given in [Tables 1](#) and [2](#), respectively.

ISO 6149-4:2017

<https://standards.iteh.ai/catalog/standards/sist/c4e1fa05-d9bb-48a9-8040-e279cdaceab1/iso-6149-4-2017>

4.2 Hex tolerances

External hex tolerances across flats shall be in accordance with ISO 4759-1:2000, product grade C. Minimum across corner dimensions are 1,092 times the nominal width across flats. The minimum side flat is 0,43 times the nominal width across flats. Internal hex tolerances across flats shall be in accordance with ISO 4759-1:2000, product grade A. External hex corners shall be chamfered 10 ° to 30 ° to a diameter equal to the width across flats, with a tolerance of $-\frac{0}{4}$ mm.

4.3 Screw threads

The screw threads on the plug shall be metric screw threads conforming to ISO 261:1998, class 6g.

5 Requirements

5.1 Working pressures and working temperatures

External hex and internal hex plugs conforming to this document shall be suitable for use at the working pressures given in [Table 3](#) when used at temperatures between -40 °C and $+120$ °C. For use at pressures and/or temperatures outside of this range, the manufacturer shall be consulted.

Plugs conforming to this document may contain elastomeric seals. Unless otherwise specified, plugs are made and delivered with elastomeric seals for use within the specified working temperature range with petroleum-based hydraulic fluids. The use of these plugs and elastomeric seals with other hydraulic fluids can result in a reduced working temperature range or can render the plugs unsuitable for the application. Manufacturers may supply, upon request, plugs with elastomeric seals for use with hydraulic fluids other than petroleum-based hydraulic fluids that meet the specified working temperature range of the plugs.

5.2 Performance

External hex and internal hex plugs conforming to this document shall meet the burst and impulse pressures given in [Table 3](#), and shall be capable of withstanding a vacuum of 6,5 kPa (0,065 bar) absolute pressure when tested in accordance with [Clause 7](#).

6 O-rings

Unless otherwise specified, for use at the pressure and temperature requirements in [5.1](#) and [Table 3](#) and for testing, the O-rings shall

- be made of NBR (nitrile) with a hardness of (90 ± 5) IRHD, measured in accordance with ISO 48,
- conform to the dimensions shown in [Figure 3](#) and given in [Table 4](#), and
- meet or exceed the O-ring quality acceptance criteria for grade N of ISO 3601-3:2005. Tolerances on O-ring dimensions shall be in accordance with ISO 6149-2.

7 Test methods

Port plug tests shall be conducted in accordance with ISO 19879 for burst, cyclic endurance (impulse) and vacuum. The qualification test torques given in [Table 5](#) shall be used in testing. Test results shall be reported on the test data form in ISO 19879.

8 Designation of port plugs

Port plugs shall be designated by an alphanumeric code to facilitate ordering. They shall be designated by the word “Plug”, then a space, followed by ISO 6149-4, then a hyphen, followed by the shape code PLEH for external hex or PLIH for internal hex, followed by a hyphen, followed by the plug size, followed by the O-ring code NBR for plugs delivered with an O-ring that conforms to the requirements of [Clause 6](#). If desired, the code may be supplemented by a hyphen followed by the plating code in accordance with ISO 4042 or ISO 10683, followed by hyphen, followed by the O-ring material code in accordance with ISO 1629.

EXAMPLE 1 Plug with an external hex for an ISO 6149-1 port size M12 × 1,5 shall be designated as follows:

Plug ISO 6149-4-PLEH-M12

EXAMPLE 2 Plug with an external hex for an ISO 6149-1 port size M12 × 1,5, ordered assembled with an O-ring that conforms to the requirements of [Clause 6](#) shall be designated as follows:

Plug ISO 6149-4-PLEH-M12-NBR

EXAMPLE 3 Plug with an external hex for an ISO 6149-1 port size M12 × 1,5, ordered assembled with an O-ring that conforms to the requirements of [Clause 6](#) but made of FKM instead of NBR shall be designated as follows:

Plug ISO 6149-4-PLEH-M12-FKM

EXAMPLE 4 Plug with an external hex for an ISO 6149-1 port size M12 × 1,5, ordered galvanized zinc coated in accordance with ISO 4042 and assembled with an O-ring that conforms to the requirements of [Clause 6](#) but made of FKM instead of NBR shall be designated as follows:

Plug ISO 6149-4-PLEH-M12-A3C-FKM

9 Identification

External hex plugs shall be identified in accordance with the identification required for non-adjustable stud ends in ISO 6149-2. Internal hex plugs shall be identified as shown in [Figure 2](#).