

# INTERNATIONAL STANDARD

## NORME INTERNATIONALE



**Global maritime distress and safety system (GMDSS) –  
Part 12: Survival craft portable two-way VHF radiotelephone apparatus –  
Operational and performance requirements, methods of testing and required test  
results**

Document Preview

**Système mondial de détresse et de sécurité en mer (SMDSM) –  
Partie 12: Radiotéléphone émetteur-récepteur portable VHF pour embarcation de  
sauvetage – Exigences d'exploitation et de fonctionnement, méthodes d'essai et  
résultats d'essai exigés**



## THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2017 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
Fax: +41 22 919 03 00  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

#### IEC Catalogue - [webstore.iec.ch/catalogue](http://webstore.iec.ch/catalogue)

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

#### IEC publications search - [www.iec.ch/searchpub](http://www.iec.ch/searchpub)

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

#### IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

#### Electropedia - [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

#### IEC Glossary - [std.iec.ch/glossary](http://std.iec.ch/glossary)

65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

#### IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [csc@iec.ch](mailto:csc@iec.ch).

### A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

### A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

#### Catalogue IEC - [webstore.iec.ch/catalogue](http://webstore.iec.ch/catalogue)

Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

#### Recherche de publications IEC - [www.iec.ch/searchpub](http://www.iec.ch/searchpub)

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

#### IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

#### Electropedia - [www.electropedia.org](http://www.electropedia.org)

Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 16 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

#### Glossaire IEC - [std.iec.ch/glossary](http://std.iec.ch/glossary)

65 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

#### Service Clients - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: [csc@iec.ch](mailto:csc@iec.ch).

# INTERNATIONAL STANDARD

# NORME INTERNATIONALE



**Global maritime distress and safety system (GMDSS) –  
Part 12: Survival craft portable two-way VHF radiotelephone apparatus –  
Operational and performance requirements, methods of testing and required  
test results**

**Système mondial de détresse et de sécurité en mer (SMDSM) –  
Partie 12: Radiotéléphone émetteur-récepteur portable VHF pour embarcation  
de sauvetage – Exigences d'exploitation et de fonctionnement, méthodes  
d'essai et résultats d'essai exigés**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

COMMISSION  
ELECTROTECHNIQUE  
INTERNATIONALE

ICS 33.060.20, 47.020.70

ISBN 978-2-8322-4606-1

**Warning! Make sure that you obtained this publication from an authorized distributor.  
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**



# REDLINE VERSION

## VERSION REDLINE



**Global maritime distress and safety system (GMDSS) –  
Part 12: Survival craft portable two-way VHF radiotelephone apparatus –  
Operational and performance requirements, methods of testing and required test  
results**

Document Preview

**Système mondial de détresse et de sécurité en mer (SMDSM) –  
Partie 12: Radiotéléphone émetteur-récepteur portable VHF pour embarcation de  
sauvetage – Exigences d'exploitation et de fonctionnement, méthodes d'essai et  
résultats d'essai exigés**

## CONTENTS

FOREWORD.....	3
1 Scope.....	5
2 Normative references .....	5
3 Performance requirements .....	6
3.1 Introduction .....	6
3.2 General .....	6
3.3 General requirements.....	6
3.4 Environmental requirements.....	8
3.5 Electromagnetic compatibility .....	8
4 Technical characteristics .....	8
4.1 General .....	8
4.2 Class of emission and modulation characteristics .....	8
4.3 Transmitter.....	8
4.4 Receiver.....	9
5 Methods of testing and required test results .....	9
5.1 Test conditions.....	10
5.2 General conditions of measurement .....	12
5.3 (3.3.8) Power supply .....	14
5.4 Transmitter.....	14
5.5 Receiver.....	22
5.6 Battery charger .....	29
5.7 (3.5) Electromagnetic compatibility.....	29
Annex A (normative) Power measuring receiver specification .....	32
Annex B (normative) Simulated solar radiation source .....	34
Annex C (informative) Bibliography .....	35
Figure 1 – Transmitter permissible frequency deviation.....	29
Figure 2 – Storage oscilloscope view $t_1$ , $t_2$ and $t_3$ .....	30
Figure 3 – Test set-up for measuring transient frequency behaviour .....	31
Figure 4 – Receiver audiofrequency response .....	31
Figure A.1 – IF filter specification .....	32
Table 1 – Transmitter transient timing (ms).....	21
Table A.1 – Selectivity characteristic .....	32
Table A.2 – Attenuation points close to carrier.....	33
Table A.3 – Attenuation points distant from carrier.....	33
Table B.1 – Spectral energy distribution and permitted tolerances .....	34

INTERNATIONAL ELECTROTECHNICAL COMMISSION

---

**GLOBAL MARITIME DISTRESS AND SAFETY SYSTEM (GMDSS) –  
Part 12: Survival craft portable two-way VHF radiotelephone  
apparatus –  
Operational and performance requirements, methods of  
testing and required test results**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

**This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.**

**IEC 61097-12 edition 1.1 contains the first edition (1996-12) [documents 80/126/FDIS and 80/136/RVD] and its amendment 1 (2017-07) [documents 80/829/CDV and 80/843/RVC].**

**In this Redline version, a vertical line in the margin shows where the technical content is modified by amendment 1. Additions are in green text, deletions are in strikethrough red text. A separate Final version with all changes accepted is available in this publication.**

International Standard IEC 61097-12 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems.

Annexes A and B form an integral part of this standard.

Annex C is for information only.

The committee has decided that the contents of the base publication and its amendment will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

**IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.**

The contents of the corrigendum 1 (2023-11) have been included in this copy.

**iTeh Standards**  
**(<https://standards.iteh.ai>)**  
**Document Preview**

[IEC 61097-12:1996](#)

<https://standards.iteh.ai/catalog/standards/iec/075f5ddd-f09c-4512-bd08-a9291ccc5e22/iec-61097-12-1996>



**GLOBAL MARITIME DISTRESS AND SAFETY SYSTEM (GMDSS) –  
Part 12: Survival craft portable two-way VHF radiotelephone apparatus**  
–  
**Operational and performance requirements, methods of  
testing and required test results**

## 1 Scope

This part of IEC 61097 specifies the minimum performance requirements, technical characteristics and methods of testing with required test results of survival craft portable two-way radiotelephone apparatus as required by chapter III of the 1988 amendments to the 1974 International Convention for the Safety of Life at Sea (SOLAS), and which is associated with IEC 945. When a requirement in this standard is different from IEC 945, the requirement in this standard shall take precedence.

This standard incorporates the applicable parts of the performance requirements included in IMO Resolution ~~A.809(19) annex 1~~ MSC.149(77) and the technical characteristics included in ITU M.489-2 and ITU-R M.542-1, and takes account of the general requirements contained in IMO Resolution A.694(17), and conforms with the ITU Radio Regulations where applicable.

NOTE – All text of this standard, whose wording is identical to that in IMO Resolutions ~~A.809(19)~~ MSC.149(77) and A.694(17) and ITU-R M.489-2 is printed in italics and the Resolution/Recommendation and paragraph numbers are indicated in brackets.

## 2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this part of IEC 61097. At the time of publication, the editions indicated were valid. All normative documents are subject to revision, and parties to agreements based on this part of IEC 61097 are encouraged to investigate the possibility of applying the most recent edition of the normative documents indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

IEC 529:1989, *Degrees of protection provided by enclosures (IP code)*

IEC 945:1994, *Marine navigational equipment – General requirements – Methods of testing and required test results*

IMO International Convention for the Safety of Life At Sea (SOLAS):1974, as amended 1988 (GMDSS) – *Chapter III: Life-saving appliances and arrangements*

IMO Resolution A.694(17):1991, *General requirements for shipborne radio equipment forming part of the global maritime distress and safety system (GMDSS) and for electronic navigational aids*

~~IMO Resolution A.809(19):1995, Performance standards for survival craft two-way VHF radiotelephone apparatus~~

IMO Resolution MSC.149(77):2003, *Revised performance standards for survival craft portable two-way VHF radiotelephone apparatus*

ITU Radio Regulations:1995, *Appendix S3: Table of maximum permitted spurious emissions power levels*

ITU Radio Regulations:1990, *Appendix 18: Table of transmitting frequencies in the band 156 – 174 MHz for stations in the maritime mobile service*

ITU-R M.489-2:1995, *Technical characteristics of radiotelephone equipment operating in the maritime mobile service in channels spaced by 25 kHz*

ITU-R M.542-1:1982, *On-board communications by means of portable radiotelephone equipment*

### 3 Performance requirements

#### 3.1 Introduction

Performance requirements described in this clause are specified by referring to IMO Resolutions and ITU Recommendations. In addition to meeting performance requirements in this clause, the equipment shall comply with the technical characteristics contained in clause 4 of this standard.

#### 3.2 General

**3.2.1** (~~A.809(19)-1~~ MSC.149(77)/2.1) *The equipment shall be portable and capable of being used for on-scene communication between survival craft, between survival craft and ship and between survival craft and rescue unit. It may also be used for on-board communications when capable of operating on appropriate frequencies.*

**3.2.2** (~~A.809(19)-1~~ MSC.149(77)/2.3) *The equipment shall:*

- 1) *be capable of being operated by unskilled personnel;*
- 2) *be capable of being operated by personnel wearing gloves as specified for immersion suits in regulation ~~33~~ 32 of chapter III of the SOLAS 1974 Convention;*
- 3) *be capable of single-handed operation except for channel selection;*
- 9) *be of small size and light weight;*
- 10) *be capable of operating in the ambient noise level likely to be encountered on board ships or survival craft;*
- 11) *have provisions for its attachment to the clothing of the user, ~~including the immersion suit~~ and also be provided with a wrist or neck strap. For safety reasons, the strap should include a suitable weak link to prevent the bearer from being ensnared; and*
- 12) *be resistant to deterioration by prolonged exposure to sunlight.*

**3.2.3** (~~A.809(19)-1~~ MSC.149(77)/2.3.13) *The equipment shall be either of a highly visible yellow/orange colour or marked with a surrounding yellow/orange marking strip.*

#### 3.3 General requirements

##### 3.3.1 Composition

(~~A.809(19)-1~~ MSC.149(77)/2.2) *The equipment shall comprise at least:*

- 1) *an integral transmitter/receiver including antenna and battery;*
- 2) *an integral control unit including a press-to-transmit switch;*
- 3) *an internal microphone and loudspeaker.*

##### 3.3.2 Controls and indicators

**3.3.2.1** (~~A.809(19)-1~~ MSC.149(77)/4.1) *An on/off switch shall be provided with positive visual indication that the radiotelephone is switched on.*

**3.3.2.2** (~~A.809(19)-1~~ MSC.149(77)/4.2) *The receiver shall be provided with a manual volume control by which the audio output may be varied.*

**3.3.2.3** (~~A.809(19)-1~~ MSC.149(77)/4.3) *A squelch (mute) control and channel selection switch shall be provided.*

**3.3.2.4** ~~(A.809(19) + MSC.149(77)/4.4)~~ *Channel selection shall be easily performed and the channels shall be clearly discernible.*

**3.3.2.5** ~~(A.809(19) + MSC.149(77)/4.5)~~ *Channel indication shall be in accordance with appendix 18 of the Radio Regulations.*

**3.3.2.6** ~~(A.809(19) + MSC.149(77)/4.6)~~ *It shall be possible to determine that channel 16 has been selected in all ambient light conditions.*

### **3.3.3 Antenna**

~~(A.809(19) + MSC.149(77)/9)~~ *The antenna shall be vertically polarized and, as far as practicable, be omnidirectional in the horizontal plane. The antenna shall be suitable for efficient radiation and reception of signals at the operating frequency.*

### **3.3.4 Safety precautions**

**3.3.4.1** ~~(A.809(19) + MSC.149(77)/6)~~ *The equipment shall not be damaged by the effect of open-circuiting or short-circuiting the antenna.*

**3.3.4.2** ~~(A.809(19) + MSC.149(77)/2.3.8)~~ *The equipment shall have no sharp projections which could damage survival craft.*

### **3.3.5 Frequency bands and channels**

**3.3.5.1** ~~(A.809(19) + MSC.149(77)/3.1)~~ **The two-way radiotelephone shall be capable of operation on the frequency 156,800 MHz (VHF CH 16) and on at least one additional channel.**

**3.3.5.2** ~~(A.809(19) + MSC.149(77)/3.2)~~ *All channels fitted shall be for single-frequency voice communication only.*

**3.3.5.3** ~~(A.809(19) + MSC.149(77)/3.3)~~ *The class of emission shall ~~be G3E to~~ comply with ~~appendix 19 of the Radio Regulations~~ Recommendation ITU-R M.489-2.*

### **3.3.6 Marking and identification**

~~(A.809(19) + MSC.149(77)/13)~~ *In addition to the items specified in resolution A.694(17) on general requirements, as detailed in IEC 945, the following shall be clearly indicated on the exterior of the equipment:*

- 1) *brief operating instructions;*
- 2) *expiry date for the primary batteries.*

### **3.3.7 Warming-up period**

~~(A.809(19) + MSC.149(77)/5)~~ *The equipment shall be operational within 5 s of switching on.*

### **3.3.8 Power supply**

**3.3.8.1** ~~(A.809(19) + MSC.149(77)/12.1)~~ *The source of energy shall be integrated in the equipment and may be replaceable by the user. In addition, provision may be made to operate the equipment using an external source of electrical energy.*

**3.3.8.2** ~~(A.809(19) + MSC.149(77)/12.2)~~ *Equipment intended for the source of energy to be user replaceable shall be provided with a dedicated primary battery for use in the event of a distress situation. This battery shall be equipped with a non-replaceable seal to indicate that it has not been used.*

**3.3.8.3** (~~A.809(19)~~ MSC.149(77)/12.3) *Equipment intended for the source of energy to be non-user-replaceable shall be provided with a primary battery. The portable two-way radiotelephone equipment shall be equipped with a non-replaceable seal to indicate that it has not been used.*

**3.3.8.4** (~~A.809(19)~~ MSC.149(77)/12.4) *The primary battery shall have sufficient capacity to ensure 8 h operation at its highest rated power with a duty cycle of 1: 9. The duty cycle is defined as 6 s transmission, 6 s reception above squelch opening level and 48 s reception below squelch opening level.*

**3.3.8.5** (~~A.809(19)~~ MSC.149(77)/12.5) *Primary batteries shall have a shelf life of at least 2 years and if intended to be user replaceable shall be of a colour or marking as defined in 3.2.3.*

**3.3.8.6** (~~A.809(19)~~ MSC.149(77)/12.6) *Primary or secondary batteries not intended for the use in the event of a distress situation shall be of a colour or marking so that they cannot be confused with batteries intended for such use.*

### **3.4 Environmental requirements**

**3.4.1** (~~A.809(19)~~ MSC.149(77)/11) *The equipment shall be so designed as to operate over the temperature range  $-20\text{ }^{\circ}\text{C}$  to  $+55\text{ }^{\circ}\text{C}$ . It shall not be damaged in stowage throughout the temperature range  $-30\text{ }^{\circ}\text{C}$  to  $+70\text{ }^{\circ}\text{C}$ .*

**3.4.2** (~~A.809(19)~~ MSC.149(77)/2.3.4) *The equipment shall withstand drops on to a hard surface from a height of 1 m.*

**3.4.3** (~~A.809(19)~~ MSC.149(77)/2.3.5) *The equipment shall be watertight to a depth of 1 m for at least 5 min.*

**3.4.4** (~~A.809(19)~~ MSC.149(77)/2.3.6) *The equipment shall maintain watertightness when subjected to a thermal shock of  $45\text{ }^{\circ}\text{C}$  under conditions of immersion.*

**3.4.5** (~~A.809(19)~~ MSC.149(77)/2.3.7) *The equipment shall not be unduly affected by seawater or oil or both.*

### **3.5 Electromagnetic compatibility**

The equipment shall comply with the EMC requirements specified in resolution A.694(17), as detailed in IEC 945.

## **4 Technical characteristics**

### **4.1 General**

The equipment shall be designed to operate satisfactorily with a channel separation of 25 kHz in accordance with appendix 18 of the Radio Regulations.

### **4.2 Class of emission and modulation characteristics**

**4.2.1** (M.489-2/1.1.1 and .3) *The class of emission shall be G3E (frequency modulation with a pre-emphasis characteristic of 6 dB/Octave).*

**4.2.2** (M.489-2/1.1.2) *The necessary bandwidth shall be 16 kHz.*

### **4.3 Transmitter**

**4.3.1** (M.489-2/1.2.1) *The frequency tolerance for ship station transmitters shall not exceed 10 parts in 10<sup>6</sup>. For practical reasons, the frequency error shall be within ±1,5 kHz.*

**4.3.2** (~~A.809(19)-1~~ MSC.149(77)/7) *The effective radiated power shall be a minimum of 0,25 W. Where the effective radiated power exceeds 1 W, a power reduction switch to reduce the power to 1 W or less is required. When this equipment provides for on-board communications, the output power shall not exceed 1 W on these frequencies.*

**4.3.3** *The frequency deviation corresponding to 100% modulation shall approach ±5 kHz as nearly as practicable.*

**4.3.4** (M.489-2/1.2.5) *The upper limit of the audiofrequency band shall not exceed 3 kHz.*

**4.3.5** (M.489-2/1.2.2) *Spurious emissions on discrete frequencies, when measured in a non-reactive load equal to the nominal output impedance of the transmitter shall be in accordance with the provisions of Appendix 8 of the Radio Regulations. The power of any conducted spurious emission on any discrete frequency shall not exceed 0,25 μW.*

**4.3.6** (M.489-2/1.2.6) *The cabinet radiated power shall not exceed 25 μW. In some radio environments, lower values may be required. The equipment shall meet the requirements of IEC 945 for radiated interference.*

#### **4.4 Receiver**

**4.4.1** (~~A.809(19)-1~~ MSC.149(77)/8.1) *The sensitivity of the receiver shall be equal to or better than 2 μV e.m.f. for a SINAD ratio of 12 dB at the output.*

**4.4.2** (~~A.809(19)-1~~ MSC.149(77)/8.2) *The immunity to interference of the receiver shall be such that the wanted signal is not seriously affected by unwanted signals.*

**4.4.3** (~~A.809(19)-1~~ MSC.149(77)/10.1) *The audio output shall be sufficient to be heard in the ambient noise level likely to be encountered on board ships or in a survival craft.*

**4.4.4** (~~A.809(19)-1~~ MSC.149(77)/10.2) *In the transmit condition the output of the receiver shall be muted.*

**4.4.5** (M.489-2/1.3.2) *The adjacent channel selectivity shall be at least 70 dB.*

**4.4.6** (M.489-2/1.3.3) *The spurious response rejection ratio shall be at least 70 dB.*

**4.4.7** (M.489-2/1.3.4) *The radio frequency intermodulation response ratio shall be at least 65 dB.*

**4.4.8** (M.489-2/1.3.5) *The power of any conducted spurious emission measured at the antenna terminals shall not exceed 2,0 nW at any discrete frequency.*

## **5 Methods of testing and required test results**

Environmental tests shall be carried out before tests to verify whether the equipment under test (EUT) meets all technical requirements. Where electrical tests are required, these shall be done using the normal test voltage as specified in IEC 945 unless otherwise stated.

In each test item indicated below, the related requirement can be identified by referring to the text with subclause number in brackets.

## 5.1 Test conditions

For field measurements and performance checks to this standard, the EUT shall be operational on channel 17.

### 5.1.1 Normal and extreme test conditions

Tests shall be made under normal test conditions and also, where stated, under extreme test conditions as specified in IEC 945, of dry heat and the upper limit of supply voltage applied simultaneously and low temperature and the lower limit of supply voltage applied simultaneously.

### 5.1.2 Test power source

During each test the EUT shall be supplied from a test power source, capable of producing normal and extreme test voltages. For the purpose of tests, the voltage of the power source shall be measured at the input terminals of the EUT. During tests, the power supply voltages shall be maintained within  $\pm 3$  % relative to the voltage level at the beginning of each test.

The test power source shall only be used in measurements where the use of the test power source is mutually agreed between manufacturer and test house. In the event of any discrepancy, results obtained using the batteries shall take precedence over results obtained using the test power source.

### 5.1.3 Procedure for tests at extreme temperatures

For tests at low temperature, the EUT shall be placed in the test chamber and left until thermal equilibrium is reached and shall then be switched to stand-by or receive position for 5 s after which the EUT shall meet the requirements of this standard.

### 5.1.4 Performance check

#### 5.1.4.1 Definition

The performance check means a shortened form of the test required by the relevant standard under normal test conditions, such as could normally be carried out in no more than 15 min.

#### 5.1.4.2 Method of measurement

After each environmental test a performance check shall be made, which shall include the following:

- the transmitter frequency error to 5.4.1.2 and the output power of the transmitter to 5.4.3.2 (high power only); and
- the receiver maximum usable sensitivity to 5.5.3.2.

#### 5.1.4.3 Results required

The frequency error shall be less than  $\pm 1,5$  kHz, the carrier power shall be not less than 0,25 W and the receiver sensitivity shall be better than 12 dB $\mu$ V.

### 5.1.5 Environmental tests

Environmental tests are intended to assess the suitability of the construction of the EUT for its intended physical conditions of use. After environmental tests, and, if specified also during the test, the EUT shall comply with the requirements of a performance check.

Environmental tests shall be carried out before any other tests. Where electrical tests are required, these shall be done with the normal test voltage unless otherwise stated.