

ETSI TS 136 101 V18.5.0 (2024-06)



**LTE;
Evolved Universal Terrestrial Radio Access (E-UTRA);
User Equipment (UE) radio transmission and reception
(3GPP TS 36.101 version 18.5.0 Release 18)**

[ETSI TS 136 101 V18.5.0 \(2024-06\)](https://standards.iteh.ai/catalog/standards/etsi/fb3351f8-3277-4e8c-97ac-a755df4cd2f1/etsi-ts-136-101-v18-5-0-2024-06)

<https://standards.iteh.ai/catalog/standards/etsi/fb3351f8-3277-4e8c-97ac-a755df4cd2f1/etsi-ts-136-101-v18-5-0-2024-06>



ReferenceRTS/TSGR-0436101v150

KeywordsLTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<https://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our

Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2024.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables. (2024-06)

The cross reference between 3GPP and ETSI identities can be found under <https://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	32
1 Scope	34
2 References	34
3 Definitions, symbols and abbreviations	35
3.1 Definitions	35
3.2 Symbols.....	37
3.3 Abbreviations	39
4 General	41
4.1 Relationship between minimum requirements and test requirements	41
4.2 Applicability of minimum requirements	41
4.3 Void.....	41
4.3A Applicability of feature-specific minimum requirements.....	41
4.4 RF requirements in later releases	43
5 Operating bands and channel arrangement.....	43
5.1 General	43
5.2 Void.....	43
5.3 Void.....	43
5.4 Void.....	43
5.5 Operating bands.....	43
5.5A Operating bands for CA	45
5.5B Operating bands for UL-MIMO	61
5.5C Operating bands for Dual Connectivity	61
5.5D Operating bands for ProSe.....	63
5.5E Operating bands for UE category 0, UE category M1 and M2 and UE category 1bis	64
5.5F Operating bands for category NB1 and NB2.....	64
5.5G Operating bands for V2X Communication.....	64
5.5H Operating bands for LTE based 5G terrestrial broadcast	65
5.5K Operating bands for Aerial UE.....	66
5.6 Channel bandwidth.....	66
5.6.1 Channel bandwidths per operating band.....	67
5.6A Channel bandwidth for CA.....	68
5.6A.1 Channel bandwidths per operating band for CA.....	71
5.6B Channel bandwidth for UL-MIMO	186
5.6B.1 Void	186
5.6C Channel bandwidth for Dual Connectivity	186
5.6C.1 Void	187
5.6D Channel bandwidth for ProSe.....	187
5.6D.1 Channel bandwidths per operating band for ProSe.....	187
5.6F Channel bandwidth for category NB1 and NB2.....	188
5.6G Channel bandwidth for V2X Communication.....	188
5.6G.1 Channel bandwidths per operating band for V2X Communication	188
5.6H PMCH bandwidth for LTE based 5G terrestrial broadcast.....	190
5.6H.1 PMCH bandwidths per operating band for LTE based 5G terrestrial broadcast.....	191
5.7 Channel arrangement.....	191
5.7.1 Channel spacing.....	191
5.7.1A Channel spacing for CA.....	191
5.7.1F Channel spacing for category NB1 and NB2.....	192
5.7.1H Channel spacing for LTE based 5G terrestrial broadcast.....	192
5.7.2 Channel raster	192
5.7.2A Channel raster for CA	192

5.7.2F	Channel raster for category NB1 and NB2	192
5.7.3	Carrier frequency and EARFCN.....	192
5.7.3F	Carrier frequency and EARFCN for category NB1 and NB2.....	194
5.7.3H	Carrier frequency and EARFCN for LTE based 5G terrestrial broadcast.....	194
5.7.4	TX–RX frequency separation	195
5.7.4A	TX–RX frequency separation for CA	196
5.7.4E	TX–RX frequency separation for category M1 and M2	196
5.7.4F	TX–RX frequency separation for category NB1 and NB2	196
6	Transmitter characteristics	196
6.1	General	196
6.2	Transmit power	196
6.2.1	Void	196
6.2.2	UE maximum output power	196
6.2.2A	UE maximum output power for CA.....	198
6.2.2B	UE maximum output power for UL-MIMO	201
6.2.2C	Void	203
6.2.2D	UE maximum output power for ProSe.....	203
6.2.2E	UE maximum output power for Category M1 and M2 UE.....	204
6.2.2F	UE maximum output power for category NB1 and NB2.....	205
6.2.2G	UE maximum output power for V2X Communication	205
6.2.2K	UE maximum output power for Aerial UE.....	207
6.2.3	UE maximum output power for modulation / channel bandwidth.....	207
6.2.3A	UE Maximum Output power for modulation / channel bandwidth for CA	208
6.2.3B	UE maximum output power for modulation / channel bandwidth for UL-MIMO	213
6.2.3D	UE maximum output power for modulation / channel bandwidth for ProSe.....	213
6.2.3E	UE maximum output power for modulation / channel bandwidth for category M1 and M2.....	214
6.2.3F	UE maximum output power for modulation / channel bandwidth for category NB1 and NB2	216
6.2.3G	UE maximum output power for modulation / channel bandwidth for V2X Communication	216
6.2.3G.1	MPR for Power class 3 V2X UE.....	216
6.2.3G.2	MPR for Power class 2 V2X UE.....	217
6.2.3K	UE maximum output power for modulation / channel bandwidth for Aerial UE	218
6.2.4	UE maximum output power with additional requirements	218
6.2.4A	UE maximum output power with additional requirements for CA	235
6.2.4A.1	A-MPR for CA_NS_01 for CA_1C	237
6.2.4A.2	A-MPR for CA_NS_02 for CA_1C	238
6.2.4A.3	A-MPR for CA_NS_03 for CA_1C	238
6.2.4A.4	A-MPR for CA_NS_04.....	239
6.2.4A.5	A-MPR for CA_NS_05 for CA_38C	241
6.2.4A.6	A-MPR for CA_NS_06.....	242
6.2.4A.7	A-MPR for CA_NS_07.....	243
6.2.4A.8	A-MPR for CA_NS_08.....	244
6.2.4A.9	Void.....	245
6.2.4A.10	A-MPR for CA_NS_10.....	245
6.2.4B	UE maximum output power with additional requirements for UL-MIMO.....	248
6.2.4D	UE maximum output power with additional requirements for ProSe.....	249
6.2.4E	UE maximum output power with additional requirements for category M1 and M2 UE.....	249
6.2.4F	UE maximum output power with additional requirements for category NB1 and NB2 UE.....	259
6.2.4G	UE maximum output power with additional requirements for V2X Communication	259
6.2.5	Configured transmitted power	261
6.2.5A	Configured transmitted power for CA	292
6.2.5B	Configured transmitted power for UL-MIMO.....	295
6.2.5C	Configured transmitted power for Dual Connectivity.....	296
6.2.5D	Configured transmitted power for ProSe	297
6.2.5F	Configured transmitted Power for category NB1 and NB2	299
6.2.5G	Configured transmitted power for V2X Communication	300
6.3	Output power dynamics.....	303
6.3.1	(Void).....	303
6.3.2	Minimum output power	303
6.3.2.1	Minimum requirement	303
6.3.2A	UE Minimum output power for CA.....	304
6.3.2A.1	Minimum requirement for CA	304

6.3.2B	UE Minimum output power for UL-MIMO	304
6.3.2B.1	Minimum requirement	304
6.3.2C	Void	305
6.3.2D	UE Minimum output power for ProSe.....	305
6.3.2F	UE Minimum output power for category NB1 and NB2.....	305
6.3.2G	UE Minimum output power for V2X Communication	305
6.3.3	Transmit OFF power.....	305
6.3.3.1.	Minimum requirement	306
6.3.3A	UE Transmit OFF power for CA	306
6.3.3A.1	Minimum requirement for CA	306
6.3.3B	UE Transmit OFF power for UL-MIMO	306
6.3.3B.1	Minimum requirement	306
6.3.3D	Transmit OFF power for ProSe.....	307
6.3.3F	Transmit OFF power for category NB1 and NB2.....	307
6.3.3G	Transmit OFF power for V2X Communication.....	307
6.3.4	ON/OFF time mask.....	308
6.3.4.1	General ON/OFF time mask	308
6.3.4.2	PRACH and SRS time mask	309
6.3.4.2.1	PRACH time mask	309
6.3.4.2.2	SRS time mask	310
6.3.4.3	Slot / Sub frame boundary time mask for subframe TTI.....	312
6.3.4.4	PUCCH / PUSCH / SRS time mask for subframe TTI	313
6.3.4.5	Symbol / Subslot boundary time mask for subslot TTI.....	315
6.3.4.6	Subslot PUCCH / subslot PUSCH / SRS time mask for subslot TTI.....	317
6.3.4.7	Symbol / Slot boundary time mask for slot TTI.....	320
6.3.4.8	Slot PUCCH / slot PUSCH / SRS time mask for slot TTI	320
6.3.4.9	Consecutive subslot and slot TTI or consecutive subslot and subframe TTI time mask.....	321
6.3.4.10	Consecutive subframe and subslot TTI or consecutive slot and subslot TTI time mask.....	321
6.3.4.11	Consecutive TTI and slot TTI or consecutive slot TTI and TTI time mask.....	322
6.3.4A	ON/OFF time mask for CA	322
6.3.4B	ON/OFF time mask for UL-MIMO	322
6.3.4D	ON/OFF time mask for ProSe.....	323
6.3.4D.1	General time mask for ProSe	323
6.3.4D.2	PSSS/SSSS time mask	323
6.3.4D.3	PSSS / SSSS / PSBCH time mask.....	324
6.3.4D.4	PSSCH / SRS time mask.....	325
6.3.4F	ON/OFF time mask for category NB1 and NB2.....	325
6.3.4F.1	General ON/OFF time mask	325
6.3.4F.2	NPRACH time mask	325
6.3.4G	ON/OFF time mask for V2X Communication.....	326
6.3.4G.1	PSSS / SSSS / PSBCH time mask.....	326
6.3.5	Power Control	327
6.3.5.1	Absolute power tolerance.....	327
6.3.5.1.1	Minimum requirements	327
6.3.5.2	Relative Power tolerance.....	328
6.3.5.2.1	Minimum requirements	328
6.3.5.3	Aggregate power control tolerance	329
6.3.5.3.1	Minimum requirement.....	329
6.3.5A	Power control for CA.....	329
6.3.5A.1	Absolute power tolerance.....	329
6.3.5A.1.1	Minimum requirements	329
6.3.5A.2	Relative power tolerance.....	330
6.3.5A.2.1	Minimum requirements	330
6.3.5A.3	Aggregate power control tolerance	330
6.3.5A.3.1	Minimum requirements	330
6.3.5B	Power control for UL-MIMO	331
6.3.5D	Power Control for ProSe.....	331
6.3.5D.1	Absolute power tolerance.....	331
6.3.5E	Power control for category M1 and M2.....	331
6.3.5E.1	Absolute power tolerance.....	331
6.3.5E.2	Relative Power tolerance.....	331
6.3.5E.3	Aggregate power control tolerance	331

6.3.5E.3.1	Minimum requirement.....	332
6.3.5F	Power Control for category NB1 and NB2.....	332
6.3.5F.1	Absolute power tolerance.....	332
6.3.5F.2	Relative power tolerance.....	333
6.3.5F.3	Aggregate power control tolerance for category NB1 and NB2	333
6.3.5F.3.1	Minimum requirement.....	334
6.3.5G	Power Control for V2X Communication	334
6.3.5G.1	Absolute power tolerance.....	334
6.4	Void.....	335
6.5	Transmit signal quality	335
6.5.1	Frequency error.....	335
6.5.1A	Frequency error for CA.....	335
6.5.1B	Frequency error for UL-MIMO	335
6.5.1D	Frequency error for ProSe.....	335
6.5.1E	Frequency error for UE category M1 and M2	335
6.5.1F	Frequency error for UE category NB1 and NB2	336
6.5.1G	Frequency error for V2X Communication.....	336
6.5.2	Transmit modulation quality.....	336
6.5.2.1	Error Vector Magnitude	336
6.5.2.1.1	Minimum requirement.....	337
6.5.2.2	Carrier leakage	337
6.5.2.2.1	Minimum requirements	337
6.5.2.3	In-band emissions	338
6.5.2.3.1	Minimum requirements	338
6.5.2.4	EVM equalizer spectrum flatness	339
6.5.2.4.1	Minimum requirements	339
6.5.2A	Transmit modulation quality for CA.....	340
6.5.2A.1	Error Vector Magnitude	340
6.5.2A.2	Carrier leakage for CA.....	341
6.5.2A.2.1	Minimum requirements.....	341
6.5.2A.3	In-band emissions	341
6.5.2A.3.1	Minimum requirement for CA.....	341
6.5.2B	Transmit modulation quality for UL-MIMO	343
6.5.2B.1	Error Vector Magnitude	343
6.5.2B.2	Carrier leakage	343
6.5.2B.3	In-band emissions	344
6.5.2B.4	EVM equalizer spectrum flatness for UL-MIMO	344
6.5.2D	Transmit modulation quality for ProSe.....	344
6.5.2D.1	Error Vector Magnitude	344
6.5.2D.2	Carrier leakage	344
6.5.2D.3	In-band emissions	344
6.5.2D.4	EVM equalizer spectrum flatness for ProSe	344
6.5.2E	Transmit modulation quality for category M1 and M2.....	344
6.5.2E.1	Error Vector Magnitude	344
6.5.2E.2	Carrier leakage	344
6.5.2E.2.1	Minimum requirements	345
6.5.2E.3	In-band emissions	345
6.5.2E.3.1	Minimum requirements	345
6.5.2F	Transmit modulation quality for Category NB1 and NB2.....	346
6.5.2F.1	Error Vector Magnitude	346
6.5.2F.2	Carrier leakage	346
6.5.2F.3	In-band emissions	346
6.5.2G	Transmit modulation quality for V2X Communication.....	347
6.5.2G.1	Error Vector Magnitude	347
6.5.2G.2	Carrier leakage	347
6.5.2G.3	In-band emissions	348
6.5.2G.4	EVM equalizer spectrum flatness	348
6.6	Output RF spectrum emissions.....	348
6.6.1	Occupied bandwidth	348
6.6.1.1	Additional minimum requirement for E-UTRA (network signalled value “NS_29”).....	349
6.6.1A	Occupied bandwidth for CA	349
6.6.1B	Occupied bandwidth for UL-MIMO.....	349

6.6.1F	Occupied bandwidth for category NB1 and NB2	349
6.6.1G	Occupied bandwidth for V2X Communication	350
6.6.2	Out of band emission	350
6.6.2.1	Spectrum emission mask	350
6.6.2.1.1	Minimum requirement	350
6.6.2.1A	Spectrum emission mask for CA	351
6.6.2.2	Additional spectrum emission mask	352
6.6.2.2.1	Minimum requirement (network signalled value "NS_03", "NS_11", "NS_20", and "NS_21") ..	352
6.6.2.2.2	Minimum requirement (network signalled value "NS_04")	353
6.6.2.2.3	Minimum requirement (network signalled value "NS_06" or "NS_07")	353
6.6.2.2.4	Minimum requirement (network signalled value "NS_33" or "NS_34")	354
6.6.2.2.5	Minimum requirement (network signalled value "NS_27" and "NS_43")	354
6.6.2.2.6	Minimum requirement (network signalled value "NS_28")	355
6.6.2.2.7	Minimum requirement (network signalled value "NS_35")	355
6.6.2.2A	Additional Spectrum Emission Mask for CA	355
6.6.2.2A.1	Minimum requirement (network signalled value "CA_NS_04")	355
6.6.2.2A.2	Minimum requirement CA_66B (network signalled value "CA_NS_09")	356
6.6.2.2A.3	Minimum requirement CA_66C (network signalled value "CA_NS_09")	357
6.6.2.2A.4	Minimum requirement CA_48B and CA_48C (network signalled value "CA_NS_10")	357
6.6.2.3	Adjacent Channel Leakage Ratio	358
6.6.2.3.1	Minimum requirement E-UTRA	358
6.6.2.3.1a	Additional minimum requirement for E-UTRA (network signalled value "NS_29")	359
6.6.2.3.1A	Void	360
6.6.2.3.1Aa	Void	360
6.6.2.3.2	Minimum requirements UTRA	360
6.6.2.3.2A	Minimum requirement UTRA for CA	360
6.6.2.3.3A	Minimum requirements for CA E-UTRA	362
6.6.2.4	Void	363
6.6.2.4.1	Void	363
6.6.2A	Void	363
6.6.2B	Out of band emission for UL-MIMO	363
6.6.2C	Void	363
6.6.2D	Out of band emission for ProSe	364
6.6.2F	Out of band emission for category NB1 and NB2	364
6.6.2F.1	Spectrum emission mask	364
6.6.2F.2	Additional Spectrum Emission Mask for Category NB1 and NB2	364
6.6.2F.2.1	Minimum requirement (network signalled value "NS_02")	364
6.6.2F.2.2	Minimum requirement (network signalled value "NS_03")	365
6.6.2F.3	Adjacent Channel Leakage Ratio for category NB1 and NB2	365
6.6.2G	Out of band emission for V2X Communication	365
6.6.3	Spurious emissions	366
6.6.3.1	Minimum requirements	366
6.6.3.1A	Minimum requirements for CA	367
6.6.3.2	Spurious emission band UE co-existence	368
6.6.3.2A	Spurious emission band UE co-existence for CA	376
6.6.3.3	Additional spurious emissions	382
6.6.3.3.1	Minimum requirement (network signalled value "NS_05")	382
6.6.3.3.2	Minimum requirement (network signalled value "NS_07")	382
6.6.3.3.3	Minimum requirement (network signalled value "NS_08")	383
6.6.3.3.4	Minimum requirement (network signalled value "NS_09")	383
6.6.3.3.5	Minimum requirement (network signalled value "NS_12")	383
6.6.3.3.6	Minimum requirement (network signalled value "NS_13")	384
6.6.3.3.7	Minimum requirement (network signalled value "NS_14")	384
6.6.3.3.8	Minimum requirement (network signalled value "NS_15")	384
6.6.3.3.9	Minimum requirement (network signalled value "NS_16")	384
6.6.3.3.10	Minimum requirement (network signalled value "NS_17")	385
6.6.3.3.11	Minimum requirement (network signalled value "NS_18")	385
6.6.3.3.12	Minimum requirement (network signalled value "NS_19")	385
6.6.3.3.13	Minimum requirement (network signalled value "NS_11")	385
6.6.3.3.14	Minimum requirement (network signalled value "NS_20")	386
6.6.3.3.15	Minimum requirement (network signalled value "NS_21")	386
6.6.3.3.16	Minimum requirement (network signalled value "NS_22")	386

6.6.3.3.17	Minimum requirement (network signalled value "NS_23").....	387
6.6.3.3.18	Void.....	387
6.6.3.3.19	Minimum requirement (network signalled value "NS_04").....	387
6.6.3.3.20	Minimum requirement (network signalled value "NS_24").....	388
6.6.3.3.21	Minimum requirement (network signalled value "NS_25").....	388
6.6.3.3.22	Minimum requirement (network signalled value "NS_26").....	388
6.6.3.3.23	Minimum requirement (network signalled value "NS_27" and "NS_43")	388
6.6.3.3.24	Minimum requirement (network signalled value "NS_28").....	389
6.6.3.3.25	Minimum requirement (network signalled value "NS_29").....	389
6.6.3.3.26	Minimum requirement (network signalled value "NS_30").....	390
6.6.3.3.27	Minimum requirement (network signalled value "NS_31").....	390
6.6.3.3.28	Minimum requirement (network signalled value "NS_36").....	391
6.6.3.3.29	Minimum requirement (network signalled value "NS_38").....	391
6.6.3.3.30	Minimum requirement (network signalled value "NS_39").....	392
6.6.3.3.31	Minimum requirement (network signalled value "NS_40" and "NS_41")	392
6.6.3.3.32	Minimum requirement (network signalled value "NS_42").....	392
6.6.3.3.33	Minimum requirement (network signalled value "NS_44").....	392
6.6.3.3.34	Minimum requirement (network signalled value "NS_45").....	393
6.6.3.3.35	Minimum requirement (network signalled value "NS_56").....	393
6.6.3.3.36	Minimum requirement (network signalled value "NS_62").....	394
6.6.3.3A	Additional spurious emissions for CA	394
6.6.3.3A.1	Minimum requirement for CA_1C (network signalled value "CA_NS_01").....	394
6.6.3.3A.2	Minimum requirement for CA_1C (network signalled value "CA_NS_02").....	395
6.6.3.3A.3	Minimum requirement for CA_1C (network signalled value "CA_NS_03").....	395
6.6.3.3A.4	Minimum requirement for CA_38C (network signalled value "CA_NS_05").....	395
6.6.3.3A.5	Minimum requirement for CA_7C (network signalled value "CA_NS_06").....	396
6.6.3.3A.6	Minimum requirement for CA_39C and CA_39C-41A (network signalled value "CA_NS_07").....	396
6.6.3.3A.7	Minimum requirement for CA_42C (network signalled value "CA_NS_08").....	396
6.6.3.3A.8	Minimum requirement for CA_41C and CA_41D (network signalled value "CA_NS_04").....	397
6.6.3.3A.9	Void.....	397
6.6.3.3A.10	Minimum requirement for CA_48B and CA_48C (network signalled value "CA_NS_10").....	397
6.6.3A	Void.....	397
6.6.3B	Spurious emission for UL-MIMO	397
6.6.3C	Void.....	397
6.6.3D	Spurious emission for ProSe.....	398
6.6.3F	Spurious emission for category NB1 and NB2	398
6.6.3F.1	Additional spurious emissions	398
6.6.3F.1.2	Minimum requirement (network signalled value "NS_06").....	398
6.6.3G	Spurious emission for V2X Communication	398
6.6.3K	Spurious emission for Aerial UE	400
6.6A	Void.....	401
6.6B	Void.....	401
6.7	Transmit intermodulation	401
6.7.1	Minimum requirement	401
6.7.1A	Minimum requirement for CA	402
6.7.1B	Minimum requirement for UL-MIMO.....	402
6.7.1F	Minimum requirement for category NB1 and NB2	402
6.7.1G	Minimum requirement for V2X Communication	403
6.8	Void.....	403
6.8A	Void.....	403
6.8B	Time alignment error for UL-MIMO	403
6.8B.1	Minimum Requirements	403
6.8C	Void.....	404
6.8D	Void.....	404
6.8E	Void.....	404
6.8F	Void.....	404
6.8G	Time alignment error.....	404
7	Receiver characteristics	404
7.1	General	404
7.2	Diversity characteristics	405

7.3	Reference sensitivity power level.....	405
7.3.1	Minimum requirements (QPSK).....	405
7.3.1A	Minimum requirements (QPSK) for CA.....	439
7.3.1B	Minimum requirements (QPSK) for UL-MIMO	470
7.3.1D	Minimum requirements (QPSK) for ProSe.....	470
7.3.1E	Minimum requirements (QPSK) for UE category 0, M1, M2 and 1bis.....	471
7.3.1F	Minimum requirements for UE category NB1 and NB2	479
7.3.1F.1	Reference sensitivity for UE category NB1 and NB2.....	479
7.3.1F.2	Void.....	480
7.3.1G	Minimum requirements (QPSK) for V2X	480
7.3.1H	Minimum requirements for LTE based 5G terrestrial broadcast	482
7.3.2	Void	482
7.4	Maximum input level	482
7.4.1	Minimum requirements.....	482
7.4.1A	Minimum requirements for CA	483
7.4.1B	Minimum requirements for UL-MIMO	484
7.4.1D	Minimum requirements for ProSe	484
7.4.1F	Minimum requirements for category NB1 and NB2.....	484
7.4.1G	Minimum requirements for V2X	484
7.4.1H	Minimum requirements for LTE based 5G terrestrial broadcast	485
7.4A	Void.....	485
7.4A.1	Void	485
7.5	Adjacent Channel Selectivity (ACS).....	485
7.5.1	Minimum requirements.....	486
7.5.1A	Minimum requirements for CA	487
7.5.1B	Minimum requirements for UL-MIMO	490
7.5.1D	Minimum requirements for ProSe	490
7.5.1F	Minimum requirements for category NB1 and NB2.....	491
7.5.1G	Minimum requirements for V2X	492
7.5.1H	Minimum requirements for LTE based 5G terrestrial broadcast	493
7.6	Blocking characteristics	494
7.6.1	In-band blocking.....	494
7.6.1.1	Minimum requirements.....	495
7.6.1.1A	Minimum requirements for CA.....	496
7.6.1.1D	Minimum requirements for ProSe.....	499
7.6.1.1F	Minimum requirements for category NB1 and NB2	500
7.6.1.1G	Minimum requirements for V2X.....	500
7.6.1.1H	Minimum requirements for LTE based 5G terrestrial broadcast.....	502
7.6.2	Out-of-band blocking.....	502
7.6.2.1	Minimum requirements	503
7.6.2.1A	Minimum requirements for CA.....	504
7.6.2.1D	Minimum requirements for ProSe.....	507
7.6.2.1F	Minimum requirements for category NB1 and NB2.....	508
7.6.2.1G	Minimum requirements for V2X.....	508
7.6.2.1H	Minimum requirements for LTE based 5G terrestrial broadcast.....	510
7.6.3	Narrow band blocking	510
7.6.3.1	Minimum requirements.....	510
7.6.3.1A	Minimum requirements for CA.....	511
7.6.3.1D	Minimum requirements for ProSe.....	512
7.6.3.1H	Minimum requirements for LTE based 5G terrestrial broadcast.....	512
7.6A	Void.....	513
7.6B	Blocking characteristics for UL-MIMO	513
7.7	Spurious response.....	513
7.7.1	Minimum requirements.....	513
7.7.1A	Minimum requirements for CA	513
7.7.1B	Minimum requirements for UL-MIMO	515
7.7.1D	Minimum requirements for ProSe	515
7.7.1F	Minimum requirements for UE category NB1 and NB2	515
7.7.1G	Minimum requirements for V2X	516
7.7.1H	Minimum requirements for LTE based 5G terrestrial broadcast.....	516
7.8	Intermodulation characteristics	517
7.8.1	Wide band intermodulation.....	517

7.8.1.1	Minimum requirements	517
7.8.1A	Minimum requirements for CA	518
7.8.1B	Minimum requirements for UL-MIMO	520
7.8.1D	Minimum requirements for ProSe	520
7.8.1F	Minimum requirements for category NB1 and NB2.....	521
7.8.1G	Minimum requirements.....	521
7.8.1H	Minimum requirements for LTE based 5G terrestrial broadcast.....	522
7.8.2	Void	523
7.9	Spurious emissions	523
7.9.1	Minimum requirements.....	523
7.9.1A	Minimum requirements.....	523
7.10	Receiver image	524
7.10.1	Void	524
7.10.1A	Minimum requirements for CA	524
7.10.1G	Minimum requirements for V2X Communication.....	524
8	Performance requirement	525
8.1	General	525
8.1.1	Receiver antenna capability	525
8.1.1.1	Simultaneous unicast and MBMS operations.....	526
8.1.1.2	Dual-antenna receiver capability in idle mode.....	526
8.1.2	Applicability of requirements	526
8.1.2.1	Applicability of requirements for different channel bandwidths.....	526
8.1.2.2	Definition of CA capability	526
8.1.2.2A	Definition of dual connectivity capability.....	531
8.1.2.3	Applicability and test rules for different CA configurations and bandwidth combination sets.....	532
8.1.2.3A	Applicability and test rules for different dual connectivity configuration and bandwidth combination set	533
8.1.2.3B	Applicability and test rules for different TDD-FDD CA configurations and bandwidth combination sets.....	534
8.1.2.3C	Applicability and test rules for SDR tests for 4Rx capable UEs	535
8.1.2.3D	Applicability and test rules for different CA with LAA SCell(s) configurations and bandwidth combination sets.....	536
8.1.2.3E	Applicability and test rules for SDR tests for 8Rx capable UEs	537
8.1.2.4	Test coverage for different number of component carriers	537
8.1.2.5	Applicability of performance requirements for Type B receiver	538
8.1.2.6	Applicability of performance requirements for 4Rx capable UEs	539
8.1.2.6.1	Applicability rule and antenna connection for single carrier tests with 2Rx	539
8.1.2.6.2	Applicability rule and antenna connection for CA and DC tests with 2Rx	540
8.1.2.6.3	Applicability rule and antenna connection for single carrier tests with 4Rx	541
8.1.2.6.4	Applicability rule for 256QAM tests.....	541
8.1.2.6.5	Applicability rule and antenna connection for CA and DC tests with 4Rx	541
8.1.2.6.6	Applicability rule for Type C with 4Rx.....	543
8.1.2.6.7	Applicability rule for 1024QAM tests.....	544
8.1.2.7	Applicability of Enhanced Downlink Control Channel Performance Requirements	544
8.1.2.8	Applicability of performance requirements for CDM-multiplexed DM RS with interfering simultaneous transmission (FRC) with multiple CSI-RS configurations.....	545
8.1.2.8A	Applicability of performance requirements for UE supporting coverage enhancement	545
8.1.2.9	Applicability of SDR requirements for CA and LAA.....	547
8.1.2.10	Applicability of performance requirements for Multi-user Superposed Transmission	547
8.1.2.11	Applicability CRS interference mitigation receivers performance requirements.....	547
8.1.2.12	Applicability of performance requirements for 8Rx capable UEs	548
8.1.2.12.1	Applicability rule and antenna connection for single carrier PDSCH tests	548
8.1.2.12.2	Applicability rule and antenna connection for control channel tests	554
8.1.2.12.3	Applicability rule and antenna connection for CA and DC tests	554
8.1.3	UE category and UE DL category	555
8.2	Demodulation of PDSCH (Cell-Specific Reference Symbols)	555
8.2.1	FDD (Fixed Reference Channel)	555
8.2.1.1	Single-antenna port performance	556
8.2.1.1.1	Minimum Requirement	556
8.2.1.1.2	Void	560
8.2.1.1.3	Void	560

8.2.1.1.4	Minimum Requirement 1 PRB allocation in presence of MBSFN.....	560
8.2.1.1.4A	Minimum Requirement 1 PRB allocation in presence of FeMBMS Unicast-mixed Cell under CA	561
8.2.1.2	Transmit diversity performance	562
8.2.1.2.1	Minimum Requirement 2 Tx Antenna Port	562
8.2.1.2.2	Minimum Requirement 4 Tx Antenna Port	562
8.2.1.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	563
8.2.1.2.3A	Minimum Requirement 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	564
8.2.1.2.4	Enhanced Performance Requirement Type A - 2 Tx Antenna Ports with TM3 interference model	566
8.2.1.2.5	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM2 interference model	567
8.2.1.2.6	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM9 interference model	568
8.2.1.2.7	Minimum Requirement 2 Tx Antenna Port (Superposed transmission)	569
8.2.1.3	Open-loop spatial multiplexing performance.....	570
8.2.1.3.1	Minimum Requirement 2 Tx Antenna Port	570
8.2.1.3.1A	Soft buffer management test	573
8.2.1.3.1B	Enhanced Performance Requirement Type C –2Tx Antenna Ports	574
8.2.1.3.1C	Enhanced Performance Requirement Type C - 2 Tx Antenna Ports with TM1 interference	575
8.2.1.3.2	Minimum Requirement 4 Tx Antenna Port	576
8.2.1.3.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	576
8.2.1.3.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	579
8.2.1.3.5	Minimum Requirement 2 Tx Antenna Port (Superposed transmission)	580
8.2.1.3.6	Minimum Requirement 2 Tx Antenna Port (network-based CRS interference mitigation).....	581
8.2.1.4	Closed-loop spatial multiplexing performance	582
8.2.1.4.1	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Port.....	582
8.2.1.4.1A	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Port.....	583
8.2.1.4.1B	Enhanced Performance Requirement Type A - Single-Layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	584
8.2.1.4.1C	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured).....	585
8.2.1.4.1D	Enhanced Performance Requirement Type B - Single-layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	586
8.2.1.4.1E	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports with CRS assistance information	588
8.2.1.4.1F	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Ports with CRS assistance information	589
8.2.1.4.2	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	590
8.2.1.4.2A	Enhanced Performance Requirement Type C – Multi-layer Spatial Multiplexing 2Tx Antenna Ports.....	590
8.2.1.4.3	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port	591
8.2.1.4.3A	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port for dual connectivity	595
8.2.1.4.4	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port (Superposed transmission)	596
8.2.1.5	MU-MIMO.....	597
8.2.1.6	[Control channel performance: D-BCH and PCH]	597
8.2.1.7	Carrier aggregation with power imbalance	597
8.2.1.7.1	Minimum Requirement	597
8.2.1.8	Intra-band non-contiguous carrier aggregation with timing offset.....	598
8.2.1.8.1	Minimum Requirement	598
8.2.1.9	HST-SFN performance	599
8.2.1.9.1	Minimum Requirement	599
8.2.1.9.2	Minimum Requirement for Rel-16 further enhanced HST	602
8.2.1.10	Intra-band contiguous carrier aggregation with minimum channel spacing.....	602
8.2.1.10.1	Minimum Requirement	602
8.2.2	TDD (Fixed Reference Channel)	603

8.2.2.1	Single-antenna port performance	604
8.2.2.1.1	Minimum Requirement	604
8.2.2.1.2	Void	608
8.2.2.1.3	Void	608
8.2.2.1.4	Minimum Requirement 1 PRB allocation in presence of MBSFN.....	608
8.2.2.2	Transmit diversity performance	608
8.2.2.2.1	Minimum Requirement 2 Tx Antenna Port	608
8.2.2.2.2	Minimum Requirement 4 Tx Antenna Port	609
8.2.2.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	609
8.2.2.2.3A	Minimum Requirement 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	611
8.2.2.2.4	Enhanced Performance Requirement Type A – 2 Tx Antenna Ports with TM3 interference model	612
8.2.2.2.5	Minimum Requirement 2 Tx Antenna Port (when <i>EIMTA-MainConfigServCell-r12</i> is configured)	613
8.2.2.2.6	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM2 interference model	614
8.2.2.2.7	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM9 interference model	615
8.2.2.2.8	Minimum Requirement 2 Tx Antenna Port (Superposed transmission)	616
8.2.2.3	Open-loop spatial multiplexing performance.....	617
8.2.2.3.1	Minimum Requirement 2 Tx Antenna Port	617
8.2.2.3.1A	Soft buffer management test	620
8.2.2.3.1B	Enhanced Performance Requirement Type C - 2Tx Antenna Ports	621
8.2.2.3.1C	Enhanced Performance Requirement Type C - 2 Tx Antenna Ports with TM1 interference	621
8.2.2.3.2	Minimum Requirement 4 Tx Antenna Port	622
8.2.2.3.3	Minimum Requirement 2Tx antenna port (demodulation subframe overlaps with aggressor cell ABS)	622
8.2.2.3.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	625
8.2.2.3.5	Minimum Requirement 2 Tx Antenna Port (Superposed transmission)	627
8.2.2.3.6	Minimum Requirement 2 Tx Antenna Port (network-based CRS interference mitigation).....	627
8.2.2.4	Closed-loop spatial multiplexing performance	629
8.2.2.4.1	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Port.....	629
8.2.2.4.1A	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Port.....	629
8.2.2.4.1B	Enhanced Performance Requirement Type A – Single-Layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	630
8.2.2.4.1C	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured).....	631
8.2.2.4.1D	Enhanced Performance Requirement Type B - Single-layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	633
8.2.2.4.1E	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports with CRS assistance information	634
8.2.2.4.1F	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Ports with CRS assistance information	635
8.2.2.4.2	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	636
8.2.2.4.2A	Enhanced Performance Requirement Type C Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	637
8.2.2.4.3	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port	638
8.2.2.4.3A	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port for dual connectivity	641
8.2.2.4.4	Void	643
8.2.2.4.5	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port (Superposed transmission)	643
8.2.2.5	MU-MIMO.....	643
8.2.2.6	[Control channel performance: D-BCH and PCH]	643
8.2.2.7	Carrier aggregation with power imbalance	643
8.2.2.7.1	Minimum Requirement	643
8.2.2.8	Intra-band contiguous carrier aggregation with minimum channel spacing.....	644
8.2.2.8.1	Minimum Requirement	644
8.2.2.9	HST-SFN performance	645

8.2.2.9.1	Minimum Requirement	645
8.2.2.9.2	Minimum Requirement for Rel-16 further enhanced HST	647
8.2.3	TDD FDD CA (Fixed Reference Channel).....	648
8.2.3.1	Single-antenna port performance	649
8.2.3.1.1	Minimum Requirement for FDD PCell	649
8.2.3.1.2	Minimum Requirement for TDD PCell	652
8.2.3.2	Open-loop spatial multiplexing performance 2Tx Antenna port.....	656
8.2.3.2.1	Minimum Requirement for FDD PCell	656
8.2.3.2.1A	Soft buffer management test for FDD PCell	659
8.2.3.2.2	Minimum Requirement for TDD PCell	660
8.2.3.2.2A	Soft buffer management test for TDD PCell	664
8.2.3.3	Closed-loop spatial multiplexing performance 4Tx Antenna Port	665
8.2.3.3.1	Minimum Requirement for FDD PCell	665
8.2.3.3.2	Minimum Requirement for TDD PCell	668
8.2.3.4	Minimum Requirement for Closed-loop spatial multiplexing performance 4Tx Antenna Port for dual connectivity	672
8.2.3.5	HST-SFN performance	674
8.2.3.5.0	General	674
8.2.3.5.1	Minimum Requirement for FDD PCell	674
8.2.3.5.2	Minimum Requirement for TDD PCell	677
8.2.4	LAA	680
8.2.4.1	Closed-loop spatial multiplexing performance 4Tx Antenna Port	680
8.2.4.1.1	FDD PCell (FDD single carrier).....	680
8.2.4.1.2	TDD PCell (TDD single carrier)	683
8.3	Demodulation of PDSCH (User-Specific Reference Symbols).....	686
8.3.1	FDD	686
8.3.1.1	Single-layer Spatial Multiplexing	687
8.3.1.1A	Enhanced Performance Requirement Type A – Single-layer Spatial Multiplexing with TM9 interference model.....	688
8.3.1.1B	Single-layer Spatial Multiplexing (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	690
8.3.1.1C	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM9 interference model.....	692
8.3.1.1D	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with CRS interference model.....	693
8.3.1.1E	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM3 interference model.....	695
8.3.1.1F	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM10 serving cell configuration and TM9 interference model	696
8.3.1.1G	Single-layer Spatial Multiplexing (CRS assistance information is configured).....	697
8.3.1.1H	Single-layer Spatial Multiplexing (With Enhanced DMRS table configured).....	698
8.3.1.1I	Single-layer Spatial Multiplexing (with assistance information for simultaneous transmission interfering PDSCH).....	699
8.3.1.2	Dual-Layer Spatial Multiplexing	700
8.3.1.2A	Enhanced Performance Requirement Type C - Dual-Layer Spatial Multiplexing	702
8.3.1.3	Performance requirements for DCI format 2D and non Quasi Co-located Antenna Ports	703
8.3.1.3.1	Minimum requirement with Same Cell ID (with single NZP CSI-RS resource).....	703
8.3.1.3.2	Minimum requirements with Same Cell ID (with multiple NZP CSI-RS resources)	704
8.3.1.3.3	Minimum requirement with Different Cell ID and Colliding CRS (with single NZP CSI-RS resource)	706
8.3.1.3.4	Minimum requirement with Different Cell ID and non-colliding CRS (with single NZP CSI- RS resource and CRS assistance information is configured).....	707
8.3.1.3.5	Minimum requirements with different Cell ID and non-colliding CRS (with multiple NZP CSI-RS resources and CRS assistance information is configured).....	709
8.3.1.3.6	Minimum requirements for QCL Type C and 2 Layers Spatial Multiplexing.....	711
8.3.1.4	Performance Requirements for semiOpenLoop transmission	712
8.3.2	TDD	713
8.3.2.1	Single-layer Spatial Multiplexing	714
8.3.2.1A	Single-layer Spatial Multiplexing (with multiple CSI-RS configurations)	716
8.3.2.1B	Enhanced Performance Requirement Type A – Single-layer Spatial Multiplexing with TM9 interference model.....	717