
**Simplified design of prestressed
concrete bridges —**

**Part 2:
Box-girder bridges**

Conception simplifiée des ponts en béton précontraint —

Partie 2: Ponts à poutres caissons

iteh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO 21725-2:2021

<https://standards.iteh.ai/catalog/standards/iso/eab29746-71f1-46a0-9d59-57523caef69/iso-21725-2-2021>



iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO 21725-2:2021

<https://standards.iteh.ai/catalog/standards/iso/eab29746-71f1-46a0-9d59-57523caacf69/iso-21725-2-2021>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	viii
Introduction.....	ix
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	1
4 Symbols and abbreviated terms.....	6
5 Design and construction procedure.....	9
5.1 Procedure.....	9
5.1.1 General.....	9
5.2 Design documentation.....	12
5.2.1 General.....	12
5.2.2 Calculation report.....	12
5.2.3 Geotechnical report.....	12
5.2.4 Structural drawings.....	12
5.2.5 Specifications.....	12
6 General provisions.....	13
6.1 Limitations.....	13
6.1.1 General.....	13
6.1.2 Permitted use.....	13
6.1.3 Maximum number of spans.....	13
6.1.4 Recommended span length.....	13
6.1.5 Maximum difference in span length.....	13
6.1.6 Maximum cantilever length.....	13
6.1.7 Maximum height of bridge.....	13
6.1.8 Maximum number of lanes.....	14
6.1.9 Width limitations.....	14
6.1.10 Clearances.....	14
6.1.11 Maximum skew angle.....	15
6.1.12 Maximum bridge horizontal curvature.....	15
6.1.13 Cross-section variation.....	15
6.1.14 Interaction between superstructure and substructure.....	15
6.2 Limit states.....	15
6.3 Ultimate limit state design format.....	16
6.3.1 General.....	16
6.3.2 Required factored loads.....	16
6.3.3 Design strength.....	17
6.4 Serviceability limit state design format.....	17
7 Structural systems and layout.....	17
7.1 Description of the components of the structure.....	17
7.1.1 General.....	17
7.1.2 Superstructure system.....	17
7.1.3 Substructure system.....	17
7.1.4 Foundation.....	18
7.2 General guide.....	18
7.2.1 Architectural guide.....	18
7.2.2 General structural guides for the project.....	18
7.3 Structural layout.....	19
7.3.1 General structural layout.....	19
7.3.2 Vertical layout.....	19
7.4 Feasibility under the guidelines.....	20
8 Actions (Loads).....	21

8.1	General.....	21
8.2	Dead loads.....	21
8.2.1	General.....	21
8.2.2	Structural elements.....	21
8.2.3	Non-structural elements.....	21
8.3	Live loads.....	22
8.3.1	General.....	22
8.3.2	Design truck.....	22
8.3.3	Design lane load.....	22
8.3.4	Dynamic effect of live loads.....	23
8.4	Longitudinal forces.....	23
8.5	Earth pressure.....	23
8.6	Wind loads.....	24
8.7	Earthquake inertial forces.....	24
8.7.1	General.....	24
8.7.2	Seismic hazard.....	24
8.7.3	No seismic hazard zones:.....	24
8.7.4	Low seismic hazard zones:.....	25
8.7.5	Intermediate seismic hazard zones:.....	25
8.7.6	High seismic hazard zones:.....	25
8.7.7	Soil profile types.....	29
8.7.8	Site effects.....	30
8.7.9	Design response spectral ordinates.....	30
8.7.10	Seismic equivalent uniformly distributed load.....	31
8.7.11	Fundamental mode shape.....	31
8.7.12	Lateral equivalent design forces.....	32
8.8	Jacking and post-tensioning forces.....	32
8.8.1	Jacking forces.....	32
8.8.2	Forces for post-tensioning anchorage.....	33
8.9	Thermal effects.....	33
8.9.1	Seasonal variation.....	33
8.9.2	Thermal coefficient.....	33
8.9.3	Differential temperature.....	33
8.10	Load combinations.....	33
8.10.1	Ultimate loads.....	33
8.10.2	Service loads.....	33
9	Structural analysis.....	34
9.1	General.....	34
9.1.1	B-region and D-region.....	34
9.1.2	Elastic behaviour.....	34
9.1.3	Small deflection theory.....	34
9.1.4	Secondary moments.....	34
9.1.5	Time-dependent properties of concrete.....	34
9.1.6	Geometric imperfections.....	34
9.1.7	Frame analysis.....	34
9.2	Longitudinal analysis.....	34
9.3	Transverse analysis.....	35
9.3.1	Empirical method.....	35
9.3.2	Approximate method.....	35
9.3.3	Refined method.....	36
10	Design requirements.....	37
10.1	General.....	37
10.2	Box girder cross-section dimensions and details.....	37
10.2.1	Minimum flange thickness.....	37
10.2.2	Minimum web thickness.....	37
10.2.3	Length of top flange cantilever.....	37
10.2.4	Overall cross-section dimensions.....	38

10.2.5	Longitudinal slope	38
10.3	Materials for structural concrete	39
10.3.1	General	39
10.3.2	Cement	39
10.3.3	Aggregates	39
10.3.4	Water	39
10.3.5	Steel reinforcement	39
10.3.6	Prestressing steel	40
10.3.7	Post-tensioning anchorages and couplers	40
10.3.8	Ducts	41
10.3.9	Admixtures	41
10.3.10	
	Storage of materials	41
10.3.11	
	Minimum and maximum reinforcement bar diameter	42
10.4	Concrete mixture proportioning	42
10.4.1	General	42
10.4.2	Durability requirements	42
10.4.3	Required average compressive strength	43
10.4.4	Proportioning of the concrete mixture	43
10.5	Concrete cover of reinforcement	44
10.5.1	Minimum concrete cover	44
10.5.2	Special corrosion protection	45
10.6	Minimum reinforcement bend diameter	45
10.7	Standard hook dimensions	45
10.8	Bar spacing and maximum aggregate size	45
10.8.1	General	45
10.8.2	Maximum nominal coarse aggregate size	45
10.8.3	Minimum clear spacing between parallel bars in a layer	46
10.8.4	Minimum clear spacing between parallel layers of reinforcement	46
10.8.5	Clear spacing between parallel lap splices	46
10.8.6	Maximum flexural reinforcement spacing in solid slabs	47
10.8.7	Maximum shrinkage and temperature reinforcement spacing in solid slabs	47
10.8.8	Maximum reinforcement spacing in structural concrete walls	47
10.8.9	Minimum spacing of prestressing tendons and ducts	48
10.8.10	
	Maximum spacing of prestressing tendons in slabs	49
10.8.11	
	Couplers in post-tensioning tendons	49
10.9	Development length, lap splicing and anchorage of reinforcement	49
10.9.1	Development length	49
10.9.2	Lap splice dimensions	50
10.10	Limits for longitudinal reinforcement	51
10.10.1	General	51
10.10.2	
	Shrinkage and temperature reinforcement	51
10.10.3	
	Minimum area of tension flexural reinforcement	52
11	Stress limitations	52
11.1	Stress limitations for prestressing tendons	52
11.2	Stress limitations for concrete	53
11.2.1	For temporary stresses before losses-fully prestressed components	53
11.2.2	For stresses at serviceability limit state after losses-fully prestressed components	54
12	Loss of prestress	55
12.1	Total loss of prestress	55
12.2	Instantaneous losses	56

	12.2.1 Anchorage set.....	56
	12.2.2 Friction.....	56
	12.2.3 Elastic shortening.....	57
12.3	Approximate estimate of time-dependent losses.....	57
13	Details of tendon.....	60
13.1	Tendon confinement.....	60
	13.1.1 General.....	60
	13.1.2 Effects of curved tendons.....	60
13.2	External tendon supports.....	61
13.3	Post-tensioned anchorage zones.....	61
	13.3.1 General.....	61
	13.3.2 General zone and local zone.....	61
	13.3.3 Design of general zone.....	62
	13.3.4 Design of local zone.....	64
14	Superstructure.....	65
14.1	Strength of members subjected to flexural moments.....	65
	14.1.1 General.....	65
	14.1.2 Factored flexural moment at section.....	65
	14.1.3 Minimum design flexural moment strength.....	65
	14.1.4 Nominal moment strength of PSC box girder.....	65
14.2	Strength of members subjected to shear stresses.....	69
	14.2.1 General.....	69
	14.2.2 Factored shear.....	69
	14.2.3 Design shear strength.....	69
	14.2.4 Design of shear reinforcement.....	69
14.3	Girders, beams, joists.....	70
14.4	Details of box girder.....	70
	14.4.1 Flange and web thickness.....	70
	14.4.2 Reinforcement.....	70
14.5	Diaphragms.....	71
14.6	Opening.....	71
14.7	Railings.....	73
14.8	Splices of strand.....	73
14.9	Continuous structure.....	73
	14.9.1 Scope of application.....	73
	14.9.2 General design.....	73
	14.9.3 Structural analysis.....	73
	14.9.4 Fixed support.....	75
	14.9.5 Intermediate support.....	76
15	Substructure.....	77
15.1	Girders that are part of a frame.....	77
15.2	Strength of members subjected to axial loads with or without flexure.....	77
15.3	Torsion.....	77
15.4	Bearing strength.....	77
15.5	Columns and piers.....	77
15.6	Concrete walls.....	77
16	Foundations.....	77
16.1	Foundation type and capacity.....	77
16.2	Subsurface exploration and testing programs.....	77
16.3	Dimensioning of the foundation elements.....	77
16.4	Footings.....	78
16.5	Foundation mats.....	78
16.6	Footings on piles.....	78
16.7	Foundation beams.....	78
16.8	Retaining walls.....	78
17	Lateral load resisting system.....	78

17.1	General.....	78
17.2	Specified lateral forces.....	78
17.3	Lateral force resisting structural system.....	78
17.4	Minimum amount of structural concrete walls.....	78
17.5	Special reinforcement details for seismic zones.....	78
18	Bearings.....	78
18.1	General.....	78
18.2	Multiple roller bearings.....	78
18.3	Elastomeric bearings.....	78
18.4	Anchorage.....	79
18.5	Design forces for supporting structure.....	79
Annex A (informative) Equivalent formulae for material factors		80
Bibliography.....		82

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO 21725-2:2021

<https://standards.iteh.ai/catalog/standards/iso/eab29746-71f1-46a0-9d59-57523caaf69/iso-21725-2-2021>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 71, *Concrete, reinforced concrete and pre-stressed concrete*, Subcommittee SC 5, *Simplified design standard for concrete structures*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

<https://standards.iteh.ai/catalog/standards/iso/eab29746-71f1-46a0-9d59-57523caaf69/iso-21725-2-2021>

Introduction

The aim of this document is to provide rules for the design and construction of relatively short span prestressed concrete box girder bridges. This document is developed for countries that do not have existing national standards on this subject and to offer to local regulatory authorities an alternative for the design of relatively small bridges that abound in urban overpasses and over creeks and rivers everywhere. This document may not be used in place of a national standard unless specifically considered and accepted by the national standards body or other appropriate regulatory organization. The design rules are based in simplified worldwide-accepted strength design models. This document is self-contained; therefore, loads, simplified analysis procedures and design specifications are included, as well as minimum acceptable construction practice guidelines.

The minimum dimensional guidelines contained in this document are intended to account for undesirable side effects that require more sophisticated analysis and design procedures. Material and construction guidelines are aimed at site-mixed concrete as well as ready-mixed concrete, and steel of the minimum available strength grades.

The earthquake resistance guidelines are included to account for the numerous regions of the world which lie in earthquake prone areas. The earthquake resistance for zones with high seismic hazard is based on the employment of structural concrete walls (shear walls) that limit the lateral deformations of the structure and provide for its lateral strength, in place of piers or frames that can be used in zones with intermediate, low or no significant earthquake hazard.

This document contains provisions that can be modified by the national standards body due to local design and construction requirements and practices. The specifications that can be modified are included using ["boxed values"]. The national standards body is expected to review the "boxed values" and may substitute alternative definitive values for these elements for use in the national application of this document.

Document Preview

[ISO 21725-2:2021](https://standards.iteh.ai/catalog/standards/iso/eab29746-71f1-46a0-9d59-57523caacf69/iso-21725-2-2021)

<https://standards.iteh.ai/catalog/standards/iso/eab29746-71f1-46a0-9d59-57523caacf69/iso-21725-2-2021>

Simplified design of prestressed concrete bridges —

Part 2: Box-girder bridges

1 Scope

This document provides information to perform the design of the prestressed concrete box girder bridge for road that complies with the limitations established in 6.1. The rules of design as set forth in the document are simplifications of more elaborate requirements. Among several erection methods of box girder bridges, the provisions of this document are mainly applicable to full staging method (FSM).

Designs and details for new road bridges address structural integrity by considering the following:

- the use of continuity and redundancy to provide one or more alternate paths;
- structural members and bearing seat widths that are resistant to damage or instability; and
- external protection systems to minimize the effects of reasonably conceived severe loads.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 28842, *Guidelines for simplified design of reinforced concrete bridges*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1

admixture

material other than water, aggregate, or hydraulic cement, used as an ingredient of concrete and added to concrete before or during its mixing to modify its properties

3.2

anchorage

device used to anchor a non-structural element to the structural framing

3.3

B-region

portion of a member in which it is reasonable to assume that strains due to flexure vary linearly through section

**3.4
beam**

horizontal, or nearly horizontal, structural member supported at one (such as a cantilever) or more points, but not throughout its length, transversely supporting a load, and subjected primarily to flexure

**3.5
clearance**

distance by which one thing clears another; the space between them

**3.6
compression reinforcement**

reinforcement provided to resist compression stresses induced by flexural moments acting on the member section

**3.7
specified compressive strength of concrete**

compressive cylinder strength of concrete used in design and evaluated in accordance with the appropriate ISO standard, expressed in megapascals (MPa)

Note 1 to entry: Whenever the quantity f_c' is under a radical sign ($\sqrt{f_c'}$), the positive square root of numerical value only is intended, and the result has units of megapascals (MPa).

**3.8
corrosion**

gradual removal or weakening of metal from its surface that requires the presence of humidity and oxygen, and is helped by the presence of other materials

**3.9
cover**

thickness of concrete between surface of any reinforcing bar and the nearest face of the concrete member

**3.10
crosstie**

continuous reinforcing bar having a 135° hook at one end and a hook not less than 90° at least a six-diameter extension at the other end

Note 1 to entry: The hooks should engage peripheral longitudinal bars. The 90° hooks of two successive crossties engaging the same longitudinal bars should be alternated end for end.

**3.11
D-region**

portion of a member with a force discontinuity or a geometric discontinuity

**3.12
deformed reinforcement**

steel reinforcement that has deformations in its surface to increase its bond to the concrete

Note 1 to entry: The following steel reinforcement should be considered deformed reinforcement according to this document: deformed reinforcing bars, deformed wire, welded plain wire fabric, and welded deformed wire fabric conforming to the appropriate ISO standards.

**3.13
design strength**

product of the nominal strength multiplied by a strength reduction factor

**3.14
development length**

length of embedded reinforcement required to develop the design strength of reinforcement at a critical section

3.15**diaphragm**

transverse stiffener which is provided between girders in order to maintain section geometry, to resist lateral forces, and to transfer loads to support

3.16**duct**

material creating a conduit in a concrete member to accommodate the prestressing steel of a post-tensioning tendon

3.17**durability**

characteristic of a structure to resist gradual degradation of its serviceability in a given environment for the design service life

3.18**effective depth**

distance measured from extreme compression fibre to centroid of tension reinforcement

3.19**factored load**

specified nominal load multiplied by the load factors prescribed in this document

3.20**girder**

main horizontal support beam, usually supporting other beams

3.21**hook**

bend at the end of a reinforcing bar

Note 1 to entry: They are defined by the angle that the bend forms with the bar as either 90°, 180° or 135° hooks.

3.22**jacking force**

<prestressed concrete> temporary force exerted by the device that introduces tension into the tendons

3.23**joist**

T-shaped beam used in parallel series directly supporting deck loads, and supported in turn by larger girders, beams, or bearing structural concrete walls

3.24**lap splice**

splice between two reinforcing bars obtained by overlapping them for a specified length

3.25**limit state**

condition beyond which a structure or member becomes unfit for service and is judged either to be no longer useful for its intended function (serviceability limit state) or to be unsafe (strength limit state)

3.26**live load**

static and dynamic effect, in terms of forces applied on the structure, produced by the use of the bridge by pedestrians and/or vehicles and not including construction or environmental loads

3.27**load effect**

force and deformation produced in structural members by the applied loads

3.28

load combination

combination of factored loads and forces as specified in this document

3.29

load factor

factor that accounts for deviations of the actual load from the nominal load, for uncertainties in the analysis that transforms the load into a load effect, and for the probability that more than one extreme load will occur simultaneously

3.30

load

force or other action that results from the weight of all bridge materials, pedestrians, vehicles, environmental effects, differential movement, and restrained dimensional changes

3.31

longitudinal reinforcement

reinforcement that is laid parallel to the longitudinal axis of the element, generally to account for flexural effects

3.32

mesh wire

welded-wire fabric reinforcement

3.33

nominal load

magnitude of the loads specified in this document (dead, live, soil, wind, snow, rain, flood, and earthquake)

3.34

nominal strength

capacity of a structure or member to resist the effects of loads, as determined by computations using specified material strengths and dimensions and the Formulae set forth in this document

Note 1 to entry: Specified material strengths are derived from accepted principles of structural mechanics or by field tests or laboratory tests of scaled models, allowing for modelling effects and differences between laboratory and field conditions.

3.35

permanent load

load in which variations over time are rare or of small magnitude

Note 1 to entry: All other loads are variable loads (see also [3.33](#)).

3.36

post-tensioning

method of prestressing reinforced concrete in which tendons are tensioned after the concrete has attained a specified minimum strength or a specified minimum age

3.37

prestressing steel

high-strength steel elements such as wire, bar, or strands used to impart prestress forces to concrete

3.38

pretensioning

method of prestressing in which prestressing steel is tensioned before the concrete is placed

3.39

required factored strength

strength of a member or cross-section required to resist factored loads or related internal moments and forces in such combinations as are stipulated by this document