
**Information technology — High
efficiency coding and media delivery
in heterogeneous environments —**

**Part 8:
Conformance specification for HEVC**

*Technologies de l'information — Codage à haute efficacité et livraison
des médias dans des environnements hétérogènes —
Partie 8: Spécification de conformité du codage vidéo à haute
efficacité*

ISO/IEC 23008-8:2018

<https://standards.iteh.ai/catalog/standards/sist/69ae7eca-0f66-4090-b02a-3f87c4820dbc/iso-iec-23008-8-2018>



iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/IEC 23008-8:2018

<https://standards.iteh.ai/catalog/standards/sist/69ae7eca-0f66-4090-b02a-3f87c4820dbc/iso-iec-23008-8-2018>



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms, definitions, abbreviated terms and conventions	1
4 Conformance testing for Rec. ITU-T H.265 ISO/IEC 23008-2	2
4.1 General	2
4.2 Bitstream conformance	2
4.3 Decoder conformance	2
4.4 Procedure to test bitstreams	2
4.5 Procedure to test decoder conformance	3
4.5.1 Conformance bitstreams	3
4.5.2 Contents of the bitstream file	3
4.5.3 Requirements on output of the decoding process and timing	3
4.5.4 Recommendations (informative)	4
4.5.5 Static tests for output order conformance	4
4.5.6 Dynamic tests for output timing conformance	4
4.5.7 Decoder conformance test of a particular profile, tier, and level	5
4.6 Specification of the test bitstreams	6
4.6.1 General	6
4.6.2 Test bitstreams — Block structure	6
4.6.3 Test bitstreams — Intra coding	7
4.6.4 Test bitstreams — Inter-frame coding	8
4.6.5 Test bitstreams — Transform and quantization	11
4.6.6 Test bitstreams — Deblocking filter	14
4.6.7 Test bitstreams — Sample adaptive offset	16
4.6.8 Test bitstreams — Entropy coding	17
4.6.9 Test bitstreams — Temporal scalability	19
4.6.10 Test bitstreams — Parallel processing tools	20
4.6.11 Test bitstreams — Other coding tools	24
4.6.12 Test bitstreams — High level syntax	26
4.6.13 Test bitstreams — 10 bit	33
4.6.14 Test bitstreams — MV-HEVC	37
4.6.15 Test bitstreams — 3D-HEVC	41
4.6.16 Test bitstreams — Format Range Extensions	48
4.6.17 Test bitstreams — Scalable extensions	58
4.7 Normative conformance test suites for Rec. ITU-T H.265 ISO/IEC 23008-2	113
4.7.1 Bitstreams for Main, Main Still Picture, and Main 10 profiles	113
4.7.2 Bitstreams for Multiview Main profile	118
4.7.3 Bitstreams for 3D Main profile	119
4.7.4 Bitstreams for Monochrome 12, Monochrome 16, Main 12, Main 4:2:2 10, Main 4:2:2 12, Main 4:4:4, Main 4:4:4 10, Main 4:4:4 12, Main Intra, Main 10 Intra, Main 12 Intra, Main 4:2:2 10 Intra, Main 4:2:2 12 Intra, Main 4:4:4 Intra, Main 4:4:4 10 Intra, Main 4:4:4 12 Intra, Main 4:4:4 16 Intra, Main 4:4:4 Still Picture and Main 4:4:4 16 Still Picture profiles	121
4.7.5 Bitstreams for Scalable Main and Scalable Main 10 profiles	123
4.7.6 Bitstreams for Scalable Monochrome, Scalable Monochrome 12, Scalable Monochrome 16, and Scalable Main 4:4:4 profiles	126

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/IEC JTC 1, Information technology, Subcommittee SC 29, Coding of audio, picture, multimedia and hypermedia information, in collaboration with ITU-T. A technically aligned twin text is published as ITU-T H.265.1.

This second edition cancels and replaces the first edition (ISO/IEC ISO/IEC 23008-8:2015), which has been technically revised.

The main changes compared to the previous edition are as follows:

- addition of conformance testing for Multiview Main and 3D Main profiles;
- addition of conformance testing for Format Range Extensions profiles;
- addition of conformance testing for Scalable profiles.

A list of all parts in the ISO/IEC 23008 series can be found on the ISO website.

Information technology — High efficiency coding and media delivery in heterogeneous environments —

Part 8: Conformance specification for HEVC

1 Scope

This document specifies a set of tests and procedures designed to indicate whether encoders or decoders meet the normative requirements specified in Rec. ITU-T H.265 | ISO/IEC 23008-2.

NOTE The conformance bitstreams identified within the text are available at <http://standards.iso.org/iso-iec/23008/-8/ed-2/en>.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

Rec. ITU-T H.265 | ISO/IEC 23008-2:2017, *Information technology — High efficiency video coding and media delivery in heterogeneous environment — Part 2: High Efficiency Video Coding*

Rec. ITU-T H.265.2 | ISO/IEC 23008-5:2018, *Information technology — High efficiency video coding and media delivery in heterogeneous environment — Part 2: High Efficiency Video Coding Reference Software*

3 Terms, definitions, abbreviated terms and conventions

For the purposes of this document, the terms, definitions, abbreviated terms and conventions given in Rec. ITU-T H.265 | ISO/IEC 23008-2 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

3.1

bitstream

sequence of bits, in the form of a NAL unit stream or a byte stream, that forms the representation of coded pictures and associated data forming one or more CVSs

Note 1 to entry: In this document, this refers specifically to video bitstream according to ISO/IEC 23008-2.

[SOURCE: Rec. ITU-T H.265 | ISO/IEC 23008-2:2017, 3.12, modified – Note 1 to entry added]

3.2

decoder

embodiment of a decoding process

Note 1 to entry: In this document, this refers specifically to a video decoder as specified in ISO/IEC 23008-2.

Note 2 to entry: The decoder does not include the display process, which is outside the scope of this document.

[SOURCE: Rec. ITU-T H.265 | ISO/IEC 23008-2:2017, 3.40, modified – Notes 1 and 2 to entry added]

3.3

encoder

embodiment of an encoding process

Note 1 to entry: The process, not specified in this document (except in regard to identification of the reference software encoder), produces a bitstream.

[SOURCE: Rec. ITU-T H.265 | ISO/IEC 23008-2:2017, 3.49, modified – Note 1 to entry added]

3.4

reference software decoder

decoding software required for this document

Note 1 to entry: For this document, the reference software decoder is provided in Rec. ITU-T H.265.2 | ISO/IEC 23008-5.

3.5

reference software encoder

encoding software required for this document

Note 1 to entry: For this document, the reference software encoder is provided in Rec. ITU-T H.265.2 | ISO/IEC 23008-5.

4 Conformance testing for Rec. ITU-T H.265 | ISO/IEC 23008-2

4.1 General

The following clauses specify normative tests for verifying conformance of video bitstreams as well as decoders. Those normative tests make use of test data (bitstream test suites) provided at <http://standards.iso.org/iso-iec/23008/-8/ed-2/en> and the reference software decoder specified in Rec. ITU-T H.265.2 | ISO/IEC 23008-5.

4.2 Bitstream conformance

Bitstream conformance for Rec. ITU-T H.265 | ISO/IEC 23008-2 is specified by ISO/IEC 23008-2:2017, C.4.

4.3 Decoder conformance

Decoder conformance for Rec. ITU-T H.265 | ISO/IEC 23008-2 is specified by ISO/IEC 23008-2:2017, C.5.

4.4 Procedure to test bitstreams

A bitstream that claims conformance with Rec. ITU-T H.265 | ISO/IEC 23008-2 shall pass the following normative test.

The bitstream shall be decoded by processing it with the reference software decoder. When processed by the reference software decoder, the bitstream shall not cause any error or non-conformance messages to be reported by the reference software decoder. This test should not be applied to bitstreams that are known to contain errors introduced by transmission, as such errors are highly likely to result in bitstreams that lack conformance to Rec. ITU-T H.265 | ISO/IEC 23008-2.

Successfully passing the reference software decoder test provides only a strong presumption that the bitstream under test is conforming to the video layer, i.e., that it does indeed meet all the requirements for the video layer (except Annexes C, D and E) specified in Rec. ITU-T H.265 | ISO/IEC 23008-2 that are tested by the reference software decoder.

Additional tests may be necessary to more thoroughly check that the bitstream properly meets all the requirements specified in Rec. ITU-T H.265 | ISO/IEC 23008-2 including the hypothetical reference decoder (HRD) conformance (based on Annexes C, D and E). These complementary tests may be performed using other video bitstream verifiers that perform more complete tests than those implemented by the reference software decoder.

Rec. ITU-T H.265 | ISO/IEC 23008-2 contains several informative recommendations that are not an integral part of that Document. When testing a bitstream for conformance, it may also be useful to test whether or not the bitstream follows those recommendations.

To check correctness of a bitstream, it is necessary to parse the entire bitstream and to extract all the syntax elements and other values derived from those syntactic elements and used by the decoding process specified in Rec. ITU-T H.265 | ISO/IEC 23008-2.

A verifier may not necessarily perform all stages of the decoding process specified in Rec. ITU-T H.265 | ISO/IEC 23008-2 in order to verify bitstream correctness. Many tests can be performed on syntax elements in a state prior to their use in some processing stages.

4.5 Procedure to test decoder conformance

4.5.1 Conformance bitstreams

A bitstream has values of `general_profile_idc`, `general_tier_flag`, and `general_level_idc` corresponding to a set of specified constraints on a bitstream for which a decoder conforming to a specified profile, tier, and level is required in Rec. ITU-T H.265 | ISO/IEC 23008-2:2017, Annex A to properly perform the decoding process.

4.5.2 Contents of the bitstream file

The conformance bitstreams are provided at <http://standards.iso.org/iso-iec/23008/-8/ed-2/en>. The following information is included in a single zipped file for each such bitstream.

- bitstream;
- decoded pictures or hashes of decoded pictures (may not be present);
- short description of the bitstream;
- trace file (results while decoding the bitstream, in ASCII format).

In cases where the decoded pictures or hashes of decoded pictures are not available, the reference software decoder shall be used to generate the necessary reference decoded pictures from the bitstream.

4.5.3 Requirements on output of the decoding process and timing

Two classes of decoder conformance are specified:

- output order conformance;
- output timing conformance.

The output of the decoding process is specified in Rec. ITU-T H.265 | ISO/IEC 23008-2:2017, Clause 8 and Annex C.

For output order conformance, it is a requirement that all of the decoded pictures specified for output in Rec. ITU-T H.265 | ISO/IEC 23008-2:2017, Annex C shall be output by a conforming decoder in the specified order and that the values of the decoded samples in all of the pictures that are output shall be (exactly equal to) the values specified in Rec. ITU-T H.265 | ISO/IEC 23008-2:2017, Clause 8.

For output timing conformance, it is a requirement that a conforming decoder shall also output the decoded samples at the rates and times specified in Rec. ITU-T H.265 | ISO/IEC 23008-2:2017, Annex C.

The display process, which ordinarily follows the output of the decoding process, is outside the scope of this document.

4.5.4 Recommendations (informative)

In addition to the requirements, it is desirable that conforming decoders implement various informative recommendations specified in Rec. ITU-T H.265 | ISO/IEC 23008-2 that are not an integral part of that document. This clause discusses some of these recommendations.

It is recommended that a conforming decoder be able to resume the decoding process as soon as possible after the loss or corruption of part of a bitstream. In most cases it is possible to resume decoding at the next start code or slice header. It is recommended that a conforming decoder be able to perform concealment for the coding tree blocks or video packets for which all the coded data has not been received.

4.5.5 Static tests for output order conformance

Static tests of a video decoder require testing of the decoded samples. This clause explains how this test can be accomplished when the decoded samples at the output of the decoding process are available. It may not be possible to perform this type of test with a production decoder (due to the lack of an appropriate accessible interface in the design at which to perform the test). In that case this test should be performed by the manufacturer during the design and development phase. Static tests are used for testing the decoding process. The test will check that the values of the samples decoded by the decoder under test shall be identical to the values of the samples decoded by the reference decoder. When a hash of the values of the samples of the decoded pictures is attached to the bitstream file, a corresponding hash operation performed on the values of the samples of the decoded pictures produced by the decoder under test shall produce the same results.

<https://standards.iso.org/standards/catalog/standards/sist/69ae7eca-0f66-4090-b02a-3f87c4820dbc/iso-iec-23008-8-2018>

4.5.6 Dynamic tests for output timing conformance

Dynamic tests are applied to check that all the decoded samples are output and that the timing of the output of the decoder's decoded samples conforms to the specification of Rec. ITU-T H.265 | ISO/IEC 23008-2:2017, Clause 8 and Annex C, and to verify that the HRD models (as specified by the CPB and DPB specification in Rec. ITU-T H.265 | ISO/IEC 23008-2:2017, Annex C) are not violated when the bits of the bitstream are delivered at the proper rate.

The dynamic test is often easier to perform on a complete decoding system, which may include a systems decoder, a video decoder and a display process. It may be possible to record the output of the display process and to check that display order and timing of decoded pictures are correct at the output of the display process. However, since the display process is not within the normative scope of Rec. ITU-T H.265 | ISO/IEC 23008-2, there may be cases where the output of the display process differs in timing or value even though the video decoder is conforming. In this case, the output of the video decoder itself (before the display process) would need to be captured in order to perform the dynamic tests on the video decoder. In particular the output order and timing of the decoded pictures shall be correct.

If buffering period and picture timing SEI messages are included in the test bitstream, HRD conformance shall be verified using the values of `nal_initial_cpb_removal_delay`, `nal_initial_cpb_removal_offset`, `au_cpb_removal_delay_minus1` and `pic_dpb_output_delay` that are included in the bitstream.

If buffering period and picture timing SEI messages are not included in the bitstream, the following inferences shall be made to generate the missing parameters:

- `fixed_pic_rate_within_cvs_flag` shall be inferred to be equal to 1;
- `low_delay_hrd_flag` shall be inferred to be equal to 0;

- `cbr_flag` shall be inferred to be equal to 0;
- The frame rate of the bitstream shall be inferred to be equal to the frame rate value specified in the corresponding table of subclause 6.7, where the bitstream is listed. If this is missing, then a frame rate of either 25 or $30\,000 \div 1\,001$ can be inferred;
- `vui_time_scale` shall be set equal to 90 000 and the value of `vui_num_units_in_tick` shall be computed based on frame rate;
- The bit rate of the bitstream shall be inferred to be equal to the maximum value for the level specified in Rec. ITU-T H.265 | ISO/IEC 23008-2:2017, Table A-1;
- CPB and DPB sizes shall be inferred to be equal to the maximum value for the level specified in Rec. ITU-T H.265 | ISO/IEC 23008-2:2017, Table A-1.

With the above inferences, the HRD shall be operated as follows.

- The CPB is filled starting at time $t = 0$, until it is full, before removal of the first access unit. This means that the `nal_initial_cpb_removal_delay` shall be inferred to be equal to the total CPB buffer size divided by the bit rate divided by 90 000 (rounded downwards) and `nal_initial_cpb_removal_offset` shall be inferred to be equal to zero.
- The first access unit is removed at time $t = \text{nal_initial_cpb_removal_delay} \div 90\,000$ and subsequent access units are removed at intervals based on the frame distance, i.e. $(90\,000 \div \text{vui_num_units_in_tick})$.
- Using these inferences, the CPB will not overflow or underflow and the DPB will not overflow.

4.5.7 Decoder conformance test of a particular profile, tier, and level

In order for a decoder of a particular profile, tier, and level to claim output order conformance to Rec. ITU-T H.265 | ISO/IEC 23008-2 as specified by this document, the decoder shall successfully pass the static test specified in subclause 6.5.5 with all the bitstreams of the normative test suite specified for testing decoders of this particular profile, tier, and level combination.

In order for a decoder of a particular profile, tier, and level to claim output timing conformance to Rec. ITU-T H.265 | ISO/IEC 23008-2 as specified by this document, the decoder shall successfully pass both the static test specified in subclause 6.5.5 and the dynamic test specified in subclause 6.5.6 with all the bitstreams of the normative test suite specified for testing decoders of this particular profile, tier, and level. Tables 1 through 6 specify the normative test suites for each profile, tier, and level combination. The test suite for a particular profile, tier, and level combination is the list of bitstreams that are marked with an 'X' in the column corresponding to that profile, tier, and level combination. In the column 'Main tier', 'X' indicate the bitstream is for Main tier. A decoder conformed to Main tier shall be capable of decoding the specified bitstreams, among the testing profile-level combination, indicated by 'X' at 'Main tier' column in Table 1. A decoder conformed to High tier shall be capable of decoding all the specified bitstreams, among the testing profile-level combination, in Table 1.

'X' indicates that the bitstream is designed to test both the dynamic and static conformance of the decoder.

The bitstream column specifies the bitstream used for each test.

A decoder that conforms to the Main profile, Main Still Picture profile, or Main 10 profile at a specific level shall be capable of decoding the specified bitstreams in Table 1.

A decoder that conforms to the Multiview Main profile at specific level shall be capable of decoding the specified bitstreams in Table 2. In addition to the bitstreams defined in Table 3, a decoder that conforms to the Multiview Main profile shall be capable of decoding the Main profile bitstreams specified in Table 1.

A decoder that conforms to the 3D Main profile (as specified in Rec. ITU-T H.265 | ISO/IEC 23008-2:2017, Clause I.11) at specific level shall be capable of decoding the specified bitstreams in [Table 3](#). In addition to the bitstreams defined in [Table 3](#), a decoder that conforms to the 3D Main profile shall be capable of decoding the Multiview Main profile bitstreams specified in [Table 2](#).

A decoder that conforms to the Monochrome, Monochrome 12, Monochrome 16, Main 12, Main 4:2:2 10, Main 4:2:2 12, Main 4:4:4, Main 4:4:4 10, Main 4:4:4 12, Main Intra, Main 10 Intra, Main 12 Intra, Main 4:2:2 10 Intra, Main 4:2:2 12 Intra, Main 4:4:4 Intra, Main 4:4:4 10 Intra, Main 4:4:4 12 Intra, Main 4:4:4 16 Intra, Main 4:4:4 Still Picture, or Main 4:4:4 16 Still Picture profile (as specified in Rec. ITU-T H.265 | ISO/IEC 23008-2:2017, A.3.5), which are collectively referred to as the format range extensions profiles, shall be capable of decoding the specified bitstreams in [Table 4](#). A decoder that conforms to some format range extensions profiles is also required to be capable of decoding bitstreams that conform to particular other profiles. Thus, in addition to the specified bitstreams in [Table 4](#), a decoder that conforms to a format range extensions profile shall also be capable of decoding the bitstreams specified in [Table 1](#) that conform to the decoding requirements specified for the format range extensions profile in Rec. ITU-T H.265 | ISO/IEC 23008-2:2017, A.3.5.

A decoder that conforms to the High Throughput 4:4:4 16 Intra profile (as specified in Rec. ITU-T H.265 | ISO/IEC 23008-2:2017, A.3.6) at specific level shall be capable of decoding the specified bitstreams in [Table 4](#).

A decoder that conforms to a list of profile, tier, level, INBLD capability quadruplets such that one of the quadruplets corresponds to a profile indication of Scalable Main or Scalable Main 10 profile (as specified in Rec. ITU-T H.265 | ISO/IEC 23008-2:2017, H.11.1.1) at specific level, shall be capable of decoding the specified bitstreams in [Table 5](#). A decoder that conforms to a list of profile, tier, level, INBLD capability quadruplets such that one of the quadruplets corresponds to a profile indication of Scalable Main or Scalable Main 10 profile at specific level shall also be capable of decoding the specified bitstreams in [Table 1](#).

A decoder that conforms to a list of profile, tier, level, INBLD capability quadruplets such that one of the quadruplets corresponds to a profile indication of Scalable Monochrome, Scalable Monochrome 12, Scalable Monochrome 16 or Scalable Main 4:4:4 (as specified in Rec. ITU-T H.265 | ISO/IEC 23008-2:2017, H.11.1.2, collectively referred to as scalable format range extension profiles) at specific level, shall be capable of decoding the specified bitstreams in [Table 6](#). A decoder that conforms to a list of profile, tier, level, INBLD capability quadruplets such that one of the quadruplets corresponds to a scalable format range extension profile is also required to be capable of decoding bitstreams that conform to particular other profiles. Thus, in addition to the specified bitstreams in [Table 6](#), a decoder that conforms to a list of profile, tier, level, INBLD capability quadruplets such that one of the quadruplets corresponds to a scalable format range extension profile shall also be capable of decoding the bitstreams specified in [Table 1](#) and [Table 5](#) that conform to the decoding requirements specified for the scalable format range extensions profile in Rec. ITU-T H.265 | ISO/IEC 23008-2:2017, H.11.1.2.

4.6 Specification of the test bitstreams

4.6.1 General

Some characteristics of each bitstream listed in [Table 1](#) are specified in this clause. In [Table 1](#), the value "29.97" shall be interpreted as an approximation of an exact value of $30\,000 \div 1\,001$ and the value "59.94" shall be interpreted as an approximation of an exact value of $60\,000 \div 1\,001$.

4.6.2 Test bitstreams — Block structure

4.6.2.1 Test bitstreams #STRUCT_A

Specification: All slices are coded as I, P or B slices. Each picture contains one slice. Various CTU and maximum CU sizes are used.

Functional stage: Test the reconstruction process of slices.

Purpose: Check that the decoder can properly decode I, P and B slices with various CTU and maximum CU sizes.

4.6.2.2 Test bitstreams #STRUCT_B

Specification: All slices are coded as I, P or B slices. Each picture contains one slice. Various CTU and minimum CU sizes are used.

Functional stage: Test the reconstruction process of slices.

Purpose: Check that the decoder can properly decode I, P and B slices with various CTU and minimum CU sizes.

4.6.3 Test bitstreams — Intra coding

4.6.3.1 Test bitstreams #IPRED_A, #IPRED_B, and #IPRED_C

Specification: All slices are coded as I slices. Each picture contains one slice. All intra prediction modes (35 modes for each of luma 32x32, luma 16x16, luma 8x8, luma 4x4, chroma 16x16, chroma 8x8 and chroma 4x4, for a total 245 modes) are used. The IPRED_B bitstream contains only one picture, and conforms to the Main Still Picture profile.

Functional stage: Test the reconstruction process of I slices.

Purpose: Check that the decoder can properly decode I slices with all intra prediction modes.

4.6.3.2 Test bitstreams #CIP_A

Specification: The bitstream contains one I slice and one B slice, using one slice per picture. Both SAO and the deblocking filter are disabled. [ISO/IEC 23008-8:2018](https://standards.iteh.ai/catalog/standards/sist/69ae7eca-0f66-4090-b02a-01f7c522051e/iso-23008-8-2018)

Functional stage: Test the reference sample substitution process for intra sample prediction.

Purpose: Check that the decoder can properly decode slices of coded pictures containing intra TUs with unavailable samples for intra prediction.

4.6.3.3 Test bitstreams #CIP_B

Specification: The bitstream contains an I-picture and 4 P-pictures. Each picture contains only one slice. constrained_intra_pred_flag is equal to 1.

Functional stage: Test the reference sample substitution process for intra sample prediction.

Purpose: Check that the decoder can properly decode slices of coded pictures containing intra TUs with unavailable samples for intra prediction.

4.6.3.4 Test bitstreams #CIP_C

Specification: The bitstream contains one I slice and one B slice, using more than one slice per picture. Both SAO and the deblocking filter are disabled.

Functional stage: Test the reference sample substitution process for intra sample prediction.

Purpose: Check that the decoder can properly decode slices of coded pictures containing intra TUs with unavailable samples for intra prediction.

4.6.4 Test bitstreams — Inter frame coding

4.6.4.1 Test bitstreams #MERGE_A

Specification: All slices are coded as I or B slices. Each picture contains only one slice. five_minus_max_num_merge_cand is set equal to 4.

Functional stage: Test the reconstruction process of motion vector prediction.

Purpose: Check that the decoder can properly decode with the maximum number of merging candidates equal to any value permitted by the standard (i.e. 1, 2, 3, 4, 5).

4.6.4.2 Test bitstreams #MERGE_B

Specification: All slices are coded as I or B slices. Each picture contains only one slice. five_minus_max_num_merge_cand is set equal to 3.

Functional stage: Test the reconstruction process of motion vector prediction.

Purpose: Check that the decoder can properly decode with the maximum number of merging candidates equal to any value permitted by the standard (i.e. 1, 2, 3, 4, 5).

4.6.4.3 Test bitstreams #MERGE_C

Specification: All slices are coded as I or B slices. Each picture contains only one slice. five_minus_max_num_merge_cand is set equal to 2.

Functional stage: Test the reconstruction process of motion vector prediction.

Purpose: Check that the decoder can properly decode with the maximum number of merging candidates equal to any value permitted by the standard (i.e. 1, 2, 3, 4, 5).

4.6.4.4 Test bitstreams #MERGE_D

Specification: All slices are coded as I or B slices. Each picture contains only one slice. five_minus_max_num_merge_cand is set equal to 1.

Functional stage: Test the reconstruction process of motion vector prediction.

Purpose: Check that the decoder can properly decode with the maximum number of merging candidates equal to any value permitted by the standard (i.e. 1, 2, 3, 4, 5).

4.6.4.5 Test bitstreams #MERGE_E

Specification: All slices are coded as I or B slices. Each picture contains only one slice. five_minus_max_num_merge_cand is set equal to 0.

Functional stage: Test the reconstruction process of motion vector prediction.

Purpose: Check that the decoder can properly decode with the maximum number of merging candidates equal to any value permitted by the standard (i.e. 1, 2, 3, 4, 5).

4.6.4.6 Test bitstreams #MERGE_F

Specification: All slices are coded as I or B slices. Each picture contains only one slice. sps_temporal_mvp_enabled_flag is equal to 0 and five_minus_max_num_merge_cand is equal to 0.

Functional stage: Test the reconstruction process of motion vector prediction.

Purpose: Check that the decoder can properly decode when the temporal merging candidate is not included in the merge candidate set.

4.6.4.7 Test bitstreams #MERGE_G

Specification: All slices are coded as I or B slices. Each picture contains only one slice. `five_minus_max_num_merge_cand` is set equal to 0.

Functional stage: Test the reconstruction process of motion vector prediction.

Purpose: Check that the decoder can properly decode with merge index ranging from 0 to 4.

4.6.4.8 Test bitstreams #PMERGE_A

Specification: All slices are coded as I or B slices. Each picture contains only one slice. `log2_parallel_merge_level_minus2` is set equal to 0.

Functional stage: Test the reconstruction process of motion vector prediction.

Purpose: Check that the decoder can properly decode parallel merge level values permitted by the standard (i.e. 2, 3, 4, 5, 6 for luma CTB size 64x64).

4.6.4.9 Test bitstreams #PMERGE_B

Specification: All slices are coded as I or B slices. Each picture contains only one slice. `log2_parallel_merge_level_minus2` is set equal to 1.

Functional stage: Test the reconstruction process of motion vector prediction.

Purpose: Check that the decoder can properly decode parallel merge level values permitted by the standard (i.e. 2, 3, 4, 5, 6 for luma CTB size 64x64).

4.6.4.10 Test bitstreams #PMERGE_C

Specification: All slices are coded as I or B slices. Each picture contains only one slice. `log2_parallel_merge_level_minus2` is set equal to 2.

Functional stage: Test the reconstruction process of motion vector prediction.

Purpose: Check that the decoder can properly decode the parallel merge level values permitted by the standard (i.e. 2, 3, 4, 5, 6 for luma CTB size 64x64).

4.6.4.11 Test bitstreams #PMERGE_D

Specification: All slices are coded as I or B slices. Each picture contains only one slice. `log2_parallel_merge_level_minus2` is set equal to 3.

Functional stage: Test the reconstruction process of motion vector prediction.

Purpose: Check that the decoder can properly decode the parallel merge level values permitted by the standard (i.e. 2, 3, 4, 5, 6 for luma CTB size 64x64).

4.6.4.12 Test bitstreams #PMERGE_E

Specification: All slices are coded as I or B slices. Each picture contains only one slice. `log2_parallel_merge_level_minus2` is set equal to 4.

Functional stage: Test the reconstruction process of motion vector prediction.

Purpose: Check that the decoder can properly decode the parallel merge level values permitted by the standard (i.e. 2, 3, 4, 5, 6 for luma CTB size 64x64).

4.6.4.13 Test bitstreams #AMVP_A

Specification: All slices are coded as I or P slices. Each picture contains only one slice. num_ref_idx_l0_default_active_minus1 is equal to 0, num_ref_idx_l1_default_active_minus1 is equal to 0 and num_ref_idx_active_override_flag is equal to 0.

Functional stage: Test the reconstruction process of motion vector prediction.

Purpose: Check that the decoder can properly decode when motion vector scaling is not needed for spatial motion vector prediction candidate generation (all inter-coded PUs within the same slice have the same inter_pred_idc and ref_idx_l0).

4.6.4.14 Test bitstreams #AMVP_B

Specification: All slices are coded as I or B slices. Each picture contains only one slice. Multiple reference pictures are used. For some slices, num_ref_idx_l0_default_active_minus1 is equal to 3 and num_ref_idx_active_override_flag is equal to 0. For other B slices, num_ref_idx_l0_default_active_minus1 is equal to 1, num_ref_idx_l1_default_active_minus1 is equal to 1 and num_ref_idx_active_override_flag is equal to 0.

Functional stage: Test the reconstruction process of motion vector prediction.

Purpose: Check that the decoder can properly decode when motion vector scaling is not needed for spatial motion vector prediction candidate generation.

4.6.4.15 Test bitstreams #AMVP_C

Specification: All slices are coded as I or P slices. Each picture contains only one slice.

Functional stage: Test the reconstruction process of motion vector prediction, specifically, motion vector prediction during the low delay condition.

Purpose: Check that the decoder can properly decode when motion vector scaling is not needed for spatial motion vector prediction candidate generation.

4.6.4.16 Test bitstreams #TMVP_A

Specification: Each picture contains only one slice. slice_temporal_mvp_enabled_flag is set equal to 0 for pictures 0 to 8 and 1 for pictures 9 to 16.

Functional stage: Test the reconstruction process of motion vector prediction.

Purpose: Check that the decoder can properly decode for different slice_temporal_mvp_enabled_flag values.

4.6.4.17 Test bitstreams #MVDL1ZERO_A

Specification: The bitstream contains multiple B slices per picture. Randomized on and off switching of the mvd_l1_zero_flag is included for multiple B slices.

Functional stage: Test the reconstruction process of motion vector prediction.

Purpose: Check that the decoder can properly decode when the parsing of list 1 motion vector difference for bi-prediction varies according to values of mvd_l1_zero_flag.

4.6.4.18 Test bitstreams #MVCLIP_A

Specification: Each picture contains only one slice. Motion vector prediction and merge candidate motion vectors are clipped to 16-bit values. Clipped motion vector prediction and merge candidates are selected.

Functional stage: Test the reconstruction process of motion vector prediction.

Purpose: Check that the decoder can properly decode when clipping of motion vector prediction and merge candidate motion vectors to 16-bit values occurs.

4.6.4.19 Test bitstreams #MVEDGE_A

Specification: Each picture contains only one slice. The bitstream includes motion vectors pointing to the padded edge regions in a picture.

Functional stage: Test the reconstruction process of motion vector prediction.

Purpose: Check that the decoder can properly decode motion vectors pointing to the padded edge regions of a picture.

4.6.4.20 Test bitstreams #WP_A

Specification: All slices are coded as I or P slices. Each picture contains only one slice. `weighted_pred_flag` is equal to 1. Plural reference indices are assigned to each reference picture.

Functional stage: Weighted sample prediction process for P slices with plural reference indices.

Purpose: Check that the decoder can properly decode weighted sample prediction for P slices with plural reference indices.

4.6.4.21 Test bitstreams #WP_B

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. `weighted_pred_flag` is equal to 1 and `weighted_bipred_flag` is equal to 1. Plural reference indices are assigned to each reference picture.

Functional stage: Weighted sample prediction process for P and B slices with plural reference indices.

Purpose: Check that the decoder can properly decode weighted sample prediction for P and B slices with plural reference indices.

4.6.5 Test bitstreams — Transform and quantization

4.6.5.1 Test bitstreams #RQT_A

Specification: All slices are coded as I or B slices. Each picture contains only one slice. `max_transform_hierarchy_depth_inter` and `max_transform_hierarchy_depth_intra` are both set equal to 0.

Functional stage: Test the reconstruction process of slices with residual quadtree.

Purpose: Check that the decoder can properly decode slices with residual quadtree with intra and inter depth equal to 0.

4.6.5.2 Test bitstreams #RQT_B

Specification: All slices are coded as I or B slices. Each picture contains only one slice. `max_transform_hierarchy_depth_inter` and `max_transform_hierarchy_depth_intra` are both set equal to 1.

Functional stage: Test the reconstruction process of slices with residual quadtree.

Purpose: Check that the decoder properly decodes slices with residual quadtree with intra and inter depth equal to 1.

4.6.5.3 Test bitstreams #RQT_C

Specification: All slices are coded as I or B slices. Each picture contains only one slice. `max_transform_hierarchy_depth_inter` and `max_transform_hierarchy_depth_intra` are both set equal to 2.