
**Air quality — Environmental
meteorology —**

**Part 3:
Ground-based remote sensing of wind
by continuous-wave Doppler lidar**

iTeh STANDARD PREVIEW
Qualité de l'air — Météorologie de l'environnement —

(standards.iteh.ai)
*Partie 3: Télédétection du vent par lidar Doppler à ondes continues
basé au sol*

ISO 28902-3:2018

<https://standards.iteh.ai/catalog/standards/sist/8dcae629-d8a6-4eb3-9be2-c32400a97174/iso-28902-3-2018>



iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 28902-3:2018

<https://standards.iteh.ai/catalog/standards/sist/8dcae629-d8a6-4eb3-9be2-c32400a97174/iso-28902-3-2018>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Fundamentals of heterodyne Doppler lidar	4
4.1 Overview.....	4
4.2 Heterodyne detection.....	5
4.3 Spectral analysis.....	7
4.3.1 Signal processing for CW lidar.....	7
4.3.2 An example of a wind speed estimation process.....	9
4.4 Target variables.....	9
4.5 Sources of noise and uncertainties.....	9
4.5.1 Local oscillator shot noise.....	9
4.5.2 Detector noise.....	10
4.5.3 Relative intensity noise.....	10
4.5.4 Speckles.....	10
4.5.5 Laser frequency.....	10
4.6 Range assignment.....	10
4.7 Known limitations.....	11
5 System specifications and tests	12
5.1 System specifications.....	12
5.1.1 Laser wavelength.....	12
5.1.2 Transmitter/receiver characteristics.....	12
5.1.3 Pointing system characteristics.....	12
5.2 Figures of merit.....	13
5.3 Precision and availability of measurements.....	13
5.3.1 Radial velocity measurement accuracy.....	13
5.3.2 Data availability.....	14
5.3.3 Maximum operational range.....	14
5.4 Testing procedures.....	14
5.4.1 General.....	14
5.4.2 Hard target return.....	14
5.4.3 Assessment of accuracy by intercomparison with other instrumentation.....	14
5.4.4 Maximum operational range validation.....	16
6 Measurement planning and installation instructions	16
6.1 Site requirements.....	16
6.2 Limiting conditions for general operation.....	17
6.3 Maintenance and operational test.....	17
6.3.1 General.....	17
6.3.2 Maintenance.....	17
6.3.3 Operational test.....	17
6.3.4 Uncertainty.....	18
Bibliography	19

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 146, *Air quality*, Subcommittee SC 5, *Meteorology*.

A list of all parts in the ISO 28902 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

Lidars (“light detection and ranging”), used in this document to designate atmospheric lidars, have proven to be valuable systems for the remote sensing of atmospheric pollutants in various meteorological parameters, such as wind, clouds, aerosols and gases. Extensive optical and physical properties of the probed targets, such as size distribution, chemical composition, shape of the particles and gas concentration, and optical properties of the atmosphere, such as visibility, extinction and backscatter, can be retrieved using lidars. Atmospheric targets such as these can be spatially resolved along their line of sight by, for example, focusing the continuous-wave beam at the chosen specific range. The measurements can be carried out without direct contact and in any direction as electromagnetic radiation is used for sensing the targets. Lidar systems, therefore, supplement the conventional *in situ* measurement technology. They are suited for a large number of applications that cannot be adequately performed by using *in situ* or point measurement methods.

There are several methods by which lidar can be used to measure atmospheric wind. The four most commonly used methods are heterodyne pulsed Doppler wind lidar (see ISO 28902-2:2017^[1]), heterodyne continuous-wave Doppler wind lidar, direct-detection Doppler wind lidar and resonance Doppler wind lidar (commonly used for mesospheric sodium layer measurements). For further reading, refer to References [2] and [3].

This document describes the use of (monostatic) heterodyne continuous-wave Doppler lidar.

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 28902-3:2018

<https://standards.iteh.ai/catalog/standards/sist/8dcae629-d8a6-4eb3-9be2-c32400a97174/iso-28902-3-2018>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 28902-3:2018

<https://standards.iteh.ai/catalog/standards/sist/8dcae629-d8a6-4eb3-9be2-c32400a97174/iso-28902-3-2018>

Air quality — Environmental meteorology —

Part 3:

Ground-based remote sensing of wind by continuous-wave Doppler lidar

1 Scope

This document specifies the requirements and performance test procedures for monostatic heterodyne continuous-wave (CW) Doppler lidar techniques and presents their advantages and limitations. The term “Doppler lidar” used in this document applies solely to monostatic heterodyne CW lidar systems retrieving wind measurements from the scattering of laser light by aerosols in the atmosphere. Performances and limits are described based on standard atmospheric conditions. This document describes the determination of the line-of-sight wind velocity (radial wind velocity).

NOTE Derivation of wind vector from individual line-of-sight measurements is not described in this document since it is highly specific to a particular wind lidar configuration. One example of the retrieval of the wind vector can be found in ISO 28902-2:2017, Annex B.

This document does not address the retrieval of the wind vector.

This document can be used for the following application areas:

- meteorological briefing for e.g. aviation, airport safety, marine applications, oil platforms;
- wind power production, e.g. site assessment, power curve determination;
- routine measurements of wind profiles at meteorological stations;
- air pollution dispersion monitoring;
- industrial risk management (direct data monitoring or by assimilation into micro-scale flow models);
- exchange processes (greenhouse gas emissions).

This document can be used by manufacturers of monostatic CW Doppler wind lidars as well as bodies testing and certifying their conformity. This document also provides recommendations for users to make adequate use of these instruments.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61400-12-1:2017, *Wind energy generation systems — Part 12-1: Power performance measurements of electricity producing wind turbines*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1 data availability

ratio between the number of actual considered measurement data with a predefined data quality and the number of expected measurement data for a given measurement period

Note 1 to entry: In the wind industry, this term commonly applies to measurements averaged over a standard period of 10 min.

3.2 displayed range resolution

spatial interval between the centres of two successive range measurements

3.3 effective range resolution

application-related variable describing an integrated range interval for which the target variable is delivered with a defined uncertainty

[SOURCE: ISO 28902-1:2012, 3.14, modified — The example has been deleted.]

3.4 effective temporal resolution

application-related variable describing an integrated time interval for which the target variable is delivered with a defined uncertainty

[SOURCE: ISO 28902-1:2012, 3.12, modified — The symbol and the example has been deleted.]

3.5 extinction coefficient

α

measure of the atmospheric opacity, expressed by the natural logarithm of the ratio of incident light intensity to transmitted light intensity, per unit light path length

[SOURCE: ISO 28902-1:2012, 3.10]

3.6 integration time

time spent in order to derive an independent value of the line-of-sight velocity

3.7 maximum acquisition range

R_{MaxA}

maximum distance at which a lidar signal can be recorded and processed

Note 1 to entry: It depends primarily on the laser wavelength and transmitter aperture size; also, to some extent, it depends on the number of acquisition points and the sampling frequency.

3.8 minimum acquisition range

R_{MinA}

minimum distance from which a lidar signal can be recorded and processed

Note 1 to entry: If the minimum acquisition range is not given, it is assumed to be zero. It can be different from zero, when the reception is blind by focusing limitations.

3.9**maximum operational range** R_{Max0}

maximum distance to which a wind speed can be derived with confidence from the lidar signal

Note 1 to entry: The maximum operational range is less than or equal to the maximum acquisition range.

Note 2 to entry: The maximum operational range is defined along an axis corresponding to the application. It is measured vertically for vertical wind profiler. It is measured horizontally for scanning lidars able to measure in the full hemisphere.

Note 3 to entry: The maximum operational range depends on lidar parameters but also on atmospheric conditions, particularly the extinction coefficient.

3.10**measurement period**

interval of time between the first and last measurements

[SOURCE: ISO 28902-2:2017, 3.10]

3.11**minimum operational range** R_{Min0}

minimum distance where wind speed can be derived with confidence from the lidar signal

Note 1 to entry: The minimum operational range is also called blind range.

Note 2 to entry: In continuous-wave lidars, the minimum operational range is determined by the closest position of the focus achievable by the transmitter optical system.

3.12**physical range resolution**

width [full width at half maximum (FWHM)] of the range weighting function

[SOURCE: ISO 28902-2:2017, 3.12]

3.13**probe length**

width [full width at half maximum (FWHM)] of the spatial weighting function selecting the region in space that contributes to the wind speed computation

Note 1 to entry: The probe length is centred on the measurement distance.

3.14**range resolution**

equipment-related variable describing the shortest range interval from which independent signal information can be obtained

[SOURCE: ISO 28902-1:2012, 3.13]

3.15**range weighting function**

weighting function of the radial wind speed along the line of sight

[SOURCE: ISO 28902-2:2017, 3.15]

3.16**temporal resolution**

equipment-related variable describing the shortest time interval from which independent signal information can be obtained

[SOURCE: ISO 28902-1:2012, 3.11]

3.17

velocity bias

maximum instrumental offset on the velocity measurement

Note 1 to entry: The velocity bias has to be minimized with adequate calibration, for example, on a fixed target.

[SOURCE: ISO 28902-2:2017, 3.17]

3.18

velocity range

range determined by the minimum measurable wind speed, the maximum measurable wind speed and the ability to measure the velocity sign, without ambiguity

Note 1 to entry: Depending on the lidar application, the velocity range can be defined as the radial wind velocity (scanning lidar) or as horizontal wind velocity (wind profiler).

[SOURCE: ISO 28902-2:2017, 3.18]

3.19

velocity resolution

instrumental velocity standard deviation

Note 1 to entry: The velocity resolution is determined by the signal processing bin width.

3.20

wind shear

variation of wind speed across a plane perpendicular to the wind direction

[SOURCE: ISO 28902-2:2017, 3.20]

ITEH STANDARD PREVIEW
(standards.iteh.ai)

4 Fundamentals of heterodyne Doppler lidar

ISO 28902-3:2018
<https://standards.iteh.ai/catalog/standards/sist/8dcae629-d8a6-4eb3-9be2-c32400a97174/iso-28902-3-2018>

4.1 Overview

A CW Doppler lidar emits a narrow laser beam (see [Figure 1](#)). As it propagates in the atmosphere, the laser radiation is scattered in all directions by aerosols, molecules and other scattering material. Part of the scattered radiation propagates back to the lidar, it is captured by a telescope, detected and analysed. Since the aerosols and molecules move with the atmosphere, a Doppler shift results, changing the frequency of the scattered laser light.

At the wavelengths (and thus frequencies) relevant to heterodyne (coherent) Doppler lidar it is the aerosols that provide the principal target for measurement of the back-scattered signal.


The analysis aims at measuring the difference Δf between the frequencies f_t of the emitted laser pulse and f_r of the backscattered light. According to the Doppler equation, this difference is proportional to the line-of-sight wind component, as shown by [Formula \(1\)](#):

$$\Delta f = f_r - f_t = -2v_r / \lambda \tag{1}$$

where

λ is the laser wavelength;

v_r is the line-of-sight wind component (component of the wind vector \vec{v} along the axis of the laser beam, counted positive when the wind is blowing away from the lidar).



Key

- 1 scattering particles moving with the wind
 - 2 optical path of the emitted laser beam
 - 3 optical axis of the receiver
 - 4 lidar instrument
- <https://standards.iteh.ai/catalog/standards/sist/8dcae629-d8a6-4eb3-9be2-c32400a97174/iso-28902-3-2018>

Figure 1 — Measurement principle of a heterodyne Doppler lidar

For a CW Doppler lidar system, the measurement range is usually determined by focusing the beam to create a waist at the chosen distance. Light backscattered from those regions in close proximity to the waist is efficiently re-imaged back into the receiver; light from a significantly closer or greater distance from the waist or focus is inefficiently gathered.

4.2 Heterodyne detection

In a heterodyne lidar, the detection of the light captured by the receiving telescope (at frequency $f_r = f_t + \Delta f$) is described schematically in Figure 2. The received light is mixed with the beam of a highly stable, continuous-wave laser called the local oscillator (LO). The sum of the two electromagnetic waves – backscattered and local oscillator – is converted into an electrical signal by a quadratic detector (producing an electrical current proportional to the power of the electromagnetic wave illuminating its sensitive surface). An analogue, high-pass filter is then applied for eliminating the low-frequency components of the signal, and a low-pass filter is also applied to avoid problems caused by aliasing in the subsequent signal processing.