



SLOVENSKI STANDARD
SIST ISO 21542:2022

01-april-2022

Gradnja stavb - Dostopnost in uporabnost grajenega okolja

Building construction - Accessibility and usability of the built environment

Cadre bâti - Accessibilité et usage de l'environnement bâti

Ta slovenski standard je istoveten z: ISO 21542:2021

**iTeh STANDARD
PREVIEW
(standards.itih.ai)**

ICS:

| | | SIST ISO 21542:2022 |
|-----------|--|--|
| 11.180.01 | Pripomočki za onespobljene in hendikepirane osebe na splošno | Aids for disabled and handicapped persons in general |
| 91.060.01 | Stavbni elementi na splošno | Elements of buildings in general |

SIST ISO 21542:2022

en,fr,de

**iTeh STANDARD
PREVIEW
(standards.iteh.ai)**

[SIST ISO 21542:2022](https://standards.iteh.ai/catalog/standards/sist/2a311ced-5518-409f-b6e2-e49b130ea98b/sist-iso-21542-2022)

<https://standards.iteh.ai/catalog/standards/sist/2a311ced-5518-409f-b6e2-e49b130ea98b/sist-iso-21542-2022>

INTERNATIONAL
STANDARD

ISO
21542

Second edition
2021-06

**Building construction — Accessibility
and usability of the built environment**

Cadre bâti — Accessibilité et usage de l'environnement bâti

**iTeh STANDARD
PREVIEW
(standards.iteh.ai)**

[SIST ISO 21542:2022](https://standards.iteh.ai/catalog/standards/sist/2a311ced-5518-409f-b6e2-e49b130ea98b/sist-iso-21542-2022)

<https://standards.iteh.ai/catalog/standards/sist/2a311ced-5518-409f-b6e2-e49b130ea98b/sist-iso-21542-2022>



Reference number
ISO 21542:2021(E)

© ISO 2021

**iTeh STANDARD
PREVIEW
(standards.iteh.ai)**

[SIST ISO 21542:2022](https://standards.iteh.ai/catalog/standards/sist/2a311ced-5518-409f-b6e2-e49b130ea98b/sist-iso-21542-2022)

<https://standards.iteh.ai/catalog/standards/sist/2a311ced-5518-409f-b6e2-e49b130ea98b/sist-iso-21542-2022>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

| | Page |
|---|------------|
| Foreword | vii |
| Introduction | ix |
| 1 Scope | 1 |
| 2 Normative references | 1 |
| 3 Terms and definitions | 2 |
| 4 General design considerations | 7 |
| 4.1 General..... | 7 |
| 4.2 Key accessibility issues..... | 8 |
| 5 Orientation and information outside and inside of a building | 11 |
| 5.1 Orientation and information..... | 11 |
| 5.1.1 General..... | 11 |
| 5.1.2 Levels of information..... | 11 |
| 5.1.3 Principle of multiple senses..... | 12 |
| 5.1.4 Tactile walking surface indicators – TWSI..... | 12 |
| 5.2 Floor and wall surfaces..... | 13 |
| 5.3 Visual contrast..... | 13 |
| 5.3.1 General..... | 13 |
| 5.3.2 Luminance contrast..... | 14 |
| 5.3.3 Luminance contrast of glossy or shiny materials..... | 14 |
| 5.3.4 Choice of colours and patterns..... | 15 |
| 5.3.5 Relevant design factors..... | 16 |
| 5.4 Lighting..... | 17 |
| 5.4.1 General..... | 17 |
| 5.4.2 External lighting..... | 17 |
| 5.4.3 Lighting inside buildings..... | 18 |
| 5.4.4 Lighting to facilitate wayfinding..... | 18 |
| 5.4.5 Controllable and adjustable lighting..... | 18 |
| 5.4.6 Light levels in different areas..... | 18 |
| 5.4.7 Glare and shadows..... | 19 |
| 5.5 Signage..... | 19 |
| 5.5.1 General..... | 19 |
| 5.5.2 Types of signs..... | 20 |
| 5.5.3 Placement of signs..... | 20 |
| 5.5.4 Height and location of signs..... | 20 |
| 5.5.5 Font and size of lettering..... | 22 |
| 5.5.6 Luminance contrast..... | 22 |
| 5.5.7 Glare and illumination..... | 22 |
| 5.5.8 Understandability..... | 23 |
| 5.5.9 Provision of raised tactile and Braille signs..... | 23 |
| 5.5.10 Tactile characters, figures, signs and graphical symbols..... | 23 |
| 5.5.11 Braille..... | 24 |
| 5.5.12 Tactile symbols..... | 24 |
| 5.5.13 Tactile maps and floor plans..... | 24 |
| 5.5.14 Information displays..... | 25 |
| 5.6 Graphical symbols..... | 25 |
| 5.7 Acoustics..... | 30 |
| 5.7.1 General..... | 30 |
| 5.7.2 Control of noise..... | 31 |
| 5.7.3 Hearing enhancement..... | 32 |
| 5.8 Emergency warning systems, signals and information..... | 34 |
| 5.8.1 General..... | 34 |
| 5.8.2 Emergency warnings..... | 34 |

ISO 21542:2021(E)

| | | |
|----------|---|-----------|
| 5.8.3 | Audible emergency warnings | 34 |
| 5.8.4 | Visual emergency warning signals | 35 |
| 5.8.5 | Fire emergency warning systems | 35 |
| 6 | Approaching and entering a building or the built environment | 35 |
| 6.1 | General | 35 |
| 6.2 | Parking | 36 |
| 6.2.1 | Location of accessible parking spaces | 36 |
| 6.2.2 | Number of designated accessible parking spaces | 36 |
| 6.2.3 | Dimensional requirements for car parking spaces | 36 |
| 6.2.4 | Dimensional requirements for parking spaces for wheelchair accessible vans | 37 |
| 6.2.5 | Signage | 38 |
| 6.2.6 | Surface characteristics of accessible parking spaces | 39 |
| 6.2.7 | Kerb ramp from parking space to an adjacent higher pedestrian path | 39 |
| 6.2.8 | Accessible indoor parking spaces | 39 |
| 6.2.9 | Parking control | 40 |
| 6.2.10 | Storage spaces for powered wheelchairs, scooters and other mobility aids | 40 |
| 6.2.11 | Storage facilities for buggies and cycles | 40 |
| 6.2.12 | Drop-off areas | 40 |
| 6.3 | Paths to the building | 40 |
| 6.3.1 | General | 40 |
| 6.3.2 | Wayfinding, guided path and other physical information | 41 |
| 6.3.3 | Width of the path and passing and turning spaces for persons using a wheelchair | 42 |
| 6.3.4 | Stepped path and stairs | 43 |
| 6.3.5 | Landings of sloped paths | 44 |
| 6.3.6 | Handrail support and guidance on paths | 44 |
| 6.3.7 | Drainage of access and egress routes | 44 |
| 6.3.8 | Obstacles in a path | 44 |
| 6.4 | Ramps | 45 |
| 6.4.1 | General | 45 |
| 6.4.2 | Slope and length | 46 |
| 6.4.3 | Width of ramps | 48 |
| 6.4.4 | Landings of ramps | 48 |
| 6.4.5 | Handrail support and guidance by handrails on ramps | 48 |
| 6.4.6 | Drainage of ramps | 49 |
| 6.4.7 | Surface materials | 49 |
| 6.5 | Protection along paths and ramps | 49 |
| 6.6 | Building entrances and final fire exits | 50 |
| 6.6.1 | General | 50 |
| 6.6.2 | Thresholds at entrances and final fire exits | 51 |
| 6.6.3 | Circulation space at entrance doors and final fire exits | 51 |
| 6.6.4 | Space requirements between doors in series and in vestibules | 52 |
| 7 | Horizontal circulation in a building | 53 |
| 7.1 | Internal circulation routes and manoeuvring spaces | 53 |
| 7.1.1 | General | 53 |
| 7.1.2 | Internal circulation routes/corridors | 53 |
| 7.1.3 | Turning space for 90° turn of a wheelchair in corridors | 53 |
| 7.1.4 | Turning space for 180° wheelchair turn | 54 |
| 7.2 | Moving walks | 55 |
| 8 | Vertical circulation in a building | 55 |
| 8.1 | General | 55 |
| 8.2 | Ramps in buildings | 55 |
| 8.3 | Stairs | 55 |
| 8.3.1 | General | 55 |
| 8.3.2 | Rise and going of steps | 55 |
| 8.3.3 | Minimum width of stair flights | 56 |
| 8.3.4 | Staircase landings | 56 |

| | | |
|-----------|---|-----------|
| 8.3.5 | Head clearance | 57 |
| 8.3.6 | Visual and tactile warnings | 58 |
| 8.3.7 | Handrails and guards along stairs | 60 |
| 8.4 | Handrails | 60 |
| 8.4.1 | General | 60 |
| 8.4.2 | Characteristics of a handrail | 60 |
| 8.4.3 | Continuity of a handrail | 61 |
| 8.4.4 | Height of a handrail | 61 |
| 8.4.5 | Horizontal extension of a handrail | 61 |
| 8.4.6 | Visual and tactile information | 61 |
| 8.4.7 | Mechanical resistance | 62 |
| 8.5 | Lifts | 62 |
| 8.5.1 | General | 62 |
| 8.5.2 | Approach and access to the lift | 63 |
| 8.5.3 | Lift car entrance — Door opening | 64 |
| 8.5.4 | Entrance width and inner dimensions of cars | 64 |
| 8.5.5 | Equipment in the car | 65 |
| 8.5.6 | Stopping/Levelling accuracy | 67 |
| 8.5.7 | Control devices and signals | 67 |
| 8.5.8 | Lifts used for evacuation | 70 |
| 8.6 | Vertical and inclined lifting platforms | 71 |
| 8.7 | Escalators and moving walks | 71 |
| 9 | Components of a building and building equipment | 72 |
| 9.1 | Doorsets and windows | 72 |
| 9.1.1 | Doors and door furniture | 72 |
| 9.1.2 | Fire-resisting doorsets | 80 |
| 9.1.3 | Windows and window furniture | 81 |
| 9.2 | Equipment, controls and switches | 81 |
| 9.2.1 | General | 81 |
| 9.2.2 | Location, heights and distances | 82 |
| 9.2.3 | Operation | 83 |
| 9.2.4 | Identification | 83 |
| 9.2.5 | Usability and consistency in design | 83 |
| 9.2.6 | Intercoms and telephones | 83 |
| 9.2.7 | Card and vending machines | 84 |
| 9.2.8 | Security access systems | 86 |
| 9.2.9 | Drinking fountains | 86 |
| 9.2.10 | Waste disposals and containers | 86 |
| 9.3 | Furnishing | 86 |
| 9.3.1 | General | 86 |
| 9.3.2 | Seating in waiting areas | 86 |
| 9.3.3 | Seating at desks or tables | 87 |
| 10 | Rooms and spaces within non-domestic buildings | 88 |
| 10.1 | Reception areas, counters, desks and ticket offices | 88 |
| 10.1.1 | General | 88 |
| 10.1.2 | Space to manoeuvre | 88 |
| 10.1.3 | Height | 88 |
| 10.1.4 | Lighting | 89 |
| 10.1.5 | Hearing and lipreading | 89 |
| 10.1.6 | Ticket systems | 89 |
| 10.2 | Cloakroom | 90 |
| 10.3 | Conference rooms and meeting rooms | 90 |
| 10.4 | Auditoriums, concert halls, sports arenas, viewing spaces in assembly areas and similar | 90 |
| 10.4.1 | General | 90 |
| 10.4.2 | Hearing enhancement systems | 90 |
| 10.4.3 | Lighting for sign language interpretation | 90 |

ISO 21542:2021(E)

| | | |
|----------------|---|------------|
| 10.4.4 | Designated seating spaces for persons using a wheelchair | 90 |
| 10.4.5 | Lines of sight over seated and standing spectators | 91 |
| 10.4.6 | Row and seat numbers | 92 |
| 10.4.7 | Access to stage and backstage | 92 |
| 10.5 | Toilet rooms, sanitary rooms and bathrooms | 92 |
| 10.5.1 | General | 92 |
| 10.5.2 | WC compartments for ambulant persons with disabilities | 92 |
| 10.5.3 | Dimensions for wheelchair accessible toilet rooms | 93 |
| 10.5.4 | Toilet room doors | 98 |
| 10.5.5 | Toilet seat | 98 |
| 10.5.6 | Grab rails | 99 |
| 10.5.7 | Toilet paper dispensers | 99 |
| 10.5.8 | Washbasin | 99 |
| 10.5.9 | Water supply | 102 |
| 10.5.10 | Taps | 102 |
| 10.5.11 | Urinals | 102 |
| 10.5.12 | Other fittings | 103 |
| 10.5.13 | Assistance alarm | 103 |
| 10.5.14 | Fire emergency warning devices | 103 |
| 10.5.15 | Showers | 103 |
| 10.5.16 | Bathrooms | 105 |
| 10.6 | Accessible bedrooms | 108 |
| 10.7 | Accessible changing rooms | 109 |
| 10.8 | Kitchen areas | 110 |
| 10.9 | Storage areas | 110 |
| 10.10 | Terraces, verandas and balconies | 110 |
| 10.11 | Bars, pubs and restaurants | 110 |
| 10.12 | Facilities for guide and other assistance dogs | 111 |
| 10.12.1 | General | 111 |
| 10.12.2 | Relief facilities for guide and assistance dogs | 111 |
| 11 | Fire safety and evacuation | 111 |
| 11.1 | General | 111 |
| 11.2 | Design objectives | 112 |
| 11.3 | Principles of fire evacuation | 112 |
| 11.4 | Emergency evacuation related building infrastructure | 113 |
| 11.4.1 | Overview on essential building infrastructure | 113 |
| 11.4.2 | Emergency evacuation routes | 113 |
| 11.4.3 | Places of relative safety | 113 |
| 11.4.4 | Lift evacuation systems | 113 |
| 11.4.5 | Areas of rescue assistance adjoining fire evacuation staircases | 114 |
| 11.4.6 | Fire evacuation staircases | 115 |
| 11.4.7 | Floors of temporary refuge | 115 |
| 11.4.8 | Final fire exit doors and fire-resisting doors | 116 |
| 11.4.9 | Fire safety plans | 116 |
| 12 | Management and maintenance issues | 116 |
| Annex A | (informative) Housing | 117 |
| Annex B | (informative) Tactile walking surface indicators (TWSI) | 125 |
| Annex C | (informative) Circulation spaces at doorways | 129 |
| Annex D | (informative) Fire prevention, protection, safety and evacuation for all | 142 |
| Annex E | (informative) Methods for the determination of the luminance contrast | 146 |
| Annex F | (informative) Management and maintenance issues | 153 |
| Annex G | (informative) Human abilities and associated design considerations | 156 |
| | Bibliography | 166 |

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 59, *Buildings and civil engineering works*, Subcommittee SC 16, *Accessibility and usability of the built environment*.

This second edition cancels and replaces the first edition (ISO 21542:2011), which has been technically revised.

The main changes compared to the previous edition are as follows:

- a) document structure: a new hierarchy level has been introduced and the clauses have been assigned accordingly and partly resorted (e.g. [Clause 5](#));
- b) editorial revision of the Introduction and the Scope;
- c) modification of the approach of exceptional considerations, which now only apply to existing buildings;
- d) update of the normative references throughout the document;
- e) revision of [Clause 3](#) on terms and definitions according to the terminology used in the document and update of the sources;
- f) restructuring of several (sub)clauses, especially those on:
 - orientation and information ([5.1](#));
 - lighting ([5.4](#));
 - acoustics ([5.7](#));
 - paths to the building ([6.3](#));
 - building entrances and final fire exits ([6.5](#));
 - vertical and inclined lifting platforms ([8.6](#));

ISO 21542:2021(E)

- doorsets and windows ([9.1](#));
 - rooms and space within non-domestic buildings ([Clause 10](#));
- g) the provisions regarding tactile walking surface indicators (TWSI) have been adapted:
- ISO 23599:2019 has been widely referenced;
 - a new subclause on tactile walking surface indicators has been introduced to [5.1](#);
 - the annex on tactile walking surface indicators was revised and shortened;
- h) revision of the provisions regarding visual contrast:
- the specifications in [5.3](#) have been revised and the relevant design factors were moved from the annex on human abilities and associated design considerations to it;
 - a separate annex for the determination of the luminance contrast has been created;
- i) complete revision and enlargement of the specifications on acoustics in [5.7](#) and emergency warning systems, signals and information in [5.8](#);
- j) clarification and enlargement of the specifications on solitary obstacles in a path in [6.3.8](#);
- k) complete revision of [6.4](#) on ramps and [8.5](#) on lifts;
- l) enlargement of the specifications on control devices and signals ([9.2](#)) and drinking fountains ([9.2.9](#));
- m) revision of the clauses related to (fire) emergency evacuation:
- merger of the specifications related to (fire) emergency evacuation in [Clause 11](#) but keeping the specifications on emergency warning systems in [5.8](#), on lifts used for evacuation in [8.5.8](#) and on fire-resisting doorsets [9.1.2](#);
 - introduction of a subclause on emergency evacuation related building infrastructure;
 - complete revision of the annex on fire prevention, protection, safety and evacuation ([Annex D](#));
- n) introduction of a new informative annex on housing ([Annex A](#));
- o) editorial revision of existing figures, removal of redundant figures and provision of new figures;
- p) update of the Bibliography including the removal of national standards.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

This document provides essential requirements and necessary recommendations for the realization of a safe, inclusive, age-friendly and sustainable built environment that is accessible and usable by all.

The purpose of this document is to describe how a building should be designed, constructed, managed and maintained in order to enable people to: approach and enter the building; use the building's facilities, services and information networks; egress from the building under normal conditions; and evacuate the building during an emergency.

Accessibility and usability for all is a dynamic and continuously evolving concept – a fundamental attribute of a sustainable built environment. It is a process of interlinked actions and tasks in the everyday lives of people, which enables them to be educated, to get a job, to participate fully in a community, and to feel socially included. Just one barrier, physical or otherwise, to that participation can restrict, terminate and make void the whole process.

The intention of this document is to meet the needs of the broadest majority of people. This goal is achieved by agreement on minimum standards of provision that are generally accepted to accommodate human diversity and variation, in age, ability, and behaviour, common in every society.

When the infrastructure of accessibility and usability is fully and effectively in place, good building management practice and procedures are essential to maintain original as-built or as-adapted performance during the life cycle of the building and, in the event of a fire or other emergency incidents, to ensure that the intended safety strategy is successfully initiated and executed.

The principles of accessibility and usability for all are supported by Preamble Paragraph (g), and Articles 9, 10, 11, 12 and 19 of the United Nations (UN) Convention on the Rights of Persons with Disabilities. These principles are reinforced by

- the UN 2015-2030 Sustainable Development Framework Agenda, particularly Sustainable Development Goal 11: 'Sustainable Cities & Communities';
- the World Health Organization's 2016-2020 Global Strategy & Action Plan on Ageing & Health.

NOTE 1 The United Nations Convention on the Rights of Persons with Disabilities (CRPD), with its Optional Protocol, was adopted by the General Assembly on 13 December 2006. It came into force, i.e. it became an international legal instrument, on 3 May 2008. Full information can be found on the UN website: <https://www.un.org/development/desa/disabilities/convention-on-the-rights-of-persons-with-disabilities.html>.

NOTE 2 Protection of persons with disabilities during severe natural events, e.g. earthquakes, floods, landslides, typhoons and tsunamis, is dealt with under the Sendai Framework on Disaster Risk Reduction (2015 - 2030), which forms part of the UN Sustainable Development Framework Agenda.

If the design requirements and recommendations in this document are taken into consideration during the earliest stages of a new building design, the financial cost of providing accessibility and usability measures is minimal, and the completed building is safer and more user-friendly for every building user. For all existing buildings, effort should be made to meet the requirements to make them accessible and usable. It is also important to ensure that buildings of historical, architectural and cultural importance are accessible.

Where these design requirements are not considered, the socio-economic cost is considerable in terms of human rights violations and a significant reduction in building user safety and satisfaction.

ISO/IEC Guide 71, and its guidance document ISO/TR 22411, augment and assist in understanding the requirements of this document.

At present, consideration is being given to the development of further documents to especially deal with environments for children with disabilities and cultural heritage.

**iTeh STANDARD
PREVIEW
(standards.iteh.ai)**

[SIST ISO 21542:2022](https://standards.iteh.ai/catalog/standards/sist/2a311ced-5518-409f-b6e2-e49b130ea98b/sist-iso-21542-2022)

<https://standards.iteh.ai/catalog/standards/sist/2a311ced-5518-409f-b6e2-e49b130ea98b/sist-iso-21542-2022>

Building construction — Accessibility and usability of the built environment

IMPORTANT — The electronic file of this document contains colours which are considered to be useful for the correct understanding of the document. Users should therefore consider printing this document using a colour printer.

1 Scope

This document specifies a range of requirements and recommendations for the elements of construction, building assemblies, components, fittings and products that relate to the design and constructional aspects of usability and accessibility of buildings, i.e. access to buildings, circulation within buildings, egress from buildings during normal conditions, and evacuation in the event of a fire.

This document also applies to the common spaces in multi-unit residential buildings. Recommendations regarding residential units are given in [Annex A](#).

This document also contains provisions with respect to outdoor features directly concerned with access to a building or a group of buildings from a relevant site boundary, or between such a group of buildings within a common site. This document does not deal with elements of the external environment, such as public open spaces, whose function is self-contained and unrelated to the use of a specific building.

This document is applicable to new buildings and new work in existing buildings.

This document introduces the concept of 'exceptional considerations for existing buildings' for situations where it is exceptionally difficult to meet the requirements specified and, thus, impossible to provide full accessibility. By means of 'exceptional considerations for existing buildings', an acceptable, though restricted, level of accessibility is specified. An exceptional consideration for existing buildings is not to be applied in other situations or invoked in an unjustified manner, or as an excuse for not achieving a higher level of accessibility, where this is economically and/or technically feasible.

The dimensions stated in this document, relevant to the use of wheelchairs, are related to the footprint of commonly used wheelchair sizes and users as specified in ISO 7176-5 and ISO/TR 13570-2, 800 mm wide and 1 300 mm long.

This document is primarily written for adults with disabilities, but it includes some recommendations on specific accessibility needs of children.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC Guide 71, *Guide for addressing accessibility in standards*

ISO 4190-5:2006, *Lift (Elevator) installation — Part 5: Control devices, signals and additional fittings*

ISO 8100-1:2019, *Lifts for the transport of persons and goods — Part 1: Safety rules for the construction and installation of passenger and goods passenger lifts*

ISO 8100-30:2019, *Lifts for the transport of persons and goods — Part 30: Class I, II, III and VI lifts installation*

ISO 9386-1, *Power-operated lifting platforms for persons with impaired mobility — Rules for safety, dimensions and functional operation — Part 1: Vertical lifting platforms*

ISO 21542:2021(E)

ISO 9386-2, *Power-operated lifting platforms for persons with impaired mobility — Rules for safety, dimensions and functional operation — Part 2: Powered stairlifts for seated, standing and wheelchair users moving in an inclined plane*

ISO 23599:2019, *Assistive products for blind and vision-impaired persons — Tactile walking surface indicators*

IEC 60118-4, *Electroacoustics — Hearing aids — Part 4: Induction-loop systems for hearing aid purposes – System performance requirements*

IEC 60268-16, *Sound system equipment — Part 16: Objective rating of speech intelligibility by speech transmission index*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/IEC Guide 71 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1 accessibility

provision of buildings or parts of buildings for people, regardless of their age, size, ability or disability, to be able to gain access to them, into them, to use them and exit from them

Note 1 to entry: Accessibility includes ease of independent approach, entry, evacuation and/or use of a building and its services and facilities, by all of the building's potential users with an assurance of individual health, safety and welfare during the course of those activities.

3.2 area of rescue assistance

area of refuge

building space that has been designed for people to temporarily wait in safety and with confidence for further information, instructions, and evacuation assistance or rescue, without obstructing or interfering with the evacuation of others

3.3 attention pattern

TWSI (3.33) design, calling attention to a hazard only, or to hazards and decision points

[SOURCE: ISO 23599:2019, 3.1, modified — Note 1 to entry has been removed.]

3.4 built environment

external and internal environments and any element, component or fitting that is commissioned, designed, constructed and managed for use by people

Note 1 to entry: Loose items are excluded because decisions with respect to their location within the built environment are more likely to be under the day-to-day control of facilities managers and not of those who commission, design or construct the built environment.

3.5 circulation space

unobstructed space necessary for access to, into and within and egress from any part of the *built environment* (3.4)

3.6**counterflow**

emergency access by firefighters or rescue teams into a building and towards a fire, while building users are still moving away from the fire and being evacuated from the building

3.7**doorset**

assembly consisting of a fixed part (door frame), one or more movable parts (door leaves), and their door furniture, the function of which is to allow or to prevent access and egress to a room or a building

Note 1 to entry: A doorset can also include, at floor level, a door saddle (also known as a sill or threshold).

3.8**fire compartment**

enclosed space, which may be subdivided, separated from adjoining spaces by fire barriers

[SOURCE: ISO 13943:2017, 3.120]

3.9**fire emergency management plan**

description of the fire emergency response procedures for an occupied building with the aim of ensuring the safety and health of all building users in the event of a fire emergency

Note 1 to entry: It includes information about the building's fire safety preparedness and prevention measures, the pre-emergency, emergency and post-emergency roles, duties and responsibilities assigned to building management personnel.

3.10**fire evacuation**

planned and orderly phased movements to withdraw, or cause to withdraw, all users from a building via accessible routes to one or more accessible *places of safety* (3.20) in the event of a fire emergency

3.11**going**

tread

tread depth

<stair> horizontal distance between two consecutive nosings

SIST ISO 21542:2022

<https://standards.iteh.ai/catalog/standards/sist/2a311ced-5518-409f-b6e2-e49b130ea98b/sist-iso-21542-2022>

3.12**guiding pattern**

TWSI (3.33) design, indicating a direction of travel or a landmark

[SOURCE: ISO 23599:2019, 3.8, modified — Note 1 to entry has been removed.]

3.13**handrail**

component providing support and grip for users

[SOURCE: ISO 6707-1:2020, 3.3.2.75]

3.14**hearing enhancement system**

piece of equipment, product system, hardware, software or service that is used to increase, maintain or improve hearing capabilities of individuals with *hearing impairments* (3.15)

Note 1 to entry: Hearing enhancement systems amplify audible communication and can be helpful to people who have hearing loss. They include a direct wire system, an *induction loop* (3.17) system, an infrared system, or a radio frequency system. All of these systems transmit a signal. Special-purpose receivers are required for infrared and radio frequency systems, while hearing aids equipped with a T-switch can receive the signal from an induction loop system. Receivers can be equipped to be compatible with hearing aids.