
**Information technology — High
efficiency coding and media delivery
in heterogeneous environments —**

**Part 2:
High efficiency video coding**

**AMENDMENT 1: Additional colour
representation code point**

*Technologies de l'information — Codage à haute efficacité et livraison
des médias dans des environnements hétérogènes —*
Partie 2: Codage vidéo à haute efficacité

*AMENDEMENT 1: Point de codage de représentation de couleur
supplémentaire*



iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/IEC 23008-2:2017/Amd 1:2018
<https://standards.iteh.ai/catalog/standards/sist/23dded3f-84ec-4fec-b3ec-45102b50a8fb/iso-iec-23008-2-2017-amd-1-2018>



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information* in collaboration with ITU-T. A technically aligned twin text is published as ITU-T H.265.

A list of all parts in the ISO/IEC 23008 series can be found on the ISO website.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 23008-2:2017/Amd 1:2018](https://standards.iteh.ai/catalog/standards/sist/23dded3f-84ec-4fec-b3ec-45102b50a8fb/iso-iec-23008-2-2017-amd-1-2018)

<https://standards.iteh.ai/catalog/standards/sist/23dded3f-84ec-4fec-b3ec-45102b50a8fb/iso-iec-23008-2-2017-amd-1-2018>

Information technology — High efficiency coding and media delivery in heterogeneous environments —

Part 2: High efficiency video coding

AMENDMENT 1: Additional colour representation code point

Page 19, Clause 4: Abbreviated terms

Add the following additional items (interspersed with the existing items in alphabetical order):

FCC Federal Communications Commission (of the United States)

NTSC National Television System Committee (of the United States)

SMPTE Society of Motion Picture and Television Engineers

Page 446, Annex E

iTeh STANDARD PREVIEW

(standards.iteh.ai)

In E.3.1, replace the semantics of `video_full_range_flag`, `colour_description_present_flag`, `colour_primaries`, `transfer_characteristics`, and `matrix_coeffs`, including [Tables E.3](#), [E.4](#), and [E.5](#), with the following.

[ISO/IEC 23008-2:2017/Amd 1:2018](https://standards.iteh.ai/catalog/standards/sist/23dded3f-84ec-4fec-b3ec-45102b50a8fb/iso-iec-23008-2-2017-amd-1-2018)

<https://standards.iteh.ai/catalog/standards/sist/23dded3f-84ec-4fec-b3ec-45102b50a8fb/iso-iec-23008-2-2017-amd-1-2018>

video_full_range_flag indicates the black level and range of the luma and chroma signals as derived from E'_Y , E'_{PB} , and E'_{PR} or E'_R , E'_G , and E'_B real-valued component signals.

When the `video_full_range_flag` syntax element is not present, the value of `video_full_range_flag` is inferred to be equal to 0.

colour_description_present_flag equal to 1 specifies that `colour_primaries`, `transfer_characteristics`, and `matrix_coeffs` are present. `colour_description_present_flag` equal to 0 specifies that `colour_primaries`, `transfer_characteristics`, and `matrix_coeffs` are not present.

colour_primaries indicates the chromaticity coordinates of the source primaries as specified in [Table E.3](#) in terms of the CIE 1931 definition of x and y as specified in ISO 11664-1.

When the `colour_primaries` syntax element is not present, the value of `colour_primaries` is inferred to be equal to 2 (the chromaticity is unspecified or is determined by the application). Values of `colour_primaries` that are identified as reserved in [Table E.3](#) are reserved for future use by ITU-T | ISO/IEC and shall not be present in bitstreams conforming to this version of this document. Decoders shall interpret reserved values of `colour_primaries` as equivalent to the value 2.

Table E.3 — Colour primaries interpretation using the colour_primaries syntax element

Value	Primaries			Informative remark
0	Reserved			For future use by ITU-T ISO/IEC
1	primary	x	y	Rec. ITU-R BT.709-6
	green	0.300	0.600	Rec. ITU-R BT.1361-0 conventional colour gamut system and extended colour gamut system (historical)
	blue	0.150	0.060	IEC 61966-2-1 sRGB or sYCC
	red	0.640	0.330	IEC 61966-2-4
	white D65	0.312 7	0.329 0	SMPTE RP 177 (1993) Annex B
2	Unspecified			Image characteristics are unknown or are determined by the application.
3	Reserved			For future use by ITU-T ISO/IEC
4	primary	x	y	Rec. ITU-R BT.470-6 System M (historical)
	green	0.21	0.71	NTSC Recommendation for transmission standards for colour television (1953)
	blue	0.14	0.08	FCC Title 47 Code of Federal Regulations (2003) 73.682 (a) (20)
	red	0.67	0.33	
	white C	0.310	0.316	
5	primary	x	y	Rec. ITU-R BT.470-6 System B, G (historical)
	green	0.29	0.60	Rec. ITU-R BT.601-7 625
	blue	0.15	0.06	Rec. ITU-R BT.1358-0 625 (historical)
	red	0.64	0.33	Rec. ITU-R BT.1700-0 625 PAL and 625 SECAM
	white D65	0.312 7	0.329 0	
6	primary	x	y	Rec. ITU-R BT.601-7 525
	green	0.310	0.595	Rec. ITU-R BT.1358-1 525 or 625 (historical)
	blue	0.155	0.070	Rec. ITU-R BT.1700-0 NTSC
	red	0.630	0.340	SMPTE ST 170 (2004)
	white D65	0.312 7	0.329 0	(functionally the same as the value 7)
7	primary	x	y	SMPTE ST 240 (1999, historical)
	green	0.310	0.595	(functionally the same as the value 6)
	blue	0.155	0.070	
	red	0.630	0.340	
	white D65	0.312 7	0.329 0	
8	primary	x	y	Generic film (colour filters using Illuminant C)
	green	0.243	0.692 (Wratten 58)	
	blue	0.145	0.049 (Wratten 47)	
	red	0.681	0.319 (Wratten 25)	
	white C	0.310	0.316	
9	primary	x	y	Rec. ITU-R BT.2020-2
	green	0.170	0.797	Rec. ITU-R BT.2100-1
	blue	0.131	0.046	
	red	0.708	0.292	
	white D65	0.312 7	0.329 0	

Table E.3 (continued)

Value	Primaries			Informative remark
10	primary	x	y	SMPTE ST 428-1 (2006) (CIE 1931 XYZ)
	green (Y)	0.0	1.0	
	blue (Z)	0.0	0.0	
	red (X)	1.0	0.0	
	centre white	1 ÷ 3	1 ÷ 3	
11	primary	x	y	SMPTE RP 431-2 (2011)
	green	0.265	0.690	
	blue	0.150	0.060	
	red	0.680	0.320	
	white	0.314	0.351	
12	primary	x	y	SMPTE EG 432-1 (2010)
	green	0.265	0.690	
	blue	0.150	0.060	
	red	0.680	0.320	
	white D65	0.312 7	0.329 0	
13...21	Reserved			For future use by ITU-T ISO/IEC
22	primary	x	y	EBU Tech. 3213-E (1975)
	green	0.295	0.605	
	blue	0.155	0.077	
	red	0.630	0.340	
	white D65	0.312 7	0.329 0	
23...255	Reserved			For future use by ITU-T ISO/IEC

transfer_characteristics, as specified in [Table E.4](#), either indicates the reference opto-electronic transfer characteristic function of the source picture as a function of a source input linear optical intensity L_c with a nominal real-valued range of 0 to 1 or indicates the inverse of the reference electro-optical transfer characteristic function as a function of an output linear optical intensity L_o with a nominal real-valued range of 0 to 1. For interpretation of entries in [Table E.4](#) that are expressed in terms of multiple curve segments parameterized by the variable α over a region bounded by the variable β or by the variables β and γ , the values of α and β are defined to be the positive constants necessary for the curve segments that meet at the value β to have continuity of value and continuity of slope at the value β , and the value of γ , when applicable, is defined to be the positive constant necessary for the associated curve segments to meet at the value γ . For example, for transfer_characteristics equal to 1, 6, 11, 14, or 15, α has the value $1 + 5.5 * \beta = 1.099\ 296\ 826\ 809\ 442\dots$ and β has the value $0.018\ 053\ 968\ 510\ 807\dots$

When the transfer_characteristics syntax element is not present, the value of transfer_characteristics is inferred to be equal to 2 (the transfer characteristics are unspecified or are determined by the application). Values of transfer_characteristics that are identified as reserved in [Table E.4](#) are reserved for future use by ITU-T | ISO/IEC and shall not be present in bitstreams conforming to this version of this document. Decoders shall interpret reserved values of transfer_characteristics as equivalent to the value 2.

NOTE 5 As indicated in [Table E.4](#), some values of transfer_characteristics are defined in terms of a reference opto-electronic transfer characteristic function and others are defined in terms of a reference electro-optical transfer characteristic function, according to the convention that has been applied in other documents. In the cases of Rec. ITU-R BT.709-6 and Rec. ITU-R BT.2020-2 (which could be indicated by transfer_characteristics equal to 1, 6, 14, or 15), although the value is defined in terms of a reference opto-electronic transfer characteristic function, a suggested corresponding reference electro-optical transfer characteristic function for flat panel displays used in HDTV studio production has been specified in Rec. ITU-R BT.1886-0.

Table E.4 — Transfer characteristics interpretation using the transfer_characteristics syntax element

Value	Transfer characteristics	Informative remark
0	Reserved	For future use by ITU-T ISO/IEC
1	$V = \alpha * L_c^{0.45} - (\alpha - 1)$ for $1 \geq L_c \geq \beta$ $V = 4.500 * L_c$ for $\beta > L_c \geq 0$	Rec. ITU-R BT.709-6 Rec. ITU-R BT.1361-0 conventional colour gamut system (historical) (functionally the same as the values 6, 14, and 15)
2	Unspecified	Image characteristics are unknown or are determined by the application.
3	Reserved	For future use by ITU-T ISO/IEC
4	Assumed display gamma 2.2	Rec. ITU-R BT.470-6 System M (historical) NTSC Recommendation for transmission standards for colour television (1953) FCC Title 47 Code of Federal Regulations (2003) 73.682 (a) (20)
5	Assumed display gamma 2.8	Rec. ITU-R BT.470-6 System B, G (historical) Rec. ITU-R BT.1700-0 625 PAL and 625 SECAM
6	$V = \alpha * L_c^{0.45} - (\alpha - 1)$ for $1 \geq L_c \geq \beta$ $V = 4.500 * L_c$ for $\beta > L_c \geq 0$	Rec. ITU-R BT.601-7 525 or 625 Rec. ITU-R BT.1358-1 525 or 625 (historical) Rec. ITU-R BT.1700-0 NTSC SMPTE ST 170 (2004) (functionally the same as the values 1, 14, and 15)
7	$V = \alpha * L_c^{0.45} - (\alpha - 1)$ for $1 \geq L_c \geq \beta$ $V = 4.0 * L_c$ for $\beta > L_c \geq 0$	SMPTE ST 240 (1999, historical)
8	$V = L_c$ for all values of L_c	Linear transfer characteristics
9	$V = 1.0 + \text{Log}10(L_c) \div 2$ for $1 \geq L_c \geq 0.01$ $V = 0.0$ for $0.01 > L_c \geq 0$	Logarithmic transfer characteristic (100:1 range)
10	$V = 1.0 + \text{Log}10(L_c) \div 2.5$ for $1 \geq L_c \geq \text{Sqrt}(10) \div 1\ 000$ $V = 0.0$ for $\text{Sqrt}(10) \div 1\ 000 > L_c \geq 0$	Logarithmic transfer characteristic (100 * Sqrt(10) : 1 range)
11	$V = \alpha * L_c^{0.45} - (\alpha - 1)$ for $L_c \geq \beta$ $V = 4.500 * L_c$ for $\beta > L_c > -\beta$ $V = -\alpha * (-L_c)^{0.45} + (\alpha - 1)$ for $-\beta \geq L_c$	IEC 61966-2-4
12	$V = \alpha * L_c^{0.45} - (\alpha - 1)$ for $1,33 > L_c \geq \beta$ $V = 4.500 * L_c$ for $\beta > L_c \geq -\gamma$ $V = -[\alpha * (-4 * L_c)^{0.45} - (\alpha - 1)] \div 4$ for $-\gamma > L_c \geq -0.25$	Rec. ITU-R BT.1361-0 extended colour gamut system (historical)
13	$V = \alpha * L_c^{(1 \div 2.4)} - (\alpha - 1)$ for $1 \geq L_c \geq \beta$ $V = 12.92 * L_c$ for $\beta > L_c \geq 0$	IEC 61966-2-1 sRGB or sYCC

Table E.4 (continued)

Value	Transfer characteristics	Informative remark
14	$V = \alpha * L_c^{0.45} - (\alpha - 1)$ for $1 \geq L_c \geq \beta$ $V = 4.500 * L_c$ for $\beta > L_c \geq 0$	Rec. ITU-R BT.2020-2 (functionally the same as the values 1, 6, and 15)
15	$V = \alpha * L_c^{0.45} - (\alpha - 1)$ for $1 \geq L_c \geq \beta$ $V = 4.500 * L_c$ for $\beta > L_c \geq 0$	Rec. ITU-R BT.2020-2 (functionally the same as the values 1, 6, and 14)
16	$V = ((c_1 + c_2 * L_o^n) \div (1 + c_3 * L_o^n))^m$ for all values of L_o $c_1 = c_3 - c_2 + 1 = 3\,424 \div 4\,096 = 0.835\,937\,5$ $c_2 = 32 * 2\,413 \div 4\,096 = 18.851\,562\,5$ $c_3 = 32 * 2\,392 \div 4\,096 = 18.687\,5$ $m = 128 * 2\,523 \div 4\,096 = 78.843\,75$ $n = 0.25 * 2\,610 \div 4\,096 = 0.159\,301\,757\,812\,5$ for which L_o equal to 1 for peak white is ordinarily intended to correspond to a reference output luminance level of 10 000 cd/m ²	SMPTE ST 2084 (2014) for 10, 12, 14, and 16-bit systems Rec. ITU-R BT.2100-1 perceptual quantization (PQ) system
17	$V = (48 * L_o \div 52.37)^{(1 \div 2.6)}$ for all values of L_o for which L_o equal to 1 for peak white is ordinarily intended to correspond to a reference output luminance level of 48 cd/m ²	SMPTE ST 428-1 (2006)
18	$V = a * \text{Ln}(12 * L_c - b) + c$ for $1 \geq L_c > 1 \div 12$ $V = \text{Sqrt}(3) * L_c^{0.5}$ for $1 \div 12 \geq L_c \geq 0$ $a = 0.178\,832\,77, b = 0.284\,668\,92, c = 0.559\,910\,73$	Association of Radio Industries and Businesses (ARIB) STD-B67 Rec. ITU-R BT.2100-1 hybrid log-gamma (HLG) system
19..255	Reserved	For future use by ITU-T ISO/IEC

NOTE 6 For transfer characteristics equal to 18, the formulae given in Table E.4 are normalized for a source input linear optical intensity L_c with a nominal real-valued range of 0 to 1. An alternative scaling that is mathematically equivalent is used in ARIB STD-B67 with the source input linear optical intensity having a nominal real-valued range of 0 to 12.

matrix_coeffs describes the matrix coefficients used in deriving luma and chroma signals from the green, blue, and red, or Y, Z, and X primaries, as specified in Table E.5.

matrix_coeffs shall not be equal to 0 unless one or more of the following conditions are true:

- BitDepth_C is equal to BitDepth_Y.
- chroma_format_idc is equal to 3 (the 4:4:4 chroma format).

The specification of the use of matrix_coeffs equal to 0 under all other conditions is reserved for future use by ITU-T | ISO/IEC.

matrix_coeffs shall not be equal to 8 unless one of the following conditions is true:

- BitDepth_C is equal to BitDepth_Y,
- BitDepth_C is equal to BitDepth_Y + 1 and chroma_format_idc is equal to 3 (the 4:4:4 chroma format).

The specification of the use of matrix_coeffs equal to 8 under all other conditions is reserved for future use by ITU-T | ISO/IEC.

When the matrix_coeffs syntax element is not present, the value of matrix_coeffs is inferred to be equal to 2 (unspecified).