

---

**Kriogene posode - Gibke cevi (ISO/DIS 21012:2021)**

Cryogenic vessels - Hoses (ISO/DIS 21012:2021)

Kryo-Behälter - Schlauchleitungen (ISO/DIS 21012:2021)

Réipients cryogéniques - Tuyaux flexibles (ISO/DIS 21012:2021)

**Ta slovenski standard je istoveten z: prEN ISO 21012**

[oSIST prEN ISO 21012:2021](https://standards.iteh.ai/catalog/standards/sist/0a4c822d-9ad5-4ee0-bf5e-1cbde99c5c60/osist-pren-iso-21012-2021)

<https://standards.iteh.ai/catalog/standards/sist/0a4c822d-9ad5-4ee0-bf5e-1cbde99c5c60/osist-pren-iso-21012-2021>

**ICS:**

23.020.40	Protiv mrazu odporne posode (kriogenske posode)	Cryogenic vessels
83.140.40	Gumene cevi	Hoses

**oSIST prEN ISO 21012:2021**

**en,fr,de**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[oSIST prEN ISO 21012:2021](#)

<https://standards.iteh.ai/catalog/standards/sist/0a4c822d-9ad5-4ee0-bf5e-1cbde99c5c60/osist-pren-iso-21012-2021>

# DRAFT INTERNATIONAL STANDARD

## ISO/DIS 21012

ISO/TC 220

Secretariat: **AFNOR**Voting begins on:  
**2021-09-17**Voting terminates on:  
**2021-12-10**

---

---

## Cryogenic vessels — Hoses

*Réceptacles cryogéniques — Tuyaux flexibles*

ICS: 83.140.40; 23.020.40

### iTeh STANDARD PREVIEW (standards.iteh.ai)

[oSIST prEN ISO 21012:2021](https://standards.iteh.ai/catalog/standards/sist/0a4c822d-9ad5-4ee0-bf5e-1cbde99c5c60/osist-pren-iso-21012-2021)<https://standards.iteh.ai/catalog/standards/sist/0a4c822d-9ad5-4ee0-bf5e-1cbde99c5c60/osist-pren-iso-21012-2021>

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

This document is circulated as received from the committee secretariat.

**ISO/CEN PARALLEL PROCESSING**



Reference number  
ISO/DIS 21012:2021(E)

© ISO 2021

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[oSIST prEN ISO 21012:2021  
https://standards.iteh.ai/catalog/standards/sist/0a4c822d-9ad5-4ee0-bf5e-1cbde99c5c60/osist-pren-iso-21012-2021](https://standards.iteh.ai/catalog/standards/sist/0a4c822d-9ad5-4ee0-bf5e-1cbde99c5c60/osist-pren-iso-21012-2021)



### **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

	Page
<b>Foreword</b> .....	<b>iv</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 General requirements</b> .....	<b>2</b>
4.1 Design and construction.....	2
4.2 Materials.....	3
4.3 Cleanliness.....	3
4.4 Mechanical properties.....	4
4.4.1 Burst pressure.....	4
4.4.2 Pressure cycles.....	4
4.4.3 Bending test (optional, upon request of purchaser).....	4
4.4.4 Resistance to abuse.....	4
4.4.5 Low temperature resistance.....	4
4.4.6 Leak tightness.....	4
4.4.7 Electrical properties.....	4
<b>5 Hose sample tests</b> .....	<b>4</b>
5.1 General.....	4
5.2 Non-destructive tests and inspection.....	6
5.2.1 Documentation of materials.....	6
5.2.2 Dimensional check.....	6
5.2.3 Cleanliness check.....	6
5.2.4 Pressure test.....	6
5.2.5 Leak test.....	6
5.2.6 Crushing test.....	6
5.3 Destructive tests.....	7
5.3.1 Hydraulic pressure cycling.....	7
5.3.2 Rolling bend cycling test.....	7
5.3.3 Hydraulic bursting test.....	7
5.3.4 Examination of sectional cut.....	8
<b>6 Production testing</b> .....	<b>8</b>
6.1 General.....	8
6.2 Pressure test.....	8
6.3 Leak test.....	8
<b>7 Marking</b> .....	<b>8</b>
<b>8 Cleaning</b> .....	<b>8</b>
<b>9 Periodic examination</b> .....	<b>9</b>
<b>10 Test certificate</b> .....	<b>9</b>
<b>Annex A (informative) Typical hose assembly</b> .....	<b>10</b>
<b>Annex B (informative) Rolling bend cycling test for metallic hose assemblies and hose assemblies made of materials with a record of satisfactory use in cryogenic service</b> .....	<b>11</b>
<b>Annex C (informative) Rolling bend cycling test for hose assemblies constructed from materials or composites not commonly used in cryogenic service</b> .....	<b>13</b>
<b>Annex D (informative) Guidelines for periodic examination of transfilling hoses</b> .....	<b>15</b>
<b>Annex E (informative) Acceptable materials</b> .....	<b>16</b>
<b>Annex ZA (informative) Relationship between this European Standard and the essential requirements of Directive 2014/68/EU (Pressure Equipment Directive) aimed to be covered</b> .....	<b>21</b>

## ISO/DIS 21012:2021(E)

### Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html). (standards.iteh.ai)

This document was prepared by ISO/TC 220, *Cryogenic vessels*, in collaboration with the European Committee for Standardization (CEN) Technical Committee – CEN/TC 268, *Cryogenic vessels*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This third edition cancels and replaces the second edition (ISO 21012:2021), which has been technically revised.

This edition includes the following significant changes with respect to the previous edition:

- Modification of the scope

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

# Cryogenic vessels — Hoses

## 1 Scope

This document specifies design, construction, type and production testing, and marking requirements for non-insulated cryogenic flexible hoses used for the transfer of cryogenic fluids within the following range of operating conditions:

- working temperature: from  $-270\text{ °C}$  to  $+65\text{ °C}$ ;
- nominal size (DN): from 10 to 100.

End fittings for mounting of any couplings are within the scope of this document, but the couplings are subject to other standards.

It is intended that the hose be designed and tested to satisfy a rated pressure. Hoses may be then selected with a PR equal to or greater than the maximum allowable pressure (PS) of the equipment to which it is to be used.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN ISO 7369:2020, *Pipework — Metal hoses and hose assemblies — Vocabulary*

EN ISO 10806:2003, *Pipework — Fittings for corrugated metal hoses*

ISO 21010:2017, *Cryogenic vessels — Gas/material compatibility*

EN ISO 21028-1:2016, *Cryogenic vessels — Toughness requirements for materials at cryogenic temperature — Part 1: Temperatures below  $-80\text{ °C}$*

EN ISO 23208:2019, *Cryogenic vessels — Cleanliness for cryogenic service*

## 3 Terms and definitions

For the purposes of this document, the terms and definitions given in EN ISO 7369:2020 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <https://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

### 3.1

#### **hose**

flexible leak-tight inner tube of either corrugated metal, elastomer or plastic

### 3.2

#### **braid**

layer, or layers, of cylindrically woven wires covering the hose and permanently attached to the flexible hose assembly end fittings, serving the function of restraining the flexible hose against elongation

**ISO/DIS 21012:2021(E)****3.3****protection coil or cover**

outer coil or cover fitted to protect the main hose and braid against damage and abrasion

**3.4****end fittings**

fitting (of material compatible with material and product transferred) attached to each end of the hose and braid (when fitted)

**3.5****hose assembly**

hose with end fittings attached, complete with braid and/or other covering, ready for service

**3.6****nominal size****DN**

alphanumeric designation of size for components of a pipework system, is used for reference purposes

Note 1 to entry: It comprises the letters DN followed by a dimensionless whole number that is indirectly related to the physical size, in millimetres, of the bore or outside diameter of the end connections.

[SOURCE: ISO 6708:1995, 2.1]

**3.7****rated pressure****PR**

<of a hose> lowest maximum allowable working pressure (MAWP) of any component of the hose at 20 °C

Note 1 to entry: PR > PS (as defined in PED).

Note 2 to entry: See also the last sentence of Clause 1.

iTeh STANDARD PREVIEW  
(standards.iteh.ai)  
oSIST prEN ISO 21012:2021  
<https://standards.iteh.ai/catalog/standards/sist/0a4c822d-9ad5-4ee0-bf5e-1cbde99c5c60/osist-pren-iso-21012-2021>

**3.8****rated minimum temperature**

lowest temperature to which the hose assembly is rated by the manufacturer

**3.9****working temperature range**

highest and lowest temperature to which the hose assembly is to be subjected

**3.10****cyclic life**

minimum number of complete cycles which, at the test conditions, the hose assembly is designed to withstand without failure

**4 General requirements****4.1 Design and construction**

The test pressure used during tests (see Clause 5) shall be greater than or equal to the rated pressure (PR) specified. In addition, the rated pressure (PR) shall not be less than the maximum allowable pressure (PS) of the equipment to which it is to be used. A hose is typically made from corrugated metal, from strip steel. The corrugation may be parallel or helical. The maximum pressure in service shall be lower than or equal to the rated pressure stamped on the hose assembly.

If elastomers or composites are used, additional requirements shall be applied in accordance with 5.3.2.2.



A braid is commonly fitted over the hose. This generally consists of woven wire in one or two layers in stainless steel, or a high strength copper alloy. It may have a cover that shall be compatible with the surroundings and with the conveyed fluid.

The design shall ensure that pressurization, or corrosion, between the inner tube and the outer braid or sheath is prevented.

End fittings shall be designed as a rigid seal to the ends of a hose to ensure:

- a tight fit to the hose;
- a strong joint between the braid, hose and end fitting to stabilize the hose against elongation at rated pressure.

Fittings for corrugated metal hose assemblies shall conform to EN ISO 10806:2003.

An area for marking shall be provided on one of the end fittings or on an attachment.

All joining methods used in corrugated hose assemblies shall be qualified. Manual welds shall be in accordance with applicable standards.

A typical cryogenic hose assembly is shown in Annex A.

## 4.2 Materials

All materials shall be compatible with the fluid conveyed and shall be controlled by the manufacturer of the hose assembly by a specification ensuring control of chemical content and physical properties, and quality at least equivalent to an internationally recognized standard. Materials for the manufacture of corrugated metal hose assemblies shall be selected on the basis of their suitability for fabrication, e.g. cold forming and welding, etc. and for the conditions under which they shall be used. In addition, the following requirements shall be met:

- end connections and couplings shall be made of materials compatible with the other materials of the hose assembly;
- a material is compatible when it does not lead to any violent reaction (ignition, etc.) or any slow reaction with the conveyed gases, and permeability shall be appropriate for intended use;
- a test certificate providing the chemical content and physical property test results shall be provided with the hose assembly.

The materials used in a cryogenic hose assembly shall:

- maintain sufficient ductility at the rated minimum temperature (as specified in EN ISO 21028-1:2016);
- be oxygen compatible, if specified for oxygen or nitrous oxide service (as specified ISO 21010:2017);
- any austenitic stainless steel hoses shall be annealed after formation for hydrogen service;
- contain less than 65 % copper, in the alloy as well as the soldering materials, if it is specified for mixtures containing acetylene.

A list of acceptable materials is given in Annex E (Table E.1 for European materials, Table E.2 for non-European materials).

## 4.3 Cleanliness

Hose assemblies specified for all cryogenic fluids shall be cleaned in accordance with EN ISO 23208:2019 to remove hydrocarbons, moisture, particles or other contaminations from inside the hose assembly.

## ISO/DIS 21012:2021(E)

### 4.4 Mechanical properties

#### 4.4.1 Burst pressure

The burst pressure shall be at least three times the rated pressure at ambient temperature. Failure shall occur only in the body of the hose and braid and not in their connections. See 5.3.3 for burst test.

#### 4.4.2 Pressure cycles

Hose assemblies shall have a minimum cyclic life of 10 000 cycles when repeatedly pressurized from <1 bar to their rated pressure in accordance with 5.3.1.

#### 4.4.3 Bending test (optional, upon request of purchaser)

Hose assemblies should have a minimum cyclic life of 10 000 cycles when repeatedly flexed at their rated pressure in accordance with 5.3.2.

NOTE Actual life cycle of hose will depend on actual operating conditions.

This test is only required if the flexible hose is subject to multiple wide/significant moves when under pressure.

#### 4.4.4 Resistance to abuse

Hose assemblies should have sufficient resistance to deterioration of the braid when they are dragged on the ground. For additional protection of the braid, a coil can be used.

Hose assemblies shall withstand a crushing test, simulating a person stepping on the hose assembly, in accordance with 5.2.6.

<https://standards.iteh.ai/catalog/standards/sist/0a4c822d-9ad5-4ec0-bf5e-1cbde99c5c60/osist-pr-en-iso-21012-2021>

#### 4.4.5 Low temperature resistance

All components of the hose assemblies which become cold during operation shall retain their toughness at the lowest design temperature.

#### 4.4.6 Leak tightness

Hose assemblies shall be leak-tight in accordance with 5.2.5.

#### 4.4.7 Electrical properties

Hose assemblies specified for flammable products shall be electrically conducting from one end to the other (electric resistance less than 25  $\Omega$ ).

## 5 Hose sample tests

### 5.1 General

The hose test samples shall be representative of production. In case of a connection breaking pre-programmed system, testing will be performed on flexible hoses without these connections. The hose sample test procedures shall include:

- a) inspection and non-destructive tests:
  - inspection: dimensions, cleanliness, material identification and marking;
  - tests: pressure test, leak and crushing tests;

b) destructive tests:

— pressure cycling, bursting test, rolling bend cycling and examination of sectional cut.

The tests shall be recorded in a written report which shall be retained for 10 years after the last hose has been placed on the market.

Four sample hose assemblies (A, B, C and D) are necessary to perform the tests.

The tests and order of tests are summarized in Table 1.

(The numbers 1 to 5 give the order of the tests).

**Table 1 — Testing scope and sequence**

Tests	Hose sample			
	A	B	C	D
<b>1) Non-destructive tests</b>				
Documentation of materials	1	1	1	1
Dimensional check	1	1	1	1
Cleanliness check	1	1	1	1
Pressure test	1	1	1	1
Leak test	2	4	3	2
Crushing test	—	2	—	—
<b>2) Destructive tests</b>				
Hydraulic pressure cycling	3	—	—	—
Rolling bend cycling (optional, if requested by purchaser)	—	3	2	—
Hydraulic bursting test	4	5	—	3
Examination of a sectional cut	—	—	4	—

The hydraulic bursting test shall be carried out to qualify all DN hose assemblies.

When a hose assembly with a given DN and a given rated pressure,  $P_R$ , has been successfully sample tested, any hose assembly of the same type, having:

— a rated pressure  $P_R$ ;

and

— a nominal diameter up to 1,25 DN

can be considered as approved except each DN hose assembly shall be hydraulic burst tested.

A hose assembly is said to be of the same type when the design and its characteristics are similar to the tested hose; similarity is defined as having the same

— materials;

— welding method;

— type of corrugation (shape and method of manufacturing);

— method of joining (hose and end fitting);

— braid (type of braiding, i.e. calculated – according to diameters to obtain the same maximum tensile stress in each wire, same materials, same welding method).

Bend radius and minimum hose length for sample hose assemblies are defined in Annexes B and C.