
**Geometrical product specifications
(GPS) — Surface texture: Profile —**

**Part 1:
Indication of surface texture**

*Spécification géométrique des produits (GPS) — État de surface:
Méthode du profil —*

Partie 1: Indication des états de surface

iteh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO 21920-1:2021

<https://standards.iteh.ai/catalog/standards/iso/ab03b9a1-0a17-4c24-8163-b4ed7798032e/iso-21920-1-2021>



iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO 21920-1:2021

<https://standards.iteh.ai/catalog/standards/iso/ab03b9a1-0a17-4c24-8163-b4ed7798032e/iso-21920-1-2021>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Tolerance acceptance rules	1
4.1 General	1
4.2 Maximum tolerance acceptance rule	2
4.3 16 % tolerance acceptance rule	2
4.4 Median tolerance acceptance rule	2
5 Specification elements for indication of profile surface texture specifications	3
5.1 General	3
5.2 Mandatory indication to be explicitly specified	3
5.3 Optional indications to specify non-default or further requirements	3
6 Indication of profile surface texture	4
6.1 General	4
6.2 Graphical symbols	4
6.3 Minimal indication	5
6.3.1 General	5
6.3.2 Minimal indication for parameters with defined defaults	5
6.3.3 Minimal indication for parameters without defined defaults	5
6.4 Complete indication	6
6.4.1 General	6
6.4.2 Complete indication for evaluation length R-parameters	7
6.4.3 Complete indication for section length R-parameters	8
6.4.4 Complete indication for evaluation length P-parameters and W-parameters	9
6.4.5 Complete indication for section length P-parameters and W-parameters	10
7 Rules for indication of profile surface texture specifications	10
7.1 General	10
7.2 Graphical symbol for the indication of profile surface texture specifications	11
7.3 Profile surface texture parameter	11
7.4 Tolerance limit value of the profile surface texture parameter	11
7.5 Tolerance types	11
7.6 Tolerance acceptance rule	11
7.7 Profile S-filter type	11
7.8 Profile S-filter nesting index	11
7.9 Profile L-filter type (for R-parameter) or profile S-filter type (for W-parameter)	12
7.10 Profile L-filter nesting index (for R-parameter) or profile S-filter nesting index (for W-parameter)	12
7.11 Evaluation length	12
7.12 Section length	12
7.13 Number of sections	12
7.14 Profile F-operator association method and element	12
7.15 Profile F-operator nesting index	12
7.16 Method of profile extraction	13
7.17 Other requirements, OR(<i>n</i>)	13
7.18 Manufacturing process	13
7.19 Surface lay and direction of lay	13
7.20 Profile direction	13
7.21 Setting class, <i>Scn</i>	13
8 Position on technical product documentation	14

8.1	General.....	14
8.2	Position and orientation of the graphical symbol.....	14
9	Simplified and additional indications.....	17
9.1	Simplified indications.....	17
9.1.1	General.....	17
9.1.2	General tolerances.....	17
9.1.3	Indication by the graphical symbol combined with a letter.....	18
9.2	Restrictive specifications.....	19
9.3	Indication of identical specifications for a number of feature elements.....	20
9.4	Indication of surface lay and direction of lay.....	20
9.4.1	General.....	20
9.4.2	Indication of surface lay without a reference.....	21
9.4.3	Indication of surface lay and direction of lay relative to a workpiece feature.....	22
9.5	Indication of the profile direction.....	22
9.5.1	General.....	22
9.5.2	Indication of the profile direction relative to the predominant direction of the surface lay.....	23
9.5.3	Indication of the profile direction relative to a workpiece feature.....	23
9.6	Indication of bilateral surface profile tolerances.....	24
9.7	Indication of different requirements for several additional processes on one surface feature.....	24
	Annex A (normative) Proportions and dimensions of graphical symbols.....	26
	Annex B (normative) Filter symbols for profile surface texture.....	28
	Annex C (normative) Symbols for association methods and association elements.....	29
	Annex D (informative) Indications for unambiguous surface profile specification.....	30
	Annex E (normative) Inspection procedure for the 16 % tolerance acceptance rule.....	43
	Annex F (informative) Criteria for the use of the maximum tolerance acceptance rule as the default.....	44
	Annex G (informative) New issues and changes to previous documents.....	45
	Annex H (informative) Overview of profile and areal standards in the GPS matrix model.....	47
	Annex I (informative) Relation to the GPS matrix model.....	48
	Bibliography.....	49

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 213, *Dimensional and geometrical product specifications and verification*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 290, *Dimensional and geometrical product specification and verification*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This document cancels and replaces ISO 1302:2002, which has been technically revised. In addition to the change of number, the main changes to ISO 1302:2002 are as follows:

- New specification elements for indication are defined.
- The maximum tolerance acceptance rule is the default tolerance acceptance rule.

A list of all parts in the ISO 21920 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

This document is a geometrical product specification (GPS) standard and is to be regarded as a general GPS standard (see ISO 14638). It influences chain link A of the chains of standards on profile surface texture.

The ISO GPS matrix model given in ISO 14638 gives an overview of the ISO GPS system of which this document is a part. The fundamental rules of ISO GPS given in ISO 8015 apply to this document and the default decision rules given in ISO 14253-1 apply to the specifications made in accordance with this document, unless otherwise indicated.

For more detailed information of the relation of this document to other standards and the GPS matrix model, see [Annex H](#), [Table H.1](#), and [Annex I](#).

This document covers the indication of profile surface texture.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO 21920-1:2021

<https://standards.iteh.ai/catalog/standards/iso/ab03b9a1-0a17-4c24-8163-b4ed7798032e/iso-21920-1-2021>

Geometrical product specifications (GPS) — Surface texture: Profile —

Part 1: Indication of surface texture

1 Scope

This document specifies the rules for indication of surface texture by profile methods in technical product documentation by means of graphical symbols.

This document does not cover population requirements.

NOTE See ISO 18391 for population (batch) specifications.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 21920-2, *Geometrical product specifications (GPS) — Surface texture: Profile — Part 2: Terms, definitions and surface texture parameters*

ISO 21920-3, *Geometrical product specifications (GPS) — Surface texture: Profile — Part 3: Specification operators*

ISO 81714-1, *Design of graphical symbols for use in the technical documentation of products — Part 1: Basic rules*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 21920-2 and ISO 21920-3 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

4 Tolerance acceptance rules

4.1 General

Tolerance acceptance rules define how the tolerance limits are applied to the measured parameter values. For profile surface texture, three tolerance acceptance rules can be indicated. See ISO 21920-3:2021, Table 1 for the position of the measurements.

4.2 Maximum tolerance acceptance rule

The maximum tolerance acceptance rule does not allow any measured value to exceed the tolerance limit. The symbol of the maximum tolerance acceptance rule is shown in [Figure 1](#).

T_{max}

Figure 1 — Symbol of the maximum tolerance acceptance rule

The maximum tolerance acceptance rule is the default case and valid with or without indication of the 'T_{max}' symbol.

NOTE 1 The suffix 'max' can be interpreted as the required maximal conformity of the measured value.

NOTE 2 The 'T_{max}' symbol can be used to prevent misinterpretation of a specification.

4.3 16 % tolerance acceptance rule

A specified 16 % tolerance acceptance rule allows at most 16 % of all measured values of a parameter to violate the tolerance limit. The symbol of the 16 % tolerance acceptance rule is shown in [Figure 2](#).

The 16 % tolerance acceptance rule shall be applied as specified in [Annex E](#).

T16%

Figure 2 — Symbol of the 16 % tolerance acceptance rule

The 16 % tolerance acceptance rule is valid for the parameter on the line where the 'T16 %' symbol is indicated.

If a bilateral tolerance is specified in one line, 16 % of all measured values may violate the upper tolerance limit and 16 % of all measured values may violate the lower tolerance limit.

NOTE 1 The 16 % tolerance acceptance rule defines how tolerance limits are applied to the measured values.

NOTE 2 In ISO 1302, the 16 % tolerance acceptance rule was called the 16 % rule.

NOTE 3 In contrast to ISO 1302, the 16 % tolerance acceptance rule is not the default (see [Annex F](#) for additional information).

NOTE 4 See ISO 21920-3:2021, Table 1 for the distribution of the measurements.

4.4 Median tolerance acceptance rule

If a median tolerance acceptance rule is specified, the median value of all measured values of a parameter shall meet the tolerance limits. The symbol of the median tolerance acceptance rule is shown in [Figure 3](#).

T_{med}

Figure 3 — Symbol of the median tolerance acceptance rule

The median tolerance acceptance rule is valid for the parameter on the line where the 'T_{med}' symbol is indicated.

At least three measured values shall be used to apply the median acceptance rule. A higher number of measurements can be specified in “other requirements” (symbol $OR(n)$, see 7.17).

NOTE 1 The median tolerance acceptance rule defines how tolerance limits are applied to the measured values.

NOTE 2 If the median value of all measured values of a parameter meets the tolerance limit, no more than half the measured values exceed the tolerance limit.

5 Specification elements for indication of profile surface texture specifications

5.1 General

Indications of profile surface texture specify requirements on the surface of a workpiece as well as the specification operator.

NOTE All specification elements permitted for indication of profile surface texture specifications are listed in 5.2 and 5.3 and described in Clause 7.

5.2 Mandatory indication to be explicitly specified

- Graphical symbol for profile surface tolerance.
- Symbol of the profile surface texture parameter.
- Tolerance limit of the profile surface texture parameter.
- For parameters without defined defaults: indication of the profile L-filter nesting index N_{ic} for R-parameters or profile S-filter nesting index N_{ic} for W-parameters or the setting class Scn .

NOTE 1 Parameters without defined default are not listed in ISO 21920-3: 2021, Tables 3 to 6.

NOTE 2 The indication of the nesting index or the setting class is optional for all parameters listed in ISO 21920-3:2021, Tables 3 to 6.

NOTE 3 It is the responsibility of the designer to choose and indicate the appropriate L-filter or S-filter. ISO 21920-3:2021, Tables 3 to 6 define defaults that can be used for surfaces without particular performance requirements.

NOTE 4 A cut-off wavelength for a profile filter is an example of a nesting index, see ISO 21920-2.

5.3 Optional indications to specify non-default or further requirements

- Tolerance type (upper, lower or bilateral tolerance limit).
- Symbol ‘T16 %’, ‘Tmax’ or ‘Tmed’ to specify a tolerance acceptance rule.
- Profile S-filter type.
- Profile S-filter nesting index.
- Profile L-filter type for R-parameters or profile S-filter type for W-parameters.
- Profile L-filter nesting index N_{ic} for R-parameters or profile S-filter nesting index N_{ic} for W-parameters.
- Evaluation length l_e for the evaluation length parameters. Section length l_{sc} and number of sections n_{sc} for the section length parameters.
- Profile F-operator association method and element.
- Profile F-operator nesting index.

- Method of profile extraction.
- Symbol 'OR(*n*)' to specify other requirements.
- Manufacturing process.
- Surface lay and direction of lay.
- Profile direction.
- Symbol 'Scn' to specify a setting class.

NOTE Default settings are defined in ISO 21920-3.

6 Indication of profile surface texture

6.1 General

Profile surface texture requirements in technical product specifications shall be specified by one of the graphical symbols described in [6.2](#).

A minimal indication of profile surface texture shall be built up of the graphical symbol, the parameter designation and the parameter tolerance limit value, see [6.3](#).

If several parameters are specified, the parameter in the first line is relevant for the determination of default settings (see ISO 21920-3).

All indicated specification elements are separated by a single blank character.

NOTE 1 Exceptions are defined in [9.1](#).


NOTE 2 See [Annex G](#), [Table G.1](#), for new issues in this document and changes to previous documents.

6.2 Graphical symbols


The form of the graphical symbols contains requirements for the production process. Proportions of the graphical symbols shall be indicated as specified in [Annex A](#).

NOTE 1 See [Figure 4](#) for the layout of the three defined graphical symbols and their interpretation.


NOTE 2 The bar above the symbol is to distinguish this symbol from the ones used in ISO 1302 and those used for indication of areal surface texture specifications.



a) Any manufacturing process permitted



b) Material shall be removed



c) Material removal is not permitted

Figure 4 — Graphical symbols indicating profile surface texture


6.3 Minimal indication

6.3.1 General

If a minimal indication is specified, all defaults shall be applied. Because defaults cannot be defined for all parameters, the minimal indication is different for parameters with and without defined defaults.

6.3.2 Minimal indication for parameters with defined defaults

Figure 5 shows all symbols and indications mandatory for a minimal indication of profile surface texture requirements and parameters with defined defaults.



Key

- a symbol for parameter
- b tolerance limit value of the profile surface texture parameter
- < > placeholder has to be specified

Figure 5 — Minimal indication for parameter with defined defaults (all defaults apply)

NOTE 1 Parameters with defined defaults are Rz, Ra, Rp, Rv, Rq, Rmax, Rt and Pt, see ISO 21920-3:2021, Tables 3 to 6.


NOTE 2 Exceptions are defined in 9.1.

NOTE 3 See Annex D for examples and additional information.

6.3.3 Minimal indication for parameters without defined defaults

Figure 6 shows all symbols and indications mandatory for a minimal indication of profile surface texture requirements and parameters without defined defaults. All defaults are defined by the mandatory specified setting class (Scn) or by one of the default values of the mandatory profile L-filter nesting index N_{ic} for R-parameters or profile S-filter nesting index N_{ic} for W-parameters.

Oblique strokes, “/”, are used to separate the specification sections.



Key

- a symbol for parameter
- b tolerance limit value of the profile surface texture parameter
- c symbol for the specified setting class Scn or a default value of profile L-filter nesting index N_{lc} for R-parameters or profile S-filter nesting index N_{lc} for W-parameters
- < > placeholder has to be specified

Figure 6 — Minimal indication for parameter without defined defaults

NOTE 1 Parameters without defined defaults are not listed in ISO 21920-3:2021, Tables 3 to 6.

NOTE 2 The specified setting class leads directly to the specified column of ISO 21920-3:2021, Table 2, with the relevant default settings.

NOTE 3 Exceptions are defined in 9.1.

NOTE 4 See [Annex D](#) for examples and additional information.

6.4 Complete indication

6.4.1 General

The specification elements described in [Clause 5](#) shall be arranged as shown in [6.4.2](#) to [6.4.5](#), depending on the parameter type. All specification elements for one parameter shall be indicated in one line.

NOTE 1 If several parameters or different specification elements for the same parameter need to be specified, the indication follows in one or several additional lines.

NOTE 2 See [Annex D](#) for examples of indication and additional information.

NOTE 3 The complete indication is shown to define the sequence of the indication of all specification elements and might be rarely used in practice.

6.4.2 Complete indication for evaluation length R-parameters

The specification elements for evaluation length R-parameters shall be arranged as shown in [Figure 7](#).

NOTE Evaluation length R-parameters include Ra, Rq, Rt, Rzx and Rk (see ISO 21920-2).

$$\frac{[s][t]}{\sqrt{\frac{[a]\langle b\rangle\langle c\rangle[d]/[e][f]-[g][h]([m])[n][p]/[q][r]}{[u]}}}$$

Key

- a tolerance type
- b symbol for R-parameter
- c tolerance limit value of the profile surface texture parameter
- d tolerance acceptance rule
- e profile S-filter type
- f profile S-filter nesting index
- g profile L-filter type
- h profile L-filter nesting index
- m evaluation length
- n profile F-operator association method and element
- p profile F-operator nesting index
- q method of profile extraction
- r placeholder for the OR(*n*) symbol for other requirements
- s manufacturing process
- t surface lay and direction of lay
- u profile direction relative to the surface lay
- < > placeholder has to be specified
- [] placeholder can be specified if different from the default or an additional requirement

Figure 7 — Indication for evaluation length R-parameters including all optional specification elements

6.4.3 Complete indication for section length R-parameters

The specification elements for section length R-parameters shall be arranged as shown in [Figure 8](#).

NOTE Section length R-parameters include Rz, Rp and Rv (see ISO 21920-2).

$$\sqrt{\frac{[s][t]}{[a]\langle b \rangle \langle c \rangle [d] / [e][f] - [g][h]([i] \times [k])[n][p] / [q][r]}} [u]$$

Key

- a tolerance type
- b symbol for R-parameter
- c tolerance limit value of the profile surface texture parameter
- d tolerance acceptance rule
- e profile S-filter type
- f profile S-filter nesting index
- g profile L-filter type
- h profile L-filter nesting index
- i section length
- k number of sections
- n profile F-operator association method and element
- p profile F-operator nesting index
- q method of profile extraction
- r placeholder for the OR(*n*) symbol for other requirements
- s manufacturing process
- t surface lay and direction of lay
- u profile direction relative to the surface lay
- < > placeholder has to be specified
- [] placeholder can be specified if different from the default or an additional requirement

NOTE The parentheses around ([*i*] × [*k*]) bring out the relationship between these specification elements as the evaluation length results from this product.

Figure 8 — Indication for section length R-parameters including all optional specification elements