

Designation: E1177 - 09

# StandardSpecification for Engine Coolant Grade Glycol<sup>1</sup>

This standard is issued under the fixed designation E1177; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon  $(\varepsilon)$  indicates an editorial change since the last revision or reapproval.

### 1. Scope

- 1.1 This specification covers commercial products, engine coolant grade ethylene glycol and propylene glycol, including virgin glycols and those derived from the recycling of vehicle engine coolants and industrial source glycols.
- 1.2 Types EG-1 and PG-1 cover glycols with sufficiently low limits on components to allow a blended coolant to meet most OEM (Original Equipment Manufacturer) specifications. These types will probably be virgin materials, although redistillation could produce a sufficiently pure product. Types EG-2 and PG-2 cover glycol that will be suitable for many coolants. These types can be either redistilled or virgin.
- 1.3 This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.
- 1.4 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

# 2. Referenced Documents

- 2.1 ASTM Standards: 2 /catalog/standards/sist/3b0aa04d
- D1122 Test Method for Density or Relative Density of Engine Coolant Concentrates and Engine Coolants By The Hydrometer
- D1123 Test Methods for Water in Engine Coolant Concentrate by the Karl Fischer Reagent Method
- D1209 Test Method for Color of Clear Liquids (Platinum-Cobalt Scale)
- D1287 Test Method for pH of Engine Coolants and Antirusts
  D1613 Test Method for Acidity in Volatile Solvents and
  Chemical Intermediates Used in Paint, Varnish, Lacquer,
  and Related Products
- <sup>1</sup> This specification is under the jurisdiction of ASTM Committee D15 on Engine Coolants and is the direct responsibility of Subcommittee D15.07 on Specifications. Current edition approved Nov. 1, 2009. Published December 2009. Originally approved in 1987. Last previous edition approved in 2006 as E1177 06. DOI:
- <sup>2</sup> For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

- D3634 Test Method for Trace Chloride Ion in Engine Coolants
- D4052 Test Method for Density, Relative Density, and API Gravity of Liquids by Digital Density Meter
- D5827 Test Method for Analysis of Engine Coolant for Chloride and Other Anions by Ion Chromatography
- D5931 Test Method for Density and Relative Density of Engine Coolant Concentrates and Aqueous Engine Coolants by Digital Density Meter
- D6130 Test Method for Determination of Silicon and Other Elements in Engine Coolant by Inductively Coupled Plasma-Atomic Emission Spectroscopy
- E202 Test Methods for Analysis of Ethylene Glycols and Propylene Glycols
- E300 Practice for Sampling Industrial Chemicals
- E394 Test Method for Iron in Trace Quantities Using the 1.10-Phenanthroline Method

# 3. Requirements

3.1 Engine coolant grade ethylene glycol or propylene glycol, including virgin glycols and those derived from the recycling of vehicle engine coolants and industrial source glycols, shall conform to the chemical and physical property requirements in Table 1.

# 4. Sampling

4.1 Sample ethylene or propylene glycol in accordance with the appropriate sections of Practice E300 for liquid samples.

### 5. Test Methods

5.1 Test each composite sample for the chemical and physical requirements listed in 3.1.

### 6. Packaging, Package Markings, and Transportation

6.1 The packaging, labeling, and transportation of commercial quantities shall conform to applicable federal, state, and local regulations. Conformance is the responsibility of the manufacturer and the shipper.

# 7. Keywords

7.1 anti-freeze; engine coolant; ethylene; glycol; propylene glycol; recycled