INTERNATIONAL STANDARD

First edition 2020-02

Solid biofuels — Simplified sampling method for small scale applications

Biocombustibles solides — Méthode d'échantillonnage simplifiée pour les applications à petite échelle

iTeh Standards (https://standards.iteh.ai) Document Preview

<u>ISO 21945:2020</u> https://standards.iteh.ai/catalog/standards/iso/85a58206-39ea-4f1f-bb9d-63745051ce4d/iso-21945-2020



Reference number ISO 21945:2020(E)

iTeh Standards (https://standards.iteh.ai) Document Preview

ISO 21945:2020

https://standards.iteh.ai/catalog/standards/iso/85a58206-39ea-4f1f-bb9d-63745051ce4d/iso-21945-2020



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Fax: +41 22 749 09 47 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Page

Contents

rore	woru	11
Intro	oduction	
1	Scope	
2	Normative references	
3	Terms and definitions	
4	Symbols and abbreviated terms	
5	Principle	
6	Visual inspection	
7	Dronaring campling plan and ronart	
/		
8	Methods for sampling	(
	8.1 General	t
	8.2 Methods for sampling stationary material	t
	0.2.1 Sampling from transport containers and larriag	
	0.2.2 Sampling from small built in storages	
	8.2.4 Sampling from stocknilles and stocked material	
	8.2.4 Sampling nom stockpiles and stacked material	
	8.3.1 Conoral	
	8.3.2 Manual sampling from falling streams	
	8 3 3 Manual sampling from conveyor helts	
	834 Manual sampling from grabs and wheel loader buckets	
0	Minimum number of increments	1/
10	Minimum number of increments	1
10	Minimum size of increment	10
11	Determination of the volume of the combined sample	1(
12	Equipment for manual sampling 5a58206-39ea-4f1f-bb9d-63745051ce4d/iso-21945-2	02011
	12.1 General	
	12.2 Sampling bucket for falling-stream	12
	12.3 Scoops	
	12.4 Shovels	
	12.5 Forks	1.
	12.6 Sample extraction using hands	I. 1
	12.7 Pipes (spears)	
	12.8 Drills (augers)	I .
13	Reduction of sample size	14
14	Handling and storage of samples	15
	14.1 Packaging, storing and transport of samples	1
	14.2 Identification/labelling	10
15	Sampling report	10
Anne	ex A (informative) Model sampling plan and sampling report (according to ISO 21945)	1
Bibli	iography	

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take Part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see <u>www.iso.org/</u> iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 238, *Solid biofuels*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <u>www.iso.org/members.html</u>.

O 21945:2020

https://standards.iteh.ai/catalog/standards/iso/85a58206-39ea-4f1f-bb9d-63745051ce4d/iso-21945-2020

Introduction

The objective of this document is to provide unambiguous and clear principles for sampling of solid biofuels from small scale applications and storages. It is to serve as a tool to enable efficient trading of biofuels and to enable good understanding between seller and buyer. It is also a tool for communication with equipment manufacturers. It will also facilitate the development of sampling plans and reporting.

This document is intended for all stakeholders.

Priority in this document is to take a number of increments which is possible to handle at small applications under practical aspects. In ISO 18135 the priority is to obtain a sample with a defined precision and to calculate the minimum number of increments on basis of the corresponding precision data.

iTeh Standards (https://standards.iteh.ai) Document Preview

ISO 21945:2020

https://standards.iteh.ai/catalog/standards/iso/85a58206-39ea-4f1f-bb9d-63745051ce4d/iso-21945-2020

iTeh Standards (https://standards.iteh.ai) Document Preview

<u>ISO 21945:2020</u> https://standards.iteh.ai/catalog/standards/iso/85a58206-39ea-4f1f-bb9d-63745051ce4d/iso-21945-2020

Solid biofuels — Simplified sampling method for small scale applications

1 Scope

This document describes simplified methods for taking samples of solid biofuels in small scale applications and storages including preparation of sampling plans and reports. The main focus is on storages with a size of ≤ 100 t. This document is applicable to the following solid biofuels:

- 1) fine (up to about 10 mm nominal top size) and regularly-shaped particulate materials that can be sampled using a scoop or pipe, e.g. sawdust, olive stones and wood pellets;
- 2) coarse or irregularly-shaped particulate materials (up to 200 mm nominal top size) that can be sampled using a fork or shovel, e.g. wood chips, hog fuel and nut shells;
- 3) large pieces (above 200 mm nominal top size) which are picked manually (e.g. firewood and briquettes).

This document can also be used for other solid biofuels not listed above if the procedures described in this document are applicable. This document specifies methods to be used, for example, when a sample is to be tested for moisture content, ash content, calorific value, bulk density, mechanical durability, particle size distribution, ash melting behaviour and chemical composition.

Additionally, it describes a method for the reduction of sample size and defines requirements on handling and storage of samples.

NOTE 1 If higher precision of analytical results is needed or when in doubt if this document is applicable ISO 18135 can be used. Using the number of increments given in this document the resulting precision for analytical results can be estimated with the formulas given in ISO 18135.

NOTE 2 Pellets can generate CO and CO_2 off gasses by nature. If pellets are sampled, check for CO and CO_2 and O_2 levels prior and during the sample taking process in a confined space like a container, silo or shed and have another person standby at the entrance.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 14780, Solid biofuels — Sample preparation

ISO 16559, Solid biofuels — Terminology, definitions and descriptions

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at https://www.iso.org/obp
- IEC Electropedia: available at <u>http://www.electropedia.org/</u>

3.1

combined sample

sample consisting of all the increments taken from a lot or sub-lot

Note 1 to entry: The *increments* may be reduced by division before being added to the combined *sample*.

[SOURCE: ISO 16559:2014, 4.52]

3.2

increment

portion of fuel extracted in a single operation of the *sampling* device

[SOURCE: ISO 16559:2014, 4.122]

3.3

laboratory sample

combined *sample* or a sub-sample of a combined sample for use in a laboratory

[SOURCE: ISO 16559:2014, 4.124]

3.4

lot

defined quantity of fuel for which the quality is to be determined

[SOURCE: ISO 16559:2014, 4.128, modified — Note 1 to entry has been removed.]

3.5

nominal top size

aperture size of the smallest sieve through which at least 95 % by mass of the material passes during the determination of particle size distribution

Note 1 to entry: For selection of sieves types and aperture sizes see ISO 17827-1 and ISO 17827-2.

Note 2 to entry: For pellets the diameter is used.

https://standards.nei.a/catalog/standards/iso/85a58206-39ea-4f1f-bb9d-63745051ce4d/iso-21945-2020

[SOURCE: ISO 16559:2014, 4.137, modified — Note 1 and 2 to entry have been added for additional information, the word "smallest" has been added and the words "of solid fuels" have been deleted.]

3.6

sample

quantity of material, representative of a larger quantity for which the quality is to be determined

[SOURCE: ISO 16559:2014, 4.170, modified — "(all increments)" has been removed from the definition, Note 1 to entry has been removed.]

3.7

sub-lot

part of a *lot* for which a test result is required

EXAMPLE Material in a transport unit or on a particular stockpile.

[SOURCE: ISO 16559:2014, 4.197, modified — Example has been added.]

3.8

sub-sample portion of a *sample*

[SOURCE: ISO 16559:2014, 4.198]

4 Symbols and abbreviated terms

- d_{95} is the nominal top size of the biofuel [mm];
- *m* is the mass of the lot or sublot [kg or t];
- *V*_{incr} is the minimum volume of an increment [l];
- V_{req} is the volume required for the foreseen analyses [1];
- *W* is the width of a sampling tool [mm].

5 Principle

The main principle of sampling is to obtain (a) representative sample(s) from the whole lot concerned. Every particle in the lot or sub-lot to be represented by the sample should have an equal probability of being included in the sample. In order to do so a sampling plan is needed. Figure 1 shows the main steps of a sampling procedure.

Under certain circumstances (e.g. certain construction types of built in storages, silos or containers) representative sampling might not be possible.

iTeh Standards (https://standards.iteh.ai) Document Preview

ISO 21945:2020

https://standards.iteh.ai/catalog/standards/iso/85a58206-39ea-4f1f-bb9d-63745051ce4d/iso-21945-2020



Figure 1 — Procedure for sampling

6 Visual inspection

Visual inspection shall be used for the choice or verification of the classification of the solid biofuels. Based on the sampling plan, verification or selection of the sampling equipment and the sampling method shall also be made by visual inspection. If the lot/sub-lot consists of substantially inhomogeneous material or if it contains impurities (such as soil or pieces of metal) this shall be stated in the sampling report. If the biofuel type or the quality of it is diverging strongly from the one expected, the sampler shall report without any delay to the appropriate party for further instructions.

If the particle size distribution should be analysed the visible surface of the complete lot should be inspected for the longest particle — in addition to the sampling and testing — and its length shall be noted in the sampling report.

NOTE 1 It is advisable to take photographs of deviations noted during visual inspection.

NOTE 2 For documentation of oversized particles photographs are useful. Therefore, it is advisable to include a folding rule or any other scale into the photograph to enable the estimation of the particles size.