INTERNATIONAL STANDARD

ISO 21956

First edition 2019-11

Road vehicles — Ergonomics aspects of transport information and control systems — Human machine interface specifications for keyless ignition systems

Véhicules routiers — Aspects ergonomiques des systèmes de commande et d'information du transport — Spécifications d'interface homme-machine pour des systèmes de démarrage sans clé

https://standards.iteh.ai)

Document Preview

ISO 21956:2019

https://standards.iteh.ai/catalog/standards/iso/5ec3714e-426e-43ed-97e0-ca15913deec3/iso-21956-2019



iTeh Standards (https://standards.iteh.ai) Document Preview

ISO 21956:2019

https://standards.iteh.ai/catalog/standards/iso/5ec3714e-426e-43ed-97e0-ca15913deec3/iso-21956-2019



COPYRIGHT PROTECTED DOCUMENT

© ISO 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Fax: +41 22 749 09 47 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Fore	word			i v
Intro	ductio	n		7
1	Scope Normative references Terms and definitions			
2				
3				
4	Design guidelines			
	4.1	Actuat	ion of keyless ignition control	;
		4.1.1	Actuation for emergency starting – Restarting the propulsion system after unintended engine stall	
		4.1.2	Actuation for starting – Design to avoid accidental starting – Stationary vehicle	
		4.1.3	Actuation for stopping while a vehicle with automatic start/stop is in run mode	
		4.1.4	Actuation for stopping (commercial vehicles only) – Design to avoid	
			accidental stopping - Stationary vehicle	
		4.1.5	Actuation for emergency stopping – Interruption of starting	:
	4.2	Startir	ng a propulsion system in case key code carrying device battery runs out	:
		4.2.1	Operation methods	
		4.2.2	Instructions in case key code carrying device battery runs out	
	4.3	Alerts and information to the driver		
		4.3.1	Key left in vehicle	
		4.3.2	Missing key code carrying device when starting vehicle propulsion system	
		4.3.3	Ignition mode active at exit	
		4.3.4	Ignition mode active at exit (commercial vehicles only)	
		4.3.5	Key code carrying device leaves the vehicle	
		4.3.6	Power shut off without key code carrying device	
		4.3.7	Power shut off when not in "parked" or without activated parking brake for automatic transmission vehicles	
		4.3.8	Power shut off when not in "parked" or "neutral" for automatic	
			transmission vehicles (commercial vehicles only)	
		4.3.9	Steering not unlocked 5/14c-420c-45cd-97c0-6415913deec3/180-21956-2019	'
Anne	ex A (in	formativ	e) Keyless ignition control use cases	;
			-,,,	

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 39, *Ergonomics*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

https://standards.iteh.ai/catalog/standards/iso/5ec3714e-426e-43ed-97e0-ca15913deec3/iso-21956-2019

Introduction

The conventional method of operating motor ignition systems requires use of a mechanical key. Keyless ignition systems, that do not require the mechanical interface with the vehicle, improve driver's convenience and are becoming more widespread. This has created a need for immediate standardization of the Human Machine Interface (HMI), since some drivers may have difficulty understanding how to use these systems. This document complements SAE J2948, which covers the operation of keyless ignition systems with the goal of helping to minimize user-initiated errors. That includes:

- the inability to start and stop the vehicle propulsion system,
- exiting the vehicle with the automatic transmission in a non-parking gear,
- exiting the vehicle while the vehicle propulsion system is enabled, and
- exiting the vehicle while the vehicle propulsion system is disabled, but the accessory or electrical systems are active.

This document's scope differs from SAE J2948 as follows:

- actuation of keyless ignition control that is equipped with automatic start/stop systems,
- actuation to start or stop the vehicle propulsion system under emergency situations,
- actuation to start the propulsion system with low battery in the key,
- actuation of keyless ignition control without key code carrying device, and
- recommendations for detailed alerts and status indications identified with specific use-case examples.

Many of these HMI issues vary among manufacturers and even among models from the same manufacturer. To help clarify the use of keyless ignition systems, this document sets guidelines for these new HMI solutions.

As additional explanation and support for developing specific requirements, keyless ignition control use cases are provided as an Annex A.

iTeh Standards (https://standards.iteh.ai) Document Preview

ISO 21956:2019

https://standards.iteh.ai/catalog/standards/iso/5ec3714e-426e-43ed-97e0-ca15913deec3/iso-21956-2019