
Praškasti premazi - 4. del: Izračun spodnje meje eksplozivnosti (ISO/DIS 8130-4:2021)

Coating powders - Part 4: Calculation of lower explosion limit (ISO/DIS 8130-4:2021)

Pulverlacke - Teil 4: Berechnung der unteren Explosionsgrenze (ISO/DIS 8130 4:2021)

Poudres pour revêtement - Partie 4: Calcul de la limite inférieure d'explosibilité (ISO/DIS 8130-4:2021)

ITeH STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: prEN ISO 8130-4

<https://standards.iteh.ai/catalog/standards/sist/e8b0a301-3b9a-4c8a-b1ca-cc9a76151f1e/osist-pren-iso-8130-4-2021>

ICS:

13.220.40	Sposobnost vžiga in obnašanje materialov in proizvodov pri gorenju	Ignitability and burning behaviour of materials and products
87.040	Barve in laki	Paints and varnishes

oSIST prEN ISO 8130-4:2021**en,fr,de**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[oSIST prEN ISO 8130-4:2021](https://standards.iteh.ai/catalog/standards/sist/e8b0a301-3b9a-4c8a-b1ca-cc9a76151f1e/osist-pren-iso-8130-4-2021)
<https://standards.iteh.ai/catalog/standards/sist/e8b0a301-3b9a-4c8a-b1ca-cc9a76151f1e/osist-pren-iso-8130-4-2021>

DRAFT INTERNATIONAL STANDARD

ISO/DIS 8130-4

ISO/TC 35/SC 9

Secretariat: BSI

Voting begins on:
2021-07-27Voting terminates on:
2021-10-19

Coating powders —

Part 4: Calculation of lower explosion limit

*Poudres pour revêtement —**Partie 4: Calcul de la limite inférieure d'explosibilité*

ICS: 87.040

iTeh STANDARD PREVIEW (standards.iteh.ai)

[oSIST prEN ISO 8130-4:2021](https://standards.iteh.ai/catalog/standards/sist/e8b0a301-3b9a-4c8a-b1ca-cc9a76151f1e/osist-pren-iso-8130-4-2021)<https://standards.iteh.ai/catalog/standards/sist/e8b0a301-3b9a-4c8a-b1ca-cc9a76151f1e/osist-pren-iso-8130-4-2021>

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

This document is circulated as received from the committee secretariat.

ISO/CEN PARALLEL PROCESSING



Reference number
ISO/DIS 8130-4:2021(E)

© ISO 2021

iTeh STANDARD PREVIEW (standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/e8b0a301-3b9a-4c8a-b1ca-cc9a76151f1e/osist-pren-iso-8130-4-2021>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle	2
5 Sampling	2
6 Determination of gross calorific value	2
7 Calculation of the lower explosion limit	2
8 Test report	3
Bibliography	4

iTeh STANDARD PREVIEW (standards.iteh.ai)

[oSIST prEN ISO 8130-4:2021
https://standards.iteh.ai/catalog/standards/sist/e8b0a301-3b9a-4c8a-b1ca-cc9a76151f1e/osist-pren-iso-8130-4-2021](https://standards.iteh.ai/catalog/standards/sist/e8b0a301-3b9a-4c8a-b1ca-cc9a76151f1e/osist-pren-iso-8130-4-2021)

ISO/DIS 8130-4:2021(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 35, *Paints and varnishes*, Subcommittee SC 9, *General test methods for paints and varnishes*.

This second edition cancels and replaces the first edition (ISO 8130-4:1992) and ISO 8130-4 Technical Corrigendum 1:1993, which have been technically revised. The main changes compared to the previous edition are as follows:

- the scope has been modified to differentiate between calculation and an estimation of the lower explosion limit;
- the definition on lower explosion limit (3.1) has been clarified for coating powders;
- the SI unit for the lower explosion limit has been corrected;
- the test report (Clause 8) shall note whether the lower explosion limit was calculated or estimated;
- the bibliography contains a new reference;
- the text has been editorially revised and the normative references have been updated.

A list of all parts in the ISO 8130 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Coating powders —

Part 4: Calculation of lower explosion limit

1 Scope

This document specifies a method for the calculation of the lower explosion limit of a coating powder, i.e. the minimum concentration of the coating powder in air which will form an explosive mixture. It is based on the measurement of the gross calorific value of the product, as determined by the method described in ISO 1928.

Reliable methods for the measurement of the lower explosion limit or the gross calorific value require the use of special apparatus which may not be readily available.

A method for determining the explosion indices of combustible dusts in air is given in ISO 6184-1. This method is, however, very intricate and requires considerable expertise.

The lower explosion limit can also be estimated by summation of the gross calorific value of the individual constituents of the coating powder. It is an estimation since the gross calorific value of the constituent may not be known or available.

The calculation method leads to lower explosion limits which have been proved in practice to be satisfactory when applied to coating application plants.

NOTE A comparison with a direct method, e.g. EN 14034-3 for determining the lower explosion limit is encouraged.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1928, *Coal and coke — Determination of gross calorific value*

ISO 8130-14, *Coating powders — Part 14: Vocabulary*

ISO 15528, *Paints, varnishes and raw materials for paints and varnishes — Sampling*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 8130-14 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

ISO/DIS 8130-4:2021(E)

3.1 lower explosion limit
 minimum concentration of coating powder as a mixture of powder and air, below which an explosion is not possible

Note 1 to entry: The lower explosion limit is expressed as grams per cubic metre ($\text{g} \cdot \text{m}^{-3}$).

4 Principle

The lower explosion limit of a coating powder is calculated by measuring the gross calorific value via the heat of combustion of 1 g of product, using [Formula \(1\)](#).

An estimation of the lower explosion limit can be made, starting with [Formula \(2\)](#), by multiplying the gross calorific value of each combustible constituent by the mass present in 1 g of product.

5 Sampling

Take a representative sample of the product to be tested as described in ISO 15528, for use in ISO 1928.

6 Determination of gross calorific value

Either measure the gross calorific value H_0 of the product under test by the method described in ISO 1928, or calculate it by summation of the gross calorific values of the combustible constituents of the product as specified in [Clause 7](#).

NOTE 1 With powders that are not flammable, such as those of the poly(vinyl chloride) type, the calculation method can nevertheless give a value for the lower explosion limit in air. Thus, any under estimation of an explosion risk is effectively avoided.

NOTE 2 The calculation used in this document is based on the following assumptions:

- that material exists in the form of a powder dispersion;
- that there is complete combustion of the material to the highest oxidation level;
- that there is an adiabatic type of reaction;
- that the flame temperature for the composition with which the minimum concentration for explosion in air is attained is 1 000 °C.

7 Calculation of the lower explosion limit

Calculate the lower explosion limit C , the minimum explosive concentration expressed in grams per cubic metre ($\text{g} \cdot \text{m}^{-3}$) for explosion in air, using [Formula \(1\)](#):

$$C = A + \frac{B}{H_0} \quad (1)$$

where

A is a constant equal to $-2,5 \text{ g/m}^3$; B is a constant equal to $1,24 \times 10^6 \text{ J/m}^3$; H_0 is the gross calorific value of the coating powder, in joules per gram, as per [Clause 6](#). To estimate the gross calorific value H_0 of the product under test from those of its combustible constituents by multiplying the gross calorific value of each combustible constituent by the mass present in 1 g of product and summing.

The gross calorific value H_0 is then given by [Formula \(2\)](#):

$$H_0 = \sum_{i=1}^{i=n} c_i H_i \quad (2)$$

where

n is the number of combustible constituents; c_i is the mass fraction of the i th constituent; H_i is the gross calorific value of the i th constituent. Report the result to the nearest whole number.

8 Test report

The test report shall contain at least the following information:

- a) all details necessary to identify the product tested;
- b) a reference to this document, i.e. ISO 8130-4:—;
- c) the results of the test as indicated in [Clause 7](#);
- d) a note whether the result is based on a calculation or an estimation via the gross calorific value of the product or individual constituents, respectively;
- e) any deviation from the test method specified;
- f) any unusual features (anomalies) observed during the test.
- g) the date of the test.

ITeH STANDARD PREVIEW
(standards.iteh.ai)
oSIST prEN ISO 8130-4:2021
<https://standards.iteh.ai/catalog/standards/sist/e8b0a301-3b9a-4c8a-b1ca-cc9a76151f1e/osist-pren-iso-8130-4-2021>

Bibliography

- [1] ISO 6184-1, *Explosion protection systems — Part 1: Determination of explosion indices of combustible dusts in air*
- [2] EN 14034-3+A1, *Determination of explosion characteristics of dust clouds — Part 3: Determination of the lower explosion limit LEL of dust clouds*
- [3] SCHÖNEWALD I. *Staub-Reinhaltung der Luft*, Vol. 31 (1971), No. 9, pp. 376–378.
- [4] MEYER, B. *Farbe + Lack*, **84** (1978), pp. 75–76.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/e8b0a301-3b9a-4c8a-b1ca-cc9a76151f1e/osist-pren-iso-8130-4-2021>