



## Standard Test Method for the Determination of Percent of Let-Off for Archery Bows<sup>1</sup>

This standard is issued under the fixed designation F1880; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

### 1. Scope

1.1 This test method covers the procedure to be used to determine the percent of let-off for archery bows.

1.2 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

### 2. Referenced Documents

2.1 *ASTM Standards:*<sup>2</sup>

F1832 [Test Method for Determining the Force-Draw and Let-Down Curves for Archery Bows](#)

### 3. Terminology

3.1 *Definitions:*

3.1.1 *Acronyms:*

3.1.1.1 *ATA*—an acronym for the Archery Trade Association.

3.1.2 *ATA draw length*—Archery Trade Association

3.2 *Definitions:*

3.2.1 *ATA actual draw length, n*—the perpendicular distance from the point where the shooting string of the bow contacts the bottom of the nock slot of the arrow to a line parallel to the string at brace height through the pivot or low point of the hand grip (draw length-pivot point), plus a standard dimension of 1 $\frac{3}{4}$  in. (44.5 mm). Draw length shall be measured with the arrow in the full-draw position.

3.1.3—*distance from the bow's string at the nocking point location, while at the bow's full draw condition, measured perpendicular to a vertical line through the pivot point of the bow grip, plus 1 $\frac{3}{4}$  in. (+  $\frac{1}{4}$ , - 0 in.).*

3.2.2 *brace height, n*—the distance in inches or millimetres from the shooting string of a bow to the pivot or low point of the hand grip, measured perpendicular to the string at the un-drawn condition.

3.1.4.3.2.3 *compound bow, n*—a type of bow that imposes a secondary system of control of the force-draw characteristic on the usual limb geometry control system of the conventional bow. This secondary control system can be composed of cams, levers, cables, or other elements, or a combination thereof. The dual control system permits great versatility in the design of the force-draw characteristic and simplifies the inclusion of let-off. In general, it is normal for compound bows to have greater stored energy than conventional bows for a given level of peak or maximum draw weight.

3.1.5 *conventional bow, n*—a bow constructed in the conventional manner, having two flexing limbs extending outwardly in opposite directions from a handle. A single shooting string of a length shorter than the bow, connects the extreme ends of the limbs causing them to assume a prestressed flexed condition. Drawing the bow causes additional bending and stressing of the limbs, storing the energy necessary to propel the arrow. Control of the force-draw characteristic of the bow is exercised entirely by the static and dynamic geometry of the flexing limbs.

3.1.6

3.2.4 *draw, n*—to move the shooting string of a bow from the rest or brace position toward the fully drawn position by applying force to said string. Such action causes the limbs of the bow to bend and store energy. Moving the string from brace height to the full-draw position corresponds to the draw cycle of a bow.

<sup>1</sup> This test method is under the jurisdiction of ASTM Committee F08 on Sports Equipment and Facilities and is the direct responsibility of Subcommittee F08.16 on Archery Products.

Current edition approved May 1, 2004. Published May 2004. Originally approved in 1998. Last previous edition approved in 1998 as F1880-98<sup>e1</sup>. DOI: 10.1520/F1880-98R04.

Current edition approved Nov. 1, 2009. Published December 2009. Originally approved in 1998. Last previous edition approved in 2004 as F1880-98 (2004). DOI: 10.1520/F1880-09.

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, [www.astm.org](http://www.astm.org), or contact ASTM Customer Service at [service@astm.org](mailto:service@astm.org). For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.