

---

**Notranji zrak v cestnih vozilih - 1. del: Preskusna komora za celotno vozilo -  
Specifikacija in metoda za določevanje hlapnih organskih spojin v notranjosti  
kabine**

Interior air of road vehicles - Part 1: Whole vehicle test chamber - Specification and  
method for the determination of volatile organic compounds in cabin interiors

**iTeh STANDARD PREVIEW**  
**(standards.itih.ai)**

Air intérieur des véhicules routiers - Partie 1: Enceinte d'essai pour un véhicule complet -  
Spécification et méthode de détermination des composés organiques volatils dans les  
habitacles d'automobiles

[https://standards.itih.ai/catalog/standards/sist/50d7cf5c-6b25-44e8-87ce-  
770e74683458/ksist-iso-fdis-12219-1-2021](https://standards.itih.ai/catalog/standards/sist/50d7cf5c-6b25-44e8-87ce-770e74683458/ksist-iso-fdis-12219-1-2021)

**Ta slovenski standard je istoveten z: ISO/DIS 12219-1**

---

**ICS:**

13.040.20	Kakovost okoljskega zraka	Ambient atmospheres
43.020	Cestna vozila na splošno	Road vehicles in general

**oSIST ISO/DIS 12219-1:2021**

**en**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[kSIST ISO/FDIS 12219-1:2021](https://standards.iteh.ai/catalog/standards/sist/50d7cf5c-6b25-44e8-87ce-770e74683458/ksist-iso-fdis-12219-1-2021)

<https://standards.iteh.ai/catalog/standards/sist/50d7cf5c-6b25-44e8-87ce-770e74683458/ksist-iso-fdis-12219-1-2021>

# DRAFT INTERNATIONAL STANDARD

## ISO/DIS 12219-1

ISO/TC 146/SC 6

Secretariat: DIN

Voting begins on:  
2020-06-18Voting terminates on:  
2020-09-10

---

---

### Interior air of road vehicles —

Part 1:

## Whole vehicle test chamber — Specification and method for the determination of volatile organic compounds in cabin interiors

*Air intérieur des véhicules routiers —**Partie 1: Enceinte d'essai pour un véhicule complet — Spécification et méthode de détermination des composés organiques volatils dans les habitacles d'automobiles*

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ICS: 13.040.20; 43.020

[kSIST ISO/FDIS 12219-1:2021](https://standards.iteh.ai/catalog/standards/sist/50d7cf5c-6b25-44e8-87ce-770e74683458/ksist-iso-fdis-12219-1-2021)<https://standards.iteh.ai/catalog/standards/sist/50d7cf5c-6b25-44e8-87ce-770e74683458/ksist-iso-fdis-12219-1-2021>

Member bodies are requested to consult relevant national interests in ISO/TC 22 before casting their ballot to the e-Balloting application.

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

This document is circulated as received from the committee secretariat.



Reference number  
ISO/DIS 12219-1:2020(E)

© ISO 2020

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[kSIST ISO/FDIS 12219-1:2021](https://standards.iteh.ai/catalog/standards/sist/50d7cf5c-6b25-44e8-87ce-770e74683458/ksist-iso-fdis-12219-1-2021)

<https://standards.iteh.ai/catalog/standards/sist/50d7cf5c-6b25-44e8-87ce-770e74683458/ksist-iso-fdis-12219-1-2021>



### **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Fax: +41 22 749 09 47  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

	Page
<b>Foreword</b> .....	<b>iv</b>
<b>Introduction</b> .....	<b>v</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>2</b>
<b>3 Terms and definitions</b> .....	<b>2</b>
<b>4 Apparatus and materials</b> .....	<b>3</b>
4.1 General.....	3
4.2 Heating radiator.....	3
4.3 Sampling trains.....	4
4.3.1 Sampling in the test vehicle.....	4
4.3.2 Sampling in the whole vehicle test chamber.....	4
4.3.3 Sampling line.....	4
4.4 Analytical equipment and materials.....	5
4.5 Test vehicle.....	5
<b>5 Principle</b> .....	<b>5</b>
<b>6 Requirements of the whole vehicle test chamber, test vehicle and measurement procedures</b> .....	<b>6</b>
6.1 Requirements for the whole vehicle test chamber.....	6
6.2 Requirements for the test vehicle.....	7
6.2.1 General.....	7
6.2.2 Restricting influencing factors.....	8
6.2.3 Requirements for sampling train set up.....	8
6.2.4 Temperature and ventilation.....	9
6.3 Requirements for VOC and carbonyl compound air sampling and measurements methods.....	9
6.4 Blank measurements.....	10
6.4.1 Field blanks.....	10
6.4.2 Analytical blanks.....	10
<b>7 Standard test procedure</b> .....	<b>11</b>
7.1 General.....	11
7.2 Preparation of the test chamber, vehicle and field blanks.....	11
7.2.1 Pre-arrangements.....	11
7.2.2 Preconditioning of the whole vehicle test chamber.....	11
7.2.3 Preconditioning of the test vehicle.....	11
7.2.4 Field blanks.....	11
7.3 Detailed description of the test procedure.....	12
7.3.1 Ambient mode.....	12
7.3.2 Parking mode.....	12
7.3.3 Driving mode.....	13
<b>8 Results</b> .....	<b>13</b>
<b>9 Performance characteristics</b> .....	<b>13</b>
<b>10 Quality assurance/quality control</b> .....	<b>14</b>
<b>Annex A (informative) Whole vehicle test chamber</b> .....	<b>15</b>
<b>Annex B (informative) Temperature measuring points for parking mode</b> .....	<b>16</b>
<b>Annex C (informative) Test report</b> .....	<b>17</b>
<b>Annex D (normative) Overview of the number of samples to be taken</b> .....	<b>28</b>

## ISO/DIS 12219-1:2020(E)

### Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 146, Air quality, Subcommittee SC 6, *Indoor air*.

This second edition cancels and replaces the first edition (ISO 12219-1:2012), which has been technically revised.

The main changes compared to the previous edition are as follows:

- Adaption of temperatures, number of samples to be taken and the pre-conditioning and measuring times to be consistent with the UN mutual resolution.

A list of all parts in the ISO 12219 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

## Introduction

Volatile organic compounds (VOCs) are widely used in industry and can be emitted by many everyday products and materials. They have attracted attention in recent years because of their impact on indoor air quality. After homes and workplaces, people spend a lot of time in their vehicles. It is important to determine the material emissions of interior parts and to reduce them to an acceptable level, if required. Therefore it is necessary to obtain comprehensive and reliable information about the types of organic compounds in the interior air of vehicles and also their concentrations.

This part of ISO 12219 outlines a method of measuring the types and levels of VOCs in vehicle cabin air under controlled conditions. It describes requirements for a whole vehicle test chamber and a test protocol. Measurements are carried out according to ISO 16000-6 (VOCs) and ISO 16000-3 (carbonyl compounds).

There are several national test methods available for measuring in-vehicle air quality, e.g. References [2][4]. However, this part of ISO 12219 requires a fixed heating radiation system whereas the methods of References [2][3] define a fixed temperature programme.

Before setting a fixed radiation density for heating the test vehicle, several validation measurements were performed (Reference [1]).

ISO 16000-3, ISO 16000-5,<sup>[6]</sup> ISO 16000-6, ISO 16000-9,<sup>[7]</sup> ISO 16000-10,<sup>[8]</sup> ISO 16000-11,<sup>[9]</sup> ISO 16000-24,<sup>[10]</sup> ISO 16000-25,<sup>[11]</sup> as well as ISO 16017-1 and ISO 16017-2<sup>[12]</sup> also focus on volatile organic compound (VOC) measurements.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ksIST ISO/FDIS 12219-1:2021](https://standards.iteh.ai/catalog/standards/sist/50d7cf5c-6b25-44e8-87ce-770e74683458/ksist-iso-fdis-12219-1-2021)

<https://standards.iteh.ai/catalog/standards/sist/50d7cf5c-6b25-44e8-87ce-770e74683458/ksist-iso-fdis-12219-1-2021>

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[kSIST ISO/FDIS 12219-1:2021](#)

<https://standards.iteh.ai/catalog/standards/sist/50d7cf5c-6b25-44e8-87ce-770e74683458/ksist-iso-fdis-12219-1-2021>



# Interior air of road vehicles —

## Part 1:

# Whole vehicle test chamber — Specification and method for the determination of volatile organic compounds in cabin interiors

## 1 Scope

This part of ISO 12219 describes and specifies the whole vehicle test chamber, the vapour sampling assembly and the operating conditions for the determination of volatile organic compounds (VOCs), and carbonyl compounds in vehicle cabin air. There are three measurements performed: one (for VOCs and carbonyl compounds) during the simulation of ambient conditions (ambient mode) at standard conditions of 23-25 °C with no air exchange; a second only for the measurement of formaldehyde at elevated temperatures (parking mode); and a third for VOCs and carbonyl compounds simulating driving after the vehicle has been parked in the sun starting at elevated temperatures (driving mode). For the simulation of the mean sun irradiation, a fixed irradiation in the whole vehicle test chamber is employed.

## iTeh STANDARD PREVIEW

The VOC method is valid for measurement of non-polar and slightly polar VOCs in a concentration range of sub-micrograms per cubic metre up to several milligrams per cubic metre. Using the principles described in this method, some semi-volatile organic compounds (SVOC) can also be analysed. Compatible compounds are those which can be trapped and released from the Tenax TA<sup>®1)</sup> sorbent tubes described in ISO 16000-6, which includes VOCs ranging in volatility from  $n$ -C<sub>6</sub> to  $n$ -C<sub>16</sub>.

The sampling and analysis procedure for formaldehyde and other carbonyl compounds is performed by collecting air on to cartridges coated with 2,4-dinitrophenylhydrazine (DNPH) and subsequent analysis by high performance liquid chromatography (HPLC) with detection by ultraviolet absorption. Formaldehyde and other carbonyl compounds can be determined in the approximate concentration range 1 µg/m<sup>3</sup> to 1 mg/m<sup>3</sup>.

The method is valid for passenger cars, as defined in ECE-TRANS-WP.29/1045.

This part of ISO 12219 describes:

- a) transport and storage of the test vehicles until the start of the test;
- b) conditioning for the surroundings of the test vehicle and the test vehicle itself as well as the whole vehicle test chamber;
- c) conditioning of the test vehicle prior to measurements;
- d) simulation of ambient air conditions (ambient mode);
- e) formaldehyde sampling at elevated temperatures (parking mode);
- f) simulation of driving after the test vehicle has been parked in the sun (driving mode).

1) Tenax TA<sup>®</sup> is the trade name of a product supplied by Buchem. This information is given for the convenience of users of this document and does not constitute an endorsement by ISO of the product named. Equivalent products may be used if they can be shown to lead to the same results.

## ISO/DIS 12219-1:2020(E)

### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 9060, *Solar energy — Specification and classification of instruments for measuring hemispherical solar and direct solar radiation*

ISO 16000-3, *Indoor air — Part 3: Determination of formaldehyde and other carbonyl compounds in indoor air and test chamber air — Active sampling method*

ISO 16000-6:2011, *Indoor air — Part 6: Determination of volatile organic compounds in indoor and test chamber air by active sampling on Tenax TA sorbent, thermal desorption and gas chromatography using MS or MS-FID*

ISO 16017-1, *Indoor, ambient and workplace air — Sampling and analysis of volatile organic compounds by sorbent tube/thermal desorption/capillary gas chromatography — Part 1: Pumped sampling*

ECE-TRANS-WP.29/1045, *Special resolution No 1, Concerning the common definitions of vehicle categories, masses and dimensions (S.R. 1)*

### 3 Terms and definitions

For the purpose of this document, the terms and definitions of ISO 16000-3, ISO 16000-6 and the following apply.

#### 3.1 background concentration

substance concentrations in the whole vehicle test chamber when the test vehicle is inside

#### 3.2 test vehicle

new, category 1-1 vehicle (3.13) to be tested. The test age of the vehicle shall not be older than 28d±5 days after the production date

Note 1 to entry: Excludes busses used for public transport and trucks only used for the transport of goods

#### 3.3 total volatile compounds TVOCs

sum of volatile organic compounds sampled on Tenax TA<sup>(1)</sup> and eluting between and including *n*-hexane and *n*-hexadecane, detected with a flame ionization detector (TVOC<sub>FID</sub>) or mass spectrometric detector (TVOC<sub>MS</sub>) and quantified converting the total area of the chromatogram in that analytical window to toluene equivalents

Note 1 to entry: Adapted from ISO 16000-6:2011, 3.4

#### 3.4 carbonyl compound

includes formaldehyde, acetaldehyde and acrolein

#### 3.5 ambient mode

mode in which sampling of substances in the interior air of a test vehicle under standardized ambient temperature conditions is performed, defined by 23-25 °C, as close as possible to 25°C

#### 3.6 parking mode

mode in which sampling of substances in the interior air of a test vehicle under elevated temperatures resulting from defined external heat radiation is performed

**3.7****driving mode**

mode in which sampling of substances in the interior air of a test vehicle, under standardized conditions starting at elevated temperatures and with the engine on using air conditioning. Driving is simulated with an idle test procedure of a vehicle driven after being parked in the sun

**3.8****breathing zone**

semi-sphere area with 50 cm radius in front of the driver's face

**3.9****sampling train**

apparatus to collect the air sample inside the test vehicle cabin from the breathing zone and to collect the air sample from in the whole vehicle test chamber, trapping the test substances in sorbent tubes under standardized conditions

**3.10****VOCs**

volatile organic compounds, ranging in volatility from n-C6 to n-C16

EXAMPLE Benzene, Toluene, Xylene, Ethylbenzene and Styrene

**3.11****production date**

date a new vehicle leaves the production line

**3.12****category 1 vehicle**

means a power driven vehicle with four or more wheels designed and constructed primarily for the carriage of (a) person(s)

**3.13****category 1-1 vehicle**

means a category 1 vehicle (3.12) comprising not more than eight seating positions in addition to the driver's seating position

Note 1 to entry: A category 1-1 vehicle cannot have standing passengers.

**4 Apparatus and materials****4.1 General**

The whole vehicle test chamber is big enough to house the test vehicle completely. An air-conditioning system is installed to allow standardized air conditions for a temperature of 23 -25 °C, humidity of 50 % RH ± 10 % RH. A solar radiator system is installed to heat the test vehicle cabin with a fixed irradiation. The resulting temperature inside the cabin depends on the insulation and the window glass material (the minimum requirements are specified in 6.1) (see also Figure 1).

**4.2 Heating radiator**

Infrared radiator, halogen radiator or other radiators (simulating sunlight) (wavelengths <300 nm shall be filtered out). The heating radiators used shall be powered to create a radiation density at the reference measurement point in the middle of the roof surface of the test vehicle of 350 W/m<sup>2</sup> to 450 W/m<sup>2</sup> (400 W/m<sup>2</sup> ± 50 W/m<sup>2</sup>).

The heating area shall cover at least the area of the test vehicle cabin and an additional 0,5 m more to each side of the lower part of the glazing (footprint) (see Figure 1). Position the heating radiators on the roof with a shining angle of 90° to the heating area. There shall be no heating radiators shining from the side. The heating area shall be calibrated in squares of 25 cm × 25 cm with a radiation density of 400 W/

## ISO/DIS 12219-1:2020(E)

$m^2 \pm 50 W/m^2$ . The required radiation density shall be available directly after the lamps are switched on (within a few minutes).

The irradiation shall be measured in accordance with ISO 9060.

Take care not to have too short a distance between radiator and surface in order to avoid hot spots.

### 4.3 Sampling trains

#### 4.3.1 Sampling in the test vehicle

Four sampling trains are employed: two for the VOC measurements in parallel and two for the carbonyl compound measurements in parallel in the test vehicle (to check the repeatability) (see ISO 16000-3 for carbonyl compounds and ISO 16000-6 or ISO 16017-1 for VOCs). There is one sampling line with a manifold for the division of the sampling flow outside the test vehicle (see 4.3.3). It consists of the probe, the sampling line (heated, if necessary), the sorbent tube for VOC or the DNPH cartridge for carbonyl compound sampling respectively, the gas meters and the pumps (see 4.5).

Prior to sampling, the sampling system shall be checked under sampling load conditions for air tightness. Do not skip this critical step because leaks have a high impact on the test results due to the large backpressure of the tubes and cartridges. To check for leaks plug the inlet to the sample system. Then use a vacuum pump to bring the sampling system to 21 inHg vacuum, then close a valve between the sample system and the pump. After 30 seconds, the sample system vacuum must be greater than 20 inHg to proceed. Do not change the sample trains in any way after the leak check procedure is performed. Other equivalent leak checks can be performed.

#### 4.3.2 Sampling in the whole vehicle test chamber

Four sampling trains are used to determine the background concentration in the whole vehicle test chamber. The sampling trains are identical to those of 4.3.1, apart from the sampling line, which is much shorter and not heated.

All sampling trains shall have a maximum vacuum decay rate of 30 kPa for an average of 10 s. The nozzle is plugged for the leak check. Other equivalent leak checks can be employed.

#### 4.3.3 Sampling line

Tubing, between the sampling point (probe) inside the test vehicle, via the manifold outside the test vehicle to the VOC sorbent tubes or DNPH cartridges respectively (see Figure 1).

The sampling line shall be constructed so as to be

- as short as possible (maximum 5 m) with an internal diameter of 4 mm or more;
- of inert, non-emitting and non-absorbing/non-adsorbing material [e.g. stainless steel or polytetrafluoroethylene (PTFE) or glass/quartz (deactivated)];
- proven that there are no contaminations or sink effects in the sampling line;
- with heating device, if necessary, to prevent condensation/deposition on the inner walls (best practice: temperature controlled to about 20 °C above air temperature inside the test vehicle).

The tubing should be inserted between the door and the door frame or between the door frame and the glazing and should be sufficiently non-compressible to ensure an unimpeded flow of air.

The second sampling line [tubing, between the sampling point (probe) in the whole vehicle test chamber in the vicinity of the test vehicle [see 6.1 b)] and the manifold and to the VOC sorbent tubes or DNPH cartridges, respectively] is identical to that described in the preceding, but no heating is necessary. This second sampling line is needed to monitor the background analyte concentration of the whole