

ETSI TS 124 502 V17.10.0 (2024-07)



5G;
Access to the 3GPP 5G Core Network (5GCN)
via non-3GPP access networks
(3GPP TS 24.502 version 17.10.0 Release 17)

[ETSI TS 124 502 V17.10.0 \(2024-07\)](https://standards.iteh.ai/catalog/standards/etsi/ad62834e-b504-4324-88ad-10fd1b19c2de/etsi-ts-124-502-v17-10-0-2024-07)

<https://standards.iteh.ai/catalog/standards/etsi/ad62834e-b504-4324-88ad-10fd1b19c2de/etsi-ts-124-502-v17-10-0-2024-07>



Reference

RTS/TSGC-0124502vha0

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
ETSI [Search & Browse Standards application](#).

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#).

Users should be aware that the present document may be revised or have its status changed,
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2024.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables. (2024-07)

The cross reference between 3GPP and ETSI identities can be found under <https://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	7
1 Scope	8
2 References	8
3 Definitions, symbols and abbreviations	10
3.1 Definitions	10
3.2 Abbreviations	11
4 General	12
4.1 Overview	12
4.2 Untrusted access	12
4.3 Identities	12
4.3.1 User identities	12
4.3.2 FQDN for N3IWF Selection	12
4.4 Quality of service support	13
4.4.1 General.....	13
4.4.2 QoS differentiation in non-3GPP access.....	13
4.4.2.1 General	13
4.4.2.2 QoS signalling.....	13
4.4.2.3 QoS differentiation in user plane	14
4.4.2.4 Reflective QoS	14
4.4.2.5 QoS enforcement.....	14
4.5 Trusted access	14
4.6 Forbidden PLMNs for non-3GPP access to 5GCN	15
5 Network discovery and selection	15
5.1 General	15
5.2 Access network discovery procedure	16
5.2.1 General.....	16
5.2.2 Discovering availability of WLAN access networks	16
5.3 Access network selection procedure.....	16
5.3.1 General.....	16
5.3.2 WLAN selection procedure	16
5.3.2.1 General	16
5.3.2.2 Manual mode WLAN selection.....	17
5.3.2.3 Automatic mode WLAN selection.....	17
5.3A PLMN selection procedures using trusted non-3GPP access	18
5.3A.1 General.....	18
5.3A.2 PLMN solicitation	18
5.3A.3 Manual PLMN selection mode procedure	19
5.3A.4 Automatic mode PLMN selection procedure.....	19
5.3A.4.1 General	19
5.3A.4.2 Attempting to select HPLMN or equivalent HPLMN.....	20
5.3A.4.3 Void.....	21
5.3B PLMN selection procedures using wireline access	21
5.3C PLMN selection procedures for NSWO in 5GS.....	21
5.4 Access network reselection procedure	21
5.4.1 General.....	21
5.4.2 WLAN reselection procedure	21
6 UE - 5GC network protocols.....	22
6.1 General	22
6.2 Void.....	22

6.3	Authentication and authorization for accessing 5GS via non-3GPP access network	22
6.3.1	General.....	22
6.3.2	Authentication of N5GC device behind a CRG over wireline access.....	22
6.3a	Authentication for NSWO in 5GS.....	23
6.4	Handling of ANDSP Information.....	23
6.4.1	General.....	23
6.4.2	UE procedures	24
6.4.2.1	General	24
6.4.2.2	Use of WLAN selection information	24
6.4.2.3	Use of N3AN node configuration information.....	24
6.4.3	ANDSP information from the network.....	24
7	Security association management procedures	24
7.1	General	24
7.2	N3AN node selection procedure	25
7.2.1	General.....	25
7.2.2	N3AN node configuration information.....	25
7.2.3	Determination of the country the UE is located in.....	25
7.2.4	N3AN node selection for non-emergency services.....	25
7.2.4.1	General	25
7.2.4.2	Determine if the visited country mandates the selection of N3IWF in this country.....	26
7.2.4.3	UE procedure when the UE only supports connectivity with N3IWF	26
7.2.4.4	UE procedure when the UE supports connectivity with N3IWF and ePDG	29
7.2.4.4.1	General	29
7.2.4.4.2	N3AN node selection for IMS service.....	29
7.2.4.4.3	N3AN node selection for Non-IMS service	32
7.2.5	Selection of an N3AN node in an SNPN	35
7.2.6	N3AN node selection for emergency services.....	36
7.2.6.1	General	36
7.2.6.2	UE procedure when the UE only supports connectivity with N3IWF	36
7.2.6.3	UE procedure when the UE supports connectivity with N3IWF and ePDG.....	36
7.3	IKE SA establishment procedure for untrusted non-3GPP access	37
7.3.1	General.....	37
7.3.2	IKE SA and signalling IPsec SA establishment procedure.....	37
7.3.2.1	IKE SA and signalling IPsec SA establishment initiation.....	37
7.3.2.2	IKE SA and signalling IPsec SA establishment accepted by the network	38
7.3.2.3	IKE SA and signalling IPsec SA establishment not accepted by the network	39
7.3.3	EAP-5G session over non-3GPP access	41
7.3.3.1	General	41
7.3.3.1A	EAP-5G session initiation	41
7.3.3.2	EAP-5G session completion initiated by the network.....	41
7.3.3.3	EAP-5G session completion initiated by the UE	42
7.3.4	Abnormal cases in the UE	43
7.3.5	Abnormal cases in the N3IWF.....	43
7.3A	IKE SA establishment procedure for trusted non-3GPP access	43
7.3A.1	General.....	43
7.3A.2	EAP session over non-3GPP access	45
7.3A.2.1	General	45
7.3A.2.2	Identity transaction.....	45
7.3A.2.3	EAP-5G session initiation	45
7.3A.2.4	EAP-5G session completion initiated by the network.....	46
7.3A.2.5	EAP-5G session completion initiated by the UE	46
7.3A.3	IKE SA and signalling IPsec SA establishment procedure.....	46
7.3A.3.1	IKE SA and signalling IPsec SA establishment initiation.....	46
7.3A.3.2	IKE SA and signalling IPsec SA establishment accepted by the network	46
7.3A.3.3	IKE SA and signalling IPsec SA establishment not accepted by the network	46
7.3A.4	Procedure for devices without NAS support.....	47
7.3A.4.1	General	47
7.3A.4.2	N5CW device registration over trusted WLAN access network.....	47
7.4	IKEv2 SA deletion procedure	48
7.4.1	General.....	48
7.4.2	IKE SA deletion procedure initiated by the N3IWF and the TNGF.....	48

7.4.2.1	IKE SA deletion initiation.....	48
7.4.2.2	IKE SA deletion accepted by the UE.....	48
7.4.2.3	Abnormal cases in the N3IWF and the TNGF.....	49
7.4.3	IKE SA deletion procedure initiated by the UE.....	49
7.4.3.1	IKE SA deletion initiation.....	49
7.4.3.2	IKE SA deletion accepted by the N3IWF and the TNGF.....	49
7.4.3.3	Abnormal cases in the UE.....	49
7.5	User plane IPsec SA creation procedure.....	50
7.5.1	General.....	50
7.5.2	Child SA creation procedure initiation.....	50
7.5.3	Child SA creation procedure accepted by the UE.....	50
7.5.4	Child SA creation procedure not accepted by the UE.....	51
7.5.5	Abnormal cases in the UE.....	51
7.5.6	Abnormal cases in the N3IWF and the TNGF.....	51
7.6	IPsec SA modification procedure.....	51
7.6.1	General.....	51
7.6.2	N3IWF and TNGF procedure for IPsec child SA modification.....	51
7.6.3	UE procedure for IPsec child SA modification.....	51
7.7	IPSec SA deletion procedure.....	52
7.7.1	General.....	52
7.7.2	N3IWF-initiated and TNGF-initiated child SA deletion procedure.....	52
7.7.2.1	N3IWF-initiated and TNGF-initiated child SA deletion procedure initiation.....	52
7.7.2.2	N3IWF-initiated and TNGF-initiated child SA deletion procedure accepted by the UE.....	53
7.7.2.3	Abnormal cases in the N3IWF and the TNGF.....	53
7.7.3	UE-initiated child SA deletion procedure.....	53
7.7.3.1	UE-initiated child SA deletion procedure initiation.....	53
7.7.3.2	UE-initiated child SA deletion procedure accepted by the N3IWF and the TNGF.....	53
7.7.3.3	Abnormal cases in the UE.....	53
7.7.4	Abnormal cases in the UE.....	53
7.7.5	Abnormal cases in the N3IWF and the TNGF.....	53
7.8	UE-initiated liveness check procedure.....	54
7.8.1	General.....	54
7.8.2	UE-initiated liveness check procedure initiation.....	54
7.8.3	UE-initiated liveness check procedure completion.....	54
7.8.4	Abnormal cases.....	54
7.9	Network-initiated liveness check procedure.....	54
7.9.1	General.....	54
7.9.2	Network-initiated liveness check procedure initiation.....	54
7.9.3	Network-initiated liveness check procedure completion.....	55
7.9.4	Abnormal cases.....	55
7.10	IKE SA rekeying procedure.....	55
7.10.1	General.....	55
7.10.2	N3IWF-initiated and TNGF-initiated IKE SA rekeying procedure.....	55
7.10.2.1	N3IWF-initiated and TNGF-initiated IKE SA rekeying procedure initiation.....	55
7.10.2.2	N3IWF-initiated and TNGF-initiated IKE SA rekeying procedure completion.....	55
7.10.2.3	Abnormal cases.....	55
7.10.3	UE-initiated IKE SA rekeying procedure.....	56
7.10.3.1	UE-initiated IKE SA rekeying procedure initiation.....	56
7.10.3.2	UE-initiated IKE SA rekeying procedure completion.....	56
7.10.3.3	Abnormal cases.....	56
7.11	IPsec SA rekeying procedure.....	56
7.11.1	General.....	56
7.11.2	N3IWF-initiated and TNGF-initiated IPsec SA rekeying procedure.....	56
7.11.2.1	N3IWF-initiated and TNGF-initiated IPsec SA rekeying procedure initiation.....	56
7.11.2.2	N3IWF-initiated and TNGF-initiated IPsec SA rekeying procedure completion.....	57
7.11.2.3	Abnormal cases.....	57
7.11.3	UE-initiated IPsec SA rekeying procedure.....	57
7.11.3.1	UE-initiated IPsec SA rekeying procedure initiation.....	57
7.11.3.2	UE-initiated IPsec SA rekeying procedure completion.....	57
7.11.3.3	Abnormal cases.....	57
7A	void.....	58

8	Message transport procedures	58
8.1	General	58
8.2	Transport of NAS messages over control plane	58
8.2.1	General.....	58
8.2.2	TCP packet encapsulation.....	58
8.2.3	Establishment of TCP connection for transport of NAS messages.....	60
8.2.3A	Re-establishment of TCP connection for transport of NAS messages.....	61
8.2.4	Transport of NAS messages over TCP connection.....	61
8.2.5	Release of TCP connection for transport of NAS messages.....	61
8.3	Transport of messages over user plane.....	61
8.3.1	General.....	61
8.3.2	Generic routing encapsulation (GRE).....	62
9	Parameters and coding.....	63
9.1	General	63
9.2	3GPP specific coding information.....	63
9.2.1	GUAMI.....	63
9.2.2	Establishment cause for non-3GPP access.....	64
9.2.3	PLMN ID	65
9.2.4	IKEv2 Notify Message Type value.....	65
9.2.4.1	General	65
9.2.4.2	Private Notify Message - Error Types.....	66
9.2.4.3	Private Notify Message - Status Types	66
9.2.5	TNGF IPv4 contact info	67
9.2.6	TNGF IPv6 contact info	68
9.2.7	NID	68
9.3	IETF RFC coding information	69
9.3.1	IKEv2 Notify payloads	69
9.3.1.1	5G_QOS_INFO Notify payload.....	69
9.3.1.2	NAS_IP4_ADDRESS Notify payload	75
9.3.1.3	NAS_IP6_ADDRESS Notify payload	75
9.3.1.4	UP_IP4_ADDRESS Notify payload	76
9.3.1.5	UP_IP6_ADDRESS Notify payload	77
9.3.1.6	NAS_TCP_PORT Notify payload	77
9.3.1.7	N3GPP_BACKOFF_TIMER Notify payload.....	78
9.3.2	EAP-5G method.....	78
9.3.2.1	General	78
9.3.2.2	Message format	78
9.3.2.2.1	EAP-Request/5G-Start message	78
9.3.2.2.2	EAP-Response/5G-NAS message	79
9.3.2.2.3	EAP-Request/5G-NAS message.....	83
9.3.2.2.4	EAP-Response/5G-Stop message.....	84
9.3.2.2.5	EAP-Request/5G-Notification message	85
9.3.2.2.6	EAP-Response/5G-Notification message.....	87
9.3.3	GRE encapsulated user data packet	88
9.4	NAS message envelope	89
Annex A (informative): Change history		91
History		96

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI TS 124 502 V17.10.0 \(2024-07\)](https://standards.iteh.ai/catalog/standards/etsi/ad62834e-b504-4324-88ad-10fd1b19c2de/etsi-ts-124-502-v17-10-0-2024-07)

<https://standards.iteh.ai/catalog/standards/etsi/ad62834e-b504-4324-88ad-10fd1b19c2de/etsi-ts-124-502-v17-10-0-2024-07>

1 Scope

The present document specifies non-3GPP access network discovery and selection procedures, the access authorization procedure used for accessing non-3GPP access networks. These non-3GPP access networks can be trusted non-3GPP access networks, untrusted non-3GPP access networks or wireline access networks.

The present document also specifies the security association management procedures used for establishing IKEv2 and IPsec security associations:

- between the UE and the N3IWF and the procedures for transporting messages between the UE and the N3IWF over the non-3GPP access networks; and
- between the UE and the TNGF and the procedures for transporting messages between the UE and the TNGF over the non-3GPP access networks.

The present document also specifies the EAP-5G procedures used for exchange of NAS messages via trusted non-3GPP access before the UE is authenticated and authorized to use the trusted non-3GPP access.

The present document is applicable to the UE, the 5G-RG, the W-AGF acting on behalf of the FN-RG or the W-AGF acting on behalf of the N5GC device and the network. In this technical specification the network refers to the 3GPP 5GCN and the trusted non-3GPP access, untrusted non-3GPP access, or wireline access network.

NOTE: The present document is not applicable to the FN-RG.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 23.501: "System Architecture for the 5G System; Stage 2".
- [3] 3GPP TS 23.502: "Procedures for the 5G System; Stage 2".
- [4] 3GPP TS 24.501: "Access-Stratum (NAS) protocol for 5G System (5GS); Stage 3".
- [4A] 3GPP TS 24.301: "Non-Access-Stratum (NAS) protocol for Evolved Packet System (EPS); Stage 3".
- [5] 3GPP TS 33.501: "Security architecture and procedures for 5G System".
- [6] IETF RFC 7296: "Internet Key Exchange Protocol Version 2 (IKEv2)".
- [7] 3GPP TS 24.302: "Access to the 3GPP Evolved Packet Core (EPC) via non-3GPP access networks; Stage 3".
- [8] 3GPP TS 23.003: "Numbering, addressing and identification".
- [9] IETF RFC 3748: "Extensible Authentication Protocol (EAP)".
- [10] 3GPP TS 33.402: "3GPP System Architecture Evolution (SAE); Security aspects of non-3GPP accesses."

- [11] IETF RFC 4303: "IP Encapsulating Security Payload (ESP)".
- [12] IETF RFC 4301: "Security Architecture for the Internet Protocol".
- [13] 3GPP TS 23.122: "Non-Access-Stratum (NAS) functions related to Mobile Station (MS) in idle mode".
- [14] IETF RFC 2784: "Generic Routing Encapsulation (GRE)".
- [15] IETF RFC 2890: "Key and Sequence Number Extensions to GRE".
- [16] 3GPP TS 23.503: "Policy and Charging Control Framework for the 5G System".
- [17] 3GPP TS 24.526: "User Equipment (UE) policies for 5G System (5GS); Stage 3".
- [18] 3GPP TS 23.402: "Architecture enhancements for non-3GPP accesses".
- [19] IEEE Std 802.11-2016: "IEEE Standard for Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications".
- [20] Wi-Fi Alliance: "Hotspot 2.0 (Release 2) Technical Specification, version 1.0.0", 2014-08-08.
- [21] ITU-T Recommendation E.212: "The international identification plan for public networks and subscriptions", 2016-09-23.
- [22] 3GPP TS 24.007: "Mobile radio interface signalling layer 3; General aspects".
- [23] IETF RFC 4555: "IKEv2 Mobility and Multihoming Protocol (MOBIKE)".
- [24] IETF RFC 791: "INTERNET PROTOCOL".
- [25] IETF RFC 8200: "Internet Protocol, Version 6 (IPv6) Specification".
- [26] IETF RFC 2474: "Definition of the Differentiated Services Field (DS Field) in the IPv4 and IPv6 Headers".
- [27] IETF RFC 793: "Transmission Control Protocol".
- [28] 3GPP TS 24.008: "Mobile radio interface Layer 3 specification; Core network protocols; Stage 3".
- [29] 3GPP TS 38.413: "NG Application Protocol (NGAP)".
- [30] IEEE Std 802.1X™-2010: "IEEE Standard for Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Port-based Network Access Control".
- [31] IETF RFC 4284 (January 2006): "Identity Selection Hints for the Extensible Authentication Protocol (EAP)".
- [32] IETF RFC 1661: "The Point-to-Point Protocol (PPP)".
- [33] IETF RFC 1570: "PPP LCP Extensions".
- [34] IETF RFC 2410: "The NULL Encryption Algorithm and Its Use With IPsec".
- [35] 3GPP TS 31.102: "Characteristics of the Universal Subscriber Identity Module (USIM) application".
- [36] CableLabs WR-TR-5WWC-ARCH-V02-200430: "5G Wireless Wireline Converged Core Architecture Technical Report".
- [37] IETF RFC 7542: "The Network Access Identifier".
- [38] 3GPP TS 24.368: "Non-Access Stratum (NAS) configuration Management Object (MO)".
- [39] 3GPP TS 29.413: "Application of the NG Application Protocol (NGAP) to non-3GPP access".

- [40] 3GPP TS 23.316: "Wireless and wireline convergence access support for the 5G System (5GS)".
- [41] 3GPP TS 23.304: "Proximity based Services (ProSe) in the 5G System (5GS); Stage 2".
- [42] BBF TR-456 issue 2 (March 2022): "AGF Functional Requirements".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1].

MTU: Maximum transmission unit (MTU) is the largest PDU size which can be transmitted and received by a network entity in one single IP packet without any need for IP fragmentation.

NWt: NWt is the reference point between the UE and the TNGF for establishing secure tunnel(s) between the UE and the TNGF so that control-plane and user-plane exchanged between the UE and the 5G core network is transferred securely over trusted non-3GPP access.

NWu: NWu is the reference point between the UE and the N3IWF for establishing secure tunnel(s) between the UE and the N3IWF so that control-plane and user-plane exchanged between the UE and the 5G core network is transferred securely over untrusted non-3GPP access.

For the purposes of the present document, the following terms and definitions given in 3GPP TS 23.501 [2] apply:

5G Access Network

5G Core Network

5G QoS flow

5G QoS identifier

5G System

Network identifier (NID)

PDU Session

Stand-alone Non-Public Network

TNGF

For the purposes of the present document, the following terms and definitions given in 3GPP TS 23.003 [8] apply:

Global Line Identifier (GLI)

Global Cable Identifier (GCI)NAI

For the purposes of the present document, the following terms and definitions given in 3GPP TS 33.501 [5] apply:

SUPI

SUCI

For the purposes of the present document, the following terms and definitions given in 3GPP TS 24.302 [7] apply:

S2a connectivity

For the purposes of the present document, the following terms and definitions given in 3GPP TS 24.501 [4] apply:

Non 5G capable over WLAN (N5CW) device

SNPN access operation mode

W-AGF acting on behalf of the N5GC device

For the purposes of the present document, the following terms and definitions given in 3GPP TS 23.316 [40] apply:

Wireline access control plane protocol (W-CP)

Wireline access user plane protocol (W-UP)

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [1].

5GCN	5G Core Network
5GS	5G System
5G-AN	5G Access Network
5QI	5G QoS Identifier
AMF	Access and Mobility Management Function
AN	Access Network
ANDS	Access Network Discovery and Selection
ANDSP	Access Network Discovery and Selection Policy
AUSF	Authentication Server Function
CP	Control Plane
CRG	Cable Residential Gateway
DHCP	Dynamic Host Configuration Protocol
DL	Downlink
DNS	Domain Name System
DSCP	Differentiated Services Code Point
ePDG	Evolved Packet Data Gateway
ESP	Encapsulating Security Payload
FQDN	Fully Qualified Domain Name
H-PCF	A PCF in the HPLMN
IP	Internet Protocol
IPsec	Internet Protocol Security
N3AN	Non-3GPP Access Network
N3IWF	Non-3GPP InterWorking Function
N5CW	Non 5G Capable over WLAN
N5GC	Non-5G Capable
NAI	Network Access Identifier
NAS	Non Access Stratum
NID	Network Identifier
NSWO	Non-Seamless WLAN Offload
PCF	Policy control Function
PDU	Protocol Data Unit
QFI	QoS Flow Identifier
RQI	Reflective QoS Indicator
SA	Security Association
SNPN	Stand-alone Non-Public Network
SPI	Security Parameters Index
SUPI	Subscription Permanent Identifier
SUCI	Subscription Concealed Identifier
TCP	Transmission Control Protocol
TNAN	Trusted Non-3GPP Access Network
TNAP	Trusted Non-3GPP Access Point
TNGF	Trusted Non-3GPP Gateway Function
TWAN	Trusted WLAN Access Network
TWAP	Trusted WLAN Access Point
TWIF	Trusted WLAN Interworking Function
UL	Uplink
UP	User Plane
UPF	User Plane Function
V-PCF	A PCF in the VPLMN
WLAN	Wireless Local Area Network
WLANSP	WLAN Selection Policy

4 General

4.1 Overview

The 5G core network (5GCN) supports the connectivity of the UE via non-3GPP access networks. These non-3GPP access networks can be trusted non-3GPP access networks, untrusted non-3GPP access networks or wireline access networks. A trusted or untrusted non-3GPP access network can advertise the PLMNs for which it supports trusted connectivity and the type of supported trusted connectivity. Different types of trusted connectivity can be advertised so that the UE can discover the non-3GPP access networks that can provide trusted connectivity to one or more PLMNs:

- a) information about PLMN list with 5G connectivity using trusted non-3GPP access;
- b) information about PLMN list with 5G connectivity without NAS using trusted non-3GPP access; or
- c) information about PLMN list with S2a connectivity using trusted non-3GPP access (access via non-3GPP access to EPC).

NOTE: A wireline access network does not indicate PLMNs for which it supports connectivity.

4.2 Untrusted access

For an untrusted non-3GPP access network, the communication between the UE and the 5GCN is not trusted to be secure.

For an untrusted non-3GPP access network, to secure communication between the UE and the 5GCN, a UE establishes secure connection to the 5G core network over untrusted non-3GPP access via the N3IWF. The UE performs registration to the 5G core network during the IKEv2 SA establishment procedure as specified in 3GPP TS 24.501 [4] and IETF RFC 7296 [6]. After the registration, the UE supports NAS signalling with 5GCN using the N1 reference point as specified in 3GPP TS 24.501 [4]. The N3IWF interfaces the 5GCN CP function via the N2 interface to the AMF and the 5GCN UP functions via N3 interface to the UPF as described in 3GPP TS 23.501 [2].

4.3 Identities

4.3.1 User identities

When the UE accesses the 5GCN over non-3GPP access networks, the same permanent identities for 3GPP access are used to identify the subscriber for non-3GPP access authentication, authorization and accounting services.

The Subscription Permanent Identifier (SUPI) is defined in 3GPP TS 33.501 [5]. The SUPI can contain an IMSI, a network specific identifier, a GCI or a GLI as specified in 3GPP TS 23.501 [2]. A SUPI containing an IMSI is defined in 3GPP TS 23.003 [8]. A SUPI containing a network specific identifier, a GCI or a GLI always takes the form of a NAI as defined in 3GPP TS 23.003 [8].

The Subscription Concealed Identifier (SUCI) is a privacy preserving identifier containing the concealed SUPI as specified in 3GPP TS 33.501 [5]. SUCI is calculated from SUPI. When the SUPI contains an IMSI, the corresponding SUCI is derived as specified in 3GPP TS 23.003 [8]. When the SUPI contains a network specific identifier, a GCI or a GLI, the corresponding SUCI in NAI format is derived as specified in 3GPP TS 23.003 [8].

User identification in non-3GPP accesses can require additional identities that are out of the scope of 3GPP.

4.3.2 FQDN for N3IWF Selection

An N3IWF FQDN is either provisioned by the home operator or constructed by the UE in either the Operator Identifier FQDN format or the Tracking Area Identity FQDN format as specified in clause 6.3.6.2 in 3GPP TS 23.501 [2].

The detailed format of the N3IWF FQDN is specified in clause 28.3.2.2 of 3GPP TS 23.003 [8].

The N3IWF FQDN is used as input to the DNS mechanism for N3IWF selection.

In order to access PLMN services via an SNPN, a UE operating in SNPN access operation mode registered to an SNPN has the following restrictions on N3IWF FQDN:

- a) the UE shall only use TAIs from a PLMN to construct a Tracking Area Identity based N3IWF FQDN; and
- b) the UE shall not consider an N3IWF FQDN for N3IWF selection configured by an SNPN.

4.4 Quality of service support

4.4.1 General

When the UE accesses the 3GPP 5G System (5GS) via non-3GPP access networks, the same QoS flow based 5G QoS model and principles are followed as described in 3GPP TS 23.501 [2]. For PDU sessions that were established over non-3GPP access, the QoS flow remains to be the finest granularity of QoS differentiation in the PDU Session.

4.4.2 QoS differentiation in non-3GPP access

4.4.2.1 General

For untrusted non-3GPP access, the N3IWF is the access network node that provides QoS signalling to support QoS differentiation and mapping of QoS flows to non-3GPP access resources.

For trusted non-3GPP access, the TNGF is the access network node that provides QoS signalling to support QoS differentiation and mapping of QoS flows to non-3GPP access resources.

For wireline access, the W-AGF serving the 5G-RG is the access network node that provides QoS signalling to support QoS differentiation and mapping of QoS flows to non-3GPP access resources.

4.4.2.2 QoS signalling

A QoS flow is controlled by the SMF and can be preconfigured, or established via the UE requested PDU Session establishment via non-3GPP access procedure, the UE or network requested PDU session modification via non-3GPP access procedure (see 3GPP TS 23.502 [3]).

During PDU session establishment, based on local policies, pre-configuration and the QoS profiles received:

- a) the N3IWF or the TNGF (depending on whether the UE is connected to untrusted non-3GPP access or trusted non-3GPP access, respectively):
 - 1) shall determine the number of IPsec child SAs to establish and the QoS profiles associated with each IPsec child SA; and
 - 2) shall then initiate IPsec SA creation procedure to establish child SAs associating to the QoS flows of the PDU session; or
- b) the W-AGF serving the 5G-RG:
 - 1) shall determine the number of W-UP resources to establish and the QoS profiles associated with each W-UP resource; and
 - 2) shall initiate creation of one or more W-UP resources using means out of scope of the present document. The W-AGF serving the 5G-RG shall associate each W-UP resource with a PDU session, zero or more QFIs, and optionally an indication of whether the W-UP resource is the default W-UP resource. For each W-UP resource, the 5G-RG becomes aware using means out of scope of the present document about association of the W-UP resource and the PDU session, the zero or more QFIs, and optionally the indication of whether the W-UP resource is the default W-UP resource.

In order to support QoS differentiation in case of access to PLMN services via an SNPN and access to SNPN services via a PLMN, the N3IWF is preconfigured with one or more QoS profiles requiring a dedicated IPsec child SA which can be associated with a DSCP value.