

SLOVENSKI STANDARD oSIST prEN ISO 11295:2021

01-marec-2021

Cevni sistemi iz polimernih materialov za obnovo cevovodov - Razvrstitev in pregled strateških in operativnih dejavnosti (ISO/DIS 11295:2021)

Plastics piping systems used for the rehabilitation of pipelines - Classification and overview of strategic and operational activities (ISO/DIS 11295:2021)

Kunststoff-Rohrleitungssysteme, die für die Sanierung verwendet werden -Klassifizierung und Überblick über strategische und operative Aktivitäten (ISO/DIS 11295:2021)

(standards.iteh.ai)

Systèmes de canalisation en plastique destinés à la réhabilitation des réseaux enterrés - Classification et vue d'ensemble des activités stratégiques et opérationnelles (ISO/DIS 11295:2021)

be44abd841f5/osist-pren-iso-11295-2021

Ta slovenski standard je istoveten z: prEN ISO 11295

ICS:

23.040.01 Deli cevovodov in cevovodi

na splošno

Pipeline components and

pipelines in general

oSIST prEN ISO 11295:2021

en,fr,de

oSIST prEN ISO 11295:2021

iTeh STANDARD PREVIEW (standards.iteh.ai)

oSIST prEN ISO 11295:2021 https://standards.iteh.ai/catalog/standards/sist/a5c40b2e-c3f1-484f-bbd9-be44abd841f5/osist-pren-iso-11295-2021

DRAFT INTERNATIONAL STANDARD ISO/DIS 11295

ISO/TC **138**/SC **8** Secretariat: **JISC**

Voting begins on: Voting terminates on:

2021-02-01 2021-04-26

Plastics piping systems used for the rehabilitation of pipelines — Classification and overview of strategic and operational activities

Systèmes de canalisation en plastique destinés à la réhabilitation des réseaux enterrés — Classification et vue d'ensemble des activités stratégiques et opérationnelles

ICS: 23.040.01; 23.040.01

iTeh STANDARD PREVIEW (standards.iteh.ai)

oSIST prEN ISO 11295:2021 https://standards.iteh.ai/catalog/standards/sist/a5c40b2e-c3f1-484f-bbd9-be44abd841f5/osist-pren-iso-11295-2021

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

This document is circulated as received from the committee secretariat.

ISO/CEN PARALLEL PROCESSING



Reference number ISO/DIS 11295:2021(E)

iTeh STANDARD PREVIEW (standards.iteh.ai)

oSIST prEN ISO 11295:2021 https://standards.iteh.ai/catalog/standards/sist/a5c40b2e-c3f1-484f-bbd9-be44abd841f5/osist-pren-iso-11295-2021



COPYRIGHT PROTECTED DOCUMENT

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

| Contents | | | | | | | |
|----------|---------------------------------|-----------------------|---|----|--|--|--|
| Fore | word | | | v | | | |
| Intro | oductio | 1 | | vi | | | |
| 1 | Scon | . | | 1 | | | |
| _ | - | | | | | | |
| 2 | | Normative references | | | | | |
| 3 | | Terms and definitions | | | | | |
| | 3.1 3.2 | | eralniques | | | | |
| | 3.3 | | ions | | | | |
| 4 | | | | | | | |
| _ | | oreviated terms | | | | | |
| 5 | Pipeline rehabilitation process | | | | | | |
| 6 | | | ndition assessment of the existing pipeline | | | | |
| | 6.1 | | riteria | | | | |
| | | | al | | | | |
| | | | ulic requirementsural requirements | | | | |
| | | | onmental requirement | | | | |
| | | | tional requirements | | | | |
| | 6.2 | | of performance | 8 | | | |
| | | 6.2.1 Gener | of performance al STANDARD PREVIEW | 8 | | | |
| | | 6.2.2 Hydra | ulic investigation ura(mvestigation ds.iteh.ai) | 10 | | | |
| | | 6.2.3 Struct | ural investigation as.iten.ai) | 10 | | | |
| | | 6.2.4 Enviro | onmental investigation | 10 | | | |
| | () | 6.2.5 Opera | tional investigation O 112952021 | 11 | | | |
| | 6.3 6.4 | Condition asse | SSINENtai/catalog/standards/sist/a5c40b2e-c3f1-484f-bbd9- | | | | |
| | 6.5 | Control measu | | 11 | | | |
| _ | | | | | | | |
| 7 | 7.1 | Classification of | aracteristics of rehabilitation techniques | 12 | | | |
| | 7.1 | | al | | | | |
| | | | g with continuous pipes | | | | |
| | | | with close-fit pipes | | | | |
| | | | with cured-in-place pipes | | | | |
| | | | with discrete pipes | | | | |
| | | | ; with adhesive-backed hoses | | | | |
| | | | with spirally-wound pipes | | | | |
| | | | with pipe segments | | | | |
| | | | with a rigidly anchored plastics inner layer | | | | |
| | | | s with sprayed polymeric materialss with inserted hosess | | | | |
| | 7.2 | | of trenchless replacement techniques | | | | |
| | 7.2 | | al | | | | |
| | | | ursting | | | | |
| | | | emoval | | | | |
| | | 7.2.4 Horiz | ontal directional drilling — HDD | 41 | | | |
| | | - | t moling | | | | |
| | | 7.2.6 Pipe ja | acking | 46 | | | |
| 8 | | | tation techniques | | | | |
| | 8.1 | | | | | | |
| | 8.2 | | | | | | |
| | 8.3 | | ormance | | | | |
| | 8.4 | ou uctural peri | formance | 51 | | | |

oSIST prEN ISO 11295:2021

ISO/DIS 11295:2021(E)

| | 8.4.1 General | 51 |
|--------|---|--|
| | 8.4.2 Non-pressure pipes | 51 |
| | 8.4.3 Pressure pipes | 52 |
| 8.5 | Environmental impact | 55 |
| 8.6 | Construction constraints | 56 |
| 8.7 | Project specification | 56 |
| Impl | ementation of rehabilitation techniques | 57 |
| 9.1 | Preconstruction activities | 57 |
| 9.2 | Inspection, storage and handling of the materials on site | 58 |
| 9.3 | Application of rehabilitation technique | 58 |
| | 9.3.1 Preparatory work | 58 |
| | 9.3.2 Construction | 58 |
| 9.4 | Acceptance control | 59 |
| | 9.4.1 General | 59 |
| | 9.4.2 Inspection | 59 |
| | 9.4.3 Leak tightness testing | 59 |
| | 9.4.4 Sampling | 61 |
| 9.5 | Completion of the work | 61 |
| | 9.5.1 Finishing off the rehabilitation work | 61 |
| | | |
| 9.6 | Documentation of the process | 61 |
| ngranh | • | |
| | 8.6 8.7 Impl 9.1 9.2 9.3 9.4 | 8.4.2 Non-pressure pipes 8.4.3 Pressure pipes 8.5 Environmental impact 8.6 Construction constraints 8.7 Project specification Implementation of rehabilitation techniques 9.1 Preconstruction activities 9.2 Inspection, storage and handling of the materials on site 9.3 Application of rehabilitation technique 9.3.1 Preparatory work 9.3.2 Construction 9.4 Acceptance control 9.4.1 General 9.4.2 Inspection 9.4.3 Leak tightness testing 9.4.4 Sampling 9.5 Completion of the work 9.5.1 Finishing off the rehabilitation work 9.5.2 Lateral reinstatement |

iTeh STANDARD PREVIEW (standards.iteh.ai)

oSIST prEN ISO 11295:2021 https://standards.iteh.ai/catalog/standards/sist/a5c40b2e-c3f1-484f-bbd9-be44abd841f5/osist-pren-iso-11295-2021

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see the following URL: www.iso.org/iso/foreword.html and ards.iteh.ai)

This document was prepared by ISO/TC 138 *Plastics pipes, fittings and valves for the transport of fluids,* Subcommittee SC 8, *Rehabilitation of pipeline systems*.

https://standards.itch.avcatalog/standards/sist/a5c40b2e-c3fl-484f-bbd9-

This third edition cancels and replaces the second edition (ISO 41295:2017), which has been technically revised, to now sequentially cover all steps in process of design of pipeline rehabilitation.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

This edition includes the following significant changes with respect to the previous edition:

- Title is renewed from "Classification and information on design and applications of plastics piping systems used for renovation and replacement" to "Plastics piping systems used for the rehabilitation of pipelines — Classification and overview of strategic and operational activities";
- <u>Clause 5</u> is new and describes the whole process of pipeline rehabilitation with references to the other clauses for further details;
- Clause 6 is new and deals with the strategic activities to possibly come to the decision to rehabilitate;
 parts of the content of the former Clause 8 are included;
- Clause 7 is a contraction of the former Clauses 5, 6 and 7, with largely unchanged content;
- Clause 8 is new and handles further strategic activities needed to specify the rehabilitation project;
 parts of the content of the former Clauses 8 and 9 are included;
- <u>Clause 9</u> still covers installation aspects but is revised and content on acceptance control is included now.

Introduction

Pipeline systems are continuously required to satisfy physical, chemical, biochemical and biological demands. These demands depend on planning, material, construction, type and period of use.

When pipeline systems become operational, they constitute a valuable asset to the network owner, requiring adequate management. For general guidelines and requirement on asset management, ISO 55000^[28], ISO 55001^[29] and ISO 55002^[30] are applicable.

For pipeline systems in particular, proper pipeline system management has to be put in place, including monitoring the performance of the pipeline system.

For the specific case of pipelines for water supply and wastewater collection, detailed information on the overall management of the networks is provided by ISO 24516-1[25] and ISO 24516-3[26].

In case a malfunctioning of a pipeline system is recognized, reactive measures initially focus on improving regular maintenance procedures, including cleaning. In case of deterioration or other serious defects, more stringent measures to rehabilitate the pipeline become necessary.

Rehabilitation is carried out when there is a need to restore or upgrade the performance of a pipeline system. Rehabilitation can consist of repair, renovation or replacement. In recent years, the rehabilitation of pipeline systems has become increasingly important and will continue to be so.

This document provides information on the design process when considering rehabilitation of an existing pipeline, in order of sequence: STANDARD PREVIEW

- a) investigation and assessment of the deficiencies of current performance of the existing pipeline;
- b) determination of viable options, based on performance criteria and process-related factors;
- c) specification of the selected type of technique and the required pipe material;
- d) the installation;

be44abd841f5/osist-pren-iso-11295-2021

e) testing the performance.

The techniques used for the renovation and trenchless replacement of existing pipelines are classified in technique families and the typical characteristics of each is described in general terms.

Plastics piping systems used for the rehabilitation of pipelines — Classification and overview of strategic and operational activities

1 Scope

This document sets out the steps of the overall process of pipeline rehabilitation, comprising:

- Information on strategic activities:
 - a) Investigation and condition assessment of the existing pipeline;
 - b) Pipeline rehabilitation planning;
 - c) Project specification.
- Information on and requirements for operational activities:
 - d) Application of techniques;
 - e) Documentation of the design and application process:

Definitions, classification and description of families of renovation and trenchless replacement techniques are provided, including their areas of application such as underground drainage and sewerage networks and underground water and gas supply networks.

OSIST pren ISO 11295:2021

NOTE 1 The following aspects are not covered by the scope of this document:

- new construction provided as network extension;
- calculation methods to determine, for each viable technique, the characteristics of lining or replacement pipe material needed to secure the desired performance of the rehabilitated pipeline;
- techniques for local repair.

NOTE 2 It is the responsibility of the designer to choose and design the renovation or trenchless replacement pipeline system.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1043-1, Plastics — Symbols and abbreviated terms — Part 1: Basic polymers and their special characteristics

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 1043-1 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at https://www.iso.org/obp

3.1 General

3.1.1

assessment

process, or result of this process, comparing a specified subject matter to relevant references

3.1.2

design working life

assumed period for which a structure or part of it is to be used for its intended purpose with anticipated repair and maintenance but without renovation or replacement being necessary

3.1.3

hazard

biological, chemical, physical or radiological agent in, or condition of water, with the potential to cause harm to public health

Note 1 to entry: Condition includes quantity.

3.1.4

pipeline system

interconnecting pipe network for the conveyance of fluids

[SOURCE: EN ISO 11298-1:2018-07, 3.1.1]

3.1.5

rehabilitation

measures for restoring or upgrading the performance of existing pipeline systems, including renovation (3.1.6), repair (3.1.7) and replacement (3.1.8) and ards.iteh.ai)

3.1.6

renovation

oSIST prEN ISO 11295:2021

work incorporating all or part of the original fabric of the pipeline. By means of which its current performance is improved be44abd841f5/osist-pren-iso-11295-2021

3.1.7

repair

rectification of local damage

3.1.8

replacement

construction of a new pipeline, on or off the line of an existing pipeline, where the function of the new pipeline system incorporates that of the old

3.1.9

network extension

new construction off the line of a pipeline or a network with the aim to expand the total capacity of the network

3.1.10

trenchless replacement

replacement (3.1.8) without opening trenches other than small excavations to provide access for the particular technique

3.1.11

maintenance

routine work undertaken to ensure the continuing performance of a pipeline system (3.1.4)

3.1.12

independent pressure pipe liner

liner (3.2.3) capable on its own of resisting without failure all applicable internal loads throughout its design life

3.1.13

interactive pressure pipe liner

liner (3.2.3) which relies on the existing pipeline for radial support in order to resist without failure all applicable internal loads throughout its design life

3.1.14

fully structural renovation

use of an *independent pressure pipe liner* (3.1.12) or a non-pressure pipe liner which is capable of resisting all external loads and all externally induced post-lining deformations irrespective of the condition of the existing pipeline

3.1.15

semi-structural renovation

use of an *interactive pressure pipe liner* (3.1.13) which is capable of long-term hole and gap spanning at operational pressure or use of an *independent pressure pipe liner* (3.1.12) which is not capable of resisting all external loads

3.1.16

flow diversion

temporary isolation of the section of pipeline to be rehabilitated by the use of a temporary bypass or other means

3.2 Techniques

technique family

3.2.1

iTeh STANDARD PREVIEW

grouping of *renovation* (3.1.6) or *trenchless replacement* (3.1.10) techniques which are considered to have common characteristics for standardization purposes

3.2.2

oSIST prEN ISO 11295:2021

lining pipe https://standards.iteh.ai/catalog/standards/sist/a5c40b2e-c3f1-484f-bbd9-

pipe inserted for renovation (3.1.6) pulsposes ist-pren-iso-11295-2021

3.2.3

liner

lining pipe (3.2.2) after installation

3.2.4

lining system

lining pipe (3.2.2) and all relevant fittings inserted into an existing pipeline for the purposes of *renovation* (3.1.6)

3.2.5

lining with continuous pipes

lining with pipe made continuous prior to insertion, where the diameter of the $lining\ pipe\ (3.2.2)$ remains unchanged

3.2.6

lining with close-fit pipes

lining with a continuous pipe (3.2.5) for which the cross-section is reduced to facilitate installation and reverted after installation to provide a close fit to the existing pipe

3.2.7

lining with cured-in-place pipes

lining with a flexible tube impregnated with a thermosetting resin, which produces a pipe after resin cure

3.2.8

lining with discrete pipes

lining with short lengths of pipe which are jointed to form a continuous pipe one by one during insertion

3.2.9

lining with adhesive-backed hoses

lining with a reinforced hose which relies on an adhesive bond to the host pipe to provide resistance to collapse

3.2.10

lining with spirally-wound pipes

lining with a profiled strip, spirally wound to form a continuous pipe after installation

3.2.11

lining with sprayed polymeric materials

lining with a sprayed two-part polymeric resin material that forms a continuous pipe after resin cure

3.2.12

lining with inserted hoses

lining with a reinforced hose which is either permanently shaped or re-rounded after installation by the application of an internal pressure

3.2.13

lining with a rigidly anchored plastics inner layer

lining with a single rigid annulus of structural cementitious grout formed between a plastics layer and the host pipe, where the plastics layer is permanently anchored in the grout

3.2.14

lining with pipe segments

lining with prefabricated segments bonded to the existing pipe, which either have longitudinal joints and cover the whole of the pipe circumference, or cover only part of circumference

(standards.iteh.ai)

3.2.15

pipe bursting

on-the-line *replacement* (3.1.8) method in which an existing pipe is broken by longitudinal splitting or brittle fracture, using a mechanically applied force from within, where the pipe fragments are forced into the surrounding ground and a new pipe of the same, smaller or larger diameter, is simultaneously pulled in

3.2.16

pipe removal

on-the-line *replacement* (3.1.8) method, in which the existing pipe is removed by *pipe eating* (3.2.17) or *pipe extraction* (3.2.18) and a new pipe is installed

3.2.17

pipe eating

type of *pipe removal* (3.2.16), where the existing pipe is progressively broken up and removed along with an annulus of the ground immediately surrounding the existing pipe

3.2.18

pipe extraction

type of *pipe removal* (3.2.16), where the existing pipe is extracted by pulling or pushing and replaced with a new one, either simultaneously or as a separate step

3.2.19

horizontal directional drilling

off-the-line $trenchless\ replacement\ (3.1.10)$ method in which a pilot bore is drilled using a steerable drilling head connected to flexible rods and then the bore is enlarged by reamers up to the diameter required for the pipe or pipes subsequently pulled/pushed into place

3.2.20

impact moling

off-the-line *trenchless replacement* (3.1.10) method in which pipes are pulled in behind a pneumatic powered soil displacement hammer

3.2.21

pipe jacking

off-the-line trenchless replacement (3.1.10) method in which pipes are pushed through the ground, and the soil inside removed either manually, mechanically or using a slurry system

3.2.22

auger boring

type of pipe jacking (3.2.21), where the bore is excavated by a rotating cutting head attached to an auger which continuously removes the spoil, and the pipeline is pushed independently from the auger

3.2.23

microtunnelling

type of pipe jacking (3.2.21) where pipes are pushed behind a steerable, small scale tunnelling machine, remotely controlled from the surface

3.2.24

grout system

cement-based grout including any fillers, reinforcement or other additives or admixtures, in specified proportions

3.3 Service conditions

3.3.1

internal pressure resistance

ability to withstand internal fluid pressurization PREVIEW

allowable operating pressure (standards.iteh.ai)

maximum hydrostatic pressure that a component is capable of withstanding continuously in service.

https://standards.iteh.ai/catalog/standards/sist/a5c40b2e-c3f1-484f-bbd9-Note 1 to entry: It is expressed in bars abd841f5/osist-pren-iso-11295-2021

Abbreviated terms

For the purposes of this document, the abbreviated terms given in ISO 1043-1 and the following apply.

CCTV closed circuit television

HDD horizontal directional drilling

EP epoxy resin

GRP glass-reinforced thermosetting plastics

PE polyethylene

PP polypropylene

PRC polyester resin concrete

PUR polyurethane

PVC-U unplasticized poly(vinyl chloride)

UP unsaturated polyester resin

VE vinyl ester resin

¹⁾ $1 \text{ bar} = 0.1 \text{ MPa} = 0.1 \text{ N/mm}^2 = 10^5 \text{ N/m}^2$.

5 Pipeline rehabilitation process

A pipeline rehabilitation process involves taking several sequential steps from the assessment of the performance condition to its set requirements, via the selection of the appropriate technique of rehabilitation to the actual rehabilitation work.

This document provides information and requirements for each of the steps:

| _ | | | |
|---|--|---|-----------------|
| 1 | Investigation of functional performance of the existing pipeline |] | |
| 2 | Condition assessment of performance against set requirements | } | Clause 6 |
| 3 | Measures to control risks / pipeline rehabilitation | | |
| 4 | Pre-selection of suitable types of rehabilitation techniques | } | Clause 7 |
| 5 | Project specification |) | Classa O |
| 6 | Selection of technique / installer | } | <u>Clause 8</u> |
| 7 | Application of rehabilitation technique |) | <u>Clause 9</u> |
| 8 | Acceptance control | } | |
| 9 | Documentation of the rehabilitation process | } | Clause 10 |
| | | | |

A substantial part of this document (<u>Clause 7</u>) is dedicated to the Classification of techniques for pipeline rehabilitation, both renovation and trenchless replacement, by means of technique families. Typical characteristics and process related factors are provided for each technique family.

NOTE 1 Guidance on the whole process of integrated management of drains and sewers is presented in $EN 752[\frac{41}{3}]$.

oSIST prEN ISO 11295:2021

6 Investigation and condition assessment of the existing pipeline

be44abd841f5/osist-pren-iso-11295-2021

6.1 Performance criteria

6.1.1 General

For every pipeline system certain objectives apply, depending on their intended functionality.

These are the basis for the performance requirements of a pipeline system. The pipeline system objectives, that impact on the performance requirements of the individual pipeline, shall be identified.

For drinking water distribution networks and wastewater collection networks, detailed guidance and requirements is provided by ISO $24516-1^{[25]}$ and ISO $24516-3^{[26]}$ respectively. The items detailed below specifically relate to the rehabilitation process of the pipeline systems in these networks, as well as in gas supply networks.

Pipeline system objectives include at least the following:

- Health and safety;
- Environmental protection;
- Sustainable operation.

Health and safety encompasses (depending on the function of the pipeline):

- Provision of access to safe and good quality drinking water;
- Preventing spread of disease by safe disposal of wastewater;
- Meeting user's needs and expectations;

- Minimizing occupational health and safety risks;
- Maintaining pipeline system integrity.

Environmental protection includes:

- Preventing pollution and minimize generating pollutants;
- Minimizing energy consumption;
- Avoiding nuisance in construction, operation and maintenance.

Sustainable operation includes:

- Providing service over many years economic, social, environmental;
- Monitoring the quality of water (sampling, surveillance, maintenance);
- Minimizing mains failures and leakages.

The objectives shall be transformed to performance requirements and the resulting design criteria that ensure functionality of the pipeline system, such as: structural integrity, design working life, water tightness, prevention of pollution, sustainability, maintenance of flow.

Objectives can be split into the following categories:

- Hydraulic requirements;
 - h STANDARD PREVIEW
- Structural requirements;

(standards.iteh.ai)

- Environmental requirements;
- Operational requirements.

attps://standards.iteh.ai/catalog/standards/sist/a5c40b2e-c3f1-484f-bbd9-

NOTE 1 In ISO 24512^[24] 'performance requirements' are recommended to be clearly defined in objective, verifiable 'Performance Indicators (PIs)', allowing for a clear comparison with the targeted objectives.

NOTE 2 In EN 752^[41], 'performance requirements' are for the status quo. When any predicted changes in time are taken into account, they become 'design criteria'.

6.1.2 Hydraulic requirements

The following hydraulic requirements shall be considered:

- a) sufficient capacity, allowing for foreseeable increases in flow over the design working life of the pipeline system;
- b) ensuring operation of the pipeline system to be safe, and economically efficient;
- c) water tightness in accordance with national or local testing requirements;
- d) in the case of water supply pipelines, additional requirements apply:
 - The effects on water quality shall satisfy the requirements of national legislation;
 - Sufficient pressure, flow rate and continuity of supply;
 - Prevention of back flow (via valves and wash outs);
 - Minimize stagnation to avoid possible deterioration of water quality;
 - Requirements for firefighting (hydrants) to follow requirements of national legislation;
 - Prevention of contamination at pumping stations.