



Designation: E2406-04 Designation: E2406 – 09

Standard Test Method for Evaluation of Laundry Sanitizers and Disinfectants for Use in High Efficiency Washing Operations¹

This standard is issued under the fixed designation E2406; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This test method is designed to evaluate sanitizing/disinfectant laundry detergents/additives for use in high efficiency (HE) automatic clothes washing operations that typically utilize very low wash water volumes. This test method is designed to provide testing with representative vegetative bacteria but can also be designed to accommodate the testing of fungi and viruses.

~~NOTE 1—Standard test method Test Method 1—Test Method E2274~~ is the recommended method to evaluate sanitizing/disinfectant laundry detergent/additives for use in traditional high wash water volume automatic clothes washing operations.

1.2 Knowledge of microbiological techniques is required for these procedures.

~~1.3 In this method metric units are used for all applications, except for distance in which case inches are used.~~

1.3 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

~~NOTE 2—In this method, metric units are used for all applications, except for distance in which case inches are used.~~

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 *ASTM Standards:*²

D1193 [Specification for Reagent Water](#)

E177 [Practice for Use of the Terms Precision and Bias in ASTM Test Methods](#)

E691 [Practice for Conducting an Interlaboratory Study to Determine the Precision of a Test Method](#)

E1054 [Test Methods for Evaluation of Inactivators of Antimicrobial Agents](#)

E2274 [Test Method for Evaluation of Laundry Sanitizers and Disinfectants](#)

2.2 *AATCC Standard:*

~~Test Method 70-1997~~ [AATCC 70-1997](#) Water Repellency; Tumble Jar Dynamic Absorption Test³

2.3 *AOAC Standard:*

~~Official Methods of Analysis of AOAC International~~ Chapter 6: Disinfectants, 17th ed., 2000

~~2.4 EPA Standard:~~

DIS/TSS 13 Laundry Additives—Disinfection and Sanitization, U.S. Environmental Protection Agency, Office of Pesticide Programs, April 1980

2.5 *Federal Standard:*

40 CFR, Part 160 [Good Laboratory Practice Standards](#)

~~2.6 Canadian Standard:~~

~~T-1-215 Canadian Pest Management Regulatory Standards Trade Memorandum Oct., 1980.~~⁴

¹ This test method is under the jurisdiction of ASTM Committee E35 on Pesticides and Alternative Control Agents and is the direct responsibility of Subcommittee E35.15 on Antimicrobial Agents.

Current edition approved Oct. 1, 2004. Published November 2004. DOI: 10.1520/E2406-04 on Antimicrobial Agents.

Current edition approved Nov. 1, 2009. Published December 2009. Originally approved in 2004. Last previous edition approved in 2004 as E2406 – 04. DOI: 10.1520/E2406-09.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ Available from American Association of Textile Chemists and Colorists (AATCC), One Davis Dr., P.O. Box 12215, Research Triangle Park, NC 27709-2215; <http://www.aatcc.org>.

⁴ Available from AOAC International, Washington, DC.

⁴ Available from United States Environmental Protection Agency (EPA), Ariel Rios Bldg., 1200 Pennsylvania Ave., NW, Washington, DC 20460, <http://www.epa.gov>.

3. Terminology

3.1 Definitions:

3.1.1 *active antimicrobial ingredient*—a substance added to a formulation intended specifically for the inhibition or inactivation of microorganisms.

3.1.2 *antimicrobial agent(s)*—an active ingredient designed to suppress the growth or action of microorganisms.

3.1.3 *carrier count control*—procedure used to determine the initial number of microorganisms on a fabric carrier following the inoculation and drying procedure.

3.1.4 *diluent*—sterile deionized water, sterile distilled water or sterile synthetic AOAC hard water that may be used to prepare the active test formulation, vehicle control or product control for use in the test procedure.

3.1.5 *diluted product solution*—test formulation, vehicle control, or product control diluted to use concentration.

3.1.6 *neutralization*—a process that results in quenching the antimicrobial activity of a test formulation. This may be achieved by dilution of the test formulation(s) to reduce the concentration of the antimicrobials, or through the use of chemical agents, called neutralizers, to suppress antibacterial activity.

3.1.7 *numbers control*—in assessing sanitizer level performance, procedure used to determine the number of microorganisms remaining on the fabric carriers and in the wash water following the test procedure in the presence of the diluent. This may also be performed using diluent or phosphate buffer dilution water with surfactant.

3.1.8 *product control*—a formulation with or without an active ingredient(s) used for comparison to the test formulation.

3.1.9 *test formulation*—a formulation containing an antimicrobial agent(s).

3.1.10 *vehicle control*—the test formulation without the active ingredient(s) used for comparison to the test formulation.

3.1.11 *wash water*—the liquid contained in the exposure chamber previously exposed to either uninoculated fabric or fabric inoculated with the challenge microorganism.

4. Summary of Test Method

4.1 Under simulated laundry conditions, sets of inoculated fabric swatches are placed into low volumes of diluted product solution and agitated. After a specified contact time, the wash water and the test fabric are individually cultured either quantitatively (sanitizer efficacy) or qualitatively (disinfectant efficacy).

NOTE 2—See 3—See appropriate regulatory guidance document for the minimum number of replicates required to make a specific claim.

5. Significance and Use

5.1 The procedure in this test method is used to evaluate the effectiveness of a test reagent (antimicrobial agent/active ingredient) or formulation to reduce or completely kill bacterial populations on contaminated fabrics and in wash water following a single wash under simulated low wash volume conditions. (See Table 1.)

TABLE 1 Typical Use Patterns

Usage Pattern	Fabric: Wash Water Ratio	Wash Water Volume	Spindle Wire Requirement
Deep Fill Top Load Washers	≥ 1:5-15	75-225 mL	Retain
High Efficiency/Horizontal Front Load Washers	< 1:5	< 75 mL	Omit

6. Apparatus

6.1 *Colony Counter*—Any of several types may be used, for example, Quebec.

6.2 *Incubator*—Any incubator that can maintain the optimum temperature $\pm 2^{\circ}\text{C}$ for growth of the challenge microorganism(s).

6.3 *Sterilizer*—Any suitable steam sterilizer producing the conditions of sterility.

6.4 *Timer (Stop-clock)*—Any device that can be read for minutes and seconds.

6.5 *Exposure Chamber*—Container with closure that can withstand sterilization. Dimension and volume capacity should be consistent for use in Test Method E2274.

NOTE 3—Standard lids may form a vacuum seal when steam sterilized. To avoid, prior to sterilization place a piece of paper between lid and jar.

6.6 *Stainless Steel Spindles*—Spindles are fabricated from a single continuous piece of stainless steel wire ($\frac{1}{16}$ in. diameter and bent to contain 3 horizontal extensions, 2 in. long connected by 2 vertical sections approximately 2 in. long). They are shaped so that vertical sections form 150° angle where the free ends of the 2 outer horizontal extensions are sharpened to a point. This will be used as scaffolding for initial wrapping of fabric ballast.

6.7 *Agitator*—Tumbling device intended to rotate Exposure Chamber through 360° vertical orbit of 4 to 8 in. diameter at 45 to 60 rpm or a comparable tumbling devices such as Launderometer or Tumble Jar described in AATCC 70-1997.

6.8 *Micropipettor (and Pipet Tips)*, suitable to deliver 0.01 to 0.03 mL volume.

6.9 *Forceps*, large and small, sterile.