

---

---

## Inlet air cleaning equipment for internal combustion engines and compressors — Performance testing

*Séparateurs aérauliques placés à l'entrée des moteurs à combustion  
interne et des compresseurs — Détermination des performances*

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ISO 5011:2020

<https://standards.iteh.ai/catalog/standards/sist/ec2d72d1-6b74-4fa8-8025-2787c8f6fdb3/iso-5011-2020>



## iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 5011:2020

<https://standards.iteh.ai/catalog/standards/sist/ec2d72d1-6b74-4fa8-8025-2787c8f6fdb3/iso-5011-2020>



### **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

Page

<b>Foreword</b>	<b>v</b>
<b>1 Scope</b>	<b>1</b>
<b>2 Normative references</b>	<b>1</b>
<b>3 Terms, definitions and symbols</b>	<b>1</b>
3.1 Terms and definitions	1
3.2 Symbols	3
<b>4 Measurement accuracy and standard conditions</b>	<b>4</b>
4.1 Measurement accuracy and precision	4
4.2 Standard conditions	4
<b>5 Test materials and test conditions</b>	<b>4</b>
5.1 Test dust	4
5.1.1 Grade	4
5.1.2 Preparation	4
5.2 Test oil for oil bath air cleaners	5
5.3 Absolute filter materials	5
5.3.1 Filter media	5
5.3.2 Validation of absolute filter media efficiency, $E_a$	5
5.4 Absolute filter mass	5
5.5 Temperature and humidity	6
<b>6 Test procedure for dry-type air cleaners for automotive applications</b>	<b>6</b>
6.1 General	6
6.2 Test equipment	6
6.3 Restriction and differential pressure test	8
6.4 Efficiency test	8
6.4.1 Purpose	8
6.4.2 Types	8
6.4.3 Test procedure — Absolute filter method	9
6.4.4 Test procedure — Direct weighing method	10
6.5 Capacity test	10
6.6 Filter element pressure collapse test	11
6.7 Variable air flow test	11
6.8 Presentation of data	12
<b>7 Test procedure for dry-type air cleaners for industrial applications</b>	<b>12</b>
7.1 General	12
7.2 Test equipment	12
7.3 Restriction and differential pressure test	13
7.4 Initial efficiency test procedure — Absolute filter method	13
7.5 Full-life efficiency and capacity test	14
7.5.1 Air cleaner dust capacity	14
7.5.2 Test procedure — Absolute filter method	14
7.5.3 Test procedure — Direct weighing method	16
7.6 Presentation of data	16
7.7 Scavenged air cleaner performance test	16
7.7.1 General	16
7.7.2 Additional equipment	17
7.7.3 Restriction and differential pressure test	17
7.7.4 Full-life efficiency and capacity test	17
7.7.5 Presentation of data	18
7.8 Precleaner performance test	18
7.8.1 Precleaner dust removal	18
7.8.2 Precleaner efficiency	19
7.8.3 Presentation of data	19

7.9	Secondary element test procedure.....	19
7.9.1	General.....	19
7.9.2	Specific efficiency test.....	19
7.9.3	Expression of results.....	20
<b>8</b>	<b>Test procedure for industrial applications of oil bath air cleaners.....</b>	<b>20</b>
8.1	General.....	20
8.2	Test equipment and conditions.....	20
8.3	Restriction and differential pressure test.....	21
8.4	Oil carry-over test.....	21
8.5	Full life efficiency and capacity test.....	21
8.6	Recovery test.....	22
8.7	Presentation of data.....	22
<b>Annex A</b> (normative)	<b>Explanation of restriction, differential pressure and pressure loss of an air cleaner.....</b>	<b>23</b>
<b>Annex B</b> (normative)	<b>Test equipment.....</b>	<b>25</b>
<b>Annex C</b> (informative)	<b>Report sheet on performance testing of air cleaner equipment according to ISO 5011 — Automotive application.....</b>	<b>35</b>
<b>Annex D</b> (informative)	<b>Report sheet on performance testing of air cleaner equipment according to ISO 5011 — Industrial application.....</b>	<b>36</b>
<b>Annex E</b> (informative)	<b>Presentation of results — Air cleaner restriction/differential pressure versus flow.....</b>	<b>38</b>
<b>Annex F</b> (informative)	<b>Presentation of results — Air cleaner capacity.....</b>	<b>39</b>
<b>Annex G</b> (normative)	<b>Airflow and resistance corrections to standard conditions.....</b>	<b>40</b>
<b>Annex H</b> (normative)	<b>Penetration sensitivity.....</b>	<b>42</b>
<b>Bibliography</b>	<b>.....</b>	<b>50</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 34, *Propulsion, powertrain and powertrain fluids*.

This fourth edition cancels and replaces the third edition (ISO 5011:2014), which has been technically revised. It also incorporates the Amendment ISO 5011:2014/Amd.1:2018. The main changes compared to the previous edition are as follows:

- added a validation procedure for verifying efficiency measurements;
- revised recommended ISO dust injector table;
- added formula for precleaner efficiency method;
- removed requirement for secondary element collapse test;
- added [Annex H](#) (Penetration sensitivity);
- added a new dust injector.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

## **iTeh STANDARD PREVIEW** **(standards.iteh.ai)**

ISO 5011:2020

<https://standards.iteh.ai/catalog/standards/sist/ec2d72d1-6b74-4fa8-8025-2787c8f6fdb3/iso-5011-2020>

# Inlet air cleaning equipment for internal combustion engines and compressors — Performance testing

## 1 Scope

This document establishes and specifies uniform test procedures, conditions, equipment and a performance report to permit the direct laboratory performance comparison of air cleaners.

The basic performance characteristics of greatest interest are air flow restriction or differential pressure, dust collection efficiency, dust capacity and oil carry-over on oil bath air cleaners. This test code therefore deals with the measurement of these parameters.

This document is applicable to air cleaners used on internal combustion engines and compressors generally used in automotive and industrial applications.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 5167-1, *Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full — Part 1: General principles and requirements*

ISO 12103-1, *Road vehicles — Test contaminants for filter evaluation — Part 1: Arizona test dust*

<https://standards.iteh.ai/catalog/standards/sist/ec2d72d1-6b74-4fa8-8025-2787c8f6fdb3/iso-5011-2020>

## 3 Terms, definitions and symbols

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

### 3.1 Terms and definitions

#### 3.1.1

##### **air filter**

##### **air cleaner**

device which removes particles suspended in the intake air as it is drawn into the engine

#### 3.1.2

##### **filter element**

replaceable part of the *air filter* (3.1.1), consisting of the filter material and carrying frame

#### 3.1.3

##### **secondary element**

*air cleaner* (3.1.1) element fitted downstream of the primary element for the purpose of providing the engine with protection against dust in the event of

- a) certain types of primary element failure, or
- b) dust being present during the removal of the primary element for servicing

### 3.1.4

#### **unit under test**

either a single *air cleaner* (3.1.1) element or a complete air cleaner assembly

### 3.1.5

#### **single-stage air cleaner**

*air cleaner* (3.1.1) which does not incorporate a separate *precleaner* (3.1.7)

### 3.1.6

#### **multistage air cleaner**

*air cleaner* (3.1.1) consisting of two or more stages, the first usually being a *precleaner* (3.1.7), followed by one or more *filter elements* (3.1.2)

Note 1 to entry: If two elements are used, the first is called the primary element and the second one is called the *secondary element* (3.1.3).

### 3.1.7

#### **precleaner**

device usually using inertial or centrifugal means to remove a portion of the test dust prior to reaching the *filter element* (3.1.2)

### 3.1.8

#### **test air flow**

measure of the quantity of air drawn through the *air cleaner* (3.1.1) outlet per unit time

Note 1 to entry: The flow rate is expressed in cubic metres per minute corrected to standard conditions.

### 3.1.9

#### **rated air flow**

flow rate specified by the user or manufacturer

Note 1 to entry: It may be used as the *test air flow* (3.1.8).

### 3.1.10

#### **scavenged air flow**

measure of the quantity of air used to remove the collected dust from a *precleaner* (3.1.7)

Note 1 to entry: It is expressed as a percentage of the *test air flow* (3.1.8).

### 3.1.11

#### **static pressure**

pressure in a duct, at the observed air flow rate, measured by connecting a pressure gauge to a hole or holes drilled in the wall of the duct

Note 1 to entry: In the tests specified in this document, a static pressure is measured by a manometer (usually a liquid manometer) as a negative pressure difference against the atmospheric pressure and in the formula this is treated as a positive value.

### 3.1.12

#### **restriction**

*static pressure* (3.1.11) measured immediately downstream of the *unit under test* (3.1.4)

### 3.1.13

#### **differential pressure**

difference in *static pressure* (3.1.11) measured immediately upstream and downstream of the *unit under test* (3.1.4)



**3.1.14****pressure loss**

measure of the loss of energy caused by an *air cleaner* (3.1.1) at the observed air flow rate

Note 1 to entry: It is expressed as the *differential pressure* (3.1.13) corrected for any difference in the dynamic head at the measuring points.

Note 2 to entry: For further information, see [Annex A](#).

**3.1.15****absolute filter**

filter downstream of the *unit under test* (3.1.4) that retains the contaminant passed by the unit under test

**3.1.16****efficiency**

ability of the *air cleaner* (3.1.1) or the unit to remove contaminant mass under specified test conditions

**3.1.17****capacity**

quantity of contaminant removed by the *unit under test* (3.1.4) in producing specified terminal conditions

**3.1.18****oil carry-over**

appearance of oil at the cleaner outlet

**3.1.19****test terminal condition**

condition, relating to an *air cleaner* (3.1.1), the occurrence of which signifies the end of the test

Note 1 to entry: A test terminal condition may be, for example, any one of the following: the *restriction* (3.1.12) or the *differential pressure* (3.1.13) reaches a specified or agreed terminal value; the dust-removing *efficiency* (3.1.16) or some other performance parameter falls to a specified or agreed value; *oil carry-over* (3.1.18) occurs; a dust pot becomes filled.

**3.1.20****automotive application**

*air cleaner* (3.1.1) generally used for internal combustion engines in passenger cars

**3.1.21****industrial application**

*air cleaner* (3.1.1) generally used for internal combustion engines in heavy-duty trucks, construction equipment and agricultural tractors

**3.2 Symbols**

The following applied units, according to ISO 80000-1, are used.

Name	Symbol	Unit
Density	$\rho$	kg/m <sup>3</sup>
Differential pressure	$\Delta p_d$	Pa
Mass	$m$	g
Mass flow rate	$q_m$	kg/min
Pressure	$p$	Pa
Pressure loss	$\Delta p_l$	Pa
Restriction	$\Delta p_r$	Pa
Temperature	$T$	°C
Time	$t$	s

Name	Symbol	Unit
Velocity	$v$	m/s
Volume flow rate	$q_V$	m <sup>3</sup> /min

## 4 Measurement accuracy and standard conditions

### 4.1 Measurement accuracy and precision

Measure the air flow rate to within  $\pm 2$  % of the actual value, except for the variable air flow test when accuracy may be  $\pm 2$  % of the maximum value of the cyclic flow rate through the cleaner.

Measure the differential pressure and restriction to within 25 Pa for pressure readings up to 10 kPa, within 1 % of reading for higher pressures.

Measure the temperature to within 0,5 °C of the actual value.

Measure the mass to within 0,1 g with the exception of absolute filter mass to be measured at 0,01 g and with the exception of the feeder mass to be measured at 1 %.

Measure the relative humidity (RH) with an accuracy of  $\pm 2$  % RH.

Measure the barometric pressure to within 0,3 kPa.

The measurement equipment shall be calibrated at regular intervals to ensure the required accuracy.

Follow [Annex H](#) to determine the reporting precision of your efficiency measurement.

### 4.2 Standard conditions

All airflow measurements shall be corrected to a standard condition of 20 °C at 101,3 kPa.

See [Annex G](#).

## 5 Test materials and test conditions

### 5.1 Test dust

#### 5.1.1 Grade

The test dust to be used shall be ISO 12103-1, A.2 (ISO fine) or ISO 12103-1, A.4 (ISO coarse), subject to agreement between the filter manufacturer and client. The chemical analysis and the particle size distribution shall conform to ISO 12103-1.

In the absence of an agreement on the dust:

- for single-stage filters, use ISO fine test dust, and
- for multistage filters, use ISO coarse test dust.

#### 5.1.2 Preparation

Before using the test dust, a quantity sufficient to cover the test requirements shall be mixed to ensure that no stratification / clumping has occurred. The test dust shall then be allowed to become acclimatised to a constant mass under the prevailing test conditions.

**NOTE** To ensure a constant rate of dust feed with some dust feeders, it can be found necessary to heat the dust prior to being acclimated to the environment.

## 5.2 Test oil for oil bath air cleaners

The oil used for testing oil bath air cleaners shall be that specified by the filter manufacturer and agreed by the user for use at the appropriate ambient temperature. If an oil is not specified, the test oil shall be a heavy-duty oil and the viscosity at the temperature of the test shall be adjusted as follows:

- 85 mm<sup>2</sup>/s for oil carry-over and restriction/differential pressure tests;
- 330 mm<sup>2</sup>/s for efficiency and capacity tests, including an oil carry-over test after the capacity test.

## 5.3 Absolute filter materials

### 5.3.1 Filter media

The absolute filter may consist of fibreglass media with a minimum thickness of 12,7 mm and a minimum density of 9,5 kg/m<sup>3</sup> <sup>1)</sup>. The fibre diameter shall be 0,76 µm to 1,27 µm and the moisture absorption should be less than 1 % by mass after exposure to 50 °C and 95 % relative humidity for 96 h. The absolute filter media shall be installed with nap side facing upstream, in an airtight holder that adequately supports the media. The face velocity shall not exceed approximately 0,8 m/s to maintain media integrity.

As an alternative, a non-woven filter media with the efficiency described in 5.3.2 may be used.

To reduce any subsequent errors in the measurements caused by losses of fibres or materials, the absolute filter shall be subject to a flow of at least 110 % of the rated flow of ambient air for a minimum of 5 min before the first (new) test weighing.

NOTE The use of an absolute filter with a backing will minimize fibre loss.

### 5.3.2 Validation of absolute filter media efficiency, $E_a$

Arrange two absolute filters in tandem. Perform a filter efficiency test and determine the mass increase of each absolute filter according to the test procedure given in 6.4.3 or 7.5.2:

$$E_a = \frac{\Delta m_A}{\Delta m_A + \Delta m_B} \times 100 \quad (1)$$

where

$E_a$  is the absolute filter efficiency, expressed as a percentage;

$\Delta m_A$  is the mass increase of the upstream absolute filter;

$\Delta m_B$  is the mass increase of the downstream absolute filter.

The absolute filter efficiency should be a minimum of 99 % for the contaminant presented to it.

## 5.4 Absolute filter mass

The absolute filter shall be weighed, to the nearest 0,01 g, after the mass has stabilized. Weight stabilization may be achieved by storage in a ventilated oven at a constant temperature of 105 °C ± 5 °C. The absolute filter shall be weighed inside the oven. Alternatively, air conditioned following 5.5 may be drawn through the absolute filter for 15 min and then the filter is weighed. Evaluate conditioning method per 5.4.1.

1) A suitable material is commercially available. Details may be obtained from the secretariat of ISO/TC 22.

#### 5.4.1 Validation of the absolute filter weighing method

Using the method of choice, the absolute pad weight method shall be performed once each day for three days and evaluate results per [Annex H](#).

### 5.5 Temperature and humidity

All tests shall be conducted with air entering the air cleaner at a temperature of  $23\text{ °C} \pm 5\text{ °C}$ . Tests shall be conducted at a relative humidity of  $(55 \pm 15)\%$ , the permissible variation at each weighing stage throughout each single test being  $\pm 2\%$ .

The test results of an air cleaner will be affected by the relative humidity of the air passing through it and the results of otherwise identical tests carried out near the two extremes of the permitted range of relative humidity may not be directly comparable. The tests should be conducted within the narrowest range of temperature and humidity possible.

## 6 Test procedure for dry-type air cleaners for automotive applications

### 6.1 General

Performance tests shall be performed on a complete air cleaner assembly or on a single air cleaner element; tests on a complete air cleaner assembly are preferred. The tests shall consist of an air flow restriction/differential pressure test, an efficiency test and a capacity test. In addition, a pressure collapse test shall be performed on the air filter element.

### 6.2 Test equipment

**6.2.1** Typical arrangements to determine resistance to air flow, dust capacity, dust removal characteristics and rupture-collapse characteristics are shown in [Annex B, Figures B.1 and B.6 to B.11](#).

Use a dust feeder which when used with the dust injector in [Figures B.2, B.3 and B.18](#) is capable of metering dust over the range of delivery rates required. This dust feed system shall not change the primary particle size distribution of the contaminant. The air feed pressure shall be 100 kPa minimum. The heavy-duty injector pressure shall be a gauge pressure of 280 kPa minimum.

The dust feed system shall be validated as follows.

- a) Charge the dust feeder with a pre-weighed amount of test dust.
- b) Simultaneously start the dust feed system and timer.
- c) At 5 min intervals, determine the mass of dust dispensed. Continue mass determinations of dust increments for 30 min.
- d) Adjust the dust feeder until the average delivery rate is within 5 % of the desired rate and the deviation in delivery rate from the average is not more than 5 %.

**6.2.2** Use a dust-transfer tube between the dust feeder and the injector of a size suitable to maintain dust suspension. Sedimentation losses in the transfer tube should be avoided by having the tube as short as possible and grounded.

**6.2.3** Use the dust injector described in [Table 1](#) and shown in [Figures B.2, B.3 and B.18](#).

**Table 1 — Recommended ISO dust injectors (see [Figures B.2 B.3 and B.18](#))**

Dust feed rate per injector (g/min)	0 to 5	5 to 26	>26
Injector type	Light-duty injector	Light-duty injector or heavy-duty injectors (A or B)	Heavy-duty injectors (A or B)

If an array of injectors is used, special care shall be taken to make sure the dust fed is distributed evenly between each injector for two reasons: First, to get homogeneous dust distribution in the airstream and second, to make sure the maximum or minimum feed rate for the injectors being used is not exceeded.

Where dust feed rates greater than this are required, more than one injector will have to be used. It should be noted that the design of the system feeding test dust to the injector may affect this maximum rate of dust feed. The maximum attainable dust feed rate should therefore be determined prior to the dust feed/injector system being used for tests.

Injector nozzles are subject to natural erosion. Erosion may affect the distribution and delivery of test contaminant. Therefore, it is recommended to use a design with replaceable parts.

**6.2.4** Use an inlet tube conforming to [Figure B.4](#). The dust injector and inlet tube shall be positioned in such a way that there is a uniform dust distribution and no loss of dust.

**6.2.5** Use a manometer or other differential-pressure measuring device with the specified accuracy.

**6.2.6** For air cleaner assembly testing, use a housing and set-up agreed upon by the manufacturer and user conforming to [Figure B.11](#). For air filter element testing, use a test set-up and shroud conforming to [Figures B.1 and B.5](#) or an arrangement as shown in [Figures B.6 or B.7](#). Where the test equipment is as shown in [Figure B.6](#), the dust is fed into the chamber and, to ensure that it does not adhere to the walls and is evenly distributed, dry compressed air jets on flexible tubing should be provided in the test chamber, arranged so to agitate any dust that settles out.

When using compressed air for agitating dust, care shall be taken not to eject any dust out of the chamber. To ensure that no dust is ejected from the chamber, a negative pressure should be maintained between the chamber and the atmosphere.

**6.2.7** Use an outlet tube conforming to [Figure B.4](#). The cross-section shall be the same as the air cleaner outlet. In the case of non-uniform flow conditions caused by special outlet tubes, special precautions may be required.

**6.2.8** Use an air flow rate measuring system having the accuracy described in [4.1](#).

Validate the air flow rate measuring system. The air flow meter shall be of an acceptable design, such as a calibrated orifice and manometer conforming to ISO 5167-1. The orifice unit shall be permanently marked such that it can be identified after calibration. Corrections shall be made for variations in absolute pressure and temperature at the meter inlet and the air flow rate shall be expressed in cubic metres per minute corrected to standard conditions (see [4.2](#)).

**6.2.9** Use an air flow rate control system capable of maintaining the indicated flow rate to within 2 % of the selected value during steady-state and variable air flow operation.

**6.2.10** Use a blower/exhauster for inducing air flow through the system, which has adequate flow rate and pressure characteristics for the filters to be tested. Pulsation of flow rate shall be so low that it is not measurable by the flow rate measuring system.

**6.2.11** Grounding is required for all test apparatus to reduce the effects of static charges and to improve the consistency of the test results. Grounding of metallic and non-metallic surfaces, housings, dust transport tubes, injectors and associated hardware is recommended.

### 6.3 Restriction and differential pressure test

**6.3.1** The purpose of this test is to determine the restriction/differential pressure/pressure loss across the unit under test which will result when air is passed through under predetermined conditions. Airflow restriction or differential pressure is measured with a clean filter element, or elements, at five equally spaced airflows of between 50 % and 150 % of the rated air flow, or as agreed upon between the user and manufacturer.

**6.3.2** Condition the unit to the air flow at which the unit is tested for at least 15 min under the temperature and humidity conditions specified in [5.5](#).

**6.3.3** Set up the test stand as shown in [Figures B.8](#) or [B.9](#) and [Figures B.14](#) or [B.15](#). Seal all joints to prevent air leaks. Connect pressure taps.

**6.3.4** Measure and record the restriction and the differential pressure versus the flow rate at approximately 50 %, 75 %, 100 %, 125 % and 150 % of the rated air flow, or as agreed upon between the user and manufacturer.

**6.3.5** Record the ambient temperature, barometric pressure and relative humidity.

**6.3.6** Correct the recorded restriction and differential pressure to standard conditions in accordance with [Annex G, Formula \(G.1\)](#).

**6.3.7** For pressure loss determination, use the formula given in [Annex A](#).

**6.3.8** Plot the results, for example as shown in [Annex E, Figure E.1](#) or equivalent.

### 6.4 Efficiency test

#### 6.4.1 Purpose

The purpose of this test is to determine the retention capabilities of the unit under test. This test can be conducted with either constant or variable air flow and with coarse dust or fine test dust. If desired, efficiency tests can be performed concurrently with capacity tests (see [6.5](#)). Determination of the efficiency at constant test air flow can be performed at the rated air flow or any percentage thereof, as agreed upon by the user and manufacturer. Determination of efficiency at variable air flow can be performed using variable air flow cycle according to [6.7](#).

#### 6.4.2 Types

Three types of efficiency tests can be performed, as follows:

- full-life efficiency determined when the terminal condition, i.e. the terminating differential pressure is reached;
- incremental efficiency determined when, for example, 10 %, 25 % and 50 % of the terminating differential pressure minus the initial differential pressure is reached;
- initial efficiency determined after the addition of 20 g of contaminant or the number of grams numerically equivalent to six times the air flow in cubic metres per minute, whichever is the greater.



### 6.4.3 Test procedure — Absolute filter method

**6.4.3.1** Based on the test flow, calculate the test dust feed rate using a dust concentration of 1,0 g/m<sup>3</sup> of air; in special cases (e.g. small filters) 0,25 g/m<sup>3</sup> or 0,5 g/m<sup>3</sup> may be allowed.

**6.4.3.2** Condition the unit under test according to 6.3.2, then measure and record the mass.

NOTE Conditioning of the absolute filter pad and air cleaner can be performed concurrently.

**6.4.3.3** Weigh the absolute filter pad as specified in 5.4 and record mass before assembly within absolute filter housing.

**6.4.3.4** Set up test stand as shown in Figure B.11 for air cleaner assemblies, or as shown in Figure B.1, B.6 or B.7 for air filter elements. Seal all joints to prevent air leakage.

**6.4.3.5** Record the temperature, barometric pressure and relative humidity.

**6.4.3.6** Prepare the specified test dust according to 5.1 and weigh out the quantity required for test in a suitable test container. For full-life efficiency tests, the quantity should be approximately 125 % of the estimated capacity of the unit under test. Record the mass of the container and dust to the nearest 0,1 g. Specified in 4.1.

**6.4.3.7** Start the air flow through the test stand and stabilize at the test flow rate. Record the differential pressure.

**6.4.3.8** Load the dust feeder from the dust container and adjust the feed rate to inject dust at the concentration calculated in 6.4.3.1. Reload the dust feeder from the dust container throughout the test as necessary.

**6.4.3.9** At specified time intervals (a minimum of five points is recommended), record the differential pressure in accordance with Annex A at the test flow and the elapsed test time.

**6.4.3.10** Continue the test until the specified terminal condition is reached.

**6.4.3.11** Record the temperature, barometric pressure and relative humidity.

**6.4.3.12** The dust on the exterior surfaces of a cleaner assembly or any which may have settled in the test chamber/ducting on the inlet side of a test element shall be collected carefully and its weight recorded. This dust shall then be discarded due to potential change in distribution.

**6.4.3.13** Reweigh the dust container and add the result to the weight recorded in 6.4.3.12. Subtract this sum from the mass recorded in 6.4.3.6. The difference is the mass of dust fed to the unit under test. The mass of dust fed to the unit under test can be determined from weight loss of the dust feeder directly.

**6.4.3.14** Carefully remove the unit under test without losing any dust. Note any evidence of seal leakage or unusual conditions. Weigh the unit, per 4.1 in grams. The increase in mass of the unit under test is this mass minus the mass determined in 6.4.3.2. In the full-life efficiency test [see 6.4.2 a)] this increase in mass is the capacity of the unit under test.

**6.4.3.15** Brush any observed dust on the downstream side of the test unit onto the absolute filter. Carefully remove the absolute filter. Repeat step 6.4.3.3 per 4.1 and determine the difference in mass. This is the increase in mass of the absolute filter.