



**SLOVENSKI STANDARD**  
**SIST ISO 6003:2018**

**01-september-2018**

**Nadomešča:**  
**SIST ISO 6003:1995**

---

**Alpske smuči - Določevanje mase in polarnega vztrajnostnega momenta - Metoda za laboratorijsko merjenje**

Alpine skis -- Determination of mass and polar moment of inertia -- Laboratory measurement method

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

Skis alpins -- Détermination de la masse et du moment d'inertie polaire -- Méthode de mesurage en laboratoire

[SIST ISO 6003:2018](https://standards.iteh.ai/catalog/standards/sist/04855928-7b08-444b-b3d0-676f1548a58c/sist-iso-6003-2018)

[https://standards.iteh.ai/catalog/standards/sist/04855928-7b08-444b-](https://standards.iteh.ai/catalog/standards/sist/04855928-7b08-444b-b3d0-676f1548a58c/sist-iso-6003-2018)

[b3d0-676f1548a58c/sist-iso-6003-2018](https://standards.iteh.ai/catalog/standards/sist/04855928-7b08-444b-b3d0-676f1548a58c/sist-iso-6003-2018)

**Ta slovenski standard je istoveten z: ISO 6003:2017**

---

**ICS:**

97.220.20      Oprema za zimske športe      Winter sports equipment

**SIST ISO 6003:2018**

**en**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST ISO 6003:2018

<https://standards.iteh.ai/catalog/standards/sist/04855928-7b08-444b-b3d0-676f1548a58c/sist-iso-6003-2018>

INTERNATIONAL  
STANDARD

ISO  
6003

Third edition  
2017-11

---

---

**Alpine skis — Determination of  
mass and polar moment of inertia —  
Laboratory measurement method**

*Skis alpins — Détermination de la masse et du moment d'inertie  
polaire — Méthode de mesurage en laboratoire*

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST ISO 6003:2018](https://standards.iteh.ai/catalog/standards/sist/04855928-7b08-444b-b3d0-676f1548a58c/sist-iso-6003-2018)

[https://standards.iteh.ai/catalog/standards/sist/04855928-7b08-444b-  
b3d0-676f1548a58c/sist-iso-6003-2018](https://standards.iteh.ai/catalog/standards/sist/04855928-7b08-444b-b3d0-676f1548a58c/sist-iso-6003-2018)



Reference number  
ISO 6003:2017(E)

© ISO 2017

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST ISO 6003:2018

<https://standards.iteh.ai/catalog/standards/sist/04855928-7b08-444b-b3d0-676f1548a58c/sist-iso-6003-2018>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Ch. de Blandonnet 8 • CP 401  
CH-1214 Vernier, Geneva, Switzerland  
Tel. +41 22 749 01 11  
Fax +41 22 749 09 47  
copyright@iso.org  
www.iso.org

# Contents

Page

<b>Foreword</b> .....	<b>iv</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 Apparatus</b> .....	<b>1</b>
<b>5 Sampling and conditioning</b> .....	<b>2</b>
<b>6 Calibration of measuring device</b> .....	<b>2</b>
<b>7 Procedure</b> .....	<b>3</b>
<b>8 Expression of results</b> .....	<b>4</b>
8.1 Mass of the ski.....	4
8.2 Polar moment of inertia of the ski.....	4
<b>9 Tolerances</b> .....	<b>6</b>
9.1 Measurement tolerances.....	6
9.2 Tolerances on published data.....	6
<b>10 Test report</b> .....	<b>6</b>

## iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 6003:2018

<https://standards.iteh.ai/catalog/standards/sist/04855928-7b08-444b-b3d0-676f1548a58c/sist-iso-6003-2018>

## ISO 6003:2017(E)

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html). (standards.iteh.ai)

This document was prepared by Technical Committee ISO/TC 83, *Sports and other recreational facilities and equipment*, Subcommittee SC 4, *Snowsports equipment*.

This third edition cancels and replaces the second edition (ISO 6003:1984), which has been technically revised.

# Alpine skis — Determination of mass and polar moment of inertia — Laboratory measurement method

## 1 Scope

This document specifies laboratory measurement methods for mass and polar moment of inertia of alpine skis.

If laboratory measurement data are determined and published by the ski manufacturer or other institutions, standard measurement procedures can be used to ensure comparability.

This document also specifies a tolerance range which can be met by the measurement data of all manufactured skis, if for the specific model length measurement data are published by the manufacturer of the ski.

NOTE The appropriate ski length can be given with the published measurement data.

It is not the purpose of this document to evaluate the measurement data with regard to their influence on the quality of the ski.

## 2 Normative references

There are no normative references in this document.

## 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

### 3.1

#### mass of ski

*m*

mass of a finished manufactured ski without any mounted parts

Note 1 to entry: Expressed in kilograms.

### 3.2

#### polar moment of inertia

*I*

mass moment of inertia of the ski about its centre of gravity

Note 1 to entry: The unit used to express the polar moment of inertia is the kilogram metre squared.

## 4 Apparatus

4.1 **Weighing device**, accurate to  $\pm 0,02$  kg.

4.2 **Fulcrum**, for locating the centre of gravity of the ski.

## ISO 6003:2017(E)

**4.3 Time measurement device** (stop watch), accurate to at least 0,1 s.

**4.4 Measuring device** in accordance with [Figure 1](#), consisting of the following parts.

**4.4.1 Clamping device A** (see [Figure 1](#)), consisting of two clamping fixtures.

The top clamping fixture has a hole with a mark to locate the centre of gravity and a further two holes at a distance  $e$  from the centre mark for fixation of the filaments B.

The recommended dimension for,  $e$ , is 25 mm and the mass of the clamping device shall be less than 0,1 kg.

**4.4.2 Top plate C**, with two holes separated by the distance  $2d_f$  for the fixation of filaments B. The plate C shall be fixed on a stiff, horizontal beam.

**4.4.3 Two filaments B**, with equal length,  $l$ , which connect the top plate with the clamping device. The ratio  $d_f:l$  shall be approximately 1:40. With the recommended dimension  $d_f = 25$  mm, the length,  $l$ , shall be 1 000 mm. The filaments shall be made of materials with low elongation and high strength (for example, tennis string, silk fishing line).

The diameter of the filaments shall be not more than 1,0 mm.

## 5 Sampling and conditioning

**5.1** In order to ensure comparability, it is recommended to use one of the following ski sizes if data of measurements are published:

— 150 cm, 165 cm or 180 cm.

From these three sizes, the one which is most representative for the tested model shall be selected.

**5.2** All measurements according to this document shall be taken from a finished manufactured ski without any mounted parts.

**5.3** All measurements according to this document shall be taken with a measuring device, which has been conditioned at a temperature of  $(20 \pm 2)$  °C and a relative humidity of  $(65 \pm 1)$  % (i.e. the device shall be placed in this atmosphere for at least 24 h before measurement).

## 6 Calibration of measuring device

Differences in construction between the different measuring devices can lead to different measurement results, which deviate from the theoretical accurate value of the polar moment of inertia.

In order to compensate such deviations, it is recommended to determine a correction factor,  $c$ , for each measuring device, to correct the measured data and improve reproducibility.

The correction factor is determined from the ratio of the calculated polar moment of inertia to the measured polar moment of inertia of a bar of steel with dimensions 0,1 cm × 2 cm × 170 cm.

The theoretical polar moment of inertia,  $I_{th}$ , is calculated by [Formula \(1\)](#):

$$I_{th} = \frac{m(a^2 + b^2)}{12} \quad (1)$$



where

- $a$  is the length of the bar in metres;
- $b$  is the width of the bar in metres;
- $m$  is the mass of the bar in kilograms.

Using this theoretical value and the measured value, the correction factor,  $c$ , can be determined by [Formula \(2\)](#):

$$c = \frac{I_{\text{th}}}{I} \quad (2)$$

where

- $I_{\text{th}}$  is the theoretical polar moment of inertia;
- $I$  is the measured polar moment of inertia.

This factor should fall within a range of 0,9 and 1,1.

If this factor lies outside of this range, the measuring device shall be checked and brought into closer conformity with this document.

## 7 Procedure

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)

Measure the mass of the ski with the weighing device (see [3.1](#)).

Place the ski on the fulcrum (see [3.2](#)), to determine the centre of gravity, until it balances. The centre shall be marked with a cross sign.

Mount the ski in the clamping device A (see [4.4.1](#)) in such a way that the centre of gravity mark is in the centre of the hole of the top clamping fixture midway between the two filaments. The longitudinal centre axis of the ski shall be perpendicular to a line drawn between the two filaments B (see [Figure 1](#)).

Let the ski come to rest suspended in the device. Eliminate any swinging motion. It is important that the test area be free of air movement, as this affects test accuracy.

With the hand, rotate the ski horizontally about its perpendicular axis through the centre of gravity. Lateral displacement of the centre of gravity exceeding 10 mm shall be avoided. The twist angle should be approximately 25°.

After displacement, the ski is released to swing freely around the perpendicular axis through the centre of gravity. The time required for the ski to complete five cycles is recorded with the stop watch (see [4.3](#)). The time,  $T$ , for 1 oscillation is determined by [Formula \(3\)](#):

$$T = \frac{T_{\text{rec}}}{5} \quad (3)$$

where

- $T$  is the oscillation time;
- $T_{\text{rec}}$  is recorded time.