

**SLOVENSKI STANDARD
SIST-TP CEN/CLC/TR 17603-31-05:2021
01-oktober-2021**

**Vesoljska tehnika - Priročnik o topotni zasnovi - 5. del: Strukturni materiali:
kovinski in kompozitni**

Space Engineering - Thermal design handbook - Part 5: Structural Materials: Metallic and Composite

Raumfahrttechnik - Handbuch für thermisches Design - Teil 5: Konstruktionswerkstoffe: Metallisch und Verbundwerkstoffe

**ITeH STANDARD PREVIEW
(standards.iteh.ai)**

Ingénierie spatiale - Manuel de conception thermique - Partie 5: Matériaux structuraux: métalliques et composites

[SIST-TP CEN/CLC/TR 17603-31-05:2021](#)

<https://standards.iteh.ai/catalog/standards/sist/39655cde-a79d-4350-ab9b-248af70054/sist-tp-cen/clc/tr-17603-31-05:2021>

Ta slovenski standard je istoveten z: CEN/CLC/TR 17603-31-05:2021

ICS:

49.140 Vesoljski sistemi in operacije Space systems and operations

SIST-TP CEN/CLC/TR 17603-31-05:2021 en,fr,de

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST-TP CEN/CLC/TR 17603-31-05:2021](#)

<https://standards.iteh.ai/catalog/standards/sist/39655cde-a79d-4350-ab9b-12d8afc79954/sist-tp-cen-clc-tr-17603-31-05-2021>

**TECHNICAL REPORT
RAPPORT TECHNIQUE
TECHNISCHER BERICHT**

**CEN/CLC/TR 17603-31-
05**

August 2021

ICS 49.140

English version

**Space Engineering - Thermal design handbook - Part 5:
Structural Materials: Metallic and Composite**

Ingénierie spatiale - Manuel de conception thermique -
Partie 5 : Matériaux de structure : métalliques et
composites

Raumfahrttechnik - Handbuch für thermisches Design -
Teil 5: Strukturmaterialien: Metalle und Verbundstoffe

This Technical Report was approved by CEN on 14 June 2021. It has been drawn up by the Technical Committee CEN/CLC/JTC 5.

CEN and CENELEC members are the national standards bodies and national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

*VIEW STANDARD PREVIEW
(standards.iteh.ai)*

SIST-TP CEN/CLC/TR 17603-31-05:2021
<https://standards.iteh.ai/catalog/standards/sist/39655cde-a79d-4350-ab9b-12d8afc79954/sist-tp-cen-clc-tr-17603-31-05-2021>



**CEN-CENELEC Management Centre:
Rue de la Science 23, B-1040 Brussels**

Table of contents

European Foreword.....	17
1 Scope.....	18
2 References	19
3 Terms, definitions and symbols	20
3.1 Terms and definitions	20
3.2 Symbols.....	20
4 Metallic materials.....	23
4.1 General.....	23
4.1.1 Modifiers of thermal radiative properties.....	26
4.1.2 Cladding definitions.....	27
4.1.3 Temper designation for heat treatable aluminium alloys.....	28
4.2 Aluminium alloys.....	28
https://standards.iteh.ai/catalog/standards/sist/39655cde-a79d-4350-ab9b-12d8a6c79954/sist-tp-cen-clc-tr-17603-31-05-2021	
4.3 Aluminium-Copper alloys.....	85
4.4 Aluminium-Magnesium alloys	104
4.5 Aluminium-Zinc alloys	114
4.6 Magnesium-Zink-Thorium alloys	131
4.7 Titanium-Aluminium-Tin alloys	133
4.8 Titanium-Aluminium-Tin alloys	144
4.9 Titanium-Aluminium-Vanadium alloys	151
4.10 Nickel-Chrome-Cobalt-Molybdenum alloys	165
4.11 Iron-Nickel alloys	175
5 Composite materials	182
5.1 List of symbols	182
5.2 List of matrices, preprints and laminates quoted in this clause	187
5.2.1 Matrices, adhesives, potting, moulding compounds	188
5.2.2 Preprints, laminates and films	193
5.2.3 Code list of manufacturers (or developers).....	195
5.3 General introduction	197
5.3.2 Composition	198

5.3.3	Commercial fiber product names, descriptions and manufacturers	200
5.3.4	Geometry of fiber reinforcement. fabrics. abridged designation	205
5.4	Physical properties	210
5.4.1	Density.....	210
5.5	Thermal properties.....	216
5.5.1	Specific heat	216
5.5.2	Thermal conductivity	222
5.5.3	Thermal diffusivity	247
5.6	Thermo-elastic properties	256
5.6.1	Coefficient of linear thermal expansion.....	256
5.7	Thermal radiation properties of bare high strength fibers	319
5.7.1	Sample characterization.....	319
5.7.2	Emittance.....	319
5.7.3	Absorptance.....	321
5.8	Thermal radiation properties of bare composite materials.....	324
5.8.1	Tabulated data	324
5.9	Thermal radiation properties of coated composite materials.....	326
5.9.1	White painted composite materials.....	327
5.9.2	Sputtered Aluminium on graphite-epoxy composite material	331
5.10	Operating temperature range https://standards.iteh.ai/catalog/standards/sist/39655cde-a79d-4350-ab9b-12d8a1c79954/sist-tp-cen-clc-tr-17603-31-05-2021	334
5.10.1	Temperatures related to the maximum service temperature https://standards.iteh.ai/catalog/standards/sist/39655cde-a79d-4350-ab9b-12d8a1c79954/sist-tp-cen-clc-tr-17603-31-05-2021	335
5.11	Electrical properties	341
5.11.1	Electrical resistance and electrical resistivity	341
5.12	Prelaunch environmental effects.....	348
5.12.1	Moisture absorption and desorption	348
5.13	Postlaunch environmental effects	355
5.13.1	Ascent.....	355
5.13.2	Orbital effects.....	357
5.13.3	Re-entry effects.....	367
5.14	Thermal vacuum cycling	371
5.14.1	Test facilities	371
5.14.2	Measurement methods	372
5.14.3	Thermal vacuum cycling effects on the coefficient of linear thermal expansion	373
5.14.4	Trends in the variation of mechanical properties	378
5.15	Coating application	378
5.15.1	Pcbz conductive white paint	378
5.15.2	APA-2474 (TiO ₂ white paint)	378

CEN/CLC/TR 17603-31-05:2021 (E)

5.15.3	Wiederhold's Z-12321	379
5.16	Past spatial uses	380
5.16.1	Intelsat v	380
5.16.2	Spelda (structure porteuse externe de lancement double ariane).....	381
5.16.3	CS-3A Japanese satellite	384
Bibliography metalic materials.....	387	
References composite materials.....	391	

Figures

Figure 4-1: Specific heat, c , of Aluminium as a function of temperature, T	30
Figure 4-2: Thermal conductivity, κ , of Aluminium as a function of temperature, T	31
Figure 4-3: Thermal conductivity integrals of Aluminium as a function of temperature, T	32
Figure 4-4: Thermal diffusivity, α , of Aluminium as a function of temperature, T	33
Figure 4-5: Linear thermal expansion, $\Delta L / L$, of Aluminium as a function of temperature, T	34
Figure 4-6: Normal spectral emittance, ε'_λ , of Aluminium as a function of wavelength, λ	37
Figure 4-7: Normal spectral emittance, ε_λ , of Aluminium conversion coatings as a function of wavelength, λ	38
Figure 4-8: Angular spectral emittance, ε'_λ , of Aluminium as a function of wavelength, λ	39
Figure 4-9: Normal total emittance, ε' , of Aluminium as a function of temperature, T	45
Figure 4-10: Normal total emittance, ε , of Aluminium anodized as a function of anodizing thickness, t_c	46
Figure 4-11: Summary of data concerning the hemispherical total emittance, ε , of Aluminium as a function of temperature, T . From Touloukian & DeWitt (1970) [42].....	47
Figure 4-12: Summary of data concerning the hemispherical total emittance, ε , of Aluminium conversion coatings vs. temperature, T . From Touloukian, DeWitt & Hernicz (1972) [43].....	52
Figure 4-13: Directional spectral absorptance, α'_λ , of Aluminium as a function of wavelength, λ . Data points ∇ correspond to $\beta = 25^\circ$	54
Figure 4-14: Absorptance to emittance ratio, α/ε , of Aluminium conversion coatings as a function of the exposure time, t	60
Figure 4-15: Normal - normal spectral reflectance, ρ''_λ , of Aluminium as a function of wavelength, λ	62
Figure 4-16: Normal - normal spectral reflectance, ρ''_λ , of Aluminium contact coatings as a function of wavelength, λ	64
Figure 4-17: Effect of coating thickness on normal - normal spectral reflectance, ρ''_λ , of Aluminium conversion coatings as a function of wavelength, λ	65
Figure 4-18: Bidirectional reflectance, ρ_λ ”, of Aluminium contact coatings as a function of wavelength, λ	66

Figure 4-19: Bidirectional spectral reflectance, ρ_λ'' , of Aluminium conversion coatings as a function of zenith angles, β and β' , of incident and reflected radiations.....	68
Figure 4-20: Summary of data concerning normal - hemispherical spectral reflectance, ρ_λ' , of Aluminium vs. wavelength, λ . From Touloukian & DeWitt (1970) [42]	69
Figure 4-21: Normal - hemispherical spectral reflectance, ρ_λ' , of Aluminium conversion coatings as a function of wavelength, λ	70
Figure 4-22: Effect of UV exposure on normal - hemispherical spectral reflectance, ρ_λ' , of Aluminium conversion coatings as a function of wavelength, λ	71
Figure 4-23: Effect of electron exposure on normal - hemispherical spectral reflectance of Aluminium conversion coatings as a function of wavelength, λ	72
Figure 4-24: Effect of simultaneous UV - electron exposure on normal - hemispherical spectral reflectance, ρ_λ' , of Aluminium conversion coatings as a function of wavelength, λ	73
Figure 4-25: Effect of proton exposure on normal - hemispherical spectral reflectance, ρ_λ' , of Aluminium conversion coatings as a function of wavelength, λ	74
Figure 4-26: Directional - hemispherical spectral reflectance, ρ_λ' , of Aluminium conversion coatings as a function of wavelength, λ	75
Figure 4-27: Hemispherical - normal spectral reflectance, ρ_λ' , of Aluminium contact coatings as a function of wavelength, λ	76
Figure 4-28: Bidirectional total reflectance, ρ'' , of Aluminium as a function of the viewing zenith angles, β'	77
Figure 4-29: Normal - normal spectral transmittance, τ_λ'' , of Aluminium as a function of wavelength.....	80
Figure 4-30: Angular spectral transmittance, τ_λ'' , of Aluminium as a function of wavelength, λ	81
Figure 4-31: Electrical resistivity, σ^{-1} , of Aluminium as a function of temperature, T	83
Figure 4-32: Specific heat, c , of Al - 4,3 Cu - 1,5 Mg - 0,6 Mn as a function of temperature, T	86
Figure 4-33: Thermal conductivity, k , of Al - 4,3 Cu - 1,5 Mg - 0,6 Mn as a function of temperature, T	87
Figure 4-34: Thermal conductivity integrals of Al - 4,3 Cu - 1,5 Mg - 0,6 Mn as a function of temperature, T	88
Figure 4-35: Thermal diffusivity, α , of Al - 4,3 Cu - 1,5 Mg - 0,6 Mn as a function of temperature, T	89
Figure 4-36: Linear thermal expansion, $\Delta L / L$, of Al - 4,3 Cu - 1,5 Mg - 0,6 Mn as a function of temperature, T	90
Figure 4-37: Normal - spectral emittance, ε_λ' , of Al - 4,3 Cu - 1,5 Mg - 0,6 Mn as a function of wavelength, λ	91
Figure 4-38: Normal total emittance, ε' , of Al - 4,3 Cu - 1,5 Mg - 0,6 Mn as a function of temperature, T	93
Figure 4-39: Normal-normal spectral reflectance, ρ_λ'' , of Al-4,3 Cu-1,5 Mg-0,6 Mn, anodized, as a function of wavelength, λ	98

CEN/CLC/TR 17603-31-05:2021 (E)

Figure 4-40: Normal - hemispherical spectral reflectance, ρ_λ' , of Al - 4,3 Cu - 1,5 Mg - 0,6 Mn as a function of wavelength, λ	99
Figure 4-41: Normal - hemispherical spectral reflectance, ρ_λ' , of Al - 4,3 Cu - 1,5 Mg - 0,6 Mn, anodized, as a function of wavelength, λ	100
Figure 4-42: Normal-hemispherical spectral reflectance, ρ_λ' , of Al-1 Mg-0,6 Si, as received, as a function of wavelength, λ	108
Figure 4-43: Normal-hemispherical spectral reflectance, ρ_λ' , of Al-1 Mg-0,6 Si, grit blasted, as a function of wavelength, λ	109
Figure 4-44: Normal-hemispherical spectral reflectance, ρ_λ' , of Al-1 Mg-0,6 Si, chemically polished, as a function of wavelength, λ	111
Figure 4-45: Normal - hemispherical spectral reflectance, ρ_λ' , of Al - 1 Mg - 0,6 Si, chemically milled, as a function of wavelength, λ	112
Figure 4-46: Specific heat, c , of Al - 5,7 Zn - 2,5 Mg - 1,6 Cu as a function of temperature, T	115
Figure 4-47: Thermal conductivity, k , of Al - 5,7 Zn - 2,5 Mg - 1,6 Cu as a function of temperature, T	116
Figure 4-48: Thermal conductivity integral of Al – 5,7 Zn – 2,5 Mg – 1,6 Cu as a function of temperature, T	117
Figure 4-49: Thermal diffusivity, α , of Al - 5,7 Zn - 2,5 Mg - 1,6 Cu as a function of temperature, T	118
Figure 4-50: Linear thermal expansion, $\Delta L/L$, of Al - 5,7 Zn - 2,5 Mg - 1,6 Cu as a function of temperature, T	119
Figure 4-51: Normal spectral emittance, ε_λ' , of Al - 5,7 Zn - 2,5 Mg - 1,6 Cu as a function of wavelength, λ	120
Figure 4-52: Angular spectral emittance, ε_λ' , of Al - 5,7 Zn - 2,5 Mg - 1,6 Cu as a function of wavelength, λ	121
Figure 4-53: Normal total emittance, ε' , of Al - 5,7 Zn - 2,5 Mg - 1,6 Cu as a function of temperature, T	122
Figure 4-54: Normal-hemispherical spectral reflectance, ρ'_λ , of Al - 5,7 Zn - 2,5 Mg - 1,6 Cu conversion coatings, as a function of wavelength, λ	126
Figure 4-55: Specific heat, c , of Ti - 5 Al - 2,5 Sn as a function of temperature, T	134
Figure 4-56: Thermal conductivity, k , of Ti - 5 Al - 2,5 Sn as a function of temperature, T	135
Figure 4-57: Thermal linear expansion, $\Delta L/L$, of Ti - 5 Al - 2,5 Sn as a function of temperature, T	136
Figure 4-58: Normal spectral emittance, ε_λ' , of Ti - 5 Al - 2,5 Sn as a function of temperature, T , for $\lambda = 6,65 \times 10^{-7}$ m.....	137
Figure 4-59: Normal total emittance, ε' , of Ti - 5 Al - 2,5 Sn as a function of temperature, T	138
Figure 4-60: Normal-normal spectral reflectance, ρ_λ'' , of Ti - 5 Al - 2,5 Sn as a function of wavelength, λ	140
Figure 4-61: Normal - hemispherical spectral reflectance, ρ_λ' , of Ti - 5 Al - 2,5 Sn as a function of wavelength, λ	141

Figure 4-62: Normal - hemispherical spectral reflectance, ρ_λ' , of Ti - 5 Al - 2,5 Sn, anodized, as a function of wavelength, λ	142
Figure 4-63: Electrical resistivity, σ^{-1} , of Ti - 5 Al - 2,5 Sn as a function of temperature, T	143
Figure 4-64: Specific heat, c , of Ti - 6 Al - 2 Sn - 4 Zr - 2 Mo as a function of temperature, T	145
Figure 4-65: Thermal conductivity, k , of Ti - 6 Al - 2 Sn - 4 Zr - 2 Mo as a function of temperature, T	146
Figure 4-66: Mean coefficient of linear thermal expansion, β , of Ti - 6 Al - 2 Sn - 4 Zr - 2 Mo from room temperature to temperature T	147
Figure 4-67: Electrical resistivity, σ^{-1} , of Ti - 6 Al - 2 Sn - 4 Zr - 2 Mo as a function of temperature, T	149
Figure 4-68: Specific heat, c , of Ti - 6 Al - 4 V as a function of temperature, T	152
Figure 4-69: Thermal conductivity, k , of Ti - 6 Al - 4 V as a function of temperature, T	153
Figure 4-70: Thermal conductivity integrals of Ti - 6 Al - 4 V as a function of temperature, T	154
Figure 4-71: Thermal diffusivity, α , of Ti - 6 Al - 4 V as a function of temperature, T	155
Figure 4-72: Thermal linear expansion, $\Delta L/L$, of Ti - 6 Al - 4 V as a function of temperature, T	156
Figure 4-73: Normal spectral emittance, ε_λ', of Ti - 6 Al - 4 V as a function of temperature, T.....	157
Figure 4-74: Normal total emittance, ε' , of Ti - 6 Al - 4 V as a function of temperature, T	158
Figure 4-75: Hemispherical total emittance, ε , of Ti - 6 Al - 4 V as a function of temperature, T	160
Figure 4-76: Normal - hemispherical spectral reflectance, ρ_λ' , of Ti - 6 Al - 4 V as a function of wavelength, λ	162
Figure 4-77: Electrical resistivity, σ^{-1} , of Ti - 6 Al - 4 V as a function of temperature, T	163
Figure 4-78: Specific heat, c , of Ni - 19 Cr - 11 Co - 10 Mo - 3 Ti as a function of temperature, T	166
Figure 4-79: Thermal conductivity, k , of Ni - 19 Cr - 11 Co - 10 Mo - 3 Ti as a function of temperature, T	167
Figure 4-80: Thermal linear expansion, $\Delta L/L$, of Ni - 19 Cr - 11 Co - 10 Mo - 3 Ti as a function of temperature, T	168
Figure 4-81: Normal spectral emittance, ε_λ' , of Ni - 19 Cr - 11 Co - 10 Mo - 3 Ti as a function of wavelength, λ	169
Figure 4-82: Normal total emittance, ε' , of Ni - 19 Cr - 11 Co - 10 Mo - 3 Ti as a function of temperature, T	170
Figure 4-83: Normal-normal spectral reflectance, ρ''_λ , of Ni - 19 Cr - 11 Co - 10 Mo - 3 Ti as a function of wavelength, λ . Data points ▷ correspond to normal-hemispherical reflectance while ▶, ◀, ◁ correspond to hemispherical-normal reflectance.	172
Figure 4-84: Specific heat, c , of Fe - 36 Ni (Invar) as a function of temperature, T	176

CEN/CLC/TR 17603-31-05:2021 (E)

Figure 4-85: Linear thermal expansion, $\Delta L/L$, of Fe - 36 Ni (Invar) as a function of temperature, T	177
Figure 4-86: Effect of the concentration of alloying elements, c , on the value of the coefficient of linear expansion, β . From MOND NICKEL Co.	178
Figure 4-87: Normal emittance, ε_λ' , of Fe - 36 Ni (Invar), for $\lambda = 6,7 \times 10^{-7}$ as a function of temperature, T	179
Figure 5-1: International ties between Carbon Fiber manufactures. From SENER (1984) [147].....	205
Figure 5-2: Schematic of an angle plied laminate. From Chamis (1987) [67].	206
Figure 5-3: Schematic of a tri-orthogonally fiber reinforced composite. a) Straight filaments. From Domínguez (1987) [82]. b) Tapes. From Aboudi (1984) [49].....	206
Figure 5-4: Main types of woven fabrics. Lengthwise (warp) yarns and crosswise (fill) yarns can be interlaced to produce woven fabrics. A fabric construction of 16 x 14 means 16 warp ends per inch and 14 fill ends per inch. a) Plain weave. Very stable. Small yarn slippage. b) Leno weave. Minimizes distortion with few yarns. c) Twill. The fabric has a broken diagonal line and, consequently, greater pliability than a plain weave. d) Crowfoot satin. Pliable and comfortable to contoured surfaces. From Domínguez (1987) [82], Weeton, Peters & Thomas (1987) [164].	207
Figure 5-5: Longitudinal (to fibers) and transverse directions for the measurement of composite properties. From Chamis (1987) [67].....	209
Figure 5-6: Cryostat assemblies for measuring the thermal conductivity, k . a) High- k samples. b) Low- k samples. From Pilling, Yates, Black & Tattersall (1979) [137]. For explanation see text CLC/TR 17603-31-05:2021	222
Figure 5-7: Facility used to measure the thermal conductivity, k , of a sample as a function of temperature in the range 90 K to 410 K. Temperature changes continuously. From Ott (1981) [132].	224
Figure 5-8: Hypodermic probe to measure the thermal conductivity of polymer melts. All the dimensions are in mm. From Lobo & Cohen (1990) [120].....	225
Figure 5-9: Thermal conductivity, k_m , of different matrices as a function of temperature, T . Numerical values are given in Table 5-10.	236
Figure 5-10: Longitudinal thermal conductivity, k_f1 , of several advanced pitch graphite fibers vs. temperature, T . The fiber designation is from Amoco Performance Products; the number stands for the fiber elasticity modulus in millions of lbs.in $^{-2}$. All the data, unless otherwise stated, are from LMSC. Pitch precursor graphite fibers have a structure which approaches that of a single crystal of graphite and, thus, their thermal conductivity is very large. From McGuire & Vollerin (1990) [127].	237
Figure 5-11: Typical assembly for measuring the thermal diffusivity, α , of a long slender bar by use of the Angström method. From Landis (1964) [116].	247
Figure 5-12: Typical assembly for measuring the thermal diffusivity, α , of a disc shaped sample. From Lachi, Legrand & Degiovanni (1988) [115].	248
Figure 5-13: Thermal diffusivity, α_f , of different fiber cloths as a function of temperature, T . Numerical values are given in Table 5-33 From Touloukian (1967) [157].	251

Figure 5-14: Experimental arrangement for the interferometric measurement of the thermal expansion. a) Specimen chamber assembly. b) Optical system. From James & Yates (1965) [108]. For explanation see text.	256
Figure 5-15: The ESTEC CTE 1000 facility for the measurement of the linear thermal expansion of structure up to 0,7 m long. All the dimensions are in mm. From Aalders (1989) [48].	258
Figure 5-16: Linear thermal expansion, β_m , as a function of temperature, T , for four different epoxy matrices. Numerical values are given in Table 5-41.	269
Figure 5-17: Linear thermal expansion coefficient measured parallel to fibers, β_1 , as a function of temperature, T , for some composite materials formed by the same matrix, DER 332/T403, and two different glass fiber reinforcements. Upper and lower limits of the shadowed regions are for 95% confidence.	278
Figure 5-18: Linear thermal expansion coefficient measured perpendicular to fibers, β_2 , as a function of temperature, T , for some composite materials formed by the same matrix, DER 332/T403, and two different glass fiber reinforcements.	280
Figure 5-19: Linear thermal expansion coefficient measured in different directions, β , as a function of temperature, T , for similar carbon fiber reinforced composite materials. The matrix is ERLA 4617/mPDA. From Rogers, Phillips, Kingston, Lee, Overy, Sargent & McCalla (1977) [144].	281
Figure 5-20: Linear thermal expansion coefficient measured parallel to fibers, β_1 , as a function of temperature, T , for different fiber volume ratios, φ_f . Fiber: Courtaulds HTS PT112/21Z; Matrix: DLS 351/BF ₃ 400.	290
Figure 5-21: Linear thermal expansion coefficient measured perpendicular to fibers, β_2 , as a function of temperature, T , for different fiber volume ratios, φ_f . Fiber: Courtaulds HTS PT112/21Z; Matrix: DLS 351/BF ₃ 400 4350-a,b.	291
Figure 5-22: Linear thermal expansion coefficient measured either in plane of laminate, β_1 , or perpendicular to it, β_3 , as a function of temperature, T , for similar carbon fibers reinforced composite materials. The fiber is carbon HTS PT112/21Z. From Yates, McCalla, Sargent, Rogers, Phillips & Kingston-Lee (1978)b [169].	292
Figure 5-23: Linear thermal expansion coefficient, β , of a carbon fiber reinforced unidirectional composite material, measured in plane of laminate, as a function of the direction of the measurement, θ . Matrix is Epikote 828/BF ₃ MEA. Fibers are Torayca T300A. Temperature range is 290 K to 340 K. From Isikawa, Koyama & Kobayashi (1977, 1978) [106] & [107].	299
Figure 5-24: Linear thermal expansion coefficient measured parallel to fibers, β_1 , as a function of temperature, T , for two nominally identical carbon fiber reinforced composite materials produced on separate occasions and having slightly different fiber volume ratios, φ_f . Fiber: HTSCarbon; Matrix: Fibredex 914C.	300
Figure 5-25: Linear thermal expansion coefficient measured perpendicular to fibers, β_2 , as a function of temperature, T , for two nominally identical carbon fiber reinforced composite materials produced on separate occasions and having slightly different fiber volume ratios, φ_f . Fiber: HTSCarbon; Matrix: Fibredex 914C.	301
Figure 5-26: Linear thermal expansion coefficient measured in 0° direction, β_0 , as a function of temperature, T , for some carbon fiber reinforced composite	

CEN/CLC/TR 17603-31-05:2021 (E)

materials with various amounts of fibers in different directions. Fiber: Courtaulds HTS, Type II; Matrix: Fibredex 914C.	306
Figure 5-27: Linear thermal expansion coefficient, β_0 , of a two-ply ($\pm \theta$) carbon fiber reinforced composite material, measured in direction 0° of the plane of laminate, as a function of the angle ply, θ . Matrix is Hercules 3002, fibers are Hercules HT (Hercules 3002T prepreg). Temperature range is 80 K to 450 K. From Friend, Poesch & Leslie (1972) [90].	308
Figure 5-28: Linear thermal expansion coefficient, β , measured in several directions of the plane of laminate for an unidirectional and an angle plied carbon fiber reinforced composite material, as a function of temperature, T . Matrix is Narmco 5208, fibers are Narmco T300. From Karlsson (1983) [111].	309
Figure 5-29: Linear thermal expansion coefficient measured either parallel, β_1 , or perpendicular, β_2 , to fibers of two composites with similar epoxy matrices, but with carbon fiber or Kevlar 49 reinforcements.	316
Figure 5-30: Linear thermal expansion coefficient measured parallel to fibers, β_1 , as a function of temperature, T , for two graphite fiber-metal and one carbon fiber-epoxy composite materials.	317
Figure 5-31: Linear thermal expansion coefficient measured perpendicular to fibers, β_2 , as a function of temperature, T , for graphite fiber-metal and carbon fiber-epoxy composite materials.	318
Figure 5-32: Normal spectral absorptance, α'_λ , of SiO ₂ Fabric at 310 K vs. wavelength, λ . Sample is described in the text. From Eagles, Babjak & Weaver (1975) [85].	320
Figure 5-33: Normal-hemispherical spectral reflectance, ρ'_λ , of SiO ₂ Fabric vs. wavelength, λ . Sample is described in the text. From Eagles, Babjak & Weaver (1975) [85].	321
Figure 5-34: Solar absorptance, α_s , of SiO ₂ Fabric-Substrate composite as a function of the solar absorptance, α_{ss} , of the substrate. Sample: 16 Harness Satin Weave 0,38x10 ⁻³ m thick, on different substrates. From Eagles, Babjak & Weaver (1975) [85].	322
Figure 5-35: Absorptance/Emissatnce ratio, α_s/ε , solar absorptance, α_s , and hemispherical total emittance, ε , of various mosaics of silica and carbon yarn as functions of the exposed black to total area fraction, A_B/A . From Eagles, Babjak & Weaver (1975) [85].	322
Figure 5-36: Normal spectral emittance, ε'_λ , of PV 100 coating on different substrates and with different thicknesses (see Table 5-67) vs. wavelength, λ , at 393 K. From Giommi, Marchetti, Salza & Testa (1985) [92].	327
Figure 5-37: Normal-hemispherical spectral reflectance factor, R'_λ , of PV 100 coating on different substrates and with different thicknesses vs. wavelength, λ . From Giommi, Marchetti, Salza & Testa (1985) [92].	329
Figure 5-38: Normal total emittance, $\varepsilon'(0)$, of sputtered aluminium on T300/5209 graphite-epoxy composite material as a function of sputtered coating thickness, t_c , and for two different textures of the supporting material. From Witte & Teichman (1989) [166].	332
Figure 5-39: Normal solar absorptance, α_s , of sputtered aluminium on T300/5209 graphite-epoxy composite material as a function of sputtered coating	

thickness, t_c , and for two different textures of the supporting material. From Witte & Teichman (1989) [166].....	333
Figure 5-40: Solar absorptance to emittance ratio of sputtered aluminium on T300/5209 graphite-epoxy composite material as a function of sputtered coating thickness, t_c , and for two different textures of the supporting material. From Witte & Teichman (1989) [166].....	334
Figure 5-41: Tensile strength, σ_t , vs. temperature, T , of structural materials. Inert atmospheres. From DeMario (1985) [81].....	335
Figure 5-42: Electrical resistivity, ρ , as a function of frequency, f , for a carbon-epoxy composite material. Fiber: Super A, Matrix: Fibredux 914C. Layup ($0^\circ \pm 45^\circ$) 16 plies. Sample size: $\bigcirc : > 1,98 \times 10^{-3}$ m, 10×10^{-3} m, 25×10^{-3} m. $\square : > 1,98 \times 10^{-3}$ m, $5,5 \times 10^{-3}$ m, 25×10^{-3} m. From Thomson (1982) [156].....	345
Figure 5-43: One-dimensional and radial models of laminar diffusion through homogeneous-isotropic media.	350
Figure 5-44: Moisture content, M , as a function of ambient temperature, T , after 100 h of exposure to distilled water at that temperature, for several carbon fiber reinforced composites. The specimens are infinitely large rods of 6×10^{-3} m diameter. $M_0 = 0,002$ assumed.....	351
Figure 5-45: Effect of UV radiation on linear thermal expansion, β , of Graphite/epoxy T300/SP 288 laminates. a) $\theta = 90^\circ$, b) $\theta = (\pm 43^\circ)_s$, c) $\theta = 0^\circ$. Ambient pressure 10^{-4} Pa to 10^{-5} Pa. From Tennyson & Zimcik (1982) [107], Hansen & Tennyson (1983) [153].....	361
Figure 5-46: Effect of UV radiation on linear thermal expansion, β , of Kevlar/epoxy 3M SP 306 laminates. a) $\theta = 90^\circ$, b) $\theta = (\pm 43^\circ)_s$, c) $\theta = 0^\circ$. Ambient pressure 10^{-4} Pa to 10^{-5} Pa. From Tennyson & Zimcik (1982) [107] , Hansen & Tennyson (1983) [95].....	361
Figure 5-47: Effect of electron radiation with (thick solid line) and without (thin solid line) UV exposure, on linear thermal expansion, β_0 , of graphite/epoxy and Kevlar/epoxy, $\theta = (\pm 43^\circ)_s$. Ambient pressure 10^{-4} Pa to 10^{-5} Pa. Exposure > 1 year and 300 ESD of UV. From Hansen & Tennyson (1983) [95].....	362
Figure 5-48: Linear thermal expansion, β_0 , as a function of temperature, T , of T50(PAN)/F263 (0/90) _{2s} HM graphite/epoxy laminates exposed to electron radiation. Calculated by the compiler by numerical derivation ($\beta = d(\Delta L/L)/d T$) of data from Mauri & Crossman (1983) [125].	362
Figure 5-49: Graphs for estimating the depletion by atomic oxygen of a material of known Reaction Efficiency, R_e . From Leger & Visentine (1986) [118].....	367
Figure 5-50: Effect of the number of thermal cycles, N , on the linear thermal expansion, β_0 , of $(\pm 22^\circ)_s$ T300/3M SP288 Graphite/Epoxy laminates. $300 \text{ K} \leq T \leq 370 \text{ K}$, $p = 1,33 \times 10^{-4}$ Pa to $1,33 \times 10^{-5}$ Pa. From Tennyson & Zimcik (1982) [154], Hansen & Tennyson (1983) [95].....	375
Figure 5-51: Effect of the number of thermal cycles, N , on the linear thermal expansion, β_0 , of $(\pm 43^\circ)_s$ T300/3M SP288 Graphite/Epoxy laminates. $300 \text{ K} \leq T \leq 370 \text{ K}$, $p = 1,33 \times 10^{-4}$ Pa to $1,33 \times 10^{-5}$ Pa. From Tennyson (1980) [153], Tennyson & Zimcik (1982) [154], Hansen & Tennyson (1983) [95].....	375
Figure 5-52: Effect of the number of thermal vacuum cycles, N , on the linear thermal expansion, β_0 , of $(\pm 0^\circ)_s$ T300/3M SP288 Graphite/Epoxy laminates. $300 \text{ K} \leq T \leq 370 \text{ K}$, $p = 1,33 \times 10^{-4}$ Pa to $1,33 \times 10^{-5}$ Pa. 50 cycles ≈ 220 days in	

CEN/CLC/TR 17603-31-05:2021 (E)

vacuum. From Tennyson & Zimcik (1982) [154], Hansen & Tennyson (1983) [95].....	376
Figure 5-53: Effect of the number of thermal vacuum cycles, N , on the linear thermal expansion, β_0 , of $(\pm \theta^\circ)_s$ 3M SP306 Kevlar/Epoxy laminates. $300 \text{ K} \leq T \leq 370 \text{ K}$, $p = 1,33 \times 10^{-4} \text{ Pa}$ to $1,33 \times 10^{-5} \text{ Pa}$. 50 cycles ≈ 220 days in vacuum. From Tennyson & Zimcik (1982) [154], Hansen & Tennyson (1983) [95].....	376
Figure 5-54: Comparison of predicted (-) and experimental (o) values of the linear thermal expansion, β_0 , vs. fiber angle, θ , for $(\pm \theta^\circ)_s$ 3M SP306 Kevlar/Epoxy laminates. 48 cycles ≈ 220 days in vacuum. $300 \text{ K} \leq T \leq 370 \text{ K}$, $p = 1,33 \times 10^{-4} \text{ Pa}$ to $1,33 \times 10^{-5} \text{ Pa}$. From Tennyson & Zimcik (1982) [171], Hansen & Tennyson (1983) [95]. Results for Graphite/Epoxy are given in Tennyson (1980) [153]. Compare also with Figure 5-27.	377
Figure 5-55: Effect of the number of thermal vacuum cycles, N , on the linear thermal expansion, β_0 , of $(\pm \theta^\circ)_s$ 3M SP290 Boron/Epoxy laminates. $300 \text{ K} \leq T \leq 370 \text{ K}$, $p = 1,33 \times 10^{-4} \text{ Pa}$ to $1,33 \times 10^{-5} \text{ Pa}$. 50 cycles ≈ 220 days in vacuum. From Tennyson & Zimcik (1982) [154], Hansen & Tennyson (1983) [95].....	377
Figure 5-56: Coefficient of the linear thermal expansion, β_0 , as a function of temperature, T , for Graphite/Epoxy circular hybrid tubes, identified as Spec. No. 12 in Table 5-84 and Table 5-85, before (solid line) and after (dashed line) thermal vacuum cycling. 3000 cycles. $98 \text{ K} \leq T \leq 370 \text{ K}$, $p = 1,33 \times 10^{-3} \text{ Pa}$. From Reibaldi (1985) [141].	378
ITel STANDARD REVIEW (standards.iteh.ai)	380
Figure 5-57: Outline of INTELSAT V communication satellite.....	380
Figure 5-58: Sketch of the ARIANE 4 upper part. From Thomas & Oliver (1985) [155].....	382
Figure 5-59: Exploded view of SPELDA. From Thomas & Oliver (1985) [155].....	383
Figure 5-60: Sketch of the CS-3a structure. From Kawashima, Inoue & Seko (1985) [112]. https://standards.iteh.ai/catalog/standards/sist/39655cde-a79d-4350-ab9b-12d8af179954/sist-tp-cen-clc-tr-17603-31-05-2021	384
Figure 5-61: Exploded view of CS-3a Central Thrust Tube. Prepared by the compiler after Kawashima, Inoue & Seko (1985) [112].	385

Tables

Table 4-1: Normal Total Emittance of Aluminium.....	40
Table 4-2: Normal Total Emittance and Normal Solar Absorptance of Aluminium Contact Coatings.....	42
Table 4-3: Normal Total Emittance and Normal Solar Absorptance of Aluminium Conversion Coatings.....	44
Table 4-4: Hemispherical Total Emittance of Aluminium Contact Coatings.....	47
Table 4-5: Hemispherical total Absorptance of Aluminium.....	55
Table 4-6: Normal Solar Absorptance of Aluminium	57
Table 4-7: Normal Solar Absorptance of Aluminium Conversion Coatings.....	58
Table 4-8: Angular Solar absorptance of Aluminium.....	60
Table 4-9: Normal-Normal Solar Reflectance of Aluminium Conversion Coatings	78
Table 4-10: Normal-Hemispherical Solar Reflectance of Both Bulk Aluminium and Contact Coatings.....	79
Table 4-11: Normal Total Emittance of Al – 4,3 Cu – 1,5 Mg – 0,6 Mn, Anodized	95

Table 4-12: Hemispherical Total Emittance of Al – 4,3 Cu – 1,5 Mg – 0,6 Mn	95
Table 4-13: Normal Solar Absorptance of Al – 4,3 Cu – 1,5 Mg – 0,6 Mn	96
Table 4-14: Normal Solar Absorptance of Al – 4,3 Cu – 1,5 Mg – 0,6 Mn, Anodized	97
Table 4-15: Normal Hemispherical Solar Reflectance of Al – 4,3 Cu – 1,5 Mg – 0,6 Mn, Anodized	102
Table 4-16: Normal Total Emittance of Al – 1 Mg – 0,6 Si	105
Table 4-17: Hemispherical Total Emittance of Al – 1 Mg – 0,6 Si	106
Table 4-18: Normal Solar Absorptance of Al – 1 Mg – 0,6 Si	107
Table 4-19: Hemispherical Total Emittance of Al – 5,7 Zn – 2,5 Mg – 1,6 Cu Conversion Coatings	124
Table 4-20: Normal Solar Absorptance and Normal-Hemispherical Solar Reflectance of Al – 5,6 Zn – 2,5 Mg 1,6 Cu	125
Table 4-21: Normal Solar Absorptance of Ti – 5 Al – 2,5 Sn	139
Table 4-22: Normal Solar Absorptance of Ti – Al – 4 V	161
Table 4-23: Cost of Ti – 6 Al – 4 – V compared with those of other structural metallic materials	164
Table 4-24: Electrical Resistivity of Ni – 19Cr – 11Co – 10Mo – 3Ti ^a	173
Table 4-25: Linear thermal expansion coefficient of Fe – 36 Ni under different temper conditions	178
Table 4-26: Magnetic Properties of Fe – 36 Ni under different temper conditions	180
Table 4-27: Relative Permeability of Fe – 36 Ni, measured at 400 A.m ⁻¹	180
Table 5-1: Abridged Designation of Single Reinforcement Laminates <small>https://standards.teh.ai/catalog/standards/sist/39635cd6-a/79d-4350-ab9b-1318a379034/standard/sist-17603-31-05-2021</small>	208
Table 5-2: Density, ρ_f [kg.m ⁻³], of High-Strength Fibers	210
Table 5-3: Density, ρ_m [kg.m ⁻³], of Matrices	215
Table 5-4: Specific Heat, c_f [J.kg ⁻¹ .K ⁻¹], of High-Strength Fibers	217
Table 5-5: Fussed Silicia	218
Table 5-6: Kevlar ^d	219
Table 5-7: Specific Heat, c_m [J.kg ⁻¹ .K ⁻¹], of Matrices	220
Table 5-8: Specific Heat, c [J.kg ⁻¹ .K ⁻¹], of Composite Materials	221
Table 5-9: Longitudinal (1) and Transverse (2) Thermal Conductivity, of High-Strength Fibers. Tabulated Data are k_{f1} [W.m ⁻¹ .K ⁻¹]/ k_{f2} [W.m ⁻¹ .K ⁻¹], of Fibers	226
Table 5-10: Thermal Conductivity, k_m [W.m ⁻¹ .K ⁻¹], of Matrices	228
Table 5-11: Araldite LY556	229
Table 5-12: DER 332/T403 (100:36) ^c	229
Table 5-13: Epitoke 210/BF ₃ 400 ^b	230
Table 5-14: Epoxin 162 ^a	230
Table 5-15: Palatal P51 ^a	231
Table 5-16: Nylon 6 ^a	232
Table 5-17: Comco, Nylon 6/6 ^{g,h}	233