INTERNATIONAL STANDARD

ISO 15645

Second edition 2018-09

Road construction and maintenance equipment — Road milling machinery — Terminology and commercial specifications

Équipement pour la construction et l'entretien des routes — Fraiseuses — Terminologie et spécifications commerciales

(https://standards.iteh.ai)
Document Preview

ISO 15645:2018

https://standards.iteh.ai/catalog/standards/iso/ed0de47f-58cf-47d5-914f-2454778h9ee0/iso-15645-2018



iTeh Standards (https://standards.iteh.ai) Document Preview

ISO 15645:2018

https://standards.iteh.ai/catalog/standards/iso/ed0de4/f-58ct-4/d5-914f-2454//8b9ee0/iso-15645-2018



COPYRIGHT PROTECTED DOCUMENT

© ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Fax: +41 22 749 09 47 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Con	tent	S	Page
Forev	vord		iv
Intro	ductio	n	v
1	Scon	e	1
2	-	native references	
_			
3	Term	is and definitions	1
4	Desc 4.1	ription of milling machine components General	
	4.2	Design of milling machine types	2
		4.2.1 Traction and transport system	
		4.2.2 Cutting and milling system	
		4.2.3 Rotor drive methods	
		4.2.4 Layout of tools	
		4.2.5 System for levelling and control of working depth	2
		4.2.6 System to remove or windrow aggregate materials	3
5		mercial specifications	
	5.1	Characteristics of the traction and transport vehicle	3
		5.1.1 Dimensional characteristics	
		5.1.2 Shipping dimensions (overall)	3
		5.1.3 Mass characteristics	3
		5.1.4 Engine characteristics	
		5.1.5 Transmission characteristics	
		5.1.6 Position of steering	4
		5.1.7 Characteristics and type of tyres or tracks	4
	5.2	5.1.8 Tank characteristics Cutting and milling system characteristics	
	5.2	Drum sprinkler device	
	5.3 5.4	System to remove or windrow aggregate materials	
Anne		formative) Examples of road milling machine designs and their assemblies	
	oranh		12

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 195, *Building construction machinery and equipment*.

This second edition cancels and replaces the first edition (ISO 15645:2002), of which it constitutes a minor revision. It also incorporates the Amendment ISO 15645:2002/Amd 1:2013. The changes compared to the previous edition are as follows:

- Clause 2 has been added according to the ISO/IEC Directives, Part 2;
- in 4.2.1, the reference to Figure A.2 has been deleted;
- Figure A.2 has been updated; a key reference and a note to figure have been added.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at https://www.iso.org/members.html.

Introduction

This document deals with road milling machinery used in the retread process, which is carried out in road maintenance.

It provides definitions of the milling machine itself and its components, and technical characteristics.

It includes figures showing milling machines with a loading device and the positioning of work tools in a rotor.

iTeh Standards (https://standards.iteh.ai) Document Preview

ISO 15645:2018

https://standards.iteh.ai/catalog/standards/iso/ed0de47f-58cf-47d5-914f-2454778h9ee0/iso-15645-2018

iTeh Standards (https://standards.iteh.ai) Document Preview

ISO 15645:2018

https://standards.iteh.ai/catalog/standards/iso/ed0de47f-58cf-47d5-914f-2454778b9ee0/iso-15645-2018

Road construction and maintenance equipment — Road milling machinery — Terminology and commercial specifications

1 Scope

This document establishes the terminology, functions, types and characteristics of road milling machinery.

It is applicable to the planing of pavements made of concrete, asphalt and similar materials with a view to removing them.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at https://www.iso.org/obp
- IEC Electropedia: available at http://www.electropedia.org/

3.1

road milling machinery

mobile road construction machine used to remove materials from paved surfaces by a milling action

3.2

road milling carrier

machine carrying all the systems constituting the road milling machine and distributing the necessary power to operate the different devices and to ensure movement during work and transfer

3.3

cutting and milling system

power-driven cylindrical bodies on which the milling tools are fitted

Note 1 to entry: The cylindrical bodies rotate during the milling operation. The tools are mostly cooled by a water sprinkler device.

3.4

levelling system

automatic or manual system used to obtain and maintain the geometry of the bottom of the cut

Note 1 to entry: The geometry of the bottom refers to both the longitudinal and cross-sections. The geometrical reference is taken from the existing section or from a specific layout.

3.5

system to remove or windrow aggregate material

transport system for the removal and storage of loose material

Note 1 to entry: The material is removed by either a front-, rear- or side-loading system, or is deposited as a windrow at the side or the back of the road milling machine.

ISO 15645:2018(E)

3.6

operating mass

mass of the base machine with all standard equipment, with or without the cab, with or without ROPS, etc., with the operator (75 kg) and full fuel tank, and all fluid systems at their rated capacities and, when applicable, with the sprinkler water tank half full

4 Description of milling machine components

4.1 General

The machine is usually equipped with all the following devices:

- a traction and transport system;
- a cutting and milling system;
- a levelling system;
- a system to remove or windrow aggregate material.

4.2 Design of milling machine types

4.2.1 Traction and transport system

The description shall include the type of the ground drive system (wheels, tracks, etc.), the total number and position of wheels or tracks, the number and position of drive wheels or tracks, and the number and position of guiding wheels or tracks. The position of the rotor in relation to the wheels or tracks and the loading device is shown in Figure A.1.

4.2.2 Cutting and milling system

The cutting and milling system comprises a rotor chamber and a drum sprinkler device (see Figure A.3).

https://standards.iteh.ai/catalog/standards/iso/ed0de47f-58cf-47d5-914f-2454778b9ee0/iso-15645-201

ocument Preview

4.2.3 Rotor drive methods

These may be

- hydraulic,
- hydromechanical, or
- mechanical (right and/or left),

or may depend on the direction of rotation of the rotor in relation to the direction of movement.

4.2.4 Layout of tools

The layout of tools on the rotor is application specific and is determined by the distance between two successive steps in the cross-section (Figure A.2).

4.2.5 System for levelling and control of working depth

The following characteristics shall be given:

- level reference (ground, machine element, cord or others);
- type of sensors (laser, ultrasound, electronic or hydraulic);
- adjustment;

- manual;
- automatic.

4.2.6 System to remove or windrow aggregate materials

The description shall include the types of conveyors, their drives and the methods of positioning.

Commercial specifications

5.1 Characteristics of the traction and transport vehicle

5.1.1 **Dimensional characteristics**

The dimensions shown in <u>Figure A.1</u> shall be specified:

- overall length with the removal system (mm);
- overall length without the removal system (mm);
- overall width in the working order (without the removal system) (mm);
- overall height (without the removal system) (mm);
- maximum front overhang (with the removal system) (mm);
- rear overhang (mm);
- inside turning radius (mm);
- outside turning radius (mm);
- distance between the rotor axis and the front wheels/tracks axis (mm);
- distance between the rotor axis and the rear wheels/tracks axis (mm); 159ee0/iso-15645-2018
 - inside slewing radius of the rotor (mm);
 - outside slewing radius of the rotor (mm);
 - maximum loading height (mm);
 - slewing angle of the removal system (degrees);
 - side-shift of the rotor to the chassis (for machines with side-shifted rotor) (mm).

5.1.2 **Shipping dimensions (overall)**

The following dimensions shall be specified:

- length (mm);
- width (mm);
- height (mm).

5.1.3 Mass characteristics

The following characteristics shall be given:

load shipping mass (kg);

ISO 15645:2018(E)

 operating mass (kg) (see <u>3.6</u> for conditions);
— other masses (all in kg);
on the front axle;
— on the rear axle;
— cab;
 protective structure;
 pumping and liquid adding device.
5.1.4 Engine characteristics
The following characteristics shall be given:
 engine brand and type;
— rated power (kW);
NOTE See ISO 14396 for guidance.
— revolutions (r/min);
 cooling type. iTeh Standards
5.1.5 Transmission characteristics://standards.iteh.ai
The following characteristics shall be given:
The following characteristics shall be given:
The following characteristics shall be given: — number of tracks or wheels; number of driving aylas:
The following characteristics shall be given: — number of tracks or wheels; — number of driving axles; ISO 15645:2018
The following characteristics shall be given: — number of tracks or wheels; — number of driving axles; — mechanical transmission; log/standards/iso/ed0de47f-58cf-47d5-914f-2454778b9ee0/iso-15645-2018
The following characteristics shall be given: — number of tracks or wheels; — number of driving axles; — mechanical transmission; log/standards/iso/ed0de47f-58cf-47d5-914f-2454778b9ee0/iso-15645-2018 — maximum working speed (km/h);
The following characteristics shall be given: — number of tracks or wheels; — number of driving axles; — mechanical transmission; log/standards/iso/ed0de47f-58cf-47d5-914f-2454778b9ee0/iso-15645-2018 — maximum working speed (km/h); — maximum transfer speed (km/h).
The following characteristics shall be given: — number of tracks or wheels; — number of driving axles; — mechanical transmission; log/standards/iso/ed0de47f-58cf-47d5-914f-2454778b9ee0/iso-15645-2018 — maximum working speed (km/h); — maximum transfer speed (km/h). 5.1.6 Position of steering
The following characteristics shall be given: — number of tracks or wheels; — number of driving axles; — mechanical transmission; log/standards/iso/ed0de47f-58cf-47d5-914f-2454778b9ee0/iso-15645-2018 — maximum working speed (km/h); — maximum transfer speed (km/h). 5.1.6 Position of steering This shall be specified as
The following characteristics shall be given: — number of tracks or wheels; — number of driving axles; — mechanical transmission; log/standards/iso/ed0de47f-58cf-47d5-914f-2454778b9ee0/iso-15645-2018 — maximum working speed (km/h); — maximum transfer speed (km/h). 5.1.6 Position of steering This shall be specified as — front,
The following characteristics shall be given: — number of tracks or wheels; — number of driving axles; — mechanical transmission; log/standards/iso/ed0de47f-58ef-47d5-914f-2454778b9ee0/iso-15645-2018 — maximum working speed (km/h); — maximum transfer speed (km/h). 5.1.6 Position of steering This shall be specified as — front, — rear, or
The following characteristics shall be given: — number of tracks or wheels; — number of driving axles; — mechanical transmission; log/standards/iso/ed0de47£58c£47d5-914£2454778b9ee0/iso-15645-2018 — maximum working speed (km/h); — maximum transfer speed (km/h). 5.1.6 Position of steering This shall be specified as — front, — rear, or — both.
The following characteristics shall be given: — number of tracks or wheels; — number of driving axles; — mechanical transmission; log/standards/iso/ed0de47f-58cf-47d5-914f-2454778b9ee0/iso-15645-2018 — maximum working speed (km/h); — maximum transfer speed (km/h). 5.1.6 Position of steering This shall be specified as — front, — rear, or — both. 5.1.7 Characteristics and type of tyres or tracks