
**Information technology — Open
Systems Interconnection — The
Directory —**

**Part 6:
Selected attribute types**

*Technologies de l'information — Interconnexion de systèmes ouverts
(OSI) — L'annuaire —*

Partie 6: Types d'attributs sélectionnés

Document Preview

ISO/IEC 9594-6:2017

<https://standards.iteh.ai/catalog/standards/iso/7ad36967-0ed3-475a-ad93-5023789b61d2/iso-iec-9594-6-2017>



iTeh Standards
(<https://standards.itih.ai>)
Document Preview

ISO/IEC 9594-6:2017

<https://standards.itih.ai/catalog/standards/iso/7ad36967-0ed3-475a-ad93-5023789b61d2/iso-iec-9594-6-2017>



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This eighth edition cancels and replaces the seventh edition (ISO/IEC 9594-6:2014), which has been technically revised.

This document was prepared by ISO/IEC JTC 1, *Information technology*, SC 6, *Telecommunications and information exchange between systems*, in collaboration with ITU-T. The identical text is published as ITU-T X.520 (10/2016).

A list of all parts in the ISO/IEC 9594 series, published under the general title *Information technology — Open Systems Interconnection — The Directory*, can be found on the ISO website.

CONTENTS

Page

1	Scope	1
2	Normative references.....	1
	2.1 Identical Recommendations International Standards	1
	2.2 Other references	2
	2.3 ISO/IEC Standards	3
3	Definitions	3
4	Abbreviations	3
5	Conventions	3
6	Definition of selected attribute types	5
	6.1 System attribute types	5
	6.2 Labelling attribute types.....	5
	6.3 Geographical attribute types.....	9
	6.4 Organizational attribute types	11
	6.5 Explanatory attribute types.....	12
	6.6 Postal addressing attribute types	14
	6.7 Telecommunications addressing attribute types.....	16
	6.8 Preferences attribute types	19
	6.9 OSI application attribute types	20
	6.10 Relational attribute types.....	20
	6.11 Domain attribute types	22
	6.12 Hierarchical attribute types	22
	6.13 Attributes for applications using tag-based identification	23
	6.14 Simple Authentication attributes held by object entries	26
	6.15 Password policy attributes.....	29
	6.16 Notification attributes.....	33
	6.17 LDAP defined attribute types.....	37
7	String preparation	39
	7.1 Transcode	39
	7.2 Map	39
	7.3 Normalize.....	39
	7.4 Prohibit.....	39
	7.5 Check bidi	40
	7.6 Insignificant Character Removal.....	40
8	Definition of matching rules.....	40
	8.1 String matching rules	40
	8.2 Syntax-based matching rules.....	43
	8.3 Time matching rules.....	46
	8.4 First component matching rules	47
	8.5 Word matching rules	48
	8.6 Approximate Matching Rules	51
	8.7 Special Matching Rules.....	51
	8.8 Zonal Match	51
	8.9 Identity matching rules.....	54
	8.10 Password policy matching rules.....	55
	8.11 LDAP defined matching rules.....	56
9	Definition of syntaxes.....	57
	9.1 Directory syntaxes.....	57
	9.2 IETF syntaxes.....	58
10	Definition of Context Types	64
	10.1 Language Context	64
	10.2 Temporal Context.....	64

	<i>Page</i>
10.3 Locale Context	68
10.4 LDAP Attribute Option Context	68
Annex A – Selected attribute types in ASN.1	69
Annex B – Attribute types for password policy in ASN.1	99
Annex C – Upper bounds	105
Annex D – Alphabetical index of attributes, matching rules and contexts	106
Annex E – Examples for zonal match matching rules	108
Annex F – Mapping Object Identifiers and Uniform Resource Names into Distinguished Names.....	110
F.1 Scope of this annex	110
F.2 Object identifier resolution.....	110
F.3 Uniform Resource Name (URN) resolution.....	111
Annex G – Object identifier based Directory names	114
G.1 Scope of this annex	114
G.2 Transformation of object identifiers into Directory names	114
G.3 The use of object-identifier-based Directory names.....	114
Annex H – Amendments and corrigenda.....	116

iTeh Standards

(<https://standards.iteh.ai>)

Document Preview

[ISO/IEC 9594-6:2017](https://standards.iteh.ai/catalog/standards/iso/7ad36967-0ed3-475a-ad93-5023789b61d2/iso-iec-9594-6-2017)

<https://standards.iteh.ai/catalog/standards/iso/7ad36967-0ed3-475a-ad93-5023789b61d2/iso-iec-9594-6-2017>

Introduction

This Recommendation | International Standard, together with other Recommendations | International Standards, has been produced to facilitate the interconnection of information processing systems to provide directory services. A set of such systems, together with the directory information that they hold, can be viewed as an integrated whole, called the *Directory*. The information held by the Directory, collectively known as the Directory Information Base (DIB), is typically used to facilitate communication between, with or about objects such as application entities, people, terminals, and distribution lists.

The Directory plays a significant role in Open Systems Interconnection, whose aim is to allow, with a minimum of technical agreement outside of the interconnection standards themselves, the interconnection of information processing systems:

- from different manufacturers;
- under different managements;
- of different levels of complexity; and
- of different ages.

This Recommendation | International Standard defines a number of attribute types which may be found useful across a range of applications of the Directory, as well as a number of standard attribute syntaxes and matching rules. One particular use for many of the attributes defined herein is in the formation of names, particularly for the classes of objects defined in Rec. ITU-T X.521 | ISO/IEC 9594-7.

This Recommendation | International Standard provides the foundation frameworks upon which industry profiles can be defined by other standards groups and industry forums. Many of the features defined as optional in these frameworks may be mandated for use in certain environments through profiles. This eighth edition technically revises and enhances the seventh edition of this Recommendation | International Standard.

This eighth edition specifies versions 1 and 2 of the Directory protocols.

The first and second editions specified only version 1. Most of the services and protocols specified in this edition are designed to function under version 1. However some enhanced services and protocols, e.g., signed errors, will not function unless all Directory entities involved in the operation have negotiated version 2. Whichever version has been negotiated, differences between the services and between the protocols defined in the eight editions, except for those specifically assigned to version 2, are accommodated using the rules of extensibility defined in Rec. ITU-T X.519 | ISO/IEC 9594-5.

Annex A, which is an integral part of this Recommendation | International Standard, provides the ASN.1 notation for the complete module which defines the attributes, attribute syntaxes and matching rules.

Annex C, which is not an integral part of this Recommendation | International Standard, provides a table of attribute types, for easy reference.

Annex D, which is not an integral part of this Recommendation | International Standard, provides an example of upper bounds value constraints. These constraints are not reflected in these Directory Specifications, but are provided as a reference for those implementations applying these constraints.

Annex E, which is not an integral part of this Recommendation | International Standard, lists alphabetically the attributes and matching rules defined in this Directory Specification.

Annex F, which is not an integral part of this Recommendation | International Standard, gives examples relevant to the definition of zonal matching.

Annex G, which is not an integral part of this Recommendation | International Standard, describes how a directory distinguished name may be based on object identifiers and on Uniform Resource Names (URNs).

Annex H, which is not an integral part of this Recommendation | International Standard, describes an alternative way of generating directory distinguished based on object identifiers. It contains information retrieved from Rec. ITU-T X.660 | ISO/IEC 9834-1.

Annex I, which is not an integral part of this Recommendation | International Standard, lists the amendments and defect reports that have been incorporated to form this edition of this Recommendation | International Standard.

**INTERNATIONAL STANDARD
ITU-T RECOMMENDATION**

**Information technology – Open Systems Interconnection –
The Directory: Selected attribute types**

SECTION 1 – GENERAL

1 Scope

This Recommendation | International Standard defines a number of attribute types and matching rules which may be found useful across a range of applications of the Directory.

Attribute types and matching rules fall into three categories, as described below.

Some attribute types and matching rules are used by a wide variety of applications or are understood and/or used by the Directory itself.

NOTE 1 – It is recommended that an attribute type or matching rule defined in this Recommendation | International Standard be used, in preference to the generation of a new one, whenever it is appropriate for the application.

NOTE 2 – The attribute and context types definitions by this Recommendation | International Standard have some associated semantics. Such specifications should not be used in situations where these semantics do not apply.

Some attribute types and matching rules are internationally standardized, but are application-specific. These are defined in the standards associated with the application concerned.

Any administrative authority can define its own attribute types and matching rules for any purpose. These are not internationally standardized, and are available to others beyond the administrative authority which created them only through bilateral agreement.

2 Normative references

The following Recommendations and International Standards contain provisions which, through reference in this text, constitute provisions of this Recommendation | International Standard. At the time of publication, the editions indicated were valid. All Recommendations and Standards are subject to revision, and parties to agreements based on this Recommendation | International Standard are encouraged to investigate the possibility of applying the most recent edition of the Recommendations and Standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards. The Telecommunication Standardization Bureau of the ITU maintains a list of currently valid ITU-T Recommendations.

2.1 Identical Recommendations | International Standards

- Recommendation ITU-T X.500 (2016) | ISO/IEC 9594-1:2017, *Information technology – Open Systems Interconnection – The Directory: Overview of concepts, models and services.*
- Recommendation ITU-T X.501 (2016) | ISO/IEC 9594-2:2017, *Information technology – Open Systems Interconnection – The Directory: Models.*
- Recommendation ITU-T X.509 (2016) | ISO/IEC 9594-8:2017, *Information technology – Open Systems Interconnection – The Directory: Public-key and attribute certificate frameworks.*
- Recommendation ITU-T X.511 (2016) | ISO/IEC 9594-3:2017, *Information technology – Open Systems Interconnection – The Directory: Abstract service definition.*
- Recommendation ITU-T X.518 (2016) | ISO/IEC 9594-4:2017, *Information technology – Open Systems Interconnection – The Directory: Procedures for distributed operation.*
- Recommendation ITU-T X.519 (2016) | ISO/IEC 9594-5:2017, *Information technology – Open Systems Interconnection – The Directory: Protocol specifications.*
- Recommendation ITU-T X.521 (2016) | ISO/IEC 9594-7:2017, *Information technology – Open Systems Interconnection – The Directory: Selected object classes.*
- Recommendation ITU-T X.525 (2016) | ISO/IEC 9594-9:2017, *Information technology – Open Systems Interconnection – The Directory: Replication.*

- Recommendation ITU-T X.530 (2001) | ISO/IEC 9594-10:2001, *Information technology – Open Systems Interconnection – The Directory: Use of systems management for administration of the Directory*.
- Recommendation ITU-T X.660 (2008) | ISO/IEC 9834-1:2008, *Information technology – Open Systems Interconnection – Procedures for the operation of OSI Registration Authorities: General procedures and top arcs of the International Object Identifier tree*.
- Recommendation ITU-T X.667 (2008) | ISO/IEC 9834-8:2008, *Information technology – Open Systems Interconnection – Procedures for the operation of OSI Registration Authorities: Generation and registration of Universally Unique Identifiers (UUIDs) and their use as ASN.1 object identifier components*.
- Recommendation ITU-T X.668 (2008) | ISO/IEC 9834-9:2008, *Information technology – Open Systems Interconnection – Procedures for the operation of OSI Registration Authorities: Registration of object identifier arcs for applications and services using tag-based identification*.
- Recommendation ITU-T X.680 (2015) | ISO/IEC 8824-1:2015, *Information technology – Abstract Syntax Notation One (ASN.1): Specification of basic notation*.

2.2 Other references

- Recommendation ITU-T E.123 (2001), *Notation for national and international telephone numbers, e-mail addresses and web addresses*.
- Recommendation ITU-T E.164 (2005), *The international public telecommunication numbering plan*.
- Recommendation ITU-T F.1 (1998), *Operational provisions for the international public telegram service*.
- Recommendation CCITT F.31 (1988), *Telegram retransmission system*.
- Recommendation CCITT F.401 (1992), *Message handling services: Naming and addressing for public message handling services*.
- Recommendation ITU-T T.30 (2005), *Procedures for document facsimile transmission in the general switched telephone network*.
- Recommendation ITU-T T.51 (1992), *Latin based coded character sets for telematic services*.
- Recommendation ITU-T T.62 (1993), *Control procedures for teletex and Group 4 facsimile services*.
- Recommendation ITU-T X.121 (2000), *International numbering plan for public data networks*.
- ISO 3166-1:2006, *Codes for the representation of names of countries and their subdivisions – Part 1: Country codes*.
- ISO 3166-3:1999, *Codes for the representation of names of countries and their subdivisions – Part 3: Code for formerly used names of countries*.
- ISO 639-2:1998, *Codes for the representation of names of languages – Part 2: Alpha-3 code*.
- ISO/IEC/IEEE 9945:2009, *Information technology – Portable Operating System Interface (POSIX) – Base Specifications, Issue 7*.
- ISO/IEC 15897:2001, *Information technology – User interfaces – Procedures for the registration of cultural elements*.
- IETF RFC 3406 (2002), *Uniform Resource Names (URN) Namespace Definition Mechanisms*.
- IETF RFC 3454 (2003), *Preparation of Internationalized Strings ("stringprep")*.
- IETF RFC 3492 (2003), *Punycode: A Bootstring encoding of Unicode for Internationalized Domain Names in Applications (IDNA)*.
- IETF RFC 3641 (2003), *Generic String Encoding Rules (GSER) for ASN.1 Types*.
- IETF RFC 3642 (2003), *Common Elements of Generic String Encoding Rules (GSER) Encodings*.
- IETF RFC 3672 (2003), *Subentries in the Lightweight Directory Access Protocol (LDAP)*.
- IETF RFC 3986 (2005), *Uniform Resource Identifier (URI): Generic Syntax*.
- IETF RFC 4512 (2006), *Lightweight Directory Access Protocol (LDAP): Directory Information Models*.
- IETF RFC 4514 (2006), *Lightweight Directory Access Protocol (LDAP): String Representation of Distinguished Names*.
- IETF RFC 4517 (2006), *Lightweight Directory Access Protocol (LDAP): Syntaxes and Matching Rules*.
- IETF RFC 4520 (2006), *Internet Assigned Numbers Authority (IANA) Considerations for the Lightweight Directory Access Protocol (LDAP)*.

- IETF RFC 4792 (2007), *Encoding Instructions for the Generic String Encoding Rules (GSER)*.
- IETF RFC 5890 (2010), *Internationalized Domain Names for Applications (IDNA): Definitions and Document Framework*.
- IETF RFC 5892 (2010), *The Unicode Code Points and Internationalized Domain Names for Applications (IDNA)*.
- National Imagery and Mapping Agency (NIMA): TR 8350.2, DoD Word Geodetic System 1984.
- The Unicode Consortium. *The Unicode Standard, Version 4.0.0*, defined by: *The Unicode Standard, Version 4.0* (Reading, MA, Addison-Wesley, 2003. ISBN 0-321-18578-1).
- *Unicode Standard Annex #15: Unicode Normalization Forms*, by Mark Davis and Martin Dürst. An integral part of *The Unicode Standard, Version 4.0*.

2.3 ISO/IEC Standards

- ISO/IEC 10646:2012, *Information technology – Universal Coded Character Set (UCS)*.

3 Definitions

For the purposes of this Recommendation | International Standard, the following definitions apply:

The following terms are defined in Rec. ITU-T X.501 | ISO/IEC 9594-2:

- a) *attribute type*;
- b) *context*;
- c) *matching rule*;
- d) *object class*.

4 Abbreviations

For the purposes of this Recommendation | International Standard, the following abbreviations apply:

AFI	Application Family Identifier
EPC	Electronic Product Code
FQDN	Fully-Qualified Domain Name
GSER	Generic String Encoding Rules
IDN	Internationalized Domain Name
LDAP	Lightweight Directory Access Protocol
LDH	Letters, Digits, Hyphen
RFID	Radio Frequency Identification
RDN	Relative Distinguished Name
UII	Unique Item Identifier
URL	Uniform Resource Locator
URN	Uniform Resource Name
UTM	Universal Transverse Mercator
UUID	Universally Unique Identifier

5 Conventions

The term "Directory Specification" (as in "this Directory Specification") shall be taken to mean Rec. ITU-T X.520 | ISO/IEC 9594-6. The term "Directory Specifications" shall be taken to mean the X.500-series Recommendations and all parts of ISO/IEC 9594.

This Directory Specification uses the term *first edition systems* to refer to systems conforming to the first edition of the Directory Specifications, i.e., the 1988 edition of the series of CCITT X.500 Recommendations and the ISO/IEC 9594:1990 edition.

This Directory Specification uses the term *second edition systems* to refer to systems conforming to the second edition of the Directory Specifications, i.e., the 1993 edition of the series of ITU-T X.500 Recommendations and the ISO/IEC 9594:1995 edition.

This Directory Specification uses the term *third edition systems* to refer to systems conforming to the third edition of the Directory Specifications, i.e., the 1997 edition of the series of ITU-T X.500 Recommendations and the ISO/IEC 9594:1998 edition.

This Directory Specification uses the term *fourth edition systems* to refer to systems conforming to the fourth edition of the Directory Specifications, i.e., the 2001 editions of Recs ITU-T X.500, X.501, X.511, X.518, X.519, X.520, X.521, X.525, and X.530, the 2000 edition of Rec. ITU-T X.509, and parts 1-10 of the ISO/IEC 9594:2001 edition.

This Directory Specification uses the term *fifth edition systems* to refer to systems conforming to the fifth edition of the Directory Specifications, i.e., the 2005 edition of the series of ITU-T X.500 Recommendations and the ISO/IEC 9594:2005 edition.

This Directory Specification uses the term *sixth edition systems* to refer to systems conforming to the sixth edition of the Directory Specifications, i.e., the 2008 edition of the series of ITU-T X.500 Recommendations and the ISO/IEC 9594:2008 edition.

This Directory Specification uses the term *seventh edition systems* to refer to systems conforming to the seventh edition of these Directory Specifications, i.e., the 2012 edition of the series of ITU-T X.500 Recommendations and the ISO/IEC 9594:2014 edition.

This Directory Specification uses the term *eighth edition systems* to refer to systems conforming to the eighth edition of these Directory Specifications, i.e., the 2016 edition of the series of ITU-T X.500 Recommendations and the ISO/IEC 9594:2017 edition.

This Directory Specification presents ASN.1 notation in the bold Courier New typeface. When ASN.1 types and values are referenced in normal text, they are differentiated from normal text by presenting them in the bold Courier New typeface. The names of procedures, typically referenced when specifying the semantics of processing, are differentiated from normal text by displaying them in bold Times New Roman. Access control permissions are presented in italicized Times New Roman.

If the items in a list are numbered (as opposed to using "-" or letters), then the items shall be considered steps in a procedure.

Attribute types, matching rules and context types are defined in this Recommendation | International Standard by use of the **ATTRIBUTE**, **MATCHING-RULE** and **CONTEXT** information object classes defined in Rec. ITU-T X.501 | ISO/IEC 9594-2.

Examples of the use of the attribute types are described using an informal notation, where attribute type and value pairs are represented by an acronym for the attribute type, followed by an equals sign ("="), followed by the example value for the attribute.

SECTION 2 – SELECTED ATTRIBUTE TYPES

6 Definition of selected attribute types

This Directory Specification defines a number of attribute types which may be found useful across a range of applications of the Directory.

Many of the attribute types defined in this Directory Specification are based on a common ASN.1 syntax:

```
UnboundedDirectoryString ::= CHOICE {
    teletexString      TeletexString(SIZE (1..MAX)),
    printableString    PrintableString(SIZE (1..MAX)),
    bmpString          BMPString(SIZE (1..MAX)),
    universalString    UniversalString(SIZE (1..MAX)),
    UTF8String         UTF8String(SIZE (1..MAX)) }
```

A few attribute types are based on the following data type:

```
DirectoryString{INTEGER: maxSize} ::= CHOICE {
    teletexString      TeletexString(SIZE (1..maxSize,...)),
    printableString    PrintableString(SIZE (1..maxSize,...)),
    bmpString          BMPString(SIZE (1..maxSize,...)),
    universalString    UniversalString(SIZE (1..maxSize,...)),
    UTF8String         UTF8String(SIZE (1..maxSize,...)) }
```

NOTE 1 – The above syntaxes are also used in other parts of these Directory Specifications.

NOTE 2 – The use of **TeletexString** is deprecated.

6.1 System attribute types

6.1.1 Knowledge Information

The *Knowledge Information* attribute type specifies a human readable accumulated description of knowledge mastered by a specific DSA.

NOTE – This attribute is now obsolete.

```
knowledgeInformation ATTRIBUTE ::= {
    WITH SYNTAX                UnboundedDirectoryString
    EQUALITY MATCHING RULE     caseIgnoreMatch
    OBSOLETE                    TRUE
    ID                          id-at-knowledgeInformation }
```

6.2 Labelling attribute types

These attributes type are concerned with information about objects which has been explicitly associated with the objects by a labelling process.

6.2.1 Name

The **name** attribute type is the attribute supertype from which string attribute types typically used for naming may be formed.

```
name ATTRIBUTE ::= {
    WITH SYNTAX                UnboundedDirectoryString
    EQUALITY MATCHING RULE     caseIgnoreMatch
    SUBSTRINGS MATCHING RULE   caseIgnoreSubstringsMatch
    LDAP-SYNTAX                directoryString.&id
    LDAP-NAME                   {"name"}
    ID                          id-at-name }
```

6.2.2 Common Name

An attribute of the type **commonName** specifies an identification of an object. A Common Name is not a directory name in itself; it is a (possibly ambiguous) name by which the object is commonly known in some limited scope (such as an organization) and conforms to the naming conventions of the country or culture with which it is associated.

An attribute value for Common Name is a string chosen by either the person or organization it describes or the organization responsible for the object it describes for devices and application entities. For example, a typical name of a

person in an English-speaking country comprises a personal title (e.g., Mr., Ms., Rd, Professor, Sir, Lord), a first name, middle name(s), last name, generation qualifier (if any, e.g., Jr.) and decorations and awards (if any, e.g., QC).

Examples

CN = "Mr. Robin Lachlan McLeod BSc(Hons) CEng MIEE";

CN = "Divisional Coordination Committee";

CN = "High Speed Modem".

Any variants should be associated with the named object as separate and alternative attribute values.

Other common variants should also be admitted, e.g., use of a middle name as a preferred first name; use of "Bill" in place of "William", etc.

```
commonName ATTRIBUTE ::= {
  SUBTYPE OF          name
  WITH SYNTAX          UnboundedDirectoryString
  LDAP-SYNTAX          directoryString.&id
  LDAP-NAME            {"cn", "commonName"}
  ID                   id-at-commonName }
```

6.2.3 Surname

An attribute of the type **surname** specifies the linguistic construct which normally is inherited by an individual from the individual's parent or assumed by marriage, and by which the individual is commonly known.

An attribute value for Surname is a string, e.g., "McLeod".

```
surname ATTRIBUTE ::= {
  SUBTYPE OF          name
  WITH SYNTAX          UnboundedDirectoryString
  LDAP-SYNTAX          directoryString.&id
  LDAP-NAME            {"sn"}
  ID                   id-at-surname }
```

6.2.4 Given Name

The *Given Name* attribute type specifies the linguistic construct which is normally given to an individual by the individual's parent, or is chosen by the individual, or by which the individual is commonly known.

An attribute value for Given Name is a string, e.g., "David" or "Jean-Paul".

```
givenName ATTRIBUTE ::= {
  SUBTYPE OF          name
  WITH SYNTAX          UnboundedDirectoryString
  LDAP-SYNTAX          directoryString.&id
  LDAP-NAME            {"givenName"}
  ID                   id-at-givenName }
```

6.2.5 Initials

The *Initials* attribute type contains the initials of some or all of an individual's names, but not the surname(s).

An attribute value for Initials is a string, e.g., "D" or "D." or "J.P.".

```
initials ATTRIBUTE ::= {
  SUBTYPE OF          name
  WITH SYNTAX          UnboundedDirectoryString
  LDAP-SYNTAX          directoryString.&id
  LDAP-NAME            {"initials"}
  ID                   id-at-initials }
```

6.2.6 Generation Qualifier

The *Generation Qualifier* attribute type contains a string which is used to provide generation information to qualify an individual's name.