
**Information technology — High
efficiency coding and media delivery
in heterogeneous environments —**

**Part 2:
High efficiency video coding**

**AMENDMENT 2: Main 10 still picture
profile**

*Technologies de l'information — Codage à haute efficacité et livraison
des médias dans des environnements hétérogènes —*

Partie 2: Codage vidéo à haute efficacité

AMENDEMENT 2: Profil main 10 pour image fixe



iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO/IEC 23008-2:2017/Amd 2:2018

<https://standards.iteh.ai/catalog/standards/iso/a640131e-8782-4e7a-80ad-ecfb7eba9abf/iso-iec-23008-2-2017-amd-2-2018>



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/IEC JTC 1, *Information technology, Subcommittee SC 29, Coding of audio, picture, multimedia and hypermedia information* in collaboration with ITU-T. A technically aligned text is published as ITU-T H.265.

A list of all parts in the ISO/IEC 23008 series can be found on the ISO website.

Information technology — High efficiency coding and media delivery in heterogeneous environments —

Part 2: High efficiency video coding

AMENDMENT 2: Main 10 still picture profile

Clause 3

Replace 3.56 with the following:

3.56

frequency index

one-dimensional or two-dimensional index associated with a *transform coefficient* prior to the application of a *transform* in the *decoding process*

Delete 3.70, and renumber the current 3.71 through 3.164 as 3.70 through 3.163.

Add the following as 3.164:

3.164

transform

part of the *decoding process* by which a *block* of *transform coefficients* is converted to a *block* of spatial-domain values

Replace 3.165 with the following:

3.165

transform block

rectangular $M \times N$ *block* of samples resulting from the same *transform* in the *decoding process*

Replace 3.166 with the following:

3.166

transform coefficient

scalar quantity, considered to be in a frequency domain that is associated with a particular one-dimensional or two-dimensional *frequency index* in a *transform* in the *decoding process*

Clause 7

Replace 7.3.3 with the following:

7.3.3 Profile, tier and level syntax

profile_tier_level(profilePresentFlag, maxNumSubLayersMinus1) {	Descriptor
if(profilePresentFlag) {	
general_profile_space	u(2)
general_tier_flag	u(1)
general_profile_idc	u(5)
for(j = 0; j < 32; j++)	
general_profile_compatibility_flag[j]	u(1)
general_progressive_source_flag	u(1)
general_interlaced_source_flag	u(1)
general_non_packed_constraint_flag	u(1)
general_frame_only_constraint_flag	u(1)
if(general_profile_idc == 4 general_profile_compatibility_flag[4] general_profile_idc == 5 general_profile_compatibility_flag[5] general_profile_idc == 6 general_profile_compatibility_flag[6] general_profile_idc == 7 general_profile_compatibility_flag[7] general_profile_idc == 8 general_profile_compatibility_flag[8] general_profile_idc == 9 general_profile_compatibility_flag[9] general_profile_idc == 10 general_profile_compatibility_flag[10]) {	
/* The number of bits in this syntax structure is not affected by this condition */	
general_max_12bit_constraint_flag	u(1)
general_max_10bit_constraint_flag	u(1)
general_max_8bit_constraint_flag	u(1)
general_max_422chroma_constraint_flag	u(1)
general_max_420chroma_constraint_flag	u(1)
general_max_monochrome_constraint_flag	u(1)
general_intra_constraint_flag	u(1)
general_one_picture_only_constraint_flag	u(1)
general_lower_bit_rate_constraint_flag	u(1)
if(general_profile_idc == 5 general_profile_compatibility_flag[5] general_profile_idc == 9 general_profile_compatibility_flag[9] general_profile_idc == 10 general_profile_compatibility_flag[10]) {	
general_max_14bit_constraint_flag	u(1)
general_reserved_zero_33bits	u(33)
} else	
general_reserved_zero_34bits	u(34)
} else if(general_profile_idc == 2 general_profile_compatibility_flag[2]) {	
general_reserved_zero_7bits	u(7)
general_one_picture_only_constraint_flag	u(1)
general_reserved_zero_35bits	u(35)
} else	
general_reserved_zero_43bits	u(43)