

SLOVENSKI STANDARD oSIST prEN 19:2021

01-november-2021

Nadomešča: SIST EN 19:2016

Industrijski ventili - Označevanje kovinskih ventilov

Industrial valves - Marking of metallic valves

Industriearmaturen - Kennzeichnung von Armaturen aus Metall

iTeh STANDARD PREVIEW Robinetterie industrielle - Marquage des appareils de robinetterie métalliques (standards.iteh.ai)

Ta slovenski standard je istoveten zsist prerEN_19

https://standards.iteh.ai/catalog/standards/sist/b0e80e1c-71b7-43a1-a8f8-

ICS:

23.060.01 Ventili na splošno

Valves in general

oSIST prEN 19:2021

en



iTeh STANDARD PREVIEW (standards.iteh.ai)

oSIST prEN 19:2021 https://standards.iteh.ai/catalog/standards/sist/b0e80e1c-71b7-43a1-a8f8d0d81c6cbf67/osist-pren-19-2021

oSIST prEN 19:2021

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

DRAFT prEN 19

ICS 23.060.01

November 2021

Will supersede EN 19:2016

English Version

Industrial valves - Marking of metallic valves

Robinetterie industrielle - Marquage des appareils de robinetterie métalliques

Industriearmaturen - Kennzeichnung von Armaturen aus Metall

This draft European Standard is submitted to CEN members for enquiry. It has been drawn up by the Technical Committee CEN/TC 69.

If this draft becomes a European Standard, CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

This draft European Standard was established by CEN in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

oSIST prEN 19:2021

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Warning : This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents

Europe	ean foreword	3		
1	Scope	4		
2	Normative references	4		
3	Terms and definitions	4		
4	Requirements	5		
4.1	General	5		
4.2	Mandatory markings	6		
4.3	Supplementary markings	6		
4.4	Other markings	6		
4.5	Omission of markings	8		
5	Details of markings	8		
5.1	Nominal size	8		
5.2	PN/Class designation	8		
5.3	Material	9		
5.4	Manufacturer's name or trademark	9		
5.5	Arrow for direction of flown STANDARD PREVIEW	9		
5.6	Ring joint number	9		
5.7	Allowable temperature, TS. (standards.iteh.ai)	9		
5.7.1	Maximum allowable temperature, TSmax	9		
5.7.2	Minimum allowable temperature, TSminLprEN 19:2021	9		
5.8	Threaded end identificationds.iteh.ai/catalog/standards/sist/b0e80e1c-71b7-43a1-a8f8-	9		
5.9	Maximum allowable pressure, P\$ ^{0d81c6cbf67/osist-pren-19-2021}	9		
5.10	Product identification	9		
5.11	Reference to the standard	9		
5.12	Melt identification	10		
5.13	Trim	10		
5.14	Service symbols	10		
5.15	Internal coating, liner, lining or internal painting	10		
5.16	Quality and test markings	10		
5.17	Inspector's identification	10		
5.18	Year of manufacture	10		
5.19	Flow coefficient	10		
5.20	Allowable differential pressure Δp	10		
5.21	Closing direction	10		
Annex ZA (informative) Relationship between this European Standard and the essential requirements of Directive 2014/68/EU (Pressure Equipment Directive) aimed to be				
	covered	11		

European foreword

This document (prEN 19:2021) has been prepared by Technical Committee CEN/TC 69 "Industrial valves", the secretariat of which is held by AFNOR.

This document is currently submitted to the CEN Enquiry.

This document will supersede EN 19:2016.

In comparison with the previous edition, the following technical modifications have been made:

- 4.1.3, 4.2.1, 5.7, 5.9 were modified;
- Table 1 was modified.

This document has been prepared under a Standardization Request given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s) / Regulation(s).

For relationship with EU Directive(s) / Regulation(s), see informative Annex ZA, which is an integral part of this document.

iTeh STANDARD PREVIEW (standards.iteh.ai)

oSIST prEN 19:2021 https://standards.iteh.ai/catalog/standards/sist/b0e80e1c-71b7-43a1-a8f8d0d81c6cbf67/osist-pren-19-2021

1 Scope

This document specifies the requirements for marking of industrial metallic valves. It defines the method of applying the markings, on the body, on a flange, on an identification plate or any other location.

When specified as a normative reference in a valve product or performance standard, this document is considered in conjunction with the specified requirements of that valve product or performance standard.

The marking requirements for plastic valves are not within the scope of this document.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 736-1, Valves - Terminology - Part 1: Definition of types of valves

EN 736-2, Valves - Terminology - Part 2: Definition of components of valves

EN 736-3, Valves - Terminology - Part 3: Definition of terms

EN 1092 (all parts), Flanges and their joints - Circular flanges for pipes, valves, fittings and accessories, PN designated **iTeh STANDARD PREVIEW**

EN 1759 (all parts), Flanges and their joint Gircular flanges for pipes, valves, fittings and accessories, class designated

EN 12516-1, Industrial valves - Shell design strength - Part 1: Tabulation method for steel valve shells

EN 12516-4, Industrial valves - Shell design strength - Part 4: Calculation method for valve shells manufactured in metallic materials other than steel

ISO 7-1, Pipe threads where pressure-tight joints are made on the threads — Part 1: Dimensions, tolerances and designation

ISO 228-1, Pipe threads where pressure-tight joints are not made on the threads — Part 1: Dimensions, tolerances and designation

ANSI/ASME B1.20.1, Pipe Threads, General Purpose, Inch

3 Terms and definitions

For the purposes of this document, the terms and definitions given in EN 736-1, EN 736-2 and EN 736-3 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <u>https://www.electropedia.org/</u>
- ISO Online browsing platform: available at https://www.iso.org/obp

3.1

integral markings

integrally cast, forged or stamped markings on the body or bonnet/cover of the valve

3.2

marking plate

plate securely fixed to the body or bonnet/cover with one or more mandatory markings

Note 1 to entry: See also 4.1.4.

3.3

identification plate

plate securely fixed to the valve with supplementary or other markings

Note 1 to entry: See also 4.1.4.

4 Requirements

4.1 General

4.1.1 Where the requirements in a valve product or performance standard differ from those given in this document, then the requirements of the product or performance standard apply.

4.1.2 Mandatory markings (see 4.2) are independent of language. When it is necessary to include descriptive words so as to properly define any supplementary markings (see 4.3) or other markings (see 4.4), then any such words shall be in the language of the manufacturer and/or one of the official CEN languages (English, French or German).

4.1.3 Table 1 lists those items which shall be considered for inclusion in product or performance standards. Details of the markings are given in Clause 5: 1. a1

The values PS and TSmax are valid for the design TSmin indicates the lowest temperature limit at PS and TSmax. https://standards.iteh.ai/catalog/standards/sist/b0e80e1c-71b7-43a1-a8f8-

In order to make the maximum/minimum allowable limits more explicit for the user of a valve, the corresponding maximum/minimum allowable limits [either the standardized pressure/temperature (p/t) rating, or the applicable values of PS, TSmax, TSmin, as applicable] shall also be indicated in the accompanied operating manuals.

4.1.4 Markings shall be located as detailed in 4.2, 4.3 and 4.4.

Painted-on markings are not permitted.

Where marking plates or identification plates are used, unless otherwise specified in product or performance standards, the material and method of fixing shall be at the discretion of the manufacturer. All marking plates and identification plates and their means of fixing shall be in a material which is resistant to atmospheric corrosion. Marking plates shall also be suitable for the allowable temperature of the valve.

4.2 Mandatory markings

4.2.1 Every valve shall be provided with integral markings or firmly attached marking plate. The following marking details shall be indicated.

a) For PN and Class designated valves that can be used in accordance with a standardized application limit [pressure/temperature (p/t) rating] specified in an EN standard: items 1 to 4, whereas the letters "PN" or "Class" followed by a dimensionless number are used for reference purposes.

In this case, the valve manufacturer affirms both, a standard compliant nominal dimensional size (same mating dimensions for compatible flange types) and a standard compliant maximum/minimum allowable application limits, i.e. pressure/temperature (p/t) rating.

b) For PN and Class designated valves with an application limit not standardized by an EN standard: items 1, 2, 3, 7.1, 7.2 and 9 are mandatory to indicate.

In this case, the manufacturer affirms with the symbols "PN" and "Class" a standard compliant nominal dimensional size. The application limit is expressed by marking PS, TSmax, TSmin.

4.2.2 Items 5 and 6 in Table 1 shall be marked on those valves requiring these markings. See 5.5 and 5.6.

4.3 Supplementary markings

iTeh STANDARD PREVIEW

Items 7 to 21 in Table 1 are optional unless otherwise specified in product or performance standard. The location of supplementary markings shall be determined by the manufacturer, unless otherwise specified in the relevant product or performance standard.

4.4 Other markings

oSIST prEN 19:2021

https://standards.iteh.ai/catalog/standards/sist/b0e80e1c-71b7-43a1-a8f8-

A manufacturer having complied with the above requirements of this document and those of product or performance standards relevant to the individual types of valve is permitted to:

- a) mark any of the items in Table 1 additionally in a place other than that specified; e.g. if a marking is mandatory on the body or bonnet/cover it may also be repeated on the identification plate;
- b) add to the markings specified, any technical and/or commercial references, providing that there is no risk of confusion between these markings and the markings in Table 1.

For industrial valves conforming to the requirements of the European legislation for pressure equipment, additional markings in accordance with 5.10 and 5.18 are required.

Item	Subject		Marking		Clause
			PN designated valves	Class designated valves	reference
1		Flanged ends	DN	DN and/or (NPS)	512
		Wafer type bodies	DN	DN allu/ol (NPS)	5.1.2
	Nominal size	Welding ends	DN	DN and/or (NPS)	5.1.2
		Threaded ends	(thread size) and/or DN	(thread size) and/or (NPS)	5.1.3
		Capillary ends	(tube O/D)	(tube 0/D)	5.1.4
		Compression ends	(tube 0/D)	(tube 0/D)	5.1.4
		Other ends	-	-	5.1.5
2	PN/Class designation		PN	CLASS	5.2
3	Material		-	-	5.3
4	Manufacturer's name or trademark		ABC	ABC	5.4
5	Arrow for direction of flow		\rightarrow	\rightarrow	5.5
6	Ring joint r	umperen STAN	DARD PREV	REW	5.6
7.1	Maximum allowable temperature, TSmax (stan		dæsdsciteh.ai)	°C or C	5.7.1
7.2	Minimum allowable temperature, <u>o</u> TSmin <u>https://standards.iteh.ai/cata</u>		<u>SIST</u> 05 <u>FN_12:2021</u> log/standards/sist/b0e80e1c-711	°C or C 97-43a1-a8í8-	5.7.2
	d0d81c Threaded end identification		6 R, Rc, RpstG, NPT 9-2021	<i>R</i> , <i>R</i> _c , <i>R</i> _p , G, NPT	5.8
8			or other marking according to the relevant standard	or other marking according to the relevant standard	
9	Maximum allowable pressure PS		bar	bar	5.9
10	Product identification		-	-	5.10
11	Reference to the standard		EN	EN	5.11
12	Melt identification		-	-	5.12
13	Trim		-	-	5.13
14	Service symbols		-	-	5.14
15	Internal coating, liner, lining or internal painting		-	-	5.15
16	Quality and test markings		-	-	5.16
17	Inspector's identification		\checkmark	\checkmark	5.17
18	Year of manufacture		2014 or 14	2014 or 14	5.18
19	Flow coefficient		<i>K</i> _v (or <i>C</i> _v)	$K_{\rm v}$ (or $C_{\rm v}$)	5.19
20	Allowable differential pressure		Δ <i>p</i> bar	Δ <i>p</i> bar	5.20
21	Closing direction		-	-	5.21

Table 1 — Valve markings

4.5 Omission of markings

4.5.1 For valves lower than or equal to DN 50 or for valves with threaded ends lower than or equal to size 2", where due to the physical size of the valve, it is not practicable to apply all the mandatory markings as required by 4.2, the relevant valve product or performance standard shall specify which markings may be omitted or alternatively placed on the identification plate or other location.

4.5.2 For Class designated valves where, due to the physical size of the valve, it is not practicable to incorporate the word "CLASS", it is permissible to omit the word "CLASS" or to indicate only the letters "CL".

4.5.3 For PN designated valves, it is permissible to omit the letters "DN" from the nominal size designation (item 1) providing the PN designation (item 2) follows immediately after the size number and on the same line, e.g. DN 50 PN 25 may be abbreviated to 50 PN 25.

4.5.4 Valves with compression or capillary ends have no defined PN or Class designation, but such valves are not required to be marked with items 7 and 9 in Table 1.

4.5.5 For cast iron valves it is permissible to omit "EN" from the material designation.

5 Details of markings

5.1 Nominal size

iTeh STANDARD PREVIEW

5.1.1 The nominal size marking shall be the size designation of the end connections with which the body has been provided. (**standards.iteh.al**)

5.1.2 For valves with flanges, butt welding <u>or socket welding</u> end connections or with wafer type bodies, the nominal size marking shall comprise the letters "DN" and the appropriate DN number as specified in the relevant flange, butt welding or socket welding standard, e.g. DN 100.

NOTE 1 For Class designated valves, the NPS marking, e.g. NPS 4 can be used in addition to or as an alternative to the DN marking. The relationship between NPS and DN is specified in the relevant flange or welding end standard.

NOTE 2 See also 4.5.3.

5.1.3 For threaded end valves, the nominal size marking shall be the thread size as specified in the relevant pipe thread standard.

NOTE In addition to, or as an alternative to the thread size marking, the DN marking can be used. The relationship between NPS and DN is specified in the relevant product or performance standard.

5.1.4 For capillary and compression ends, the nominal size marking shall be the outside diameter of the tube for which the valve is suitable and shall be as specified in the relevant tube standard.

5.1.5 For valves provided with other end connections or having the pipe end connections of differing nominal sizes or type, e.g. one flanged end and one welding end, the nominal size marking shall be as specified in the relevant product or performance standard or shall be agreed between the manufacturer and the purchaser.

5.2 PN/Class designation

5.2.1 For PN designated valves, the marking shall comprise the letters "PN" and the appropriate PN designation number, e.g. PN 16.