



Designation: F2161-01 ~~Designation: F2161 - 10~~

## Standard Guide for Instrument and Precision Bearing Lubricants—Part 1 Oils<sup>1</sup>

This standard is issued under the fixed designation F2161; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

### 1. Scope

1.1 This guide is a tool to aid in the choice of an oil for precision rolling element bearing applications. There are two areas where this guide should have the greatest impact: (1) when a lubricant is being chosen for a new bearing application and (2) when a lubricant for a bearing has to be replaced because the original lubricant specified for the bearing can no longer be obtained. The Report (Section 5) contains a series of tests performed by the same laboratory on a wide variety of oils commonly used in bearing applications to allow comparisons of those properties of the oil that the committee thought to be most important when making a choice of lubricant. This guide contains a listing of the properties of oils by chemical type, that is, ester, silicone, and so forth. This organization is necessary since the operational requirements in a particular bearing application may limit the choice of lubricant to a particular chemical type due to its temperature stability, viscosity index or temperature-vapor pressure characteristics, and so forth. The Report includes the results of tests on the oils included in this study. The Report recommends replacement lubricants for those oils tested that are no longer available. The Report also includes a glossary of terms used in describing/discussing the lubrication of precision and instrument bearings. The Report presents a discussion of elastohydrodynamic lubrication as applied to rolling element bearings.

1.2 Although other compendia of lubricant properties have been published, for example, the Barden Product Standard, Lubricants<sup>2</sup> and the *NASA Lubricant Handbook for the Space Industry*<sup>3</sup>, none have centered their attention on lubricants commonly used in precision rolling element bearings (PREB). The PREB put a host of unique requirements upon a lubricant. The lubricant must operate at both high and low temperatures. The lubricant must provide lubrication for months, if not years, without replenishment. The lubricant must be able to support high loads but cannot be so viscous that it will interfere with the operation of the bearing at very high speeds or low temperatures, or both. The lubricant must provide boundary lubrication during low-speed or intermittent operation of the bearing. And, in many applications, its vapor pressure must be low enough under operating conditions that evaporative losses do not lead to lubricant depletion or contamination of nearby components. These and other considerations dictated the series of tests that were performed on each lubricant included in this study.

1.3 Another important consideration was encompassed in this study. Almost all of the testing was performed by the same laboratory, The Petroleum Products Research Department of the Southwest Research Institute in San Antonio, Texas, using ASTM procedures. This continuity of testing should form a solid basis for comparing the properties of the multitude of lubricants tested by avoiding some of the variability introduced when lubricants are tested by different laboratories using different or even the “same” procedures.

1.4 It should be noted that no functional tests (that is, bearing tests) were performed. The results of the four-ball wear test give some comparison, “a figure of merit,” of the lubrication properties of the oils under the condition of this test. But experience has shown that testing the lubricant in running bearings is the best means of determining lubricant performance.

### 2. Referenced Documents

#### 2.1 ASTM Standards:<sup>4</sup>

D92 Test Method for Flash and Fire Points by Cleveland Open Cup Tester

D97 Test Method for Pour Point of Petroleum Products

D445 Test Method for Kinematic Viscosity of Transparent and Opaque Liquids (and Calculation of Dynamic Viscosity)

<sup>1</sup> This guide is under the jurisdiction of ASTM Committee F34 on Rolling Element Bearings and is the direct responsibility of Subcommittee F34.02 on Tribology. Current edition approved Dec. 10, 2001. Published February 2002. DOI: 10.1520/F2161-01 on Tribology and was developed by DoD Instrument Bearing Working Group (IBWG) former F34.

Current edition approved Jan. 1, 2010. Published February 2010 originally approved in 2001. Last previous edition approved in 2001 as F2161-01. DOI: 10.1520/F2161-10.

<sup>2</sup> *Product Standard, Lubricants*,<sup>2</sup> available from The Barden Corp., Danbury, CT.

<sup>3</sup> *NASA Lubricant Handbook for the Space Industry*, Ernest L. McMurtrey, *NASA Technical Memorandum TM-86556*, George C. Marshall Space Flight Center, National Aeronautics and Space Administration, December 1985.

<sup>4</sup> For referenced ASTM standards, visit the ASTM website, [www.astm.org](http://www.astm.org), or contact ASTM Customer Service at [service@astm.org](mailto:service@astm.org). For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

- D974 Test Method for Acid and Base Number by Color-Indicator Titration  
 D972 Test Method for Evaporation Loss of Lubricating Greases and Oils  
 D1331 Test Methods for Surface and Interfacial Tension of Solutions of Surface-Active Agents  
 D2270 Practice for Calculating Viscosity Index from Kinematic Viscosity at 40 and 100C  
 D4172 Test Method for Wear Preventive Characteristics of Lubricating Fluid (Four-Ball Method)

2.2 *Government Documents*<sup>5</sup>:

- MIL-DTL-53131 Lubricating Oil, Precision Rolling Element Bearing, Polyalphaolefin Based  
 MIL-L-6085 Lubricating Oil, Aircraft Turbine Engine, Synthetic Base  
 MIL-L-14107 Lubricating Oil, Weapons, Low Temperature  
 MIL-L-23699 Lubricating Oil, Aircraft Turbine Engines, Synthetic Base  
 MIL-L-7808 Lubricating Oil, Aircraft Turbine Engine, Synthetic Base  
 MIL-L-81846 Lubricating Oil, Instrument, Ball Bearing, High Flash Point  
 MIL-S-81087 Silicone, Fluid, Chlorinated Phenyl Methyl Polysiloxane

### 3. Terminology

3.1 *Definitions of Terms Specific to This Standard:*

3.1.1 *ABEC, n*—Annular Bearing Engineer’s Committee of the American Bearing Manufacturers Association (ABMA). The ABEC establishes bearing tolerance classes. Precision bearings are ABEC 5P and ABEC-5T and higher.

3.1.2 *absolute viscosity* ( $\eta$ ), *n*—(sometimes called dynamic viscosity or just viscosity)—a measure of the tendency of the fluid to resist shear. The elastohydrodynamic theory (EHD) film thickness and torque losses in a ball bearing are very strong functions of  $\eta$ . Since the ratio of absolute viscosity to density,  $\eta/\rho$ , appears frequently in hydrodynamic analyses, it was given its own name, kinematic viscosity,  $\nu$ . The cgs unit of viscosity is the centipoise (cP). The SI unit of viscosity is the Pascal-s (Pa-s).

Absolute viscosity is defined for a Newtonian fluid as follows. The shear stress at any point in the fluid is proportional to the rate of shear. The proportionality constant is called the absolute viscosity. Viscosity is thus defined by the force,  $F$ , to move one surface of area,  $A$ , with respect to another surface separated by a fluid film,  $h$ , at a speed,  $U$ , through the following relationship:

$$\eta = (F/A)(h/U)$$

The value of the absolute viscosity changes greatly with temperature,  $T$ . As the temperature increases viscosity decreases. ASTM International has adopted the following relationship between kinematic viscosity and temperature:

where:

$m$  and  $c$  = constants for each fluid.

ASTM International supplies chart paper with the ordinate proportional to  $\log_{10} \log_{10}(\nu + 0.8)$  and with the abscissa proportional to  $\log_{10} T$ . Thus the values of kinematic viscosity versus temperature can be plotted as a straight line on the paper allowing extrapolation of values intermediate to those that have been measured.

Absolute viscosity is a weak function of the pressure imposed upon the fluid. However, the pressures generated in the ball-race contact zone of a ball bearing can be on the order of  $10^3$  GPa ( $10^5$  psi) and at these pressures significant increases in viscosity can occur. Experiments have shown that viscosity varies exponentially with pressure and can be expressed as follows:

where:

$\eta_0$  = viscosity at a pressure of one atmosphere,

$p$  = pressure, and

$\alpha$  = pressure-viscosity coefficient.

A table of values of  $\alpha$  for some common classes of bearing lubricants can be found after the definition of pressure-viscosity coefficient included in this glossary.

Recent work has shown that the viscosity changes with temperature can also be modeled by an exponential relationship. Thus, viscosity at any pressure and temperature can be expressed as follows:

where:

$\beta$  = temperature-viscosity coefficient.

3.1.3 *acid number, n*—a measure of the quality of a lubricant. High acid numbers (much higher than the fresh oil) are an indication of lubricant oxidation/degradation. Oils with high acid numbers should not be used. Acid number is measured as milligrams of KOH needed to neutralize one gram of oil.

3.1.4 *additive, n*—any chemical compound added to a lubricant to improve or meet special needs necessary for service (formulated lubricants). The most important additives are antioxidants, rust and corrosion inhibitors, and extreme pressure (EP) and antiwear (AW) additives.

3.1.5 *antioxidants* (oxidation inhibitors), *n*—chemical compounds used to improve the oxidation stability and subsequent deterioration of lubricants.

<sup>5</sup> Available from Document Automation and Production Service, Building 4/D, 700 Robins Ave., Philadelphia, PA 19111-5094.

3.1.6 *boundary lubrication, n*—a condition of lubrication in which the friction between two surfaces in relative motion is determined by the roughness of the surfaces and by the properties of the lubricant other than viscosity. Antiwear and extreme pressure additives reduce the wear of components operating under this regime.

3.1.7 *centipoise, n*—a unit of dynamic viscosity. The unit in the cgs system is one centipoise (cP). The SI unit of dynamic viscosity is 1 Pa·s and equivalent to  $10^3$  cP.

3.1.8 *centistoke, n*—a unit of kinematic viscosity. The unit in the cgs system is one centistoke (cSt). The SI unit of kinematic viscosity is  $1 \text{ m}^2/\text{s}$  and is equivalent to  $10^6$  cSt.

3.1.9 *compatibility, n*—a measure of the ability of a lubricant to be mixed with other lubricants or bearing preservatives (fluids that form films on metal surfaces to prevent corrosion during storage) to form a uniform mixture without causing any resultant reaction or precipitation of material. Compatibility is also a measure of the ability of a lubricant not to cause any detrimental effect to metal, plastic, or elastomer materials.

3.1.9.1 *Discussion*—It is recommended that any preservative material be removed from bearings before lubrication.

3.1.10 *contamination, n*—(1) The presence of mostly solid foreign materials like sand, grinding powder, dust, and so forth, in a lubricant that might cause an increase in wear, torque, and noise and result in reduced bearing life. (2) The presence of fluids like water, solvents, and other oils that might cause accelerated oxidation, washout, rusting, or crystallization of the additives and other phenomena that reduce a bearing's life.

3.1.11 *corrosion, n*—the gradual destruction of a metal surface due to chemical attack caused by polar or acidic agents like humidity (water), compounds formed by lubricant deterioration, or by contaminants from the environment.

3.1.12 *corrosion inhibitors, n*—corrosion inhibitors protect metal surfaces against corrosion or rust by forming a protective coating or by deactivation of corrosive compounds formed during the operation of a bearing.

3.1.13 *density, n*—the mass per unit volume of a substance. The cgs unit of density ( $\rho$ ) is  $1 \text{ g}/\text{cm}^3$ , and the SI unit of density is  $1 \text{ kg}/\text{m}^3$ . Density depends on the chemical composition and in itself is no criterion of quality. It is a weak function of temperature and pressure for liquids and solids.

3.1.14 *DN value, n*—the product of the bearing bore diameter in millimetres multiplied by the speed in revolutions per minute (compare to  $nD_m$ -value).

3.1.15 *dynamic viscosity, n*—another name for absolute viscosity.

3.1.16 *elastohydrodynamic theory (EHD), n*—See ~~Appendix X2~~Appendix X1.

3.1.17 *EP lubricants (extreme pressure lubricants), n*—lubricants (oil or greases) that contain extreme pressure additives to protect the bearings against wear and welding (scoring).

3.1.18 *esters, n*—esters are formed from the reaction of acids and alcohols. Esters form a class of synthetic lubricants. Esters of higher alcohols with divalent fatty acids form diester lubricants while esters of polyhydric alcohols are called the polyol ester lubricants. These latter esters have higher viscosity and are more heat-resistant than diesters.

3.1.19 *evaporation loss, n*—lubrication fluid losses occurring at higher temperatures or under vacuum, or both, due to evaporation. This can lead to an increase in lubricant consumption and also to an alteration of the fluid properties of a lubricant (especially an increase in the viscosity of blended lubricants). The evaporation loss is expressed as a weight loss in milligrams ( $10^{-6}$  kg) or wt %.

3.1.20 *fire point, n*—the lowest temperature at which the vapor or a lubrication fluid ignites under specified test conditions and continues to burn for at least 5 s without the benefit of an outside flame. The fire point is a temperature above the flash point. Perfluoropolyethers have no fire point.

3.1.21 *flash point, n*—the lowest temperature of a lubrication fluid at which the fluid gives off vapors that will ignite when a small flame is periodically passed over the liquid surface under specified test conditions. The flash and fire points provide a rough characterization of the flammable nature of lubrication fluids. Perfluoropolyethers have no flash point.

3.1.22 *four-ball tester, n*—a tester used to evaluate the wear behavior of lubricants under extreme pressure. Four steel balls are arranged in a pyramidal shape. During the test, the three balls comprising the base of the pyramid are stationary while the upper ball rotates. The lubricant sample is placed in the ball pot. The average wear scar (measured in millimetres) formed on the stationary balls is reported.

3.1.23 *fretting corrosion, n*—a special type of wear produced on materials in intimate contact that are subjected to the combined action of oscillatory motions of small amplitudes and high frequencies. Fretting corrosion appears similar to atmospheric corrosion (rust) as a reddish-brown layer on steel surfaces.

3.1.24 *interfacial tension, n*—when two immiscible liquids are in contact, their interface has many characteristics in common with a gas-liquid surface. This interface possesses interfacial free energy because of the unbalanced attractive forces exerted on the molecules at the interface by the molecules within the separate phases. This free energy is called the interfacial tension.

3.1.25 *instrument bearings, n*—all bearings whose outer diameter is 30 mm or less, as defined by The American Bearing Manufacturers Association (ABMA).

3.1.26 *kinematic viscosity, n*—the ratio of absolute viscosity to fluid density. This ratio arises frequently in lubrication analyses and thus kinematic viscosity has become a separate term describing the viscosity of a fluid. Many experimental measurements of viscosity of fluids result in a measure of kinematic viscosity from which absolute viscosity is calculated. See *absolute viscosity*. The cgs unit of kinematic viscosity is cSt, and the SI unit is  $\text{m}^2/\text{s}$ . The viscosity of a PREB oil is a major factor in lubricant

selection. The viscosity is directly involved in frictional, thermal, and fluid film conditions which reflect the influence of load, speed, temperature, and design characteristics of the bearing being lubricated.

3.1.27 *military (MIL) specifications, n*—specifications of the U.S. Armed Forces indicating the minimum mandatory requirements for an item that is to be procured. Military specifications are widely used as procurement requirements and as a quality standard.

3.1.28 *mineral oil, n*—oils based on petroleum stocks. These oils come in two types, naphthenic and paraffinic. The naphthenic oils contain unsaturated hydrocarbons, usually in the form of aromatic species. The paraffinic oils are primarily saturated hydrocarbons with only low levels of unsaturation.

3.1.29 *nD<sub>m</sub>-value (index), n*—also called speed index—a relative indicator of the lubricant stress imposed by a bearing rotating at a given speed, where *n* is the rotational speed of the rolling element bearing in revolutions per minute and *D<sub>m</sub>* is the mean diameter in millimetres (arithmetic mean of bore diameter *d* and outside diameter *D*). The speed index is multiplied by a factor *k<sub>a</sub>* depending on the roller element bearing type:

- k<sub>a</sub>* = 1 for deep groove ball bearings, angular contact ball bearings, self-aligning ball bearings, radially loaded cylindrical roller bearings, and thrust ball bearings,
- k<sub>a</sub>* = 2 for spherical roller bearings, taper roller bearings, and needle roller bearings, and
- k<sub>a</sub>* = 3 for axially loaded cylindrical roller bearings and full complement roller bearings.

The factor *k<sub>a</sub>* takes into account the various rates of sliding friction that usually occurs during the operation of a rolling element bearing. The *nD<sub>m</sub>*-value is an aid in choosing a suitable lubricant viscosity for a given bearing speed and is particularly applicable to grease-lubricated bearings.

3.1.30 *neutralization number, n*—a measure of the acidity or alkalinity of a lubricating fluid. The test determines the quantity of base (milligrams of potassium hydroxide) or acid (also expressed as milligrams of potassium hydroxide) needed to neutralize the acidic or alkaline compounds present in a lubricating fluid. Actually, the neutralization number is not one number but several numbers: strong acid number, total acid number, strong base number, and total base number. The neutralization number is used for quality control, and to determine changes that occur in a lubricant in service.

3.1.31 *oxidation stability, n*—the stability of a lubricant in the presence of air or oxygen is an important chemical property. Oxidation stability has a strong influence on numerous physical properties of a lubricant. These properties include the change of viscosity under static conditions for long periods of time (storage) or when exposed to temperatures high above room temperature, or both. The slow chemical reaction of fluid (base oil) and oxygen (air) is called oxidation. Inhibitors (see *antioxidants*) are used to improve the oxidation stability of the lubricants. Synthetic fluids, especially perfluoropolyethers and silicones, are much more resistant to oxidation than mineral oils.

3.1.32 *precision bearings, n*—regardless of size, the class of bearings used in instrument types of applications and with similar tolerances as instrument bearings. Bearings usually used in these applications are of high quality and are not put under high stress, thus they usually do not fail under fatigue.

3.1.33 *perfluoropolyethers (PFPE or PFAE), n*—fully fluorinated long-chain aliphatic ethers. The perfluoropolyethers show some extraordinary properties like chemical inertness, nonflammability, high thermal and oxidative resistance, very good viscosity-temperature characteristics, and compatibility with a wide range of materials, including metals and plastics. The perfluoropolyethers, however, are not suitable for use with aluminum, magnesium, and titanium alloys. The perfluoropolyethers are not compatible with other types of synthetic fluids and mineral oils and cannot dissolve common lubricant additives.

3.1.34 *pH value, n*—a scale for measuring the acidity or alkalinity of a product. Zero pH is very acid, 7 is neutral, and 14 is very alkaline.

3.1.35 *poise (P), n*—See *centipoise (cP)*.

3.1.36 *pour point, n*—(of a lubricating fluid)—the lowest temperature at which the lubricating fluid will pour, or flow.

3.1.37 *pressure-viscosity coefficient, n*—the dynamic viscosity of a fluid increases with increasing pressure. The dependence of viscosity (absolute),  $\eta$ , on pressure, *p*, can be expressed by the equation:

**TABLE 1 Pressure-Viscosity Coefficients for the Lubricant Classes Covered in This Guide**

Oil Type	$\alpha^A$ (GPa <sup>-1</sup> )
Mineral oil (paraffinic-naphthenic)	21
Mineral oil (naphthenic-aromatic)	30
Polyalphaolefin	18
Diester-(2-ethylhexyladipate)	7.6
Polyolester (pentaerythritolvalerate)	7.5
Polydimethylsilicone (1000 mm <sup>2</sup> /s at 40°C)	2.3
PFPE—linear	4–12
PFPE—branched	26–36

<sup>A</sup> 1 atm = 0.001013 GPa.

where:

$\eta$  = absolute viscosity at pressure,  $p$ ,

$\eta_0$  = absolute viscosity at one atmosphere, and

$\alpha$  = the pressure-viscosity coefficient.

The pressure-viscosity coefficient is very small and varies with the chemical composition of the fluid. Some values of  $\alpha$  for the classes of lubricants discussed in the Report section are given in Table 1.<sup>6</sup>

One limitation of the use of  $\eta_0$  and the corresponding equation is that the measurements of  $\eta_0$  are made under static conditions where the pressure is held constant while the viscosity attains a steady-state value. In actual bearing operations, the lubricant may see high pressure in the contact zone for only a few milliseconds and the viscosity changes due to this high pressure may not reach steady-state values.

3.1.38 *rated viscosity*, ( $v_1$ ),  $n$ —the kinematic viscosity attributed to a defined lubricating condition of a rolling element bearing. The rated viscosity is a function of the speed and can be determined by the mean bearing diameter in millimetres ( $10^{-3}$  m) and the rotational speed (rpm). More details can be found in ~~Appendix X2~~Appendix X1.

3.1.39 *repeatability*,  $n$ —a criterion for judging the acceptability of test results. Repeatability is the difference between successive test results obtained by the same operator with the same apparatus under constant operating conditions on identical test material. Repeatability is usually reported as a range of values that would, in the normal and correct operation of the test method, encompass two standard deviations from the median value of the test.

3.1.40 *reproducibility*,  $n$ —a criterion for judging the acceptability of test results. Reproducibility is the difference between two single and independent results, obtained by different operators working with identical test material. This difference, in the long run and under normal and correct operation of the test method, would not exceed a specified value.

3.1.41 *saponification number*,  $n$ —a measure of the amount of constituents of a lubrication fluid that will easily saponify under test conditions. The saponification number is expressed in milligrams of potassium hydroxide that are required to neutralize the free and bonded acids contained in one gram of lubricating fluid. The saponification number is a measure of fatty acids compounded in an oil and a measure of the state of oil deterioration.

3.1.42 *saponify*,  $v$ —to hydrolyze an ester and to convert the free acid into soap.

3.1.43 *seal compatibility*,  $n$ —the extent of the reaction of sealing materials with lubricating oils, greases, and other fluids. The reaction can result in swelling, shrinking, plasticizing, embrittlement, or even dissolution. Operating temperatures and lubricant composition are dominant factors influencing the extent of the interaction between the sealing material and the lubricating fluid.

3.1.44 *setting point*,  $n$ —of a lubricating fluid—the temperature at which the fluid ceases to flow when cooled under specified conditions. The low-temperature behavior of the fluid slightly above the setting point may be unsatisfactory and, therefore, this behavior should be determined by measuring the low-temperature kinematic or absolute viscosity.

3.1.45 *shelf life*,  $n$ —the expression shelf life of a lubricant is not exactly specified. Two versions of the definition exist:

(1) *shelf life*—the ability of a lubricated part to function even after long-term storage. This definition is very critical because it includes not only the aging properties of the lubricant used but also the loss of lubricant due to evaporation and creeping.

(2) *shelf life*—the storage stability of the bulk lubricant in its original container. Stability is defined here as no change in the physical or chemical properties of the lubricant.

3.1.46 *silicone oils*,  $n$ —synthetic fluids composed of organic esters of long chain complex silicic acids. Silicone oils have better physical properties than mineral oils. However, silicone oils have poorer lubrication properties, lower load-carrying capacity, and a strong tendency to spread on surfaces (see *surface tension*). To prevent this spreading the use of barrier films is necessary.

3.1.47 *stability*,  $n$ —the resistance of a lubricant to a change in its properties after being stored for a defined period of time. The methods to test a lubricant for stability are defined in individual military or commercial specifications.

3.1.48 *surface energy/surface tension*,  $n$ —a fundamental property of liquids is the existence of a free energy at the surface. A consequence of this free energy is the property that a liquid spontaneously contracts to the smallest possible area. For example, liquid droplets assume a spherical shape if no outside forces are acting on the droplet. To deform the droplet from its spherical shape, a definite amount of work must be done. This work (or energy expended) when normalized per unit area is called surface tension and has the unit mN/m (formally dyne/cm). Surface tension is dependent upon temperature but not upon pressure. The surface tension is a measure for the wetting of a bearing surface and for the creeping (spreading) property of a lubricant. Fluids with low surface tensions like dimethylsilicones show improved wetting but increased creeping (migration) tendency.

3.1.49 *swelling properties*,  $n$ —the swelling of natural rubber and elastomers under the influence of lubricants.

3.1.50 *synthetic fluids*,  $n$ —lubricating fluids produced by chemical synthesis. The synthetic route to lubricants allows the manufacturer to introduce those chemical structures into the lubricant molecule that will impart specific properties into the resultant fluid such as very low pour point, good viscosity-temperature relationship, low evaporation loss, long lubricating lifetime, and so forth.

3.1.51 *viscosity*,  $n$ —See *absolute viscosity*.

3.1.52 *viscosity index (VI)*,  $n$ —indicates the range of change in viscosity of a lubricating fluid within a given temperature range. With an increase in the viscosity index, the fluid becomes less sensitive to temperature, that is, a low-viscosity index signifies a

<sup>6</sup> *Journal of Synthetic Lubrication*, Vol 1, 1984, pp. 73-86.

relatively large change, whereas a high-viscosity index relates to a relatively small change in viscosity with temperature.

3.1.53 *wear, n*—the attrition or rubbing away of the surface of material as a result of mechanical action.

#### 4. Significance and Use

4.1 The purpose of this guide is to report on the testing of, to discuss and compare the properties of, and to provide guidelines for the choice of lubricants for precision rolling element bearings (PREB). The PREB are, for the purposes of this guide, meant to include bearings of ABEC 5 quality and above. This guide limits its scope to oils used in PREB and is to be followed by a similar document to encompass greases used in PREB.

4.2 The number of lubricants, both oils and greases, used in PREB increased dramatically from the early 1940s to the mid 1990s. In the beginning of this period, petroleum products were the only widely available base stocks. Later, synthetic lubricants became available including synthetic hydrocarbons, esters, silicones, and fluorinated materials, including perfluorinated ethers and the fluorosilicones. This broad spectrum of lubricant choices has led to the use of a large number of different lubricants in PREB applications. The U.S. Department of Defense, as a user of many PREB, has seen a significant increase in the logistics effort required to support the procurement and distribution of these items. In addition, as time has passed some of the lubricants used in certain PREB are no longer available. The SRG Series, LSO-26, and Teresso V-78 are examples of such lubricants. This implies that replacement lubricants must be found as, in this era of extending the lifetime of DoD assets, stockpiles of replacement parts become depleted.

4.3 One of the primary goals of this study was to take a broad spectrum of the lubricants used in PREB and do a comprehensive series of tests on them in order that their properties could be compared and, if necessary, potential replacement lubricants identified. This study is also meant to be a design guide for choosing lubricants for PREB applications. This guide represents a collective effort of many members of this community who span the spectrum from bearing manufacturers, original equipment manufacturers (OEMs), lubricant manufacturers and suppliers, procurement specialists, and quality assurance representatives (QARs) from DoD and end users both inside and outside DoD.

#### 5. Report

5.1 Tables 2-6<sup>7</sup> give the test results of the 44 PREB oils tested. Each oil was tested for kinematic viscosity, pour point, flash point, evaporation loss, surface tension, four-ball wear, and acid number. In addition, a viscosity index was calculated for each of the oils tested by using the kinematic viscosities at 40°C and 100°C in cSt and using the following formula:

iTeh Standards  
ASTM F2161-10  
Document Preview

#### ASTM F2161-10

<sup>7</sup>This temperature limit is only a general guideline. Individual mineral oils may perform at temperature limits significantly different from this.  
<sup>7</sup>Supporting data have been filed at ASTM International Headquarters and may be obtained by requesting Research Report RR: RR:F34-1001.

**TABLE 2 Properties of PREB Mineral-Based Oils**

Mineral Oils <sup>A</sup>	Properties									
	Kinematic Viscosity [cSt] (10 <sup>-6</sup> m <sup>2</sup> /s) <sup>B</sup>				Density (0.87 – 0.91 g/cm <sup>3</sup> ) (0.87 – 0.91 × 10 <sup>3</sup> kg/m <sup>3</sup> )					
	40°C	100°C	Low Temperature	Viscosity Index (VI)	Pour Point <sup>C</sup> [°C]	Flash Point <sup>D</sup> [°C]	Evaporation Loss <sup>E</sup> [% wt]	Surface Tension <sup>F</sup> (22°C) [dyne/cm]	4-Ball Wear [MN/m] or [mm]	Acid Number [mg KOH/g]
Geray100	97.00	9.13	ND <sup>G</sup>	63.6	-20	196	8.24	28.86	0.70	0.04
S-1	97.00	9.13	ND <sup>G</sup>	63.6	-20	196	8.24	28.86	0.70	0.04
KendallSRG-40 <sup>H</sup>	24.75	4.61	3039 (-20°C)	100	-33	143	24.07	26.31	0.58	0.05
S-2 <sup>H</sup>	24.75	4.61	3039 (-20°C)	100	-33	143	24.07	26.31	0.58	0.05
KendallSRG-60 <sup>H</sup>	83.35	10.41	1557 (-5°C)	107	-18	199	3.88	25.95	0.54	0.06
S-3 <sup>H</sup>	83.35	10.41	1557 (-5°C)	107	-18	199	3.88	25.95	0.54	0.06
KendallSRG-80 <sup>H</sup>	135.00	14.80	2300 (0°C)	110	-7	265	0.59	28.66	0.55	0.03
S-4 <sup>H</sup>	135.00	14.80	2300 (0°C)	110	-7	265	0.59	28.66	0.55	0.03
Mobil-DTE-Medium	42.00	6.50	ND <sup>G</sup>	105	-7	201	2.13	28.4	0.78	0.22
S-5 <sup>H</sup>	42.00	6.50	ND <sup>G</sup>	105	-7	201	2.13	28.4	0.78	0.22
Teresso-V-78 <sup>H</sup>	131.29	14.19	1710 (0°C)	106	-12	191	4.10	24.86	0.58	0.11
S-6 <sup>H</sup>	131.29	14.19	1710 (0°C)	106	-12	191	4.10	24.86	0.58	0.11

<sup>A</sup> See Table X3.1 for manufacturer information as listed in RR:F34-1001.2

<sup>B</sup> Test Method D445

<sup>C</sup> Test Method D97

<sup>D</sup> Test Method D92

<sup>E</sup> Test Method D972

<sup>F</sup> Test Methods D1331

<sup>G</sup> Not determined.

<sup>H</sup> No longer available.