

ETSI TS 138 104 V18.6.0 (2024-08)



5G; NR; Base Station (BS) radio transmission and reception (3GPP TS 38.104 version 18.6.0 Release 18)

[ETSI TS 138 104 V18.6.0 \(2024-08\)](https://standards.iteh.ai/catalog/standards/etsi/05f412b2-6938-422d-93bd-ff8e02a280fc/etsi-ts-138-104-v18-6-0-2024-08)

<https://standards.iteh.ai/catalog/standards/etsi/05f412b2-6938-422d-93bd-ff8e02a280fc/etsi-ts-138-104-v18-6-0-2024-08>



ReferenceRTS/TSGR-0438104vi60

Keywords5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
ETSI [Search & Browse Standards application](#).

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#).

Users should be aware that the present document may be revised or have its status changed,
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2024.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables. (2024-08)

The cross reference between 3GPP and ETSI identities can be found under <https://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	14
1 Scope	16
2 References	16
3 Definitions, symbols and abbreviations	17
3.1 Definitions	17
3.2 Symbols.....	21
3.3 Abbreviations	23
4 General	26
4.1 Relationship with other core specifications.....	26
4.2 Relationship between minimum requirements and test requirements	26
4.3 Conducted and radiated requirement reference points	26
4.3.1 BS type 1-C	26
4.3.2 BS type 1-H	27
4.3.3 BS type 1-O and BS type 2-O	28
4.4 Base station classes	28
4.5 Regional requirements.....	29
4.6 Applicability of requirements.....	32
4.7 Requirements for contiguous and <i>non-contiguous spectrum</i>	33
4.8 Requirements for BS capable of multi-band operation	33
4.9 OTA co-location with other base stations	34
5 Operating bands and channel arrangement	36
5.1 General	36
5.2 Operating bands	36
5.3 BS channel bandwidth	39
5.3.1 General.....	39
5.3.2 Transmission bandwidth configuration	40
5.3.3 Minimum guardband and transmission bandwidth configuration	41
5.3.4 RB alignment.....	42
5.3.5 BS channel bandwidth per operating band	42
5.3A BS channel bandwidth for CA.....	47
5.3A.1 Transmission bandwidth configuration for CA	47
5.3A.2 Minimum guardband and transmission bandwidth configuration for CA	47
5.4 Channel arrangement.....	50
5.4.1 Channel spacing.....	50
5.4.1.1 Channel spacing for adjacent NR carriers	50
5.4.1.2 Channel spacing for CA	50
5.4.2 Channel raster	51
5.4.2.1 NR-ARFCN and channel raster.....	51
5.4.2.1A NB-IoT carrier frequency numbering.....	52
5.4.2.2 Channel raster to resource element mapping.....	52
5.4.2.3 Channel raster entries for each <i>operating band</i>	52
5.4.3 Synchronization raster	58
5.4.3.1 Synchronization raster and numbering.....	58
5.4.3.3 Synchronization raster entries for each operating band.....	59
6 Conducted transmitter characteristics	64
6.1 General	64
6.2 Base station output power	64
6.2.1 General.....	64
6.2.2 Minimum requirement for BS type 1-C.....	65

6.2.3	Minimum requirement for <i>BS type 1-H</i>	65
6.2.4	Additional requirements (regional).....	65
6.3	Output power dynamics.....	66
6.3.1	General.....	66
6.3.2	RE power control dynamic range	66
6.3.2.1	General	66
6.3.2.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	66
6.3.3	Total power dynamic range	66
6.3.3.1	General	66
6.3.3.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	67
6.3.4	NB-IoT RB power dynamic range for NB-IoT operation in NR in-band	67
6.3.4.1	General	67
6.3.4.2	Minimum Requirement	67
6.4	Transmit ON/OFF power	68
6.4.1	Transmitter OFF power	68
6.4.1.1	General	68
6.4.1.2	Minimum requirement for <i>BS type 1-C</i>	68
6.4.1.3	Minimum requirement for <i>BS type 1-H</i>	68
6.4.2	Transmitter transient period	68
6.4.2.1	General	68
6.4.2.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	69
6.4.2.3	Void.....	69
6.5	Transmitted signal quality	69
6.5.1	Frequency error.....	69
6.5.1.1	General	69
6.5.1.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	70
6.5.2	Modulation quality.....	70
6.5.2.1	General	70
6.5.2.2	Minimum Requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	70
6.5.2.3	EVM frame structure for measurement.....	70
6.5.3	Time alignment error	71
6.5.3.1	General	71
6.5.3.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	71
6.6	Unwanted emissions.....	71
6.6.1	General.....	71
6.6.2	Occupied bandwidth	72
6.6.2.1	General	72
6.6.2.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	72
6.6.3	Adjacent Channel Leakage Power Ratio	73
6.6.3.1	General	73
6.6.3.2	Limits and <i>Basic limits</i>	73
6.6.3.3	Minimum requirement for <i>BS type 1-C</i>	76
6.6.3.4	Minimum requirement for <i>BS type 1-H</i>	76
6.6.4	Operating band unwanted emissions	77
6.6.4.1	General	77
6.6.4.2	<i>Basic limits</i>	78
6.6.4.2.1	<i>Basic limits</i> for Wide Area BS (Category A)	78
6.6.4.2.2	<i>Basic limits</i> for Wide Area BS (Category B)	80
6.6.4.2.3	<i>Basic limits</i> for Medium Range BS (Category A and B).....	84
6.6.4.2.4	<i>Basic limits</i> for Local Area BS (Category A and B).....	87
6.6.4.2.4A	<i>Basic limits</i> for Local Area and Medium Range BS for bands n46, n96 and n102 (Category A and B).....	89
6.6.4.2.5	<i>Basic limits</i> for additional requirements	92
6.6.4.3	Minimum requirements for <i>BS type 1-C</i>	94
6.6.4.4	Minimum requirements for <i>BS type 1-H</i>	94
6.6.5	Transmitter spurious emissions.....	95
6.6.5.1	General	95
6.6.5.2	<i>Basic limits</i>	95
6.6.5.2.1	General transmitter spurious emissions requirements	95
6.6.5.2.2	Protection of the BS receiver of own or different BS	96
6.6.5.2.3	Additional spurious emissions requirements	96
6.6.5.2.4	Co-location with other base stations.....	107

6.6.5.3	Minimum requirements for <i>BS type 1-C</i>	113
6.6.5.4	Minimum requirements for <i>BS type 1-H</i>	113
6.7	Transmitter intermodulation	113
6.7.1	General	113
6.7.2	Minimum requirements for <i>BS type 1-C</i>	114
6.7.2.1	Co-location minimum requirements	114
6.7.2.2	Additional requirements	114
6.7.3	Minimum requirements for <i>BS type 1-H</i>	115
6.7.3.1	Co-location minimum requirements	115
6.7.3.2	Intra-system minimum requirements	116
6.7.3.3	Additional requirements	116
7	Conducted receiver characteristics	118
7.1	General	118
7.2	Reference sensitivity level	118
7.2.1	General	118
7.2.2	Minimum requirements for <i>BS type 1-C</i> and <i>BS type 1-H</i>	118
7.3	Dynamic range	124
7.3.1	General	124
7.3.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	124
7.4	In-band selectivity and blocking	136
7.4.1	Adjacent Channel Selectivity (ACS)	136
7.4.1.1	General	136
7.4.1.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	136
7.4.1.3	Void	139
7.4.1.4	Void	139
7.4.2	In-band blocking	139
7.4.2.1	General	139
7.4.2.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	139
7.4.2.3	Void	143
7.4.2.4	Void	143
7.4.2.5	Additional narrowband blocking requirement for Band n100	143
7.5	Out-of-band blocking	143
7.5.1	General	143
7.5.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	144
7.5.3	Co-location minimum requirements for <i>BS type 1-C</i> and <i>BS type 1-H</i>	145
7.5.4	Void	146
7.5.5	Additional out-of-band blocking requirements for the use of RMR bands	146
7.6	Receiver spurious emissions	146
7.6.1	General	146
7.6.2	<i>Basic limits</i>	146
7.6.3	Minimum requirement for <i>BS type 1-C</i>	147
7.6.4	Minimum requirement for <i>BS type 1-H</i>	147
7.7	Receiver intermodulation	148
7.7.1	General	148
7.7.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	148
7.7.3	Additional narrowband intermodulation requirement for Band n100	154
7.8	In-channel selectivity	154
7.8.1	General	154
7.8.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	154
8	Conducted performance requirements	167
8.1	General	167
8.1.1	Scope and definitions	167
8.1.2	Void	167
8.2	Performance requirements for PUSCH	167
8.2.1	Requirements for PUSCH with transform precoding disabled	167
8.2.1.1	General	167
8.2.1.2	Minimum requirements	168
8.2.2	Requirements for PUSCH with transform precoding enabled	177
8.2.2.1	General	177
8.2.2.2	Minimum requirements	178

8.2.3	Requirements for UCI multiplexed on PUSCH	179
8.2.3.1	General	179
8.2.3.2	Minimum requirements	180
8.2.4	Requirements for PUSCH for high speed train	181
8.2.4.1	General	181
8.2.4.2	Minimum requirements	182
8.2.5	Requirements for UL timing adjustment	184
8.2.5.1	Minimum requirements for high speed train	185
8.2.5.2	Minimum requirements for normal mode	186
8.2.6	Requirements for PUSCH 0.001% BLER	187
8.2.6.1	General	187
8.2.6.2	Minimum requirements	187
8.2.7	Requirements for PUSCH repetition Type A	188
8.2.7.1	General	188
8.2.7.2	Minimum requirements	189
8.2.8	Requirements for PUSCH mapping Type B with non-slot transmission	191
8.2.8.1	General	191
8.2.8.2	Minimum requirements	191
8.2.9	Requirements of PUSCH for 2-step RA type	192
8.2.9.1	General	192
8.2.9.2	Minimum requirements	193
8.2.10	Requirements for interlaced PUSCH	193
8.2.10.1	General	193
8.2.10.2	Minimum requirements	194
8.2.11	Performance requirements for CG-UCI multiplexed on interlaced PUSCH	195
8.2.11.1	General	195
8.2.11.2	Minimum requirements	196
8.2.12	Requirements for TB processing over multi-slot PUSCH (TBOMS)	197
8.2.12.1	General	197
8.2.12.2	Minimum requirements	197
8.2.13	Requirements for PUSCH with DM-RS bundling	198
8.2.13.1	General	198
8.2.13.2	Minimum requirements	199
8.3	Performance requirements for PUCCH	204
8.3.1	DTX to ACK probability	204
8.3.1.1	General	204
8.3.1.2	Minimum requirement	204
8.3.2	Performance requirements for PUCCH format 0	205
8.3.2.1	General	205
8.3.2.2	Minimum requirements	205
8.3.3	Performance requirements for PUCCH format 1	206
8.3.3.1	NACK to ACK requirements	206
8.3.3.1.1	General	206
8.3.3.1.2	Minimum requirements	206
8.3.3.2	ACK missed detection requirements	207
8.3.3.2.1	General	207
8.3.3.2.2	Minimum requirements	207
8.3.4	Performance requirements for PUCCH format 2	208
8.3.4.1	ACK missed detection requirements	208
8.3.4.1.1	General	208
8.3.4.1.2	Minimum requirements	208
8.3.4.2	UCI BLER performance requirements	209
8.3.4.2.1	General	209
8.3.4.2.2	Minimum requirements	209
8.3.5	Performance requirements for PUCCH format 3	210
8.3.5.1	General	210
8.3.5.2	Minimum requirements	211
8.3.6	Performance requirements for PUCCH format 4	211
8.3.6.1	General	211
8.3.6.2	Minimum requirement	212
8.3.7	Performance requirements for multi-slot PUCCH	213
8.3.7.1	General	213

8.3.7.2	Performance requirements for multi-slot PUCCH format 1	213
8.3.7.2.1	NACK to ACK requirements	213
8.3.7.2.1.1	General	213
8.3.7.2.1.2	Minimum requirements	214
8.3.7.2.2	ACK missed detection requirements	214
8.3.8	Performance requirements for interlaced PUCCH format 0	214
8.3.8.1	General	214
8.3.8.2	Minimum requirements	215
8.3.9	Performance requirements for interlaced PUCCH format 1	215
8.3.9.1	NACK to ACK requirements	215
8.3.9.1.1	General	215
8.3.9.1.2	Minimum requirements	216
8.3.9.2	ACK missed detection requirements	216
8.3.9.2.1	General	216
8.3.9.2.2	Minimum requirements	216
8.3.10	Performance requirements for interlaced PUCCH format 2	217
8.3.10.1	General	217
8.3.10.2	Minimum requirements	217
8.3.11	Performance requirements for interlaced PUCCH format 3	218
8.3.11.1	General	218
8.3.11.2	Minimum requirements	218
8.3.12	Performance requirements for PUCCH format 1 with DM-RS bundling	219
8.3.12.1	NACK to ACK requirements	219
8.3.12.1.1	General	219
8.3.12.1.2	Minimum requirements	219
8.3.12.2	ACK missed detection requirements	220
8.3.12.2.1	General	220
8.3.12.2.2	Minimum requirements	220
8.3.13	Performance requirements for PUCCH format 3 with DMRS bundling	220
8.3.13.1	General	220
8.3.13.2	Minimum requirements	221
8.3.14	Performance requirements for sub-slot repetition PUCCH format 0	222
8.3.14.1	General	222
8.3.14.2	Minimum requirements	222
8.4	Performance requirements for PRACH	223
8.4.1	PRACH False alarm probability	223
8.4.1.1	General	223
8.4.1.2	Minimum requirement	223
8.4.2	PRACH detection requirements	223
8.4.2.1	General	223
8.4.2.2	Minimum requirements for Normal Mode	223
8.4.2.3	Minimum requirements for high speed train	224
8.4.2.4	Minimum requirements for PRACH with $L_{RA}=1151$ and $L_{RA}=571$	225
9	Radiated transmitter characteristics	227
9.1	General	227
9.2	Radiated transmit power	227
9.2.1	General	227
9.2.2	Minimum requirement for <i>BS type 1-H</i> and <i>BS type 1-O</i>	228
9.2.3	Minimum requirement for <i>BS type 2-O</i>	228
9.3	OTA base station output power	228
9.3.1	General	228
9.3.2	Minimum requirement for <i>BS type 1-O</i>	229
9.3.3	Minimum requirement for <i>BS type 2-O</i>	229
9.3.4	Additional requirements (regional)	229
9.4	OTA output power dynamics	229
9.4.1	General	229
9.4.2	OTA RE power control dynamic range	229
9.4.2.1	General	229
9.4.2.2	Minimum requirement for <i>BS type 1-O</i>	229
9.4.3	OTA total power dynamic range	229
9.4.3.1	General	229

9.4.3.2	Minimum requirement for <i>BS type 1-O</i>	230
9.4.3.3	Minimum requirement for <i>BS type 2-O</i>	230
9.5	OTA transmit ON/OFF power.....	230
9.5.1	General.....	230
9.5.2	OTA transmitter OFF power.....	230
9.5.2.1	General.....	230
9.5.2.2	Minimum requirement for <i>BS type 1-O</i>	230
9.5.2.3	Minimum requirement for <i>BS type 2-O</i>	231
9.5.3	OTA transient period.....	231
9.5.3.1	General.....	231
9.5.3.2	Minimum requirement for <i>BS type 1-O</i>	231
9.5.3.3	Minimum requirement for <i>BS type 2-O</i>	231
9.6	OTA transmitted signal quality.....	231
9.6.1	OTA frequency error.....	231
9.6.1.1	General.....	231
9.6.1.2	Minimum requirement for <i>BS type 1-O</i>	231
9.6.1.3	Minimum requirement for <i>BS type 2-O</i>	232
9.6.2	OTA modulation quality.....	232
9.6.2.1	General.....	232
9.6.2.2	Minimum Requirement for <i>BS type 1-O</i>	232
9.6.2.3	Minimum Requirement for <i>BS type 2-O</i>	232
9.6.2.3.1	EVM frame structure for measurement.....	232
9.6.3	OTA time alignment error.....	232
9.6.3.1	General.....	232
9.6.3.2	Minimum requirement for <i>BS type 1-O</i>	233
9.6.3.3	Minimum requirement for <i>BS type 2-O</i>	233
9.7	OTA unwanted emissions.....	233
9.7.1	General.....	233
9.7.2	OTA occupied bandwidth.....	234
9.7.2.1	General.....	234
9.7.2.2	Minimum requirement for <i>BS type 1-O</i> and <i>BS type 2-O</i>	234
9.7.3	OTA Adjacent Channel Leakage Power Ratio (ACLR).....	235
9.7.3.1	General.....	235
9.7.3.2	Minimum requirement for <i>BS type 1-O</i>	235
9.7.3.3	Minimum requirement for <i>BS type 2-O</i>	235
9.7.4	OTA operating band unwanted emissions.....	237
9.7.4.1	General.....	237
9.7.4.2	Minimum requirement for <i>BS type 1-O</i>	237
9.7.4.2.1	Additional requirements.....	238
9.7.4.2.1.1	Protection of DTT.....	238
9.7.4.2.1.2	Limits in FCC Title 47.....	238
9.7.4.3	Minimum requirement for <i>BS type 2-O</i>	238
9.7.4.3.1	General.....	238
9.7.4.3.2	OTA operating band unwanted emission limits (Category A).....	239
9.7.4.3.3	OTA operating band unwanted emission limits (Category B).....	240
9.7.4.3.4	Additional OTA operating band unwanted emission requirements.....	241
9.7.5	OTA transmitter spurious emissions.....	241
9.7.5.1	General.....	241
9.7.5.2	Minimum requirement for <i>BS type 1-O</i>	241
9.7.5.2.1	General.....	241
9.7.5.2.2	General OTA transmitter spurious emissions requirements.....	242
9.7.5.2.3	Protection of the BS receiver of own or different BS.....	242
9.7.5.2.4	Additional spurious emissions requirements.....	242
9.7.5.2.5	Co-location with other base stations.....	242
9.7.5.3	Minimum requirement for <i>BS type 2-O</i>	242
9.7.5.3.1	General.....	242
9.7.5.3.2	General OTA transmitter spurious emissions requirements.....	243
9.7.5.3.3	Additional OTA transmitter spurious emissions requirements.....	244
9.8	OTA transmitter intermodulation.....	244
9.8.1	General.....	244
9.8.2	Minimum requirement for <i>BS type 1-O</i>	244
9.8.3	Additional requirements (regional).....	245

10	Radiated receiver characteristics	247
10.1	General	247
10.2	OTA sensitivity	248
10.2.1	BS type 1-H and BS type 1-O	248
10.2.1.1	General	248
10.2.1.2	Minimum requirement	248
10.2.2	BS type 2-O	248
10.3	OTA reference sensitivity level	249
10.3.1	General	249
10.3.2	Minimum requirement for BS type 1-O	249
10.3.3	Minimum requirement for BS type 2-O	251
10.4	OTA dynamic range	252
10.4.1	General	252
10.4.2	Minimum requirement for BS type 1-O	252
10.5	OTA in-band selectivity and blocking	265
10.5.1	OTA adjacent channel selectivity	265
10.5.1.1	General	265
10.5.1.2	Minimum requirement for BS type 1-O	265
10.5.1.3	Minimum requirement for BS type 2-O	266
10.5.2	OTA in-band blocking	267
10.5.2.1	General	267
10.5.2.2	Minimum requirement for BS type 1-O	267
10.5.2.3	Minimum requirement for BS type 2-O	270
10.6	OTA out-of-band blocking	271
10.6.1	General	271
10.6.2	Minimum requirement for BS type 1-O	271
10.6.2.1	General minimum requirement	271
10.6.2.2	Co-location minimum requirement	272
10.6.3	Minimum requirement for BS type 2-O	272
10.6.3.1	General minimum requirement	272
10.7	OTA receiver spurious emissions	273
10.7.1	General	273
10.7.2	Minimum requirement for BS type 1-O	273
10.7.3	Minimum requirement for BS type 2-O	274
10.8	OTA receiver intermodulation	275
10.8.1	General	275
10.8.2	Minimum requirement for BS type 1-O	275
10.8.3	Minimum requirement for BS type 2-O	280
10.9	OTA in-channel selectivity	281
10.9.1	General	281
10.9.2	Minimum requirement for BS type 1-O	281
10.9.3	Minimum requirement for BS type 2-O	285
11	Radiated performance requirements	287
11.1	General	287
11.1.1	Scope and definitions	287
11.1.2	OTA demodulation branches	287
11.1.3	Void	288
11.2	Performance requirements for PUSCH	288
11.2.1	Requirements for BS type 1-O	288
11.2.1.1	Requirements for PUSCH with transform precoding disabled	288
11.2.1.2	Requirements for PUSCH with transform precoding enabled	288
11.2.1.3	Requirements for UCI multiplexed on PUSCH	288
11.2.1.4	Requirements for PUSCH for high speed train	288
11.2.1.5	Requirements for UL timing adjustment	288
11.2.1.6	Requirements for PUSCH 0.001% BLER	288
11.2.1.7	Requirements for PUSCH repetition Type A	288
11.2.1.8	Requirements for PUSCH mapping Type B with non-slot transmission	288
11.2.1.9	Requirements for PUSCH for 2-step RA type	288
11.2.1.10	Requirements for interlaced PUSCH	288
11.2.1.11	Requirements for CG-UCI multiplexed on interlaced PUSCH	288
11.2.1.12	Requirements for TB processing over multi-slot PUSCH (TBoMS)	288

11.2.1.13	Requirements for PUSCH with DM-RS bundling	289
11.2.2	Requirements for <i>BS type 2-O</i>	289
11.2.2.1	Requirements for PUSCH with transform precoding disabled	289
11.2.2.1.1	General	289
11.2.2.1.2	Minimum requirements	289
11.2.2.2	Requirements for PUSCH with transform precoding enabled	294
11.2.2.2.1	General	294
11.2.2.2.2	Minimum requirements	294
11.2.2.3	Requirements for UCI multiplexed on PUSCH	295
11.2.2.3.1	General	295
11.2.2.3.2	Minimum requirements	296
11.2.2.4	Requirements for PUSCH for 2-step RA type	298
11.2.2.4.1	General	298
11.2.2.4.2	Minimum requirements	299
11.2.2.5	Requirements for PUSCH repetition Type A.....	299
11.2.2.5.1	General	299
11.2.2.5.2	Minimum requirements	300
11.2.2.6	Requirements for PUSCH mapping Type B with non-slot transmission	301
11.2.2.6.1	General	301
11.2.2.6.2	Minimum requirements	301
11.2.2.7	Requirements for PUSCH for high speed train	302
11.2.2.7.1	General	302
11.2.2.7.2	Minimum requirements	302
11.2.2.8	Requirements for UL timing adjustment.....	303
11.2.2.8.1	General	303
11.2.2.8.2	Minimum requirements for high speed train	304
11.2.2.9	Requirements for TB processing over multi-slot PUSCH (TBoMS)	305
11.2.2.9.1	General	305
11.2.2.9.2	Minimum requirements	305
11.2.2.10	Requirements for PUSCH with DM-RS bundling	306
11.2.2.10.1	General	306
11.2.2.10.2	Minimum requirements	306
11.3	Performance requirements for PUCCH	307
11.3.1	Requirements for <i>BS type 1-O</i>	307
11.3.1.1	DTX to ACK probability	307
11.3.1.2	Performance requirements for PUCCH format 0	307
11.3.1.3	Performance requirements for PUCCH format 1	307
11.3.1.4	Performance requirements for PUCCH format 2	307
11.3.1.5	Performance requirements for PUCCH format 3	307
11.3.1.6	Performance requirements for PUCCH format 4	307
11.3.1.7	Performance requirements for multi-slot PUCCH	307
11.3.1.8	Performance requirements for PUCCH format 1 with DMRS bundling.....	307
11.3.1.9	Performance requirements for PUCCH format 3 with DMRS bundling.....	308
11.3.1.10	Performance requirements for sub-slot repetition PUCCH format 0	308
11.3.2	Requirements for <i>BS type 2-O</i>	308
11.3.2.1	DTX to ACK probability	308
11.3.2.2	Performance requirements for PUCCH format 0.	308
11.3.2.2.1	General	308
11.3.2.2.2	Minimum requirements	308
11.3.2.3	Performance requirements for PUCCH format 1.	309
11.3.2.3.1	NACK to ACK requirements	309
11.3.2.3.1.1	General.....	309
11.3.2.3.1.2	Minimum requirements.....	310
11.3.2.3.2	ACK missed detection requirements	311
11.3.2.3.2.1	General.....	311
11.3.2.3.2.2	Minimum requirements.....	311
11.3.2.4	Performance requirements for PUCCH format 2	312
11.3.2.4.1	ACK missed detection requirements	312
11.3.2.4.1.1	General.....	312
11.3.2.4.1.2	Minimum requirements.....	312
11.3.2.4.2	UCI BLER performance requirements	313
11.3.2.4.2.1	Genera.....	313

11.3.2.4.2.2	Minimum requirements.....	313
11.3.2.5	Performance requirements for PUCCH format 3	314
11.3.2.5.1	General	314
11.3.2.5.2	Minimum requirements	314
11.3.2.6	Performance requirements for PUCCH format 4	315
11.3.2.6.1	General	315
11.3.2.6.2	Minimum requirements	316
11.3.2.7	Performance requirements for PUCCH format 1 with DMRS bundling.....	317
11.3.2.7.1	NACK to ACK requirements	317
11.3.2.7.1.1	General.....	317
11.3.2.7.1.2	Minimum requirements.....	318
11.3.2.7.2	ACK missed detection requirements	318
11.3.2.7.2.1	General.....	318
11.3.2.7.2.2	Minimum requirements.....	319
11.3.2.8	Performance requirements for PUCCH format 3 with DMRS bundling.....	319
11.3.2.8.1	General	319
11.3.2.8.2	Minimum requirements	320
11.4	Performance requirements for PRACH.....	320
11.4.1	Requirements for <i>BS type 1-O</i>	320
11.4.1.1	PRACH False alarm probability	320
11.4.1.2	PRACH detection requirements	320
11.4.2	Requirements for <i>BS type 2-O</i>	320
11.4.2.1	PRACH False alarm probability	320
11.4.2.1.1	General	320
11.4.2.1.2	Minimum requirement.....	320
11.4.2.2	PRACH detection requirements	321
11.4.2.2.1	General	321
11.4.2.2.2	Minimum requirements for Normal mode.....	321
11.4.2.2.3	Minimum requirements for high speed train	322
11.4.2.2.4	Minimum requirements for PRACH with $L_{RA}=1151$ and $L_{RA}=571$	322
11.4.2.2.5	Minimum requirements for multiple PRACH transmission	323

Annex A (normative): Reference measurement channels324

A.1	Fixed Reference Channels for reference sensitivity level, ACS, in-band blocking, out-of-band blocking, receiver intermodulation and in-channel selectivity (QPSK, $R=1/3$).....	324
A.2	Fixed Reference Channels for dynamic range (16QAM, $R=2/3$).....	327
A.3	Fixed Reference Channels for performance requirements (QPSK, $R=193/1024$)	329
A.3A	Fixed Reference Channels for performance requirements (QPSK, $R=99/1024$)	336
A.3B	Fixed Reference Channels for performance requirements (QPSK, $R=308/1024$)	338
A.4	Fixed Reference Channels for performance requirements (16QAM, $R=658/1024$)	342
A.5	Fixed Reference Channels for performance requirements (64QAM, $R=567/1024$)	347
A.6	PRACH Test preambles	350
A.7	Fixed Reference Channels for performance requirements (16QAM, $R=434/1024$)	351
A.8	Fixed Reference Channels for performance requirements (QPSK, $R=157/1024$)	353
A.9	Fixed Reference Channels for performance requirements (256QAM, $R=682.5/1024$)	354
A.10	Fixed Reference Channels for performance requirements (64QAM, $R=517/1024$)	356
A.11	Fixed Reference Channels for performance requirements (64QAM, $R=438/1024$)	360
A.12	Void.....	361

Annex B (normative): Error Vector Magnitude (FR1)363

B.1	Reference point for measurement.....	363
B.2	Basic unit of measurement	363

B.3	Modified signal under test	364
B.4	Estimation of frequency offset	364
B.5	Estimation of time offset	364
B.5.1	General	364
B.5.2	Window length	365
B.6	Estimation of TX chain amplitude and frequency response parameters	366
B.7	Averaged EVM	368
Annex C (normative):	Error Vector Magnitude (FR2)	370
C.1	Reference point for measurement	370
C.2	Basic unit of measurement	370
C.3	Modified signal under test	371
C.4	Estimation of frequency offset	371
C.5	Estimation of time offset	371
C.5.1	General	371
C.5.2	Window length	372
C.6	Estimation of TX chain amplitude and frequency response parameters	373
C.7	Averaged EVM	375
Annex D (normative):	Characteristics of the interfering signals	377
Annex E:	Void	378
Annex F (normative):	Relationship between EIRP based regulatory requirements and 3GPP requirements	379
F.1	General	379
F.2	Relationship between EIRP based regulatory requirements and conducted requirements	379
F.3	Relationship between EIRP based regulatory requirements and OTA requirements	380
Annex G (Normative):	Propagation conditions	381
G.1	Static propagation condition	381
G.2	Multi-path fading propagation conditions	381
G.2.1	Delay profiles	381
G.2.1.1	Delay profiles for FR1	382
G.2.1.2	Delay profiles for FR2	383
G.2.2	Combinations of channel model parameters	385
G.2.3	MIMO Channel Correlation Matrices	386
G.2.3.1	MIMO Correlation Matrices using Uniform Linear Array (ULA)	386
G.2.3.1.1	Definition of MIMO Correlation Matrices	386
G.2.3.1.2	MIMO Correlation Matrices at High, Medium and Low Level	390
G.2.3.2	Multi-Antenna channel models using cross polarized antennas	392
G.2.3.2.1	Definition of MIMO Correlation Matrices using cross polarized antennas	393
G.2.3.2.2	Spatial Correlation Matrices at UE and gNB sides	393
G.2.3.2.2.1	Spatial Correlation Matrices at UE side	393
G.2.3.2.2.2	Spatial Correlation Matrices at gNB side	394
G.2.3.2.3	MIMO Correlation Matrices using cross polarized antennas	394
G.3	High speed train condition	394
G.4	Moving propagation conditions	399
Annex H (informative):	Change history	401

History415

iTeh Standards

(<https://standards.iteh.ai>)

Document Preview

[ETSI TS 138 104 V18.6.0 \(2024-08\)](https://standards.iteh.ai/catalog/standards/etsi/05f412b2-6938-422d-93bd-ff8e02a280fc/etsi-ts-138-104-v18-6-0-2024-08)

<https://standards.iteh.ai/catalog/standards/etsi/05f412b2-6938-422d-93bd-ff8e02a280fc/etsi-ts-138-104-v18-6-0-2024-08>