



SLOVENSKI STANDARD
oSIST prEN ISO 7278-2:2022
01-januar-2022

**Merilni sistemi za nafto - 2. del: Načrtovanje, kalibracija in delovanje merilnika cevi
(ISO/DIS 7278-2:2021)**

Petroleum measurement systems - Part 2: Pipe prover design, calibration and operation
(ISO/DIS 7278-2:2021)

Flüssige Kohlenwasserstoffe - Dynamische Messung - Prüfsysteme für volumetrische
Meßgeräte - Teil 2: Rohrprüfer (ISO/DIS 7278-2:2021)

ITEH STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: prEN ISO 7278-2
oSIST prEN ISO 7278-2:2022
<https://standards.iteh.ai/catalog/standards/sist/378-2022-8509-44cf4b9e37c8/osist-pren-iso-7278-2-2022>

ICS:

75.180.30	Oprema za merjenje prostornine in merjenje	Volumetric equipment and measurements
-----------	---	--

oSIST prEN ISO 7278-2:2022

en,fr,de

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[oSIST prEN ISO 7278-2:2022](https://standards.iteh.ai/catalog/standards/sist/ddf4349e-1949-4e22-8509-44cf4b9e37c8/osist-pren-iso-7278-2-2022)

<https://standards.iteh.ai/catalog/standards/sist/ddf4349e-1949-4e22-8509-44cf4b9e37c8/osist-pren-iso-7278-2-2022>

DRAFT INTERNATIONAL STANDARD

ISO/DIS 7278-2

ISO/TC 28/SC 2

Secretariat: BSI

Voting begins on:
2021-11-18Voting terminates on:
2022-02-10

Petroleum measurement systems —

Part 2: Pipe prover design, calibration and operation

ICS: 75.180.30

iTeh STANDARD PREVIEW

(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/ddf4349e-1949-4e22-8509-44cf4b9e37c8/osist-pren-iso-7278-2-2022>

This document is circulated as received from the committee secretariat.

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

ISO/CEN PARALLEL PROCESSING



Reference number
ISO/DIS 7278-2:2021(E)

© ISO 2021

iTeh STANDARD PREVIEW (standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/ddf4349e-1949-4e22-8509-44cf4b9e37c8/osist-pren-iso-7278-2-2022>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword.....	v
Introduction.....	vi
1 Scope.....	1
2 Normative references.....	1
3 Terms, definitions, symbols and units.....	1
3.1 Terms and definitions.....	1
3.2 Symbols and units.....	7
4 Design classification of pipe provers.....	9
4.1 Common features.....	9
4.2 Sphere provers.....	10
4.2.1 General.....	10
4.2.2 Unidirectional Sphere Provers.....	11
4.2.3 Bidirectional sphere provers.....	12
4.3 Piston provers.....	13
4.3.1 General.....	13
4.3.2 Unidirectional Piston provers.....	14
4.3.3 Bidirectional piston provers.....	14
5 Operational classification of provers.....	14
5.1 General.....	14
5.2 Conventional prover.....	15
5.3 Reduced volume prover.....	16
5.4 Small volume prover (SVP).....	16
6 Design.....	18
6.1 General considerations.....	18
6.2 Prover barrel.....	19
6.2.1 End chambers (Launch and Receive Chambers).....	19
6.2.2 Run-in length.....	20
6.2.3 Prover pipe or barrel.....	20
6.2.4 Internal Finish.....	20
6.3 Small volume piston provers.....	21
6.4 Sizing of provers.....	22
6.4.1 General.....	22
6.4.2 Calibrated volume.....	23
6.4.3 Length between detectors.....	23
6.4.4 Diameter and Velocity.....	24
6.4.5 Pressure loss.....	24
6.5 Displacers.....	25
6.5.1 General.....	25
6.5.2 Spheres.....	25
6.5.3 Pistons.....	26
6.6 Displacer Velocity.....	26
6.6.1 General.....	26
6.6.2 Minimum Velocity.....	26
6.6.3 Maximum Velocity.....	27
6.7 Detectors.....	27
6.8 Prover valves.....	28
6.9 Additional design considerations.....	29
7 Ancillary equipment.....	30
7.1 Temperature and pressure measurement.....	30
7.1.1 Temperature measurement.....	30
7.1.2 Pressure measurement.....	31
7.2 Calibration connections.....	31

ISO/DIS 7278-2:2021(E)

7.3	System control.....	31
8	Pulse interpolation.....	32
9	Installation.....	32
9.1	Mechanical installation.....	32
9.1.1	General.....	32
9.1.2	Fixed Provers.....	35
9.1.3	Mobile Provers.....	36
9.2	Electrical installation.....	36
9.3	Other installation requirements.....	36
10	Traceability.....	37
11	Calibration.....	39
11.1	General.....	39
11.2	Calibration Circuits and equipment.....	39
11.3	Water draw calibration method.....	41
11.3.1	Description.....	41
11.3.2	Volumetric measure as reference.....	42
11.3.3	Gravimetric as reference.....	44
11.4	Master meter calibration method.....	46
11.5	Sequential master meter method.....	49
11.6	Concurrent master meter method.....	50
11.7	Calibration procedures.....	50
12	Operation to prove a flowmeter.....	50
12.1	Setting up a prover.....	50
12.1.1	Mobile prover prior to arrival on site.....	51
12.1.2	Mobile prover on arrival on site.....	51
12.2	Stabilizing temperature.....	51
12.3	Periodical checks of factors affecting accuracy.....	52
12.4	Meter proving operation.....	52
12.5	Preliminary assessment of the results.....	53
12.6	Fault finding.....	54
13	Safety.....	54
13.1	General.....	54
13.2	Permits.....	55
13.3	Opening End Chambers and Removing a Displacer.....	55
13.4	Special Precautions When Proving With LPG.....	55
13.5	Fire precautions.....	56
13.6	Miscellaneous safety precautions.....	56
13.7	Safety records.....	56
	Annex A (Informative) Calculations.....	57
	Annex B (Informative) Selecting a Prover volume for a flowmeter.....	68
	Annex C (Informative) Acceptance criteria and Performance specification.....	70
	Annex D (Informative) Troubleshooting.....	80
	Annex E (Informative) Sphere or detector replacement and twin pairs of detectors.....	86
	Annex F (Informative) Pulse Interpolation.....	88
	Annex G (Informative) Alternative designs.....	92
	Annex H Calibration procedures.....	94
	Annex I (Informative) Example of prover calibration certificate.....	99
	Bibliography.....	104

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html (standards.iteh.ai)

This document was prepared by Technical Committee ISO/TC 28, *Petroleum and related products, fuels and lubricants from natural or synthetic sources*, Subcommittee SC 2, *Measurement of petroleum and related products*.
<https://standards.iteh.ai/catalog/standards/sist/dd4349e-1949-4e22-8509-44cf4b9e37c8/osist-pren-iso-7278-2-2022>

This new edition cancels and replaces the first edition (ISO 7278 -2 1988), which has been technically revised. It also cancels and replaces the first edition of ISO 7278-4, the content of which has been incorporated. The main changes compared to the previous edition are as follows:

- The content and scope now covers the design of pipe provers given in ISO 7278-2 1988 and the guidance for operators given in ISO 7278-4.
- The inclusion of small volume provers as described in FDIS ISO 7278-5 which was not published or now available
- The document now provides guidance on best practice for the design and use of pipe, or displacement, provers, the incorporation of small volume provers, and taking into account alternative standards produced by the American Petroleum Institute (API) and the Energy Institute (EI).
- This edition has been produced in conjunction with the Energy Institute and will be published as a parallel Energy Institute document.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

In the petroleum industry the term 'proving' is used to refer to the calibration of devices used in the measurement of quantities of crude oil and petroleum products. Proving will use defined methods to show, or prove, that the result falls within specified acceptance criteria. Proving provides an assurance that the resultant measurement will provide an acceptable uncertainty for the duty.

A pipe prover, otherwise called a displacement prover, is a volumetric reference device providing a calibration reference standard for flowmeters with an electronic pulsed output. The fluid remains contained within the piping system and proving can be carried out dynamically at various flowrates and pressures without interruption to the flow.

Pipe provers are used extensively within petroleum industry to provide in situ calibration of flowmeters used for fiscal, custody transfer and pipeline integrity applications. They are used with both crude and refined oils but may be used with many other fluids within and outside the petroleum industry.

A pipe prover consists of a length of pipe, a section of which has had its internal volume determined by calibration. A displacer, usually a piston or a tightly fitting sphere or ball, travels along this section of pipe displacing an accurately determined volume of liquid. This volume can be compared with an equivalent volume measured by the flowmeter under test.

The calibrated volume of the prover is defined by detection of the displacer passing along the calibrated section of pipe. Detectors sense the passage of the displacer indicating the start and end of travel through the calibrated section and they trigger the counting of pulses, hence indicated volume measured, from the flowmeter.

Pipe provers are of different designs and are manufactured with a wide range of pipe diameters and volumes. They are available for use as a part of a fiscal measurement system in fixed locations and as mobile reference devices

Any type of flow meter giving a pulsed output may be calibrated however the volume, design and type of the prover may impose limitations on the type and size of meter which would be compatible.

This guide describes the design, construction, calibration and use of pipe provers primarily used for the calibration, proving and verification of flowmeters used for liquid petroleum products and may be applied to other liquid applications requiring a high standard of measurement accuracy.

Petroleum measurement systems —

Part 2:

Pipe prover design, calibration and operation

WARNING — The use of this document may involve hazardous materials, operations and equipment. This document does not purport to address all of the safety problems associated with its use. It is the responsibility of the user of this document to establish appropriate safety and health practices.

1 Scope

The guidance document provides descriptions of the different types of pipe provers, otherwise known as displacement provers, currently in use. These include sphere (ball) provers and piston provers operating in unidirectional and bidirectional forms. It applies to provers operated in conventional, reduced volume, and small volume modes.

The guidance document describes;

- the calibration methods, installation and use of pipe provers of each type.
- the interaction between a pipe prover and different types of flowmeters is described.
- the calculations used to derive the volumes of liquid ([Annex A](#)).
- the expected acceptance criteria for fiscal and custody transfer applications are given as guidance for both the calibration of pipe provers and when proving flowmeters ([Annex C](#)).

The document covers the use of pipe provers for crude oils and light hydrocarbon products which are liquid at ambient conditions. The principles will apply across applications for a wider range of liquids, including water. This includes low vapour pressure, chilled and cryogenic products however use with these products may require additional guidance.

2 Normative references

There are no normative references.

3 Terms, definitions, symbols and units

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

ISO Online browsing platform: available at <https://www.iso.org/obp>

IEC Electropedia: available at <https://www.electropedia.org/>

ISO/DIS 7278-2:2021(E)**3.1.1****accuracy**

closeness of the agreement between a measured quantity value and a true quantity value of a measurand

Note 1 to entry: The concept 'measurement accuracy' is not a quantity and should not be given a numerical value. The quantitative expression of accuracy should be in terms of uncertainty. "Good accuracy" or "more accurate" implies small measurement error. Any given numerical value should be taken as indicative of this.

[SOURCE: VIM:2012; 2.13^[1]]

3.1.2**adjustment**

set of operations carried out on a measuring system so that it provides prescribed indications corresponding to given values of a quantity to be measured

Note 1 to entry: Adjustment should not be confused with calibration which is a prerequisite for adjustment.

Note 2 to entry: After adjustment, a recalibration is usually required.

[SOURCE: VIM:2012; 3.11^[1]]

3.1.3**batch**

the set of consecutive proving runs that is deemed to be necessary to derive both a mean value of volume, meter factor or K-factor, suitable for subsequent use and may also be used as an indication of the repeatability of the measurements.

Note 1 to entry: a batch may consist of multiple runs or one run of a significant number of multiple passes.

3.1.4**block-and-bleed valve**

double-block-and-bleed valve

twin seal valve

high integrity valve with double seals and provision for detecting leakage past either seal

ITeH STANDARD PREVIEW
(standards.iteh.ai)

oSIST prEN ISO 7278-2:2022

[https://standards.iteh.ai/catalog/standards/sist/ddf4349e-1949-4e22-8509-](https://standards.iteh.ai/catalog/standards/sist/ddf4349e-1949-4e22-8509-44c91b9e37c8/osist-pr-en-iso-7278-2-2022)

[44c91b9e37c8/osist-pr-en-iso-7278-2-2022](https://standards.iteh.ai/catalog/standards/sist/ddf4349e-1949-4e22-8509-44c91b9e37c8/osist-pr-en-iso-7278-2-2022)

3.1.5**calibration**

operation that, under specified conditions, in a first step, establishes a relation between the quantity values with measurement uncertainties provided by measurement standards and corresponding indications with associated measurement uncertainties and in a second step uses this information to establish a relation for obtaining a measurement result from an indication

Note 1 to entry: A simplified definition is: set of operations that establish, under specified conditions, the relationship between quantities indicated by an instrument and the corresponding values realized by standards

Note 2 to entry: Calibration should not be confused with adjustment of a measuring system.

Note 3 to entry: The word "proving" is used in the oil industry and has the same meaning but can include a check of the results against specified acceptance criteria.

[SOURCE: VIM:2012; 2.39^[1]]

3.1.6**calibrated volume**

base volume

volume of a prover between detectors, or of a volumetric measure between a top and bottom datum, as determined by calibration and expressed at standard conditions

3.1.7 cavitation

phenomenon related to, and following, *flashing* (3.1.14), where vapour bubbles or voids form and subsequently collapse or implode

Note 1 to entry: Cavitation causes significant measurement error and also potentially causes damage to the pipe, valves and other components meter through erosion.

3.1.8 cyclic distortion

periodic variation in the pulse frequency generated by a meter caused by mechanical asymmetry within the meter and accessories.

Note 1 to entry: See also intra-rotational linearity

Note 2 to entry: Examples of accessories are calibrators and temperature compensators, mechanical or electronic.

3.1.9 detectors

devices set to directly, or indirectly, sense the passage of the displacer hence indicating each end of the calibrated volume.

3.1.10 discrimination

The ability of a measuring instrument to respond to small changes in the value of the input.

3.1.11 displacer

A sphere or a piston used to sweep out the calibrated volume between the detectors of a pipe prover.

3.1.12 correction factor

numerical factor by which the uncorrected result of a measurement at the measured conditions is multiplied

Note 1 to entry: Correction factors to standard conditions are used to convert a volume at observed conditions to the volume at another (standard) condition.

3.1.13 error

measured quantity value minus a reference quantity value

Note 1 to entry: Relative error is error divided by a reference value. This can be expressed as a percentage.

[SOURCE: VIM:2012; 2.16^[1]]

3.1.14 flashing

phenomenon which occurs when the line pressure drops to, or below, the vapour pressure of the liquid, allowing gas to appear from solution or through a component phase change

Note 1 to entry: Vapour pressure of the fluid can increase with increasing temperature.

Note 2 to entry: Flashing is often due to a local pressure drop caused by an increase in liquid velocity, and generally causes significant measurement error.

Note 3 to entry: The free gas produced will remain for a considerable distance downstream of the meter even if pressure recovers.

3.1.15 four-way valve

flow reversal valve

single high-integrity valve which reverses the directional flow passing through a bidirectional prover.

ISO/DIS 7278-2:2021(E)

3.1.16**gating**

the initiation and cessation of pulse totalization in a counter, triggered from an external event or signal from detectors.

3.1.17**interchange valve**

sphere handling valve

a high integrity mechanism to relocate the displacer from the downstream end of a pipe prover to the launch position of a unidirectional sphere prover while preventing flow to pass.

3.1.18**intra-rotational linearity**

quantitative measure of the degree of regularity of spacing between the pulses produced by a flowmeter at a constant flowrate.

Note 1 to entry: to entry. This is generally expressed as the standard deviation of the pulse widths around the mean value.

Note 2 to entry: This may be referred to as inter-pulse deviations.

Note 3 to entry: Inter-rotational linearity is the regularity which repeats in a periodic or cyclic manner normally attributed to the rotation of a meter internal mechanism. This may be referred to as pulse rate modulation.

3.1.19**K-factor**

ratio of the number of pulses obtained from a meter to the quantity passed through the meter

3.1.20**end chamber****launch chamber****receive chamber**

enlarged section at the ends of the pipe prover in which the displacer rests prior to launch or decelerates and comes to rest when received upon completion of a pass.

3.1.21**linearity**

total range of deviation of the accuracy curve from a constant value across a specified measurement range

Note 1 to entry: The maximum deviation is based on the mean of derived values at any one flow point.

Note 2 to entry: The deviation is the largest minus the smallest value of mean values at each flowrate.

Note 3 to entry: Relative linearity is the range of values divided by a specified value, e.g. the independent linearity as defined in ISO 11631^[2].

3.1.22**meter factor**

ratio of the quantity indicated by the reference standard to quantity indicated by the meter

3.1.23**nominal volume**

design volume of a prover or volumetric measure

3.1.24**pass**

single movement of a displacer between two detectors.

3.1.25**pipe prover**

displacement prover

device where a volume of fluid is displaced from a calibrated length of pipe and used to provide a calibration reference for flowmeters

3.1.26**performance indicator**

derived value which may be used to indicate the performance of the meter

Note 1 to entry: Example of performance indicators are ; error, K-factor, or meter factor.

3.1.27**proving**

calibration with comparison to defined acceptance criteria

Note 1 to entry: The term "proving" is used in the oil industry and is similar to verification.

Note 2 to entry: Proving is a calibration, sometimes of limited measurement range, according to methods defined by standards, regulations or procedures, providing a determination of the errors of a device and showing (proving) it performs to defined acceptance criteria.

3.1.28**pulse interpolation**

means of increasing the effective resolution of the pulses output from a meter by multiplying the pulse frequency or measuring the fraction of a pulse associated with the total collected across a time period

Note 1 to entry: The most common method employed is the double timing (chronometry) technique.

3.1.29**pulse interpolation divisor**

ratio of the enhanced pulse frequency to the frequency of the pulses generated by the meter

Note 1 to entry: A pulse interpolation divisor is usually associated with the phase-locked-loop system of pulse interpolation.

3.1.30**range**

measuring range

set of values of flowrate for which the *error* of a measuring instrument (flowmeter) is intended to lie within specified limits

[SOURCE: ISO Guide 99:1993^[3]]

3.1.31**range**

range of values

difference between the maximum and minimum values of a set of values

Note 1 to entry: This can be expressed as a half range (\pm) number. Relative range is normally expressed as a percentage of a specified value e.g. mean, minimum or other calculated value.

3.1.32**reference conditions**

reference conditions of measurement

Operating condition prescribed for evaluating the performance of a measuring instrument

Note 1 to entry: The reference conditions generally include reference values or reference ranges for the influence quantities affecting the measuring instrument.

[SOURCE: VIM:2012; 4.11^[1]]

ISO/DIS 7278-2:2021(E)**3.1.33****reference measure**

volumetric measure calibrated, used and maintained to provide traceability to other volume measures and devices, including pipe provers and reference flowmeters

Note 1 to entry: A reference measure can be calibrated gravimetrically (primary measure) or volumetrically by means of a primary measure which itself has been calibrated gravimetrically.

Note 2 to entry: A reference measure may be a test measure or proving tank as described in ISO 8222; 2020^[4]

3.1.34**repeatability**

measurement precision

closeness of agreement between indications or measured quantity values obtained by replicate measurements under specified conditions

Note 1 to entry: Specified conditions normally implies the same reference, same conditions, same operators and procedures and that the data are obtained sequentially over a short period of time.

Note 2 to entry: Repeatability can be expressed as the range (difference between the maximum and minimum) values of error or K-factor. Alternatively, repeatability can be expressed as a function of the standard deviation of the values.

Note 3 to entry: Dividing repeatability by the mean gives the relative value which can be expressed as a percentage. It is noted some standards suggest dividing by the minimum value.

[SOURCE: VIM:2012; 2.15^[1]]

iTeh STANDARD PREVIEW
(standards.iteh.ai)

3.1.35**resolution**

a quantitative expression of the ability of an indicating device to distinguish meaningfully between closely adjacent values of the quantity indicated.

oSIST prEN ISO 7278-2:2022
<https://standards.iteh.ai/catalog/standards/sist/ddf4349e-1949-4e22-8509-44c4b9e37c8/osist-pren-iso-7278-2-2022>

3.1.36**round-trip**

Movement of the displacer between the detectors of a bi-directional prover that corresponds to a run being a pass in both the forward and reverse directions

3.1.37**round-trip volume**

Sum of the swept volumes in both the forward and reverse directions in a bi-directional pipe prover..

3.1.38**run**

single determination of a prover volume or of a flowmeter meter performance indicator (error, meter factor or K-factor) suitable for reporting.

Note 1 to entry: A run may consist of a single prover pass for a unidirectional prover, two passes of a bidirectional prover or a larger number of consecutive passes for a small volume prover to give single a reportable result.

Note 2 to entry: The individual results within a multi-pass run are not normally reported unless required, but may be recorded and retained for diagnostic purposes.

Note 3 to entry: The repeatability of a multi-pass run may be used to monitor performance is consistent with an acceptance criteria.

3.1.39**run-in length**

length of prover barrel between displacer launch point and the first detector chosen, for the maximum rated flowrate, to ensure the all valves have fully operated, sealed and the flowrate and flowmeter are stable.

3.1.40**standard condition**

base condition

condition of temperature and pressure to which measurements of volume or density are referred to standardize the quantity

Note 1 to entry: These are the specified values of the conditions to which the measured quantity is converted.

Note 2 to entry: For the petroleum industry, these are usually 15 °C, 20 °C or 60 °F and 101,325 kPa.

Note 3 to entry: Standard conditions can refer to the liquid or the volume of the measure. These may be different.

Note 4 to entry: Quantities of volume expressed at standard conditions may be indicated by prefixing the volume unit by "S", e.g. 4 Sm³ or 700 kg/Sm³. This abbreviation is used in place of the unit m³ (standard conditions) where there is limited space and there is no risk of confusion regarding the unit.

Note 5 to entry: Standard conditions should not be confused with the reference (operating) conditions prescribed for evaluating the measure

3.1.41**standard volume**

base volume

volume expressed as being at standard conditions

3.1.42**traceability**

metrological traceability

property of a measuring result whereby the result can be related to a reference through a documented unbroken chain of calibrations, each contributing to the measurement uncertainty

[SOURCE: VIM:2012; 2.41^[1]]

[oSIST prEN ISO 7278-2:2022](https://standards.iteh.ai/catalog/standards/sist/ddf4349e-1949-4e22-8509-44cf4b9e37c8/osist-pren-iso-7278-2-2022)

3.1.43**transfer point**

point or location in a fluid transfer where the quantity and accountability of the fluid passes from one measurement system to another

<https://standards.iteh.ai/catalog/standards/sist/ddf4349e-1949-4e22-8509-44cf4b9e37c8/osist-pren-iso-7278-2-2022>

3.1.44**uncertainty**

non-negative parameter characterizing the dispersion of the quantity values attributed to a measurand based on the information used

[SOURCE: VIM:2012; 2.26^[1]]

Note 1 to entry: The uncertainty is normally expressed as a half width range along with the probability distribution with that range. It can be expressed as a value or as a percentage of the perceived true value.

3.1.45**volumetric measure**

measure used to provide an accurate measurement of volume to provide a reference for other volume measuring devices e.g. pipe provers or flowmeters.

Note 1 to entry: Proving tanks are volumetric measures of larger size with a top and bottom neck.

3.1.46**water-draw**

technique for calibrating a pipe prover or volumetric measure by withdrawing liquid from the prover or measure into a reference measure (volumetric or gravimetric).

3.2 Symbols and units