

SLOVENSKI STANDARD oSIST prEN ISO 22568-4:2021

01-april-2021

Ščitniki nog in stopal - Zahteve in preskusne metode za sestavne dele obutve - 4. del: Nekovinski vložki, odporni proti prediranju (ISO/DIS 22568-4:2021)

Foot and leg protectors - Requirements and test methods for footwear components - Part 4: Non-metallic perforation resistant inserts (ISO/DIS 22568-4:2021)

Fuß- und Beinschutz - Anforderungen und Prüfverfahren für Schuhkomponenten - Teil 4: Nichtmetallische Einlagen mit Widerstand gegen Durchstich (ISO/DIS 22568-4:2021)

Protecteurs du pied et de la jambe - Exigences et méthodes d'essais pour les composants de chaussure - Partie 4: Inserts anti-perforation non métalliques (ISO/DIS 22568-4:2021)

https://standards.iteh.ai/catalog/standards/sist/09c708d1-7b4a-4036-adc1-5b0646a15ef3/osist-pren-iso-22568-4-2021

Ta slovenski standard je istoveten z: prEN ISO 22568-4

ICS:

13.340.50 Varovanje nog in stopal Leg and foot protection

oSIST prEN ISO 22568-4:2021 en,fr,de

oSIST prEN ISO 22568-4:2021

iTeh STANDARD PREVIEW (standards.iteh.ai)

oSIST prEN ISO 22568-4:2021 https://standards.iteh.ai/catalog/standards/sist/09c708d1-7b4a-4036-adc1-5b0646a15ef3/osist-pren-iso-22568-4-2021

DRAFT INTERNATIONAL STANDARD ISO/DIS 22568-4

ISO/TC **94**/SC **3** Secretariat: **BSI**

Voting begins on: Voting terminates on:

2021-02-10 2021-05-05

Foot and leg protectors — Requirements and test methods for footwear components —

Part 4:

Non-metallic perforation resistant inserts

Protecteurs du pied et de la jambe — Exigences et méthodes d'essais pour les composants de chaussure — Partie 4: Inserts anti-perforation non métalliques

ICS: 13.340.50

iTeh STANDARD PREVIEW (standards.iteh.ai)

oSIST prEN ISO 22568-4:2021 https://standards.iteh.ai/catalog/standards/sist/09c708d1-7b4a-4036-adc1-5b0646a15ef3/osist-pren-iso-22568-4-2021

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

This document is circulated as received from the committee secretariat.

ISO/CEN PARALLEL PROCESSING



Reference number ISO/DIS 22568-4:2021(E)

iTeh STANDARD PREVIEW (standards.iteh.ai)

oSIST prEN ISO 22568-4:2021 https://standards.iteh.ai/catalog/standards/sist/09c708d1-7b4a-4036-adc1-5b0646a15ef3/osist-pren-iso-22568-4-2021



COPYRIGHT PROTECTED DOCUMENT

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Contents					
Forew	ord		iv		
Introd	luction	1	v		
1	Scope	3	1		
2	-	ative references			
3	Terms and definitions				
4	Requirements for non-metallic perforation resistant inserts 4.1 General				
	4.2	Resistance to nail perforation			
	4.3	Flexing resistance			
	4.4	Stability against ageing and environmental influence	3		
	4.5	Electrical resistance	3		
5	Test n	nethods for the non-metallic perforation tests	3		
	5.1	Determination of perforation resistance	3		
		5.1.1 Method PL: with conical nail 4,5 mm diameter	3		
	.	5.1.2 Method PS: with conical nail 3.0 mm diameter			
	5.2	Determination of flexing resistance			
		5.2.1 Apparatus 5.2.2 Sampling			
		5.2.3 Test procedure Results Results	5		
		5.2.5 Test report	5		
	5.3	5.2.5 Test reports and arcis item. Test methods for the assessment non-metallic perforation resistant inserts			
		in critical environment 5.3.1 Sampling <u>oSIST prEN ISO 22568-4:2021</u> 5.3.2 https://effect.or.night/emperatureds/sist/09c708d1-7b4a-4036-adc1- 5.3.3 Effect of acid sweat/osist-pren-iso-22568-4-2021	6		
		5.3.1 Sampling <u>0.5151 pt.1 v150 22500-4.2021</u>	6		
		5.3.2 Effort of 500 40x1.5cH/osist-pren-iso-22568-4-2021	6		
		5.3.4 Effect of alkali sweat	6		
		5.3.5 Effect of fuel oil			
		5.3.6 Results			
		5.3.7 Test report	6		
	5.4	Determination of the electrical resistance			
		5.4.1 Testing procedure			
		5.4.2 Test report	8		
6	Mark	ing	8		
Annex	A (no	rmative) Method PL: Perforation resistance with the conical nail 4,5 mm diamet	er9		
Annex	B (no	rmative) Method PS: Perforation resistance with the conical nail 3,0 mm diamete	er13		
Biblio	graphy	y	18		

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html. (standards.iteh.ai)

This document was prepared by Technical Committee ISO/TC 94, *Personal safety* — *Personal protective equipment*, Subcommittee SC 3, *Foot protection*. pren ISO 22568-4:2021 https://standards.itch.ai/catalog/standards/sist/09c708d1-7b4a-4036-adc1-

A list of all parts in the ISO 22568 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

This second edition cancels and replaces the first edition (ISO 22568-4: 2019), which has been technically revised.

The main changes compared to the previous edition are as follows:

- Table 2, changes in the type names from X and Y to PL and PS, new requirements ("tent effect" and minimum value of 950N)
- New nail see Figure B.1 (conical shape instead of pyramidal)
- 3.2 new definition
- Figure B.3 new dimension of the nail
- The annex C and the reference material have been deleted.

Introduction

ISO DIS 20345:2020, ISO DIS 20346:2021 and ISO DIS 20347:2021 are related to safety, protective and occupational footwear which define the performance and required properties of the footwear. On introducing these standards all national standards relating to perforation resistant inserts were withdrawn leaving the manufacturers of these items with no means of demonstrating the performance of their products. This document has been prepared to allow manufacturers to demonstrate the type of the perforation resistant inserts before being inserted into the footwear.

Non-metallic perforation resistant inserts and materials complying with the requirements of this document are suitable components of "PPE footwear".

iTeh STANDARD PREVIEW (standards.iteh.ai)

oSIST prEN ISO 22568-4:2021 https://standards.iteh.ai/catalog/standards/sist/09c708d1-7b4a-4036-adc1-5b0646a15ef3/osist-pren-iso-22568-4-2021 oSIST prEN ISO 22568-4:2021

iTeh STANDARD PREVIEW (standards.iteh.ai)

oSIST prEN ISO 22568-4:2021 https://standards.iteh.ai/catalog/standards/sist/09c708d1-7b4a-4036-adc1-5b0646a15ef3/osist-pren-iso-22568-4-2021

Foot and leg protectors — Requirements and test methods for footwear components —

Part 4:

Non-metallic perforation resistant inserts

1 Scope

This document specifies requirements and test methods for the non-metallic inserts with resistance against mechanical perforation, intended to function as components of PPE footwear (e.g. as described by ISO DIS 20345:2020, ISO DIS 20346:2021and ISO DIS 20347:2020).

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 105-E04:2013, Textiles — Tests for colour fastness 8-4 Part E04: Colour fastness to perspiration

ISO/DIS 20344:2020, Personal protective equipment—Test methods for footwear

ISO/DIS 20345:2020, Personal protective equipment — Safety footwear

ISO/DIS 20346:2020, Personal protective equipment — Protective footwear

ISO/DIS 20347:2020, Personal protective equipment — Occupational footwear

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO DIS 20345:2020, ISO DIS 20346:2020 and ISO DIS 20347:2020 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at https://www.iso.org/obp
- IEC Electropedia: available at http://www.electropedia.org/

3.1

non-metallic perforation resistant insert

non-metallic footwear component placed (or intended to be placed) in the sole complex in order to provide protection against mechanical perforation

3.2

"tent effect"

separation between the layers of the test piece during the testing procedure given procedure of Annex A

4 Requirements for non-metallic perforation resistant inserts

4.1 General

Depending on the footwear construction, the non-metallic perforation resistant inserts could be in contact with the wearer foot, therefore the requirements of ISO DIS 20345:2020, ISO DIS 20346:2020 and ISO DIS 20347:2020 should be taken into account (for example abrasion resistance, water absorption, innocuousness).

Perforation resistant material can be tested in accordance with this document, even in an unshaped status, if it is intended to be cut and/or shaped by the footwear or sole manufacturer. When shaped non-metallic perforation resistant inserts are tested in accordance with this document, their suitability to fit into footwear is not assured, because the dimensional conformity to the footwear depends on the individual shape of each model of footwear.

Property	Subclause	Number of samples	Status		
Resistance to nail	4.2	Non-metallic material: 1 sample	mandatory		
perforation	4.2	Ready –shaped inserts: 1 sample			
		Non-metallic material: 1 sample			
Flexing resistance	4.3	Ready – shaped inserts: 2 different	mandatory		
	iTah ST	AND A D sizes			
Stability against ageing	11011 51	Non-metallic material: 1 sample for			
and environmental	4.4 (S1	andards.itest.ai) Ready -shaped inserts: 1 sample for	mandatory		
influence		SIST or NISO 2358 4 2021			
Electrical resistance	https://st <mark>4r5</mark> ards.iteh.a	/caNon-metallic material: 1 sample 036-add	_{e1-} optional		
NOTE For details, see <u>4.2</u> to <u>4.5</u> . 5b0646a15ef3/osist-pren-iso-22568-4-2021					

Table 1 — Summary of requirements and number of samples

For each of the required measurements performed in accordance with this standard, a corresponding estimate of the uncertainty of measurement should be evaluated. One of the following approaches shall be used:

- a statistical method, e.g. that given in ISO 5725-2^[2];
- a mathematical method, e.g. that given in ISO/IEC Guide 98-3^[4];
- uncertainty and conformity assessment as given in ISO/IEC Guide 98-4^[5];
- ICGM 100:2008^[6].

4.2 Resistance to nail perforation

When the non-metallic perforation resistant inserts are tested in accordance with the applicable methods described in 5.1, they shall meet one of the two types given in Table 2.

Table 2 — Minimum requirements for the p	derioration force
--	-------------------

Types	Test method	Requirements
Type PL	See <u>5.1.1</u>	Perforation test (see <u>A.4</u>); the four results reported shall be "pass" with a force of 1100N
		No "tent effect" shall occur
Type PS	Perforation force (B.4) See 5.1.2 the average value reported shall be greater or equal to 1 100 No single value shall be lower than 950N	

NOTE This property has two types in term of the protection afforded. This covers the degree of risk or hazard that a user will face in terms of the type of working places. Type PS offers more appropriate protection from smaller diameter and sharper objects than type PL

4.3 Flexing resistance

When tested in accordance with the method described in 5.2, the non-metallic perforation resistant insert shall exhibit no visible signs of cracking, disintegration or delamination after having been subjected to 1×10^6 (one million) flexion cycles.

4.4 Stability against ageing and environmental influence

When subjected to each single one of the 4 treatments described in <u>5.3</u> and tested in accordance with the method described in <u>5.1</u>, the non-metallic perforation resistant insert shall conform to the requirements of <u>4.2</u>. **iTeh STANDARD PREVIEW**

4.5 Electrical resistance (standards.iteh.ai)

This property is optional and frequently requested when the non-metallic perforation resistant inserts are supposed to be used in a footwear with electrical properties (ISO DIS 20345:2020, 6.2.2.1 and 6.2.2.2).

5b0646a15eB/osist-pren-iso-22568-4-2021

The results of this test, see 5.4, is given as an information, this document does not fix requirements.

5 Test methods for the non-metallic perforation tests

5.1 Determination of perforation resistance

5.1.1 Method PL: with conical nail 4,5 mm diameter

The test method described in Annex A shall be used.

5.1.2 Method PS: with conical nail 3.0 mm diameter

The test method described in Annex B shall be used.

5.2 Determination of flexing resistance

5.2.1 Apparatus

Flexing apparatus, comprising a suitable flexing guide (e.g. a pair of bars) to move the free end of the non-metallic perforation resistant insert through a specified distance at a defined rate and a clamping device consisting of two elastic interlayers approximately 4 mm thick and of Shore A hardness 75 ± 5 with two metal clamping plates at least 130 mm wide.

In the zero position, the guide acts at a distance of (70 ± 1) mm from the clamping plates (see Figure 1).