



**SLOVENSKI STANDARD**  
**kSIST-TP FprCEN/CLC/TR 17603-20-01:2021**  
**01-julij-2021**

---

**Vesoljska tehnika - Priročnik o pojavu multipaktor**

Space engineering - Multipactor handbook

Raumfahrttechnik - Multipactor-Handbuch

Ingénierie spatiale - Manuel sur la décharge auto-entretenu

**Ta slovenski standard je istoveten z: FprCEN/CLC/TR 17603-20-01**

[kSIST-TP FprCEN/CLC/TR 17603-20-01:2021](https://standards.iteh.ai/catalog/standards/sist/6e835371-9f62-46c0-b59e-0409d49240b9/ksist-tp-fprcen-clc-tr-17603-20-01-2021)

<https://standards.iteh.ai/catalog/standards/sist/6e835371-9f62-46c0-b59e-0409d49240b9/ksist-tp-fprcen-clc-tr-17603-20-01-2021>

**ICS:**

49.140      Vesoljski sistemi in operacije      Space systems and  
operations

**kSIST-TP FprCEN/CLC/TR 17603-20-01:2021**      **en,fr,de**

## **iTeh STANDARD PREVIEW (standards.iteh.ai)**

[kSIST-TP FprCEN/CLC/TR 17603-20-01:2021](https://standards.iteh.ai/catalog/standards/sist/6e835371-9f62-46c0-b59e-0409d49240b9/ksist-tp-fprcen-clc-tr-17603-20-01-2021)

<https://standards.iteh.ai/catalog/standards/sist/6e835371-9f62-46c0-b59e-0409d49240b9/ksist-tp-fprcen-clc-tr-17603-20-01-2021>

TECHNICAL REPORT  
RAPPORT TECHNIQUE  
TECHNISCHER BERICHT

**FINAL DRAFT**  
**FprCEN/CLC/TR 17603-  
20-01**

May 2021

ICS 49.140

English version

## Space engineering - Multipactor handbook

Ingénierie spatiale - Manuel sur la décharge auto-  
entretenu

Raumfahrttechnik - Multipactor-Handbuch

This draft Technical Report is submitted to CEN members for Vote. It has been drawn up by the Technical Committee CEN/CLC/JTC 5.

CEN and CENELEC members are the national standards bodies and national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

**Warning :** This document is not a Technical Report. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a Technical Report.



**CEN-CENELEC Management Centre:**  
**Rue de la Science 23, B-1040 Brussels**

## Table of contents

<b>European Foreword</b>	<b>9</b>
<b>Introduction</b>	<b>10</b>
<b>1 Scope</b>	<b>11</b>
<b>2 References</b>	<b>12</b>
<b>3 Terms, definitions and abbreviated terms</b>	<b>14</b>
3.1 Terms from other documents	14
3.2 Abbreviated terms	15
<b>4 Verification</b>	<b>16</b>
4.1 Verification process	16
4.2 Multipactor verification plan	16
4.2.1 Generation and updating	16
4.2.2 Description	16
4.3 Power requirements	16
4.3.1 General power requirements	16
4.4 Classification of equipment or component type	17
4.4.1 General classification of equipment or component type	17
4.5 Verification routes	20
4.6 Single carrier	20
4.6.1 General	20
4.6.2 Verification by analysis	20
4.6.3 Verification by test	20
4.7 Multicarrier	22
4.7.1 General	22
4.7.2 Verification by analysis	22
4.7.3 Verification by test	22
4.8 Bibliography for clause 4	23
<b>5 Design analysis</b>	<b>24</b>
5.1 Overview	24
5.2 Field analysis	24

5.3	Multipactor design analysis .....	24
5.3.1	Frequency selection .....	24
5.3.2	Design analysis levels .....	24
5.3.3	Available data for Multipactor analysis .....	58
5.4	Bibliography for clause 5.....	62
<b>6</b>	<b>Multipactor - Test conditions.....</b>	<b>64</b>
6.1	Cleanliness .....	64
6.2	Pressure .....	65
6.3	Temperature .....	66
6.4	Signal characteristics .....	67
6.4.1	Applicable bandwidth .....	67
6.4.2	Single-frequency test case .....	67
6.4.3	Multi-frequency test case .....	68
6.4.4	Pulsed testing .....	73
6.5	Electron seeding .....	74
6.5.1	General .....	74
6.5.2	Multipactor test in CW operation .....	74
6.5.3	Multipactor test in pulsed operation .....	74
6.5.4	Multipactor test in multi-carrier operation.....	74
6.5.5	Seeding sources .....	74
6.5.6	Seeding verification .....	82
6.6	Bibliography for clause 6.....	82
<b>7</b>	<b>Multipactor - Methods of detection .....</b>	<b>83</b>
7.1	General.....	83
7.2	Detection methods.....	83
7.2.1	Introduction .....	83
7.2.2	Global detection methods.....	84
7.2.3	Local detection methods .....	86
7.3	Detection method parameters.....	87
7.3.1	Verification .....	87
7.3.2	Sensitivity.....	87
7.3.3	Rise time.....	87
<b>8</b>	<b>Multipactor - test procedure .....</b>	<b>88</b>
8.1	General.....	88
8.2	Test bed configuration .....	89
8.3	Test bed validation.....	89

**FprCEN/CLC/TR 17603-20-01:2021 (E)**

8.3.1	Reference multipactor test .....	89
8.4	Test sequence .....	93
8.4.1	Power profile .....	93
8.5	Acceptance criteria .....	93
8.5.1	Definitions .....	93
8.5.2	Multipactor Free Equipment or component.....	93
8.5.3	Steps in case of Discharges or Events during test.....	93
8.5.4	Investigation of Test Anomalies.....	93
8.6	Test procedure .....	93
8.6.1	Test procedure for high power loads .....	93
8.7	Test reporting .....	97
8.8	Bibliography for clause 8.....	99
<b>9</b>	<b>Secondary electron emission yield requirements .....</b>	<b>100</b>
9.1	General.....	100
9.1.1	SEY definition and properties.....	100
9.1.2	SEY and Multipactor .....	101
9.1.3	Factors affecting SEY .....	102
9.1.4	SEY testing .....	103
9.2	SEY measurements justification .....	106
9.3	Worst case SEY measurement.....	106
9.4	SEY measurements conditions.....	106
9.4.1	Environmental conditions .....	106
9.4.2	SEY test bed conditions .....	115
9.4.3	SEY sample characteristics.....	118
9.5	SEY measurements procedure.....	119
9.5.1	SEY Measurements procedure documents .....	119
9.5.2	SEY measurement calibration.....	119
9.6	ECSS SEY data selection.....	120
9.7	Bibliography for clause 9.....	139
 <b>Figures</b>		
Figure 4-1: Component assembly with consideration of reflection coefficient .....		16
Figure 4-2: Isolator block diagram .....		17
Figure 4-3: Tested component – Coaxial filter .....		18
Figure 4-4: Multipactor simulations and multipactor measurements with and without thermal baking for a RF component with different dielectric materials .....		19
Figure 4-5: Schematic diagram of discharge at a triple point in the inverted voltage gradient configuration with potential contours indicated by colour scale. ....		20

Figure 4-6: Component assembly with consideration of the reflection coefficient of the downstream component assembly for test margin.....	21
Figure 4-7: Power correction with respect to mismatch of the payload downstream component assembly .....	21
Figure 5-1: 2D schematic of a typical iris-like structure .....	25
Figure 5-2: 2D Typical Sombrin chart with fringing field effect for different d/l ratios. ....	27
Figure 5-3: 2D Typical multipactor chart computed with non-stationary theory with fringing field effect for different d/l ratios. ....	28
Figure 5-4: 2D Experimental results corresponding to EVEREST project [5-12] .....	29
Figure 5-5: 2D Experimental results corresponding to ESA-TESAT activity [5-10].....	29
Figure 5-6: 2D Experimental results corresponding to ESA-AURORASAT activity [5-11].....	30
Figure 5-7: 2D Numerical results corresponding to ESA-AURORASAT activity [5-11].	30
Figure 5-8: 2D Analytical results corresponding to ESA-AURORASAT activity [5-11]..	31
Figure 5-9: Fringing field analysis method 1 for L1 analysis type. ....	32
Figure 5-10: Fringing field analysis method 2 for L1 analysis type. ....	33
Figure 5-11: Single-carrier L1 analysis flow diagram. ....	34
Figure 5-12: Schematic network used for multipactor analysis. ....	36
Figure 5-13: Example of multicarrier signal and corresponding pulse approximation. ...	37
Figure 5-14: Electron absorption rate for zero applied voltage.....	38
Figure 5-15: L1 analysis for multicarrier. Pulsed model flow chart.....	39
Figure 5-16: 3D view of Ku-band transformer of ESA TRP activity [5-19] .....	40
Figure 5-17: Pulse amplitude and carrier amplitude vs $t_{on}$ .....	41
Figure 5-18: Example with 3 different “on intervals” corresponding to 10%, 30% and 70% of the envelope period together with the theoretical limit (boundary) .	42
Figure 5-19: 3D of Ku band bandpass filter of ESA TRP activity [5-19].....	43
Figure 5-20: Hybrid L1/L2 multi-carrier analysis steps. ....	45
Figure 5-21: Electron growth over 10 envelope periods for 10 different “on intervals” for one amplitude factor.....	47
Figure 5-22: Convergence of the amplitude factor, showing also how $\Gamma$ converges towards one electron.....	47
Figure 5-23: Hatch and William chart with the multicarrier in-phase amplitude indicated by a green circle. The red dashed line is the fd-product of the average multicarrier frequency and the critical gap size .....	48
Figure 5-24: KS3 sample geometry. ....	49
Figure 5-25: KS3 sample simulated RF performance .....	50
Figure 5-26: 3D view of L-band sample .....	51
Figure 5-27: Predicted S-parameter Performance of Preliminary L-band RF Device Design.....	52
Figure 5-28: Predicted Voltage Distribution in Preliminary L-band RF Device Design..	53

**FprCEN/CLC/TR 17603-20-01:2021 (E)**

Figure 5-29: Predicted S-parameter Performance of Finalised L-band RF Device (1525 MHz) .....	53
Figure 5-30: Predicted Voltage Distribution in Finalised L-band RF Device (1525 MHz) .....	54
Figure 5-31: Predicted S-parameter Performance of Finalised L-band RF Device (1405 MHz) .....	54
Figure 5-32: Predicted Voltage Distribution in Finalised L-band RF Device (1405 MHz) .....	55
Figure 5-33: Variation of peak voltage on each resonator with frequency – 30 MHz design bandwidth .....	56
Figure 5-34: Variation of peak voltage on each resonator with frequency – 10 MHz design bandwidth .....	56
Figure 5-35: Variation of peak voltage on central resonator with bandwidth change ( $F_c = 1525$ MHz) .....	57
Figure 5-36: RF performances with machining tolerances (Resonant reference sample S-3 and S-4).....	58
Figure 5-37: Electric field (12,75 GHz – samples S-3 and S-4).....	59
Figure 5-38: Voltage inside critical gap (samples S-3 and S-4).....	59
Figure 5-39: Nominal model .....	60
Figure 5-40: Re-tuned model.....	61
Figure 5-41: Return Loss nominal (red) and tuned (pink).....	61
Figure 6-1: Work in a clean room environment.....	64
Figure 6-2: Screenshot of clean room monitoring. The pressure reading corresponds to the overpressure delta in the clean room.....	64
Figure 6-3: A pressure gauge.....	65
Figure 6-4: Picture of a typical pressure profile for a P1 component or equipment. ....	65
Figure 6-5: Picture of a typical pressure profile for a P2/P3 component or equipment with pressure spikes related to outgassing.....	66
Figure 6-6: RF cable with thermocouples.....	66
Figure 6-7: RF cable with thermocouples.....	67
Figure 6-8: A multicarrier test facility.....	68
Figure 6-9: Schematic of a three-carrier multipactor test bed.....	68
Figure 6-10: Error probability distributions for different $f \cdot d$ .....	69
Figure 6-11: Error dependency on the similarity degree .....	70
Figure 6-12: Margin definition with respect pulsed model and CW operation.....	71
Figure 6-13: Typical pulse parameters during multipactor test.....	73
Figure 6-14: Decay of Strontium-90.....	75
Figure 6-15: Picture of an encapsulated radioactive source.....	75
Figure 6-16: Sketch of the photoelectric effect.....	77
Figure 6-17: Picture of the UV lamp as part of a test bed.....	77
Figure 6-18: Spectrum of the typical lamps used for electron seeding.....	78



Figure 6-19: Diagram of an electron gun. ....	79
Figure 6-20: Sketch of the functioning of an electron gun. ....	79
Figure 6-21: Picture of an electron gun installed into a test bed. ....	80
Figure 7-1: Schematic of global detection systems implemented in a typical test bed. ....	84
Figure 7-2: Electron probe circuit diagram. ....	86
Figure 8-1: Multipactor test procedure overview. ....	89
Figure 8-2: Example of an L- and S-band reference sample. ....	90
Figure 8-3: Measured S-parameter performance of broadband multipactor sample. ....	91
Figure 8-4: Ku-band Broadband Multipactor Sample. ....	91
Figure 8-5: Multipactor threshold variation vs. gap height. ....	92
Figure 8-6: Ku-band reference sample dimensions. ....	92
Figure 8-7: Heat pipe. ....	94
Figure 9-1: Typical dependence of SEY coefficients on primary electron energy. ....	101
Figure 9-2: Energy distribution curve of emitted electron from gold target surface submitted to 112 eV electron irradiation [9-1] ....	101
Figure 9-3: Experimental arrangement for SEY test with emission collector ....	103
Figure 9-4: SEY experimental setup (without collector around the sample) ....	105
Figure 9-5: Typical composition of exposed to air metal surface. ....	107
Figure 9-6: Measured SEY of metals exposed to air without a specific surface cleaning procedure ....	108
Figure 9-7: Schematic view of material exposed to atmosphere: the case of silver ....	109
Figure 9-8: Effect of cleaning of the surface by heating on the SEY of Nb. ....	110
Figure 9-9: Effect of the water absorption on the SEY. ....	110
Figure 9-10: Effect of baking on the SEY of dielectrics. ....	111
Figure 9-11: Evolution of the SEY of the technical silver versus pressure. ....	112
Figure 9-12: Effect of the temperature on the SEY of silver. Figure extracted from [9- 18]. ....	113
Figure 9-13: Effect of the temperature on the SEY of MgO and BN-SiO <sub>2</sub> ceramics. ....	114
Figure 9-14: Effect of the temperature on the SEY of coverglass and CVD diamond. ....	115
Figure 9-15: Effect of the incidence angle variations on the SEY of silver ....	116
Figure 9-16: Effect of electron irradiation on SEY (CERN). ....	116
Figure 9-17: Influence of the primary electron energy on the charging process. TEEY = SEY, $E_{C1} = E_1$ and $E_{C2} = E_2$ ....	117
Figure 9-18: Influence of the primary electron energy on the charging process, EEY = SEY, $E_{C1} = E_1$ and $E_{C2} = E_2$ ....	118
Figure 9-19: SEY as a function of the primary electron energy for aluminium. ....	120
Figure 9-20: SEY as a function of the primary electron energy for copper ....	121
Figure 9-21: SEY as a function of the primary electron energy for gold ....	121
Figure 9-22: SEY as a function of the primary electron energy for silver coatings. ....	122

**FprCEN/CLC/TR 17603-20-01:2021 (E)**

Figure 9-23: Comparison of the SEY curves for Cu, Al, Ag and Au .....	122
---	-----

**Tables**

Table 4-1: Multipactor simulations and multipactor measurements with and without thermal baking for a RF component with different dielectric materials .....	18
Table 5-1: Characteristics Ku-band transformer of ESA TRP activity [5-19].....	40
Table 5-2: Characteristics Ku-band transformer of ESA TRP activity [5-19].....	43
Table 5-3: Multicarrier signal characteristics.....	43
Table 5-4: Predicted and testes multipactor breakdown levels .....	44
Table 5-5: SEY characteristics of KS3 sample .....	50
Table 5-6: Multipactor thresholds for KS3 sample .....	51
Table 5-7: SEY data for L-band sample.....	57
Table 5-8: Multipactor thresholds for L-band sample .....	57
Table 5-9: Multipactor threshold vs. manufacturing errors (samples S-3 and S-4).....	60
Table 6-1: Error statistics in dB for silver and aluminium, and different values of carriers, frequency band and fxd product .....	69
Table 6-2: Rate and energy of injected electrons going through a particular aluminium wall [6-4].....	76
Table 8-1: Example of Multipactor Test Specification Sheet .....	88
Table 8-2: Maximum RF power applied to the load range (margin in bold). .....	95
Table 8-3: Multipactor test report summary.....	97
Table 8-4: Test setup validation without sample.....	98
Table 8-5: Test setup validation with reference sample .....	98
Table 8-6: Test of DUT at reduced power level at ambient pressure just before closing the vacuum chamber (RECOMMENDED .....	99
Table 9-1: Average values of the main SEY parameters for all “as built” (mentioned, “Before RF testing” in the below table) and all the “as tested” SEY samples (mentioned, “After RF testing” in the below table) for a given SEY measurement facility .....	109
Table 9-2: Requirement in the experimental conditions for SEY measurement .....	119
Table 9-3: SEY parameters of the SEY curves of Al, Cu, Au and Ag samples.....	120
Table 9-4: SEY curve data for aluminium .....	123
Table 9-5: SEY curve data for copper.....	127
Table 9-6: SEY curve data for gold.....	131
Table 9-7: SEY curve data for silver .....	135

## European Foreword

---

This document (FprCEN/CLC/TR 17603-20-01:2021) has been prepared by Technical Committee CEN/CLC/JTC 5 "Space", the secretariat of which is held by DIN.

It is highlighted that this technical report does not contain any requirement but only collection of data or descriptions and guidelines about how to organize and perform the work in support of EN 16603-20-01:2020.

This Technical report (FprCEN/CLC/TR 17603-20-01:2021) originates from ECSS-E-HB-20-01A.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association.

This document has been developed to cover specifically space systems and has therefore precedence over any TR covering the same scope but with a wider domain of applicability (e.g.: aerospace).

**This document is currently submitted to the CEN CONSULTATION.**

**ITih STANDARD PREVIEW**  
**(standards.iteh.ai)**

[kSIST-TP FprCEN/CLC/TR 17603-20-01:2021](https://standards.iteh.ai/catalog/standards/sist/6e835371-9f62-46c0-b59e-0409d49240b9/ksist-tp-fprcen-clc-tr-17603-20-01-2021)  
<https://standards.iteh.ai/catalog/standards/sist/6e835371-9f62-46c0-b59e-0409d49240b9/ksist-tp-fprcen-clc-tr-17603-20-01-2021>

## Introduction

---

Multipactor is a well-understood RF breakdown mechanism in high vacuum conditions. It has been investigated both theoretically and experimentally over many years, as listed in references from [2-1] to [2-7]. Essential ingredient for multipactor is initial free electrons, also called primary electrons. Free electrons can be accelerated under the action of the high power electromagnetic signals inside the RF component. These accelerated electrons impact the RF internal surface with such a kinetic energy to knock out secondary electrons. This resonant process repeats until an avalanche-like growth of electrons is reached, and a multipactor discharge occurs. A multipactor discharge produces signal noise, power reflection and ultimately a local ionization that leads to a complete short circuit. In the worst case, this can develop to a complete system failure.

A typical multipactor event can be described as follows:

1. Free electrons exist within the RF field region of a component whose dimensions are small compared with the electron mean free path as a result of low pressure within the component.
2. The electric field within the component accelerates the free electrons towards a surface.
3. The electrons impact on the surface with appropriate energies to liberate more secondary electrons than the incident ones.
4. Under the specific condition of synchronism of the RF electric field and the electron impact time, resonance conditions are met and steps b. and c. repeat until multipactor discharge occurrence.

Beside the multipactor discharge, other electrical breakdown of different nature in RF components such as multipactor leading to corona due to local outgassing and discharge occurrence in intermediate pressure range can also arise [2-8], [2-9] and [2-10].

**NOTE** The Multipactor Handbook follows the same structure as the Standard. Where the WG has decided that the content of a clause of the Standard needs no supporting material this clause is left empty. The text "*No supporting material needed.*" is added there.

# 1

## Scope

---

This Handbook describes the guidelines and recommendations for the design and test of RF components and equipment to achieve acceptable performance with respect to multipactor-free operation in service in space. This document is the mirror document of the ECSS-ST-20-01 normative document. Thus it includes the same contents as the normative text and has the same structure.

This Handbook is intended to result in the effective design and verification of the multipactor performance of the equipment and consequently in a high confidence in achieving successful product operation.

This Handbook covers multipactor events occurring in all classes of RF satellite components and equipment at all frequency bands of interest. Operation in single carrier CW and pulse modulated mode are included, as well as multi-carrier operations. A detailed chapter on secondary emission yield is also included.

This Handbook does not include breakdown processes caused by collisional processes, such as plasma formation.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[kSIST-TP FprCEN/CLC/TR 17603-20-01:2021](https://standards.iteh.ai/catalog/standards/sist/6e835371-9f62-46c0-b59e-0409d49240b9/ksist-tp-fprcen-clc-tr-17603-20-01-2021)

<https://standards.iteh.ai/catalog/standards/sist/6e835371-9f62-46c0-b59e-0409d49240b9/ksist-tp-fprcen-clc-tr-17603-20-01-2021>

# 2

## References

EN Reference	Reference in text	Title
EN 16601-00-01	ECSS-S-ST-00-01	ECSS system – Glossary of terms
EN 16603-10-02	ECSS-E-ST-10-02	Space engineering – Verification
EN 16603-10-03	ECSS-E-ST-10-03	Space engineering - Testing
EN 16603-20-01	ECSS-E-ST-20-01	Space engineering – Multipactor design and test
EN 16601-10	ECSS-M-ST-10	Space project management – Project planning and implementation
EN 16601-40	ECSS-M-ST-40	Space project management – Configuration and information management
EN 16602-20-08	ECSS-Q-ST-20-08	Space product assurance – Storage, handling and transportation of spacecraft hardware
EN 16602-70-01	ECSS-Q-ST-70-01	Space product assurance – Cleanliness and contamination control
EN 16602-70-02	ECSS-Q-ST-70-02	Space product assurance – Thermal vacuum outgassing test for the screening of space materials
	ESCC-20600	Preservation, packaging and despatch of ESCC component
	ISO 14644-1:2015	Clean rooms and associated controlled environments – Part 1: Classification of air cleanliness by particle concentration

- [2-1] A. Woode & J. Petit, Diagnostic Investigations into the Multipactor Effect, Susceptibility Zone Measurements and Parameters Affecting A Discharge, ESTEC Working Paper 1556, November 1989
- [2-2] Abstract Book, Workshop on Multipactor and Passive Intermodulation Products Problems in Spacecraft Antennas, ESTEC, December 1990
- [2-3] Final Presentations & Working Meeting: Multipactor & PIM in Space RF Hardware, ESTEC, January 1993
- [2-4] A. J. Marrison, R. May, J.D. Sanders, A. D. Dyne, A. D. Rawlins, J. Petit, A study of Multipactor in Multicarrier RF Components, Report no AEA/ TYKB/31761/01/RP/05 Issue 1, January 1997
- [2-5] A. J. Hatch and H.B. Williams, J. Appl. Phys. 25, 417 (1954)
- [2-6] A. J. Hatch and H.B. Williams, Phys. Rev. 112, 681 (1958)
- [2-7] R. Woo, Multipacting Discharges between Coaxial Electrodes, J. Appl. Phys. 39, 1528-1533 (1968)
- [2-8] R. Woo, Final Report on RF Voltage Breakdown in Coaxial Transmission Lines, JPL Technical Report 32-1500, October 1970

- [2-9] F. Höhn, W. Jacob, R. Beckmann, R. Wilhelm, The Transition of a Multipactor to a low-pressure gas discharge, *Phys. Plasma*, 4, 940-944 (1997)
- [2-10] J. M. Meek and J. D. Craggs, *Electrical Breakdown of Gases*, Wiley (1978)

## **iTeh STANDARD PREVIEW** **(standards.iteh.ai)**

[kSIST-TP FprCEN/CLC/TR 17603-20-01:2021](https://standards.iteh.ai/catalog/standards/sist/6e835371-9f62-46c0-b59e-0409d49240b9/ksist-tp-fprcen-clc-tr-17603-20-01-2021)  
<https://standards.iteh.ai/catalog/standards/sist/6e835371-9f62-46c0-b59e-0409d49240b9/ksist-tp-fprcen-clc-tr-17603-20-01-2021>