

INTERNATIONAL
STANDARD

ISO
9206

Third edition
2018-12

**Aerospace — Fixed displacement
hydraulic motors — General
specifications**

*Aéronautique et espace — Moteurs hydrauliques à cylindrée fixe —
Spécifications générales*

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 9206:2018](#)

<https://standards.iteh.ai/catalog/standards/iso/736efa98-6e94-45ea-a8d4-882a69d4e287/iso-9206-2018>



Reference number
ISO 9206:2018(E)

© ISO 2018

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 9206:2018](#)

<https://standards.iteh.ai/catalog/standards/iso/736efa98-6e94-45ea-a8d4-882a69d4e287/iso-9206-2018>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Classification	6
5 General requirements	6
5.1 Order of precedence	6
5.2 Hydraulic system characteristics	7
5.3 Airworthiness regulations	7
5.4 Qualification	7
6 Functional requirements	7
6.1 Hydraulic fluid	7
6.2 Pressures	7
6.2.1 Rated supply pressure	7
6.2.2 Rated differential pressure	7
6.2.3 No-load break-out pressure	8
6.2.4 Motor outlet port pressure	8
6.2.5 Case drain pressure	8
6.3 Flows	8
6.3.1 Rated consumption	8
6.3.2 Case drain flow	8
6.3.3 Shaft seal leakage flow	8
6.3.4 External leakage	9
6.4 Speed and direction of rotation	9
6.4.1 Speed	9
6.5 Torque	12
6.5.1 Rated torque	12
6.5.2 Break-out torque	12
6.5.3 Stalling torque	12
6.5.4 Torque pulsations	12
6.6 Motor overall efficiency	12
6.7 Dynamic characteristics	12
6.7.1 General	12
6.7.2 Dynamic braking	12
6.7.3 Rapid reversals	13
6.8 Passive operation	13
6.9 Rated temperature	13
6.10 Acoustic noise level	13
6.11 Rated endurance	13
6.12 Environmental requirements	14
7 Detail design requirements	14
7.1 Dimensionally critical components	14
7.2 Maintainability features	14
7.3 Seals	14
7.4 Lubrication	15
7.5 Balance	15
7.6 Self-contained failure	15
7.7 Safety wire sealing	15
7.8 Electro-conductive bonding	15
7.9 Marking	15
7.9.1 Nameplate	15
7.9.2 Fluid identification	16

7.9.3	Ports	16
8	Strength requirements	16
8.1	General	16
8.2	Proof pressure	16
8.2.1	Motor case	16
8.2.2	Motor inlet port	16
8.2.3	Motor outlet port	16
8.3	Ultimate pressure	17
8.3.1	Motor case	17
8.3.2	Motor inlet port	17
8.3.3	Motor outlet port	17
8.4	Pressure impulse (fatigue)	17
8.5	Port strength	17
9	Construction requirements	17
9.1	Materials	17
9.1.1	General	17
9.1.2	Metals	18
9.2	Corrosion protection	18
9.2.1	General	18
9.2.2	Ferrous and copper alloys	18
9.2.3	Aluminium alloys	19
9.3	Castings	19
10	Installation requirements	19
10.1	Dimensions	19
10.2	Mass	19
10.3	Mounting	19
10.4	Orientation	20
10.5	Coupling shaft	20
10.6	Ports	20
11	Maintenance requirements	20
11.1	Maintenance concept	20
11.2	Service life limitations and storage specifications	21
12	Reliability requirements	21
12.1	Equipment compliance	21
12.2	Requirements	21
13	Quality assurance provisions	21
13.1	Responsibility for inspection	21
13.2	Classification of tests	21
13.3	Test stand requirements	21
14	Acceptance tests	22
14.1	General	22
14.2	Examination of the product	22
14.3	Test programme	22
14.3.1	General	22
14.3.2	External leakage requirements	23
14.3.3	Break-in run	23
14.3.4	Proof pressure and overspeed tests	23
14.3.5	Operational tests at rated conditions	24
14.3.6	Teardown inspection examination	24
14.3.7	Run-in	24
14.3.8	Performance data	25
14.3.9	Fluid contamination test	25
14.3.10	Electro-conductive bonding	26
14.4	Storage and packaging	26

15	Qualification procedures	26
15.1	General	26
15.2	Qualification procedure	26
15.2.1	Qualification by analogy	26
15.2.2	Motor qualification test report	26
15.2.3	Samples and program of qualification tests	27
15.3	Qualification testing	27
15.3.1	Dimensional check	27
15.3.2	Expanded envelope acceptance tests	28
15.3.3	Overspeed test	28
15.3.4	Operational test at overpressure	28
15.3.5	Calibration	28
15.3.6	Endurance testing	29
15.3.7	Environmental tests	32
15.3.8	Structural tests	33
15.3.9	Supplementary tests	35
	Bibliography	36

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 9206:2018](#)

<https://standards.iteh.ai/catalog/standards/iso/736efa98-6e94-45ea-a8d4-882a69d4e287/iso-9206-2018>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html

This document was prepared by Technical Committee ISO/TC 20, *Aircraft and space vehicles*, Subcommittee SC 10, *Aerospace fluid systems and components*.

This third edition of ISO 9206 cancels and replaces the second edition (ISO 9206:2016) which has been technically revised.

The main changes compared to the previous edition are as follows:

- title replaced “Constant displacement” with “Fixed displacement”;
- deletion of requirement for minimum case drain flow ([6.3.2](#));
- update of external leakage requirements ([6.3.4](#));
- correction of requirement for overspeed ([6.4.1.2](#));
- coupling shaft requirements re-written ([10.5](#));
- the test stand requirements have been revised ([13.3](#));
- requirement to leave the case drain port unplugged in the Inlet port proof pressure test ([14.3.4.3](#)) and the Case port proof pressure test ([14.3.4.4](#));
- update of test procedures in Operational tests at rated conditions ([14.3.5](#));
- revision of the Sampling requirements ([14.3.6.1](#));
- correction of flow measurement in Torque and flow rate ([15.3.5.3](#));
- additional detail provided in the stalling torque and internal leakage test ([15.3.5.7](#));
- endurance test representativity text added ([15.3.6.1](#));
- revision of Endurance test alternating loads test requirements ([15.3.6.1](#) and [15.3.6.3](#));

- revision of filter used for endurance testing ([15.3.6.6](#));
- revision of Recalibration requirements ([15.3.6.9](#));
- correction of low-temperature test requirement ([15.3.7.2](#));
- clarification of motor operation during vibration tests ([15.3.8.1.4](#));
- clarification of resonant frequency vibration test ([15.3.8.1.4](#));
- ports identified for the ultimate pressure test ([15.3.8.5](#)); and
- clarification of coupling shear test ([15.3.8.6](#)).

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

iTeh Standards (<https://standards.iteh.ai>) Document Preview

[ISO 9206:2018](#)

<https://standards.iteh.ai/catalog/standards/iso/736efa98-6e94-45ea-a8d4-882a69d4e287/iso-9206-2018>

Aerospace — Fixed displacement hydraulic motors — General specifications

1 Scope

This document establishes the general requirements for constant displacement hydraulic motors, suitable for use in aircraft hydraulic systems at pressures up to 35 000 kPa (5 000 psi).

Primary and secondary function motors (see [Clause 4](#)) are covered in this document; however, actuators with internal rotation angle limits and low-speed motors are not covered.

This document is to be used in conjunction with the detail specification that is particular to each application.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2093, *Electroplated coatings of tin — Specification and test methods*

ISO 2669, *Environmental tests for aircraft equipment — Steady-state acceleration*

ISO 2671, *Environmental tests for aircraft equipment — Part 3.4 : Acoustic vibration*

ISO 2685, *Aircraft — Environmental test procedure for airborne equipment — Resistance to fire in designated fire zones*

ISO 3323, *Aircraft — Hydraulic components — Marking to indicate fluid for which component is approved*

ISO 3601-1, *Fluid power systems — O-rings — Part 1: Inside diameters, cross-sections, tolerances and designation codes*

ISO 7137, *Aircraft — Environmental conditions and test procedures for airborne equipment*

ISO 7320, *Aerospace — Couplings, threaded and sealed, for fluid systems — Dimensions*

ISO 8078, *Aerospace process — Anodic treatment of aluminium alloys — Sulfuric acid process, undyed coating*

ISO 8079, *Aerospace process — Anodic treatment of aluminium alloys — Sulfuric acid process, dyed coating*

ISO 8081, *Aerospace process — Chemical conversion coating for aluminium alloys — General purpose*

ISO 8399-1, *Aerospace — Accessory drives and mounting flanges (Metric series) — Part 1: Design criteria*

ISO 8399-2, *Aerospace — Accessory drives and mounting flanges (Metric series) — Part 2: Dimensions*

ISO 8625-1, *Aerospace — Fluid systems — Vocabulary — Part 1: General terms and definitions related to pressure*

ISO 8625-2, *Aerospace — Fluid systems — Vocabulary — Part 2: General terms and definitions relating to flow*

ISO 8625-3, *Aerospace — Fluid systems — Vocabulary — Part 3: General terms and definitions relating to temperature*

ISO 11218, *Aerospace — Cleanliness classification for hydraulic fluids*

ISO 16889, *Hydraulic fluid power — Filters — Multi-pass method for evaluating filtration performance of a filter element*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 8625-1, ISO 8625-2, ISO 8625-3, and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

3.1 General

3.1.1

fixed displacement hydraulic motor

mechanical actuator that converts hydraulic pressure and flow into torque and angular velocity (rotation)

3.1.2

purchaser

organization that has the engineering responsibility for the hydraulic system that includes the motor

Note 1 to entry: Typically, the purchaser is an aircraft manufacturer, an equipment manufacturer that has the actuation system responsibility or a modification centre.

Note 2 to entry: The purchaser is responsible for the compilation of the detail specification.

3.1.3

detail specification

[ISO 9206:2018](#)

document compiled by the *purchaser* (3.1.2) that specifies the following: [14-882a69d4e287/iso-9206-2018](#)

- a) technical requirements;
- b) acceptance and qualification test requirements;
- c) reliability requirements;
- d) quality requirements;
- e) packaging requirements; and
- f) other requirements

3.1.4

supplier

organization that provides the motor

Note 1 to entry: Typically, the supplier is the manufacturer of the motor who will be responsible for the design, production, and qualification of the motor.

3.2 Ports of the hydraulic motor

A fixed displacement hydraulic motor typically achieves bi-directional operation by reversing the differential pressure across the inlet/outlet ports, thus reversing the output torque. [Table 1](#) below

illustrates the phasing of the motor ports in relation to the motor operation for this application, using the port identification identifiers listed below.

- port A – motor inlet/outlet port
- port B - motor inlet/outlet port
- port C – motor case drain port
- port D – motor shaft seal port

Table 1 — Phasing of the motor ports in relation to the motor operation

Motor drive coupling shaft rotation	Port A	Port B	Port C	Port D
Clockwise	Motor inlet	Motor return outlet	Case drain	Shaft seal
Counter clockwise	Motor return outlet	Motor inlet	Case drain	Shaft seal

3.2.1

motor inlet port

port that receives flow from the hydraulic system to supply the motor

3.2.2

motor outlet port

port that returns flow back to the system

3.2.3

motor case drain port

port that drains internal leakage flow to the reservoir

3.2.4

shaft seal port

port that routes any shaft seal leakage from the motor to an overboard drain, collector tank, etc.

3.3 Temperature terms

All temperatures are expressed in degrees Celsius.

3.3.1

rated temperature

maximum continuous temperature of the fluid to be supplied at the inlet port of the motor

3.3.2

minimum continuous temperature

minimum temperature of the fluid at the inlet port of the motor at which the motor is able to function

Note 1 to entry: This temperature is generally higher than the survival temperature.

3.3.3

normal operating temperature

temperature of the fluid to be supplied at the inlet port of the motor at which full motor performance is required

3.4 Pressure terms

3.4.1

design operating pressure

normal maximum steady pressure

Note 1 to entry: Excluded are reasonable tolerances, transient pressure effects such as may arise from the following:

- pressure ripple;
- reactions to system functioning; and
- demands that may affect fatigue.

3.4.2

rated supply pressure

system rated pressure, which is normally the hydraulic power generation system design operating pressure (3.4.1)

3.4.3

rated differential pressure

differential pressure measured between the motor inlet and outlet ports required to produce *rated torque* (3.8.1)

3.4.4

no-load break-out pressure

differential pressure required for starting the output shaft, without interruption, with the case drain port at the rated case drain pressure and the outlet port at the rated return pressure

3.4.5 Motor return pressure

3.4.5.1

nominal motor return pressure

pressure generated at the outlet port as the motor returns flow back to the system

<https://standards.iteh.ai/catalog/standards/iso/736efa98-6e94-45ea-a8d4-882a69d4e287/iso-9206-2018>

3.4.5.2

rated motor return pressure

maximum pressure at the outlet port

Note 1 to entry: This is applicable to uni-directional motors only.

Note 2 to entry: This is a stressing term only as the nominal motor pressure is generally considerably less than the rated motor return pressure.

3.4.6 Case drain pressure

3.4.6.1

rated case drain pressure

nominal pressure at which the motor case is required to operate continuously in the system

3.4.6.2

maximum case pressure

maximum of either

- the maximum pressure peak that may be imposed by the hydraulic system on the *motor case drain port* (3.2.3); or
- the pressure resulting from integral bypassing of the rated flow towards the outlet and drain ports in order to take into account the accidental transitory separation of the components