



SLOVENSKI STANDARD
oSIST prEN 1755:2022
01-januar-2022

Vozila za talni transport - Varnostne zahteve in preverjanje - Dodatne zahteve za delovanje v potencialno eksplozivnih atmosferah

Industrial Trucks - Safety requirements and verification - Supplementary requirements for operation in potentially explosive atmospheres

Flurförderzeuge - Sicherheitsanforderungen und Verifizierung - Zusätzliche Anforderungen für den Einsatz in explosionsgefährdeten Bereichen

Chariots de manutention - Prescriptions de sécurité et vérification - Prescriptions supplémentaires pour le fonctionnement en atmosphères explosibles

<https://standards.iteh.ai/catalog/standards/sist/45f1580e-819a-426a-8a0f-18060e16440b/osist-pr-en-1755-2022>

Ta slovenski standard je istoveten z: prEN 1755

ICS:

13.230	Varstvo pred eksplozijo	Explosion protection
53.060	Industrijski tovornjaki	Industrial trucks

oSIST prEN 1755:2022

en,fr,de

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[oSIST prEN 1755:2022](#)

<https://standards.iteh.ai/catalog/standards/sist/45f1580e-819a-426a-8a0f-18060e16440b/osist-pren-1755-2022>

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

DRAFT
prEN 1755

October 2021

ICS 53.060

Will supersede EN 1755:2015

English Version

Industrial Trucks - Safety requirements and verification - Supplementary requirements for operation in potentially explosive atmospheres

Chariots de manutention - Prescriptions de sécurité et
vérification - Prescriptions supplémentaires pour le
fonctionnement en atmosphères explosibles

Flurförderzeuge - Sicherheitsanforderungen und
Verifizierung - Zusätzliche Anforderungen für den
Einsatz in explosionsgefährdeten Bereichen

This draft European Standard is submitted to CEN members for enquiry. It has been drawn up by the Technical Committee CEN/TC 150.

If this draft becomes a European Standard, CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

This draft European Standard was established by CEN in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Warning : This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents	Page
European foreword	4
Introduction	5
1 Scope	7
2 Normative references	7
3 Terms and definitions	10
4 Safety requirements and/or protective measures	13
4.1 General.....	13
4.2 Hot surfaces	14
4.2.1 General.....	14
4.2.2 Temperature monitoring.....	14
4.2.3 Temperature classification	15
4.3 Safety shutdown	15
4.4 Mechanically generated sparks	16
4.4.1 Load handling devices.....	16
4.4.2 Fans of electrical equipment.....	16
4.4.3 Radiator fans on IC-engines	16
4.4.4 Other fans	16
4.4.5 Other rotating parts.....	17
4.5 Electrical system	17
4.5.1 General.....	17
4.5.2 Electrical equipment.....	18
4.5.3 Electrical system bipolarity	19
4.5.4 Insulation monitoring.....	20
4.5.5 Battery and battery connectors.....	20
4.6 Category 3G trucks equipped with restricted breathing enclosures “nR” and gas detection systems	20
4.6.1 General.....	20
4.6.2 Gas detection systems	21
4.6.3 Gas sensors.....	22
4.6.4 Restricted breathing enclosures “nR” in combination with a gas detection system..	23
4.7 Internal combustion engines.....	23
4.8 Electrostatic risks	23
4.8.1 Bonding	23
4.8.2 Circuit resistance	24
4.8.3 Non-conductive parts	24
4.8.4 Transmission belts.....	25
4.8.5 Hydraulic systems	26
4.8.6 Castors and wheels.....	26
4.9 Requirements for brakes, clutches and couplings.....	27
4.9.1 General.....	27
4.9.2 Mechanical clutches and couplings	27
4.9.3 Hydrokinetic clutches	27
4.9.4 Service brakes and friction clutches for category 3G and 3D trucks	28
4.9.5 Service brakes and friction clutches for category 2G trucks.....	28

4.9.6	Service brakes and friction clutches for category 2D trucks	29
4.9.7	Parking brakes	29
4.9.8	Emergency stop brake	29
4.10	Requirements for pneumatic systems	29
4.11	Flammability of non-metallic materials.....	29
5	Verification of safety requirements and/or protective measures.....	30
5.1	Determination of the maximum surface temperatures.....	30
5.1.1	General	30
5.1.2	Test conditions	30
5.1.3	Test procedures	30
5.1.4	Measurements	33
5.2	Measurement of circuit resistance and capacitance.....	34
5.2.1	Verification and tests of circuit resistance and bonding resistance	34
5.2.2	Measurement of capacitance of insulated metal parts	35
6	Information for use.....	35
6.1	General	35
6.2	Instruction handbook	35
6.2.1	Operation of the truck.....	35
6.2.2	Service and maintenance of the truck.....	35
6.2.3	Additional safety information.....	37
6.2.4	Information for charging of the battery and battery handling	37
6.3	Marking.....	38
6.3.1	General	38
6.3.2	Minimum marking.....	38
6.3.3	Additional marking according to this document (Ex - marking).....	38
6.4	Warning labels.....	39
Annex A (normative)	List of significant hazards	40
Annex B (informative)	Relationship between zones (area classification) and truck categories	41
Annex C (informative)	Typical example of cladding of load handling devices.....	42
Annex D (informative)	Typical examples of non-conductive surface areas according to 4.8.3.1.....	44
Annex E (normative)	Requirements for transmission belts in accordance with ISO 9563:2015 or ISO 1813:2014	47
Annex F (informative)	Significant technical changes between this document and the previous edition of this European Standard.....	48
Annex G (informative)	Warning labels for trucks with restricted breathing enclosure(s) in combination with gas detection system	50
Annex ZA (informative)	Relationship between this European Standard and the Essential Requirements of EU Directive 2014/34/EU aimed to be covered	51
Bibliography	54

prEN 1755:2021 (E)**European foreword**

This document (prEN 1755:2021) has been prepared by Technical Committee CEN/TC 150 “Industrial Trucks - Safety”, the secretariat of which is held by BSI.

This document is currently submitted to the CEN Enquiry.

This document will supersede EN 1755:2015.

In comparison with the previous edition, the following technical modifications have been made:

- Inclusion of requirements for driverless trucks;
- Requirements of EN 1175:2020 have been assessed and clarified where appropriate;
- Removal of requirement b) for brake materials as does not represent state of the art in brake material technology;
- Normative standard references updated.

This document has been prepared under a Standardization Request given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s) / Regulation(s).

For relationship with EU Directive(s) / Regulation(s), see informative Annex ZA, which is an integral part of this document.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/45f1580e-819a-426a-8a0f-18060e16440b/osist-pren-1755-2022>

Introduction

This document is a type-C standard as stated in EN ISO 12100:2010.

This document is of relevance, in particular, for the following stakeholder groups representing the market players with regard to machinery safety:

- machine manufacturers (small, medium and large enterprises);
- health and safety bodies (regulators, accident prevention organizations, market surveillance, etc.).

Others can be affected by the level of machinery safety achieved with the means of the document by the above-mentioned stakeholder groups:

- machine users/employers (small, medium and large enterprises);
- machine users/employees (e.g. trade unions, organizations for people with special needs);
- service providers, e.g. for maintenance (small, medium and large enterprises);
- consumers (in case of machinery intended for use by consumers).

The above-mentioned stakeholder groups have been given the possibility to participate at the drafting process of this document.

The machines concerned and the extent to which hazards, hazardous situations or hazardous events are covered are indicated in the Scope of this document.

When requirements of this type-C standard are different from those which are stated in type-A or type B standards, the requirements of this type-C standard take precedence over the requirements of the other standards for machines that have been designed and built according to the requirements of this type-C standard.

This document covers specific safety requirements where industrial trucks will operate in potentially explosive atmospheres that are not covered exhaustively by:

- EN 1459-1:2017+A1:2020 and EN 1459-2:2015+A1:2018;
- ISO 24134:2006;
- EN ISO 3691-1:2015⁵;
- EN ISO 3691-2:2016;
- EN ISO 3691-3:2016;
- EN ISO 3691-4:2020;
- EN ISO 3691-5:2015¹;
- EN ISO 3691-6:2015.

¹ As impacted by EN ISO 3691-5:2015/A1:2020.

prEN 1755:2021 (E)**Assessment of hazards**

The product needs to be designed in such a way that it is fit for its purpose or function and can be adjusted and maintained without putting persons at risk when used under the conditions foreseen by the manufacturer.

In order to properly design a product and to cover all specific safety requirements, the manufacturer needs to identify the hazards that apply to their product and carry out a risk assessment. The manufacturer then needs to design and construct the product taking this assessment into account.

The aim of this procedure is to eliminate the risk of accidents throughout the foreseeable lifetime of the machinery, including the phases of assembling and dismantling where risks of accidents can also arise from foreseeable abnormal situations.

In selecting the most appropriate methods, the manufacturer needs to apply the following principles, in the order given here:

- a) eliminate or reduce risks as far as possible by design (inherently safe machinery design and construction);
- b) take the necessary protective measures in relation to risks that cannot be eliminated by design;
- c) inform users of any shortcoming of the protective measures adopted;
- d) indicate whether any particular training is required;
- e) specify any need to provide personal protection equipment;
- f) refer to the appropriate user's document for proper operating instructions.

Industrial trucks need to be designed to prevent foreseeable misuse wherever possible, if such would engender risk. In other cases, the manufacturer's instructions need to draw the user's attention to ways shown by experience in which the machinery ought not to be used.

This document does not repeat all the technical rules which are state-of-the-art, and which are applicable to the material used to construct the industrial truck. Refer to ISO 12100:2010.

1 Scope

This document applies to self-propelled and pedestrian propelled manual and semi-manual industrial trucks as defined in ISO 5053-1:2020 including their load handling devices and attachments (hereafter referred to as trucks) intended for use in potentially explosive atmospheres.

NOTE 1 Attachments mounted on the load carrier or on fork arms which are removable by the user are not considered to be a part of the truck.

This document specifies supplementary technical requirements for the prevention of the ignition of an explosive atmosphere of flammable gases, vapours, mists or dusts by industrial trucks of equipment group II and equipment category 2G, 3G, 2D or 3D.

NOTE 2 The relationship between an equipment category (hereafter referred to as category) and the corresponding zone (area classification) is shown in informative Annex B.

This document is not applicable to:

- trucks of equipment group I;
- trucks of equipment group II, equipment category 1;
- trucks intended for use in potentially explosive atmospheres with hybrid mixtures;
- protective systems.

This document is not applicable to trucks intended for use in potentially explosive atmospheres of carbon disulphide (CS₂), carbon monoxide (CO) and/or ethylene oxide (C₂H₄O) due to the special properties of these gases.

Technical requirements relating to lithium-ion batteries and fuel cells as energy sources are not given in this document due to their specific hazards.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 1127-1:2019, *Explosive atmospheres - Explosion prevention and protection - Part 1: Basic concepts and methodology*

EN 1149-5:2018, *Protective clothing - Electrostatic properties - Part 5: Material performance and design requirements*

EN 1175:2020, *Safety of industrial trucks - Electrical/electronic requirements*

EN 1459-1:2017+A1:2020, *Rough-terrain trucks - Safety requirements and verification - Part 1: Variable-reach trucks*

EN 1459-2:2015+A1:2018, *Rough-terrain trucks - Safety requirements and verification - Part 2: Slewing variable-reach trucks*

EN 1834-1:2000, *Reciprocating internal combustion engines - Safety requirements for design and construction of engines for use in potentially explosive atmospheres - Part 1: Group II engines for use in flammable gas and vapour atmospheres*

prEN 1755:2021 (E)

EN 1834-3:2000, *Reciprocating internal combustion engines - Safety requirements for design and construction of engines for use in potentially explosive atmospheres - Part 3: Group II engines for use in flammable dust atmospheres*

EN 14986:2017, *Design of fans working in potentially explosive atmospheres*

EN 50271:2018, *Electrical apparatus for the detection and measurement of combustible gases, toxic gases or oxygen - Requirements and tests for apparatus using software and/or digital technologies*

EN 60079-7:2015,² *Explosive atmospheres - Part 7: Equipment protection by increased safety "e" (IEC 60079-7:2015)*

EN 60079-14:2014, *Explosive atmospheres - Part 14: Electrical installations design, selection and erection (IEC 60079-14:2014)*

EN 60079-17:2014, *Explosive atmospheres - Part 17: Electrical installations inspection and maintenance (IEC 60079-17:2013)*

EN 60079-29-1:2016, *Explosive atmospheres - Part 29-1: Gas detectors - Performance requirements of detectors for flammable gases (IEC 60079-29-1:2016)*

EN 60079-29-2:2015, *Explosive atmospheres - Part 29-2: Gas detectors - Selection, installation, use and maintenance of detectors for flammable gases and oxygen (IEC 60079-29-2:2015)*

EN 60079-29-3:2014, *Explosive atmospheres - Part 29-3: Gas detectors - Guidance on functional safety of fixed gas detection systems (IEC 60079-29-3:2014)*

EN 60079-31:2014, *Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure "t" (IEC 60079-31:2013)*

EN 60384-14:2013,³ *Fixed capacitors for use in electronic equipment - Part 14: Sectional specification - Fixed capacitors for electromagnetic interference suppression and connection to the supply mains (IEC 60384-14:2013)*

EN 60529:1991,⁴ *Degrees of protection provided by enclosures (IP Code) (IEC 60529:1989)*

EN 60695-11-10:2013, *Fire hazard testing - Part 11-10: Test flames - 50 W horizontal and vertical flame test methods (IEC 60695-11-10:2013)*

EN 61508-1:2010, *Functional safety of electrical/electronic/programmable electronic safety-related systems - Part 1: General requirements (IEC 61508-1:2010)*

EN 61508-6:2010, *Functional safety of electrical/electronic/programmable electronic safety-related systems - Part 6: Guidelines on the application of IEC 61508-2 and IEC 61508-3 (IEC 61508-6:2010)*

² As impacted by EN 60079-7:2015/A1:2018.

³ As impacted by EN 60384-14:2013/A1:2016.

⁴ As impacted by EN 60529:1991/A1:2000 and EN 60529:1991/A2:2013.

EN IEC 60079-0:2018, *Explosive atmospheres - Part 0: Equipment - General requirements (IEC 60079-0:2017)*

EN IEC 60079-15:2019, *Explosive atmospheres - Part 15: Equipment protection by type of protection "n" (IEC 60079-15:2017)*

EN ISO 284:2012, *Conveyor belts - Electrical conductivity - Specification and test method (ISO 284:2012)*

EN ISO 3691-1:2015,⁵ *Industrial trucks - Safety requirements and verification - Part 1: Self-propelled industrial trucks, other than driverless trucks, variable-reach trucks and burden-carrier trucks (ISO 3691-1:2011)*

EN ISO 3691-4:2020, *Industrial trucks - Safety requirements and verification - Part 4: Driverless industrial trucks and their systems (ISO 3691-4:2020)*

EN ISO 13849-1:2015, *Safety of machinery - Safety-related parts of control systems - Part 1: General principles for design (ISO 13849-1:2015)*

EN ISO 20344:2011, *Personal protective equipment - Test methods for footwear (ISO 20344:2011)*

EN ISO 80079-36:2016, *Explosive atmospheres - Part 36: Non-electrical equipment for explosive atmospheres - Basic method and requirements (ISO 80079-36:2016)*

EN ISO 80079-37:2016, *Explosive atmospheres - Part 37: Non-electrical equipment for explosive atmospheres - Non-electrical type of protection constructional safety "c", control of ignition sources "b", liquid immersion "k" (ISO 80079-37:2016)*

CLC/TR 60079-32-1:2018, *Explosive atmospheres - Part 32-1: Electrostatic hazards, guidance*

IEC/TS 60079-46:2017, *Explosive atmospheres - Part 46: Equipment assemblies*

ISO 1813:2014, *Belt drives — V-ribbed belts, joined V-belts and V-belts including wide section belts and hexagonal belts — Electrical conductivity of antistatic belts: Characteristics and methods of test*

ISO 9563:2015, *Belt drives — Electrical conductivity of antistatic endless synchronous belts — Characteristics and test method*

ISO 15870:2000, *Powered industrial trucks — Safety signs and hazard pictorials — General principles*

⁵ As impacted by EN ISO 3691-1:2015/A1:2020

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <https://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

3.1

explosive atmosphere

mixture with air, under atmospheric conditions, of flammable substances in the form of gases, vapours, mists or dusts in which, after ignition has occurred, combustion spreads to the entire unburned mixture

[SOURCE: EN 13237:2012, 3.28]

3.2

potentially explosive atmosphere

atmosphere which could become explosive due to local and operational conditions

[SOURCE: EN 13237:2012, 3.28.2]

3.3

hybrid mixture

mixture of flammable substances with air in different physical states

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SOURCE: EN 13237:2012, 3.40]

3.4

auto ignition temperature

lowest temperature (of a hot surface) at which under specified test conditions an ignition of a flammable gas or flammable vapour in mixture with air or air/inert gas occurs

oSIST prEN 1755:2022

<https://standards.iteh.ai/catalog/standards/sist/45f1580e-819a-426a-8a0f-18060e16440b/osist-pren-1755-2022>

[SOURCE: EN 13237:2012, 3.45]

3.5

minimum ignition temperature of a dust cloud

lowest temperature of a hot surface on which the most ignitable mixture of the dust with air is ignited under specified test conditions

[SOURCE: EN 13237:2012, 3.45.1]

3.6

minimum ignition temperature of a dust layer

lowest temperature of a hot surface at which ignition occurs in a dust layer under specified test conditions

[SOURCE: EN 13237:2012, 3.45.2]

3.7**service temperature**

maximum or minimum temperature reached at specific points of the equipment when the equipment is operating at rated conditions, including ambient temperature and any external sources of heating or cooling

Note 1 to entry: Each equipment may reach different service temperatures in different parts.

Note 2 to entry: This definition applies to both electrical and non-electrical equipment and components.

[SOURCE: EN IEC 60079-0:2018, 3.79]

3.8**maximum surface temperature**

temperature used for marking of the equipment which is the highest temperature that can be attained in service under the most adverse operating conditions (but within the recognized tolerance) by any part or surface of equipment or protective system or component which can produce an ignition of the surrounding explosive atmosphere with an appropriate safety margin

Note 1 to entry: The manufacturer will prescribe the product standard and also in their particular design they should take into account the following other conditions:

- a) fault conditions specified in the standard for the type of protection concerned;
- b) all operating conditions specified in any other standard specified by him including recognized overloads; any other operating condition specified by him.

Note 2 to entry: The relevant surface temperature may be internal or external depending upon the type of protection concerned.

[oSIST prEN 1755:2022](https://standards.iteh.ai/catalog/standards/sist/45f1580e-819a-426a-8a0f-1880e140e31e/osist-pr-en-1755-2022)

<https://standards.iteh.ai/catalog/standards/sist/45f1580e-819a-426a-8a0f-1880e140e31e/osist-pr-en-1755-2022>

Note 3 to entry: For equipment intended for use in explosive dust atmospheres, the surface temperature is determined without any deposited dust on the equipment. See EN ISO 80079-36:2016, 6.2.7.2.

[SOURCE: EN ISO 80079-36:2016, 3.4]

3.9**wheel**

circular structure able to rotate on an axle, either directly or with the use of bearing(s), with the external part in contact with the ground

[SOURCE: ISO 22877:2004, 1.1.1]

3.10**castor**

assembly comprising a housing, one or more wheels, an axle and, if required, accessories

[SOURCE: ISO 22877:2004, 3.1]

3.11**tyre**

outer part of a wheel, produced from different material from the wheel centre

[SOURCE: ISO 22877:2004, 1.1.6]

prEN 1755:2021 (E)**3.12****service brake**

brake system allowing the operator or driverless control system to control, directly or indirectly, the speed of the truck or to bring the truck to a halt

EXAMPLE The brake can be electrical, hydraulic or mechanical or a combination of the three.

[SOURCE: ISO 6292:2020, 3.9, modified: “braking system” replaced with “brake”, addition of an example]

3.13**restricted breathing enclosure “nR”**

enclosure that is designed to restrict the entry of gases, vapours and mists

[SOURCE: EN IEC 60079-15:2019, 3.3]

3.14**safety function**

function to be implemented by a safety device, which is intended to achieve or maintain a safe state for the equipment under control (EUC), in respect of ignition hazards

Note 1 to entry: See EN 50495 for the definitions of “safety device”, “safe state” and “equipment under control”.

[SOURCE: EN 50495:2010, 3.7, modified, addition of Note 1 to entry]

3.15**safety shutdown**

shutdown of a truck or a piece of equipment activated by a safety function to prevent potential ignition sources from becoming effective

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[oSIST prEN 1755:2022](https://standards.iteh.ai/catalog/standards/sist/45f1580e-819a-426a-8a0f-18060e16440b/osist-pren-1755-2022)

<https://standards.iteh.ai/catalog/standards/sist/45f1580e-819a-426a-8a0f-18060e16440b/osist-pren-1755-2022>

3.16**normal operation**

operation of equipment conforming electrically and mechanically with its design specification and used within the limits specified by the manufacturer

Note 1 to entry: Failures (such as a breakdown of pump seals, flange gaskets or releases of substances caused by accidents) which involve repair or shut-down are not considered to be part of normal operation.

[SOURCE: EN ISO 80079-36:2016, 3.2]

3.17**malfunction**

equipment, protective systems and components do not perform the intended function

[SOURCE: EN ISO 80079-36:2016, 3.3.1, modified, “with respect to explosion protection” deleted]

3.18**expected malfunction**

disturbance or equipment malfunction which normally occur in practice

[SOURCE: EN ISO 80079-36:2016, 3.3.2]

3.19**rare malfunction**

type of malfunction which may happen only in rare instances

[SOURCE: EN ISO 80079-36:2016, 3.3.3]

3.20**earthing strap**

strap made of conductive or dissipative material strong enough to withstand mechanical and chemical influences and installed to achieve potential equalization between truck chassis and the floor/ground

3.21**controlled stop**

condition in which the truck is in a safe stationary state

3.22**highly efficient electrostatic charge generating mechanism**

process that generates a higher rate of electrostatic charge than simple operations

Note 1 to entry: For more information, see EN ISO 80079-36:2016, 6.7.3.

EXAMPLE 1 Rubbing, cleaning with a dry cloth, raising from a seat, walking, wiping of clothes are examples of simple operations

EXAMPLE 2 The flow of insulating liquids or powders, high voltage spray charging, running of transmission belts are examples of highly efficient electrostatic charge generating mechanisms

4 Safety requirements and/or protective measures**4.1 General**

<https://standards.iteh.ai/catalog/standards/sist/45f1580e-819a-426a-8a0f-18060e16440b/osist-pren-1755-2022>

Trucks for use in potentially explosive atmospheres shall comply with the additional requirements given in 4.1 up to and including 4.11.

Where the additional hazards specified in normative Annex A could occur, an ignition hazard assessment in accordance with EN 1127-1:2019 and EN ISO 80079-36:2016 shall be carried out and appropriate measures implemented.

Trucks of Group II shall be subdivided according to the explosive gas atmosphere for which they are intended. See EN IEC 60079-0:2018, 4.3.

Group II subdivisions:

- a) IIA;
- b) IIB;
- c) IIB + H₂;
- d) IIB + C₂H₂ ;
- e) IIB + H₂ + C₂H₂.

NOTE 1 Trucks marked IIB are also suitable for IIA applications.

NOTE 2 Trucks marked IIB+H₂, IIB+C₂H₂ or IIB+H₂+C₂H₂ are also suitable for IIA or IIB applications.