

ETSI TS 124 501 V17.16.0 (2024-10)



5G; Non-Access-Stratum (NAS) protocol for 5G System (5GS); Stage 3 (3GPP TS 24.501 version 17.16.0 Release 17)

[ETSI TS 124 501 V17.16.0 \(2024-10\)](https://standards.iteh.ai/catalog/standards/etsi/afc5beb4-a746-45c3-b668-480025bdd470/etsi-ts-124-501-v17-16-0-2024-10)

<https://standards.iteh.ai/catalog/standards/etsi/afc5beb4-a746-45c3-b668-480025bdd470/etsi-ts-124-501-v17-16-0-2024-10>



ReferenceRTS/TSGC-0124501vhg0

Keywords5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
ETSI [Search & Browse Standards application](#).

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#).

Users should be aware that the present document may be revised or have its status changed,
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2024.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables. (2024-10)

The cross reference between 3GPP and ETSI identities can be found under <https://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document **"shall"**, **"shall not"**, **"should"**, **"should not"**, **"may"**, **"need not"**, **"will"**, **"will not"**, **"can"** and **"cannot"** are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and **"must not"** are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	24
1 Scope	25
2 References	25
3 Definitions and abbreviations.....	29
3.1 Definitions	29
3.2 Abbreviations	40
4 General	43
4.1 Overview	43
4.2 Coordination between the protocols for 5GS mobility management and 5GS session management	43
4.3 UE domain selection	44
4.3.1 UE's usage setting	44
4.3.2 Domain selection for UE originating sessions / calls.....	44
4.3.3 Change of UE's usage setting.....	46
4.3.4 Change or determination of IMS voice availability	46
4.4 NAS security	47
4.4.1 General.....	47
4.4.2 Handling of 5G NAS security contexts.....	47
4.4.2.1 General	47
4.4.2.2 Establishment of a mapped 5G NAS security context during inter-system change from S1 mode to N1 mode in 5GMM-CONNECTED mode.....	50
4.4.2.3 Establishment of a 5G NAS security context during N1 mode to N1 mode handover	51
4.4.2.4 Establishment of an EPS security context during inter-system change from N1 mode to S1 mode in 5GMM-CONNECTED mode	52
4.4.2.5 Establishment of secure exchange of NAS messages	52
4.4.2.6 Change of security keys	54
4.4.3 Handling of NAS COUNT and NAS sequence number	55
4.4.3.1 General	55
4.4.3.2 Replay protection	56
4.4.3.3 Integrity protection and verification.....	56
4.4.3.4 Ciphering and deciphering	56
4.4.3.5 NAS COUNT wrap around	57
4.4.4 Integrity protection of NAS signalling messages.....	57
4.4.4.1 General	57
4.4.4.2 Integrity checking of NAS signalling messages in the UE	58
4.4.4.3 Integrity checking of NAS signalling messages in the AMF	58
4.4.5 Ciphering of NAS signalling messages	60
4.4.6 Protection of initial NAS signalling messages.....	60
4.4.7 Protection of NAS IEs	62
4.5 Unified access control	63
4.5.1 General.....	63
4.5.2 Determination of the access identities and access category associated with a request for access for UEs not operating in SNPN access mode	65
4.5.2A Determination of the access identities and access category associated with a request for access for UEs operating in SNPN access mode	70
4.5.3 Operator-defined access categories.....	75
4.5.4 Access control and checking.....	77
4.5.4.1 Access control and checking in 5GMM-IDLE mode and in 5GMM-IDLE mode with suspend indication.....	77
4.5.4.2 Access control and checking in 5GMM-CONNECTED mode and in 5GMM-CONNECTED mode with RRC inactive indication	79
4.5.5 Exception handling and avoiding double barring	81

4.5.6	Mapping between access categories/access identities and RRC establishment cause	85
4.6	Network slicing	86
4.6.1	General.....	86
4.6.2	Mobility management aspects.....	88
4.6.2.1	General	88
4.6.2.2	NSSAI storage.....	89
4.6.2.3	Provision of NSSAI to lower layers in 5GMM-IDLE mode.....	94
4.6.2.4	Network slice-specific authentication and authorization.....	96
4.6.2.5	Mobility management based network slice admission control.....	97
4.6.2.6	Provision of NSAG information to lower layers.....	98
4.6.3	Session management aspects	99
4.6.3.0	General	99
4.6.3.1	Session management based network slice admission control	100
4.6.3.2	Support of network slice admission control and interworking with EPC	100
4.6.3.3	Session management based network slice data rate limitation control.....	100
4.7	NAS over non-3GPP access	101
4.7.1	General.....	101
4.7.2	5GS mobility management aspects	101
4.7.2.1	General	101
4.7.2.2	Establishment cause for non-3GPP access.....	102
4.7.3	5GS session management aspects.....	103
4.7.4	Limited service state over non-3GPP access	103
4.7.5	NAS signalling using trusted WLAN access network	104
4.8	Interworking with E-UTRAN connected to EPC	104
4.8.1	General.....	104
4.8.2	Single-registration mode.....	105
4.8.2.1	General	105
4.8.2.2	Single-registration mode with N26 interface	105
4.8.2.3	Single-registration mode without N26 interface	105
4.8.2.3.1	Interworking between NG-RAN and E-UTRAN	105
4.8.2.3.2	Interworking between TNGF or N3IWF connected to 5GCN and E-UTRAN.....	107
4.8.3	Dual-registration mode	108
4.8.4	Core Network selection for UEs not using CIoT 5GS optimizations	109
4.8.4A	Core Network selection and redirection for UEs using CIoT optimizations.....	109
4.8.4A.1	Core network selection.....	109
4.8.4A.2	Redirection of the UE by the core network.....	110
4.9	Disabling and re-enabling of UE's N1 mode capability	110
4.9.1	General.....	110
4.9.2	Disabling and re-enabling of UE's N1 mode capability for 3GPP access.....	110
4.9.3	Disabling and re-enabling of UE's N1 mode capability for non-3GPP access.....	113
4.10	Interworking with ePDG connected to EPC.....	113
4.11	UE configuration parameter updates	113
4.12	Access traffic steering, switching and splitting (ATSSS).....	114
4.13	Support of NAS signalling using wireline access network.....	114
4.14	Non-public network.....	115
4.14.1	General.....	115
4.14.2	Stand-alone non-public network	115
4.14.3	Public network integrated non-public network (PNI-NPN).....	117
4.15	Time synchronization and time sensitive communication.....	118
4.15.1	General.....	118
4.15.2	Void	118
4.15.2.1	Void.....	118
4.15.2.2	Void.....	118
4.15.2.3	Void.....	118
4.15.3	Time synchronization	118
4.15.4	User plane node management	118
4.16	UE radio capability signalling optimisation	119
4.17	5GS mobility management in NB-N1 mode	120
4.18	5GS session management in NB-N1 mode	120
4.19	5GS mobility management in WB-N1 mode for IoT	121
4.20	5GS session management in WB-N1 mode for IoT	121
4.21	Authentication and Key Management for Applications (AKMA)	122

4.22	Uncrewed aerial vehicle identification, authentication, and authorization	122
4.22.1	General	122
4.22.2	Authentication and authorization of UAV	122
4.22.3	Authorization of C2 communication	123
4.22.4	Void	124
4.23	NAS over Non-Terrestrial Network	124
4.23.1	General	124
4.23.2	List of "PLMNs not allowed to operate at the present UE location"	124
4.23.3	5GS mobility management via a satellite NG-RAN cell	125
4.23.4	5GS session management via a satellite NG-RAN cell	125
4.23.5	Handling multiple tracking area codes from the lower layers	125
4.24	Minimization of service interruption	126
4.25	Support of MUSIM features	127
5	Elementary procedures for 5GS mobility management	128
5.1	Overview	128
5.1.1	General	128
5.1.2	Types of 5GMM procedures	128
5.1.3	5GMM sublayer states	129
5.1.3.1	General	129
5.1.3.2	5GMM sublayer states	130
5.1.3.2.1	5GMM sublayer states in the UE	130
5.1.3.2.1.1	General	130
5.1.3.2.1.2	Main states	130
5.1.3.2.1.2.1	5GMM-NUL	130
5.1.3.2.1.2.2	5GMM-DEREGISTERED	130
5.1.3.2.1.2.3	5GMM-REGISTERED-INITIATED	130
5.1.3.2.1.2.4	5GMM-REGISTERED	130
5.1.3.2.1.2.5	5GMM-DEREGISTERED-INITIATED	130
5.1.3.2.1.2.6	5GMM-SERVICE-REQUEST-INITIATED	131
5.1.3.2.1.3	Substates of state 5GMM-DEREGISTERED	131
5.1.3.2.1.3.1	General	131
5.1.3.2.1.3.2	5GMM-DEREGISTERED.NORMAL-SERVICE	131
5.1.3.2.1.3.3	5GMM-DEREGISTERED.LIMITED-SERVICE	131
5.1.3.2.1.3.4	5GMM-DEREGISTERED.ATTEMPTING-REGISTRATION	131
5.1.3.2.1.3.5	5GMM-DEREGISTERED.PLMN-SEARCH	131
5.1.3.2.1.3.6	5GMM-DEREGISTERED.NO-SUPI	131
5.1.3.2.1.3.7	5GMM-DEREGISTERED.NO-CELL-AVAILABLE	131
5.1.3.2.1.3.8	5GMM-DEREGISTERED.eCALL-INACTIVE	132
5.1.3.2.1.3.9	5GMM-DEREGISTERED.INITIAL-REGISTRATION-NEEDED	132
5.1.3.2.1.4	Substates of state 5GMM-REGISTERED	132
5.1.3.2.1.4.1	General	132
5.1.3.2.1.4.2	5GMM-REGISTERED.NORMAL-SERVICE	132
5.1.3.2.1.4.3	5GMM-REGISTERED.NON-ALLOWED-SERVICE	132
5.1.3.2.1.4.4	5GMM-REGISTERED.ATTEMPTING-REGISTRATION-UPDATE	132
5.1.3.2.1.4.5	5GMM-REGISTERED.LIMITED-SERVICE	133
5.1.3.2.1.4.6	5GMM-REGISTERED.PLMN-SEARCH	133
5.1.3.2.1.4.7	5GMM-REGISTERED.NO-CELL-AVAILABLE	133
5.1.3.2.1.4.8	5GMM-REGISTERED.UPDATE-NEEDED	133
5.1.3.2.2	5GS update status in the UE	134
5.1.3.2.3	5GMM sublayer states in the network side	134
5.1.3.2.3.1	General	134
5.1.3.2.3.2	5GMM-DEREGISTERED	135
5.1.3.2.3.3	5GMM-COMMON-PROCEDURE-INITIATED	135
5.1.3.2.3.4	5GMM-REGISTERED	135
5.1.3.2.3.5	5GMM-DEREGISTERED-INITIATED	135
5.1.4	Coordination between 5GMM and EMM	135
5.1.4.1	General	135
5.1.4.2	Coordination between 5GMM for 3GPP access and EMM with N26 interface	135
5.1.4.3	Coordination between 5GMM for 3GPP access and EMM without N26 interface	136
5.1.5	Coordination between 5GMM and GMM	136
5.2	Behaviour of the UE in state 5GMM-DEREGISTERED and state 5GMM-REGISTERED	136

5.2.1	General.....	136
5.2.2	UE behaviour in state 5GMM-DEREGISTERED	136
5.2.2.1	General.....	136
5.2.2.2	Primary substate selection.....	137
5.2.2.2.1	Selection of the substate after power on.....	137
5.2.2.3	Detailed description of UE behaviour in state 5GMM-DEREGISTERED.....	137
5.2.2.3.1	NORMAL-SERVICE.....	137
5.2.2.3.2	LIMITED-SERVICE.....	138
5.2.2.3.3	ATTEMPTING-REGISTRATION	138
5.2.2.3.4	PLMN-SEARCH.....	139
5.2.2.3.5	NO-SUPI.....	139
5.2.2.3.6	NO-CELL-AVAILABLE	139
5.2.2.3.7	eCALL-INACTIVE.....	139
5.2.2.3.8	INITIAL-REGISTRATION-NEEDED	139
5.2.2.4	Substate when back to state 5GMM-DEREGISTERED from another 5GMM state	139
5.2.3	UE behaviour in state 5GMM-REGISTERED	140
5.2.3.1	General.....	140
5.2.3.2	Detailed description of UE behaviour in state 5GMM-REGISTERED	140
5.2.3.2.1	NORMAL-SERVICE.....	140
5.2.3.2.2	NON-ALLOWED-SERVICE	140
5.2.3.2.3	ATTEMPTING-REGISTRATION-UPDATE	141
5.2.3.2.4	LIMITED-SERVICE.....	142
5.2.3.2.5	PLMN-SEARCH.....	142
5.2.3.2.6	NO-CELL-AVAILABLE	142
5.2.3.2.7	UPDATE-NEEDED	142
5.3	General on elementary 5GMM procedures	143
5.3.1	5GMM modes and N1 NAS signalling connection	143
5.3.1.1	Establishment of the N1 NAS signalling connection.....	143
5.3.1.2	Re-establishment of the N1 NAS signalling connection.....	144
5.3.1.3	Release of the N1 NAS signalling connection	146
5.3.1.4	5GMM-CONNECTED mode with RRC inactive indication.....	149
5.3.1.5	Suspend and resume of the N1 NAS signalling connection.....	152
5.3.2	Permanent identifiers.....	153
5.3.3	Temporary identities	156
5.3.4	Registration areas.....	157
5.3.5	Service area restrictions	158
5.3.5.1	General.....	158
5.3.5.2	3GPP access service area restrictions.....	158
5.3.5.3	Wireline access service area restrictions.....	162
5.3.6	Mobile initiated connection only mode	163
5.3.7	Handling of the periodic registration update timer and mobile reachable timer	164
5.3.8	Handling of timer T3502	166
5.3.9	Handling of NAS level mobility management congestion control	166
5.3.10	Handling of DNN based congestion control.....	167
5.3.11	Handling of S-NSSAI based congestion control.....	167
5.3.12	Handling of local emergency numbers	168
5.3.12A	Handling of local emergency numbers received via 3GPP access and non-3GPP access	169
5.3.12A.1	General.....	169
5.3.12A.2	Receiving a REGISTRATION ACCEPT message via non-3GPP access.....	169
5.3.13	Lists of 5GS forbidden tracking areas.....	170
5.3.13A	Forbidden PLMN lists	171
5.3.14	List of equivalent PLMNs.....	171
5.3.15	Transmission failure abnormal case in the UE	171
5.3.16	Extended DRX cycle for UEs in 5GMM-IDLE and 5GMM-CONNECTED mode with RRC inactive indication	171
5.3.17	Service Gap Control.....	172
5.3.18	Restriction on use of enhanced coverage.....	174
5.3.19	Handling of congestion control for transport of user data via the control plane	175
5.3.19a	Specific requirements for UE configured to use timer T3245	175
5.3.19a.1	UE not operating in SNPN access operation mode	175
5.3.19a.2	UE operating in SNPN access operation mode.....	176
5.3.20	Specific requirements for UE when receiving non-integrity protected reject messages	176

5.3.20.1	General	176
5.3.20.2	Requirements for UE in a PLMN.....	176
5.3.20.3	Requirements for UE in an SNPN.....	181
5.3.21	CIoT 5GS optimizations	184
5.3.22	Interaction between MICO mode with active time and extended idle mode DRX cycle	187
5.3.23	Forbidden wireline access area	187
5.3.24	WUS assistance	187
5.3.25	Paging Early Indication with Paging Subgrouping Assistance	188
5.4	5GMM common procedures.....	189
5.4.1	Primary authentication and key agreement procedure	189
5.4.1.1	General	189
5.4.1.2	EAP based primary authentication and key agreement procedure	189
5.4.1.2.1	General	189
5.4.1.2.2	EAP-AKA' related procedures.....	192
5.4.1.2.3	EAP-TLS related procedures.....	198
5.4.1.2.3A	Procedures related to EAP methods other than EAP-AKA' and EAP-TLS	203
5.4.1.2.3B	Procedures related to EAP methods used for primary authentication of an N5GC device.....	207
5.4.1.2.4	EAP message reliable transport procedure	208
5.4.1.2.4.3	EAP message reliable transport procedure accepted by the UE.....	209
5.4.1.2.5	EAP result message transport procedure	211
5.4.1.3	5G AKA based primary authentication and key agreement procedure	212
5.4.1.3.1	General	212
5.4.1.3.2	Authentication initiation by the network	213
5.4.1.3.3	Authentication response by the UE	213
5.4.1.3.4	Authentication completion by the network.....	214
5.4.1.3.5	Authentication not accepted by the network.....	215
5.4.1.3.6	Authentication not accepted by the UE	217
5.4.1.3.7	Abnormal cases	218
5.4.2	Security mode control procedure	222
5.4.2.1	General	222
5.4.2.2	NAS security mode control initiation by the network.....	222
5.4.2.3	NAS security mode command accepted by the UE.....	225
5.4.2.4	NAS security mode control completion by the network	228
5.4.2.5	NAS security mode command not accepted by the UE.....	228
5.4.2.6	Abnormal cases in the UE	228
5.4.2.7	Abnormal cases on the network side	229
5.4.3	Identification procedure	229
5.4.3.1	General	229
5.4.3.2	Identification initiation by the network.....	229
5.4.3.3	Identification response by the UE	230
5.4.3.4	Identification completion by the network	230
5.4.3.5	Abnormal cases in the UE	230
5.4.3.6	Abnormal cases on the network side	230
5.4.4	Generic UE configuration update procedure.....	231
5.4.4.1	General	231
5.4.4.2	Generic UE configuration update procedure initiated by the network	235
5.4.4.3	Generic UE configuration update accepted by the UE.....	239
5.4.4.4	Generic UE configuration update completion by the network	245
5.4.4.5	Abnormal cases in the UE	245
5.4.4.6	Abnormal cases on the network side	246
5.4.5	NAS transport procedure(s)	248
5.4.5.1	General	248
5.4.5.2	UE-initiated NAS transport procedure	248
5.4.5.2.1	General	248
5.4.5.2.2	UE-initiated NAS transport procedure initiation	249
5.4.5.2.3	UE-initiated NAS transport of messages accepted by the network	251
5.4.5.2.4	UE-initiated NAS transport of messages not accepted by the network	255
5.4.5.2.5	Abnormal cases on the network side	258
5.4.5.2.6	Abnormal cases in the UE	262
5.4.5.3	Network-initiated NAS transport procedure	264
5.4.5.3.1	General	264
5.4.5.3.2	Network-initiated NAS transport procedure initiation	265

5.4.5.3.3	Network-initiated NAS transport of messages	269
5.4.6	5GMM status procedure	274
5.4.6.1	General	274
5.4.6.2	5GMM status received in the UE	275
5.4.6.3	5GMM status received in the network	275
5.4.7	Network slice-specific authentication and authorization procedure	275
5.4.7.1	General	275
5.4.7.2	Network slice-specific EAP message reliable transport procedure	276
5.4.7.2.1	Network slice-specific EAP message reliable transport procedure initiation	276
5.4.7.2.2	Network slice-specific EAP message reliable transport procedure accepted by the UE	277
5.4.7.2.3	Abnormal cases on the network side	277
5.4.7.2.4	Abnormal cases in the UE	277
5.4.7.3	Network slice-specific EAP result message transport procedure	278
5.4.7.3.1	Network slice-specific EAP result message transport procedure initiation	278
5.5	5GMM specific procedures	278
5.5.1	Registration procedure	278
5.5.1.1	General	278
5.5.1.2	Registration procedure for initial registration	280
5.5.1.2.1	General	280
5.5.1.2.2	Initial registration initiation	280
5.5.1.2.3	5GMM common procedure initiation	288
5.5.1.2.4	Initial registration accepted by the network	288
5.5.1.2.5	Initial registration not accepted by the network	309
5.5.1.2.6	Initial registration for emergency services not accepted by the network	322
5.5.1.2.6A	Initial registration for initiating an emergency PDU session not accepted by the network	323
5.5.1.2.7	Abnormal cases in the UE	324
5.5.1.2.8	Abnormal cases on the network side	326
5.5.1.3	Registration procedure for mobility and periodic registration update	328
5.5.1.3.1	General	328
5.5.1.3.2	Mobility and periodic registration update initiation	328
5.5.1.3.3	5GMM common procedure initiation	341
5.5.1.3.4	Mobility and periodic registration update accepted by the network	342
5.5.1.3.5	Mobility and periodic registration update not accepted by the network	368
5.5.1.3.6	Mobility and periodic registration update for initiating an emergency PDU session not accepted by the network	382
5.5.1.3.6A	Mobility and periodic registration update for an emergency services fallback not accepted by the network	383
5.5.1.3.7	Abnormal cases in the UE	383
5.5.1.3.8	Abnormal cases on the network side	387
5.5.2	De-registration procedure	390
5.5.2.1	General	390
5.5.2.2	UE-initiated de-registration procedure	392
5.5.2.2.1	UE-initiated de-registration procedure initiation	392
5.5.2.2.2	UE-initiated de-registration procedure completion	392
5.5.2.2.3	UE-initiated de-registration procedure completion for 5GS services over 3GPP access	393
5.5.2.2.4	UE-initiated de-registration procedure completion for 5GS services over non-3GPP access	393
5.5.2.2.5	UE-initiated de-registration procedure completion for 5GS services over both 3GPP access and non-3GPP access	393
5.5.2.2.6	Abnormal cases in the UE	394
5.5.2.2.7	Abnormal cases in the network side	396
5.5.2.3	Network-initiated de-registration procedure	396
5.5.2.3.1	Network-initiated de-registration procedure initiation	396
5.5.2.3.2	Network-initiated de-registration procedure completion by the UE	398
5.5.2.3.3	Network-initiated de-registration procedure completion by the network	409
5.5.2.3.4	Abnormal cases in the UE	409
5.5.2.3.5	Abnormal cases in the network side	409
5.5.3	eCall inactivity procedure	411
5.5.4	Authentication and key agreement procedure for 5G ProSe UE-to-network relay	411
5.5.4.1	General	411
5.5.4.2	ProSe relay transaction identity (PRTI)	412
5.5.4.3	UE-initiated authentication and key agreement procedure initiation	412
5.5.4.4	UE-initiated authentication and key agreement procedure accepted by the network	413

5.5.4.5	UE-initiated authentication and key agreement procedure not accepted by the network.....	414
5.5.4.6	Abnormal cases in the UE.....	414
5.5.4.7	Abnormal cases on the network side.....	414
5.6	5GMM connection management procedures.....	415
5.6.1	Service request procedure.....	415
5.6.1.1	General.....	415
5.6.1.2	Service request procedure initiation.....	419
5.6.1.2.1	UE is not using 5GS services with control plane CIoT 5GS optimization.....	419
5.6.1.2.2	UE is using 5GS services with control plane CIoT 5GS optimization.....	421
5.6.1.3	Common procedure initiation.....	424
5.6.1.4	Service request procedure accepted by the network.....	424
5.6.1.4.1	UE is not using 5GS services with control plane CIoT 5GS optimization.....	424
5.6.1.4.2	UE is using 5GS services with control plane CIoT 5GS optimization.....	428
5.6.1.5	Service request procedure not accepted by the network.....	432
5.6.1.6	Service request procedure for initiating an emergency PDU session not accepted by the network....	444
5.6.1.6A	Service request procedure for an emergency services fallback not accepted by the network.....	445
5.6.1.7	Abnormal cases in the UE.....	445
5.6.1.8	Abnormal cases on the network side.....	449
5.6.2	Paging procedure.....	450
5.6.2.1	General.....	450
5.6.2.2	Paging for 5GS services.....	451
5.6.2.2.1	General.....	451
5.6.2.2.2	Abnormal cases on the network side.....	453
5.6.2.2.3	Abnormal cases in the UE.....	453
5.6.3	Notification procedure.....	454
5.6.3.1	General.....	454
5.6.3.2	Notification procedure initiation.....	454
5.6.3.3	Notification procedure completion.....	456
5.6.3.4	Abnormal cases on the network side.....	457
5.6.3.5	Abnormal cases on the UE side.....	457
6	Elementary procedures for 5GS session management.....	457
6.1	Overview.....	457
6.1.1	General.....	457
6.1.2	Types of 5GSM procedures.....	458
6.1.3	5GSM sublayer states.....	459
6.1.3.1	General.....	459
6.1.3.2	5GSM sublayer states in the UE.....	459
6.1.3.2.1	Overview.....	459
6.1.3.2.2	PDU SESSION INACTIVE.....	459
6.1.3.2.3	PDU SESSION ACTIVE PENDING.....	459
6.1.3.2.4	PDU SESSION ACTIVE.....	459
6.1.3.2.5	PDU SESSION INACTIVE PENDING.....	460
6.1.3.2.6	PDU SESSION MODIFICATION PENDING.....	460
6.1.3.2.7	PROCEDURE TRANSACTION INACTIVE.....	460
6.1.3.2.8	PROCEDURE TRANSACTION PENDING.....	460
6.1.3.3	5GSM sublayer states in the network side.....	460
6.1.3.3.1	Overview.....	460
6.1.3.3.2	PDU SESSION INACTIVE.....	461
6.1.3.3.3	PDU SESSION ACTIVE.....	461
6.1.3.3.4	PDU SESSION INACTIVE PENDING.....	461
6.1.3.3.5	PDU SESSION MODIFICATION PENDING.....	461
6.1.3.3.6	PROCEDURE TRANSACTION INACTIVE.....	461
6.1.3.3.7	PROCEDURE TRANSACTION PENDING.....	461
6.1.4	Coordination between 5GSM and ESM.....	462
6.1.4.1	Coordination between 5GSM and ESM with N26 interface.....	462
6.1.4.2	Coordination between 5GSM and ESM without N26 interface.....	475
6.1.4a	Coordination between 5GSM and SM.....	477
6.1.5	Coordination for interworking with ePDG connected to EPC.....	477
6.2	General on elementary 5GSM procedures.....	478
6.2.1	Principles of PTI handling for 5GSM procedures.....	478
6.2.2	PDU session types.....	479

6.2.3	PDU session management	480
6.2.4	IP address allocation	480
6.2.4.1	General	480
6.2.4.2	IP address allocation via NAS signalling	481
6.2.4.3	Additional RG related requirements for IP address allocation	481
6.2.4.4	Additional requirements of the UE acting as 5G ProSe layer-3 UE-to-network relay UE for IP address allocation	482
6.2.5	Quality of service	482
6.2.5.1	General	482
6.2.5.1.1	QoS rules	482
6.2.5.1.1.1	General	482
6.2.5.1.1.2	Signalled QoS rules	482
6.2.5.1.1.3	Derived QoS rules	484
6.2.5.1.1.4	QoS flow descriptions	484
6.2.5.1.2	Session-AMBR	485
6.2.5.1.2A	Void	485
6.2.5.1.3	UL user data packet matching	485
6.2.5.1.4	Reflective QoS	485
6.2.5.1.4.1	General	485
6.2.5.1.4.2	Derivation of packet filter for UL direction from DL user data packet	486
6.2.5.1.4.3	Creating a derived QoS rule by reflective QoS in the UE	488
6.2.5.1.4.4	Updating a derived QoS rule by reflective QoS in the UE	488
6.2.5.1.4.5	Deleting a derived QoS rule in the UE	488
6.2.5.1.4.6	Ignoring RQI in the UE	489
6.2.5.2	QoS in MA PDU session	489
6.2.6	Local area data network (LADN)	489
6.2.7	Handling of DNN based congestion control	490
6.2.8	Handling of S-NSSAI based congestion control	491
6.2.9	Interaction with upper layers	494
6.2.9.1	General	494
6.2.9.2	URSP	494
6.2.9.3	ProSeP	494
6.2.10	Handling of 3GPP PS data off	494
6.2.11	Multi-homed IPv6 PDU session	496
6.2.12	Handling of network rejection not due to congestion control	496
6.2.13	Handling of Small data rate control	499
6.2.14	Handling of Serving PLMN rate control	499
6.2.15	Handling of Reliable Data Service	500
6.2.16	Handling of header compression for control plane CIoT optimizations	500
6.2.17	Handling of edge computing enhancements	500
6.2.18	Support of redundant PDU sessions	501
6.3	Network-requested 5GSM procedures	502
6.3.1	PDU session authentication and authorization procedure	502
6.3.1.1	General	502
6.3.1.2	PDU EAP message reliable transport procedure	504
6.3.1.2.1	PDU EAP message reliable transport procedure initiation	504
6.3.1.2.2	PDU EAP message reliable transport procedure accepted by the UE	505
6.3.1.2.3	Abnormal cases on the network side	506
6.3.1.2.4	Abnormal cases in the UE	506
6.3.1.3	PDU EAP result message transport procedure	506
6.3.1.3.1	PDU EAP result message transport procedure initiation	506
6.3.1.3.2	Abnormal cases in the UE	507
6.3.1A	Service-level authentication and authorization procedure	507
6.3.1A.1	General	507
6.3.1A.2	Service-level authentication and authorization procedure initiation	508
6.3.1A.3	Service-level authentication and authorization procedure accepted by the UE	509
6.3.1A.4	Abnormal cases on the network side	509
6.3.1A.5	Abnormal cases in the UE	509
6.3.2	Network-requested PDU session modification procedure	509
6.3.2.1	General	509
6.3.2.2	Network-requested PDU session modification procedure initiation	510
6.3.2.3	Network-requested PDU session modification procedure accepted by the UE	515

6.3.2.4	Network-requested PDU session modification procedure not accepted by the UE.....	523
6.3.2.5	Abnormal cases on the network side	528
6.3.2.6	Abnormal cases in the UE	529
6.3.3	Network-requested PDU session release procedure	529
6.3.3.1	General	529
6.3.3.2	Network-requested PDU session release procedure initiation	529
6.3.3.3	Network-requested PDU session release procedure accepted by the UE	532
6.3.3.4	N1 SM delivery skipped.....	541
6.3.3.5	Abnormal cases on the network side	541
6.3.3.6	Abnormal cases in the UE	541
6.4	UE-requested 5GSM procedures.....	542
6.4.1	UE-requested PDU session establishment procedure	542
6.4.1.1	General	542
6.4.1.2	UE-requested PDU session establishment procedure initiation	542
6.4.1.3	UE-requested PDU session establishment procedure accepted by the network	552
6.4.1.4	UE-requested PDU session establishment procedure not accepted by the network.....	566
6.4.1.4.1	General	566
6.4.1.4.2	Handling of network rejection due to congestion control.....	569
6.4.1.4.3	Handling of network rejection not due to congestion control.....	576
6.4.1.5	Handling the maximum number of established PDU sessions.....	583
6.4.1.5A	Handling the maximum number of allowed active user-plane resources for PDU sessions of UEs in NB-N1 mode	585
6.4.1.6	Abnormal cases in the UE	585
6.4.1.7	Abnormal cases on the network side	587
6.4.2	UE-requested PDU session modification procedure.....	588
6.4.2.1	General	588
6.4.2.2	UE-requested PDU session modification procedure initiation.....	589
6.4.2.3	UE-requested PDU session modification procedure accepted by the network	594
6.4.2.4	UE-requested PDU session modification procedure not accepted by the network	594
6.4.2.4.1	General	594
6.4.2.4.2	Handling of network rejection due to congestion control.....	595
6.4.2.4.3	Handling of network rejection not due to congestion control.....	602
6.4.2.5	Abnormal cases in the UE	605
6.4.2.6	Abnormal cases on the network side	606
6.4.3	UE-requested PDU session release procedure	607
6.4.3.1	General	607
6.4.3.2	UE-requested PDU session release procedure initiation	607
6.4.3.3	UE-requested PDU session release procedure accepted by the network.....	608
6.4.3.4	UE-requested PDU session release procedure not accepted by the network.....	608
6.4.3.5	Abnormal cases in the UE	609
6.4.3.6	Abnormal cases on the network side	610
6.5	5GSM status procedure	610
6.5.1	General.....	610
6.5.2	5GSM status received in the UE	611
6.5.3	5GSM status received in the SMF	611
6.6	Miscellaneous procedures	611
6.6.1	Exchange of extended protocol configuration options.....	611
6.6.2	Remote UE report procedure	612
6.6.2.1	General	612
6.6.2.2	Remote UE report procedure initiation	612
6.6.2.3	Remote UE report procedure accepted by the network.....	613
6.6.2.4	Abnormal cases in the UE	613
6.6.2.5	Abnormal cases on the network side	613
7	Handling of unknown, unforeseen, and erroneous protocol data	614
7.1	General	614
7.2	Message too short or too long	614
7.2.1	Message too short	614
7.2.2	Message too long	614
7.3	Unknown or unforeseen procedure transaction identity or PDU Session identity.....	614
7.3.1	Procedure transaction identity.....	614
7.3.2	PDU Session identity.....	615

7.4	Unknown or unforeseen message type	616
7.5	Non-semantical mandatory information element errors	616
7.5.1	Common procedures	616
7.5.2	5GS mobility management	617
7.5.3	5GS session management	617
7.6	Unknown and unforeseen IEs in the non-imperative message part.....	618
7.6.1	IEs unknown in the message	618
7.6.2	Out of sequence IEs	618
7.6.3	Repeated IEs	618
7.7	Non-imperative message part errors.....	618
7.7.1	Syntactically incorrect optional IEs	618
7.7.2	Conditional IE errors	618
7.8	Messages with semantically incorrect contents	619
8	Message functional definitions and contents.....	619
8.1	Overview	619
8.2	5GS mobility management messages.....	619
8.2.1	Authentication request	619
8.2.1.1	Message definition	619
8.2.1.2	Authentication parameter RAND	619
8.2.1.3	Authentication parameter AUTN	620
8.2.1.4	Void.....	620
8.2.1.5	EAP message.....	620
8.2.2	Authentication response.....	620
8.2.2.1	Message definition	620
8.2.2.2	Authentication response parameter	620
8.2.2.3	EAP message.....	620
8.2.3	Authentication result.....	620
8.2.3.1	Message definition	620
8.2.3.2	ABBA	621
8.2.4	Authentication failure	621
8.2.4.1	Message definition	621
8.2.4.2	Authentication failure parameter.....	622
8.2.5	Authentication reject.....	622
8.2.5.1	Message definition	622
8.2.5.2	EAP message.....	622
8.2.6	Registration request	622
8.2.6.1	Message definition	622
8.2.6.2	Non-current native NAS key set identifier.....	625
8.2.6.3	5GMM capability.....	625
8.2.6.4	UE security capability.....	625
8.2.6.5	Requested NSSAI	625
8.2.6.6	Last visited registered TAI.....	625
8.2.6.7	S1 UE network capability	625
8.2.6.8	Uplink data status.....	626
8.2.6.9	PDU session status	626
8.2.6.10	MICO indication	626
8.2.6.11	UE status	626
8.2.6.12	Additional GUTI	626
8.2.6.13	Allowed PDU session status	626
8.2.6.14	UE's usage setting	626
8.2.6.15	Requested DRX parameters	626
8.2.6.16	EPS NAS message container.....	626
8.2.6.17	LADN indication.....	627
8.2.6.17A	Payload container type	627
8.2.6.18	Payload container.....	627
8.2.6.19	Network slicing indication	627
8.2.6.20	5GS update type	627
8.2.6.21	NAS message container	627
8.2.6.22	Requested extended DRX parameters.....	627
8.2.6.23	EPS bearer context status.....	627
8.2.6.24	T3324 value.....	627

8.2.6.25	Mobile station classmark 2.....	628
8.2.6.26	Supported codecs	628
8.2.6.27	UE radio capability ID	628
8.2.6.28	Requested mapped NSSAI.....	628
8.2.6.29	Additional information requested.....	628
8.2.6.30	Requested WUS assistance information.....	628
8.2.6.31	Void.....	628
8.2.6.32	N5GC indication	628
8.2.6.33	Requested NB-N1 mode DRX parameters.....	628
8.2.6.34	UE request type	628
8.2.6.35	Paging restriction	628
8.2.6.35	Service-level-AA container.....	628
8.2.6.36	NID	629
8.2.6.37	MS determined PLMN with disaster condition.....	629
8.2.6.38	Requested PEIPS assistance information	629
8.2.6.39	Requested T3512 value	629
8.2.7	Registration accept.....	629
8.2.7.1	Message definition	629
8.2.7.2	5G-GUTI.....	632
8.2.7.3	Equivalent PLMNs.....	632
8.2.7.4	TAI list	633
8.2.7.5	Allowed NSSAI	633
8.2.7.6	Rejected NSSAI	633
8.2.7.7	Configured NSSAI	633
8.2.7.8	5GS network feature support.....	633
8.2.7.9	PDU session status	633
8.2.7.10	PDU session reactivation result.....	633
8.2.7.11	PDU session reactivation result error cause	634
8.2.7.12	LADN information	634
8.2.7.13	MICO indication	634
8.2.7.14	Network slicing indication	634
8.2.7.15	Service area list	634
8.2.7.16	T3512 value.....	634
8.2.7.17	Non-3GPP de-registration timer value	634
8.2.7.18	T3502 value.....	634
8.2.7.19	Emergency number list	634
8.2.7.20	Extended emergency number list	634
8.2.7.21	SOR transparent container	634
8.2.7.22	EAP message.....	635
8.2.7.23	NSSAI inclusion mode.....	635
8.2.7.24	Operator-defined access category definitions	635
8.2.7.25	Negotiated DRX parameters	635
8.2.7.26	Non-3GPP NW policies	635
8.2.7.27	Negotiated extended DRX parameters	635
8.2.7.28	T3447 value.....	635
8.2.7.29	T3448 value.....	635
8.2.7.30	T3324 value.....	635
8.2.7.31	EPS bearer context status	635
8.2.7.32	UE radio capability ID	636
8.2.7.33	UE radio capability ID deletion indication.....	636
8.2.7.34	Pending NSSAI	636
8.2.7.35	Ciphering key data	636
8.2.7.36	CAG information list.....	636
8.2.7.37	Truncated 5G-S-TMSI configuration.....	636
8.2.7.38	Negotiated NB-N1 mode DRX parameters.....	636
8.2.7.39	Negotiated WUS assistance information.....	636
8.2.7.40	Extended rejected NSSAI	636
8.2.7.41	Service-level-AA container.....	637
8.2.7.42	Negotiated PEIPS assistance information	637
8.2.7.43	5GS additional request result	637
8.2.7.44	NSSRG information.....	637
8.2.7.45	Disaster roaming wait range.....	637