

ETSI TS 124 301 V18.8.0 (2024-10)



**Universal Mobile Telecommunications System (UMTS);
LTE;
5G;
Non-Access-Stratum (NAS)
protocol for Evolved Packet System (EPS);
Stage 3
(3GPP TS 24.301 version 18.8.0 Release 18)**



Reference

RTS/TSGC-0124301v18.8.0

Keywords

5G,LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
ETSI [Search & Browse Standards application](#).

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#).

Users should be aware that the present document may be revised or have its status changed,
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2024.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables. (2024-10)

The cross reference between 3GPP and ETSI identities can be found under <https://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	21
1 Scope	23
2 References	23
3 Definitions and abbreviations.....	26
3.1 Definitions	26
3.2 Abbreviations	34
4 General	35
4.1 Overview	35
4.2 Linkage between the protocols for EPS mobility management and EPS session management	36
4.2.A Handling of NAS signalling low priority indication	36
4.3 UE mode of operation	37
4.3.1 General.....	37
4.3.2 Change of UE mode of operation	38
4.3.2.1 General.....	38
4.3.2.2 Change of UE's usage setting.....	40
4.3.2.3 Change of voice domain preference for E-UTRAN.....	41
4.3.2.4 Change or determination of IMS registration status.....	42
4.3.2.5 Change of configuration regarding the use of SMS.	44
4.4 NAS security	45
4.4.1 General.....	45
4.4.2 Handling of EPS security contexts	45
4.4.2.1 General	45
4.4.2.2 Establishment of a mapped EPS security context during intersystem handover	46
4.4.2.3 Establishment of secure exchange of NAS messages	47
4.4.2.4 Change of security keys	49
4.4.2.5 Derivation of keys at CS to PS SRVCC handover from A/Gb mode to S1 mode or from Iu mode to S1 mode	50
4.4.3 Handling of NAS COUNT and NAS sequence number	51
4.4.3.1 General	51
4.4.3.2 Replay protection	52
4.4.3.3 Integrity protection and verification.....	52
4.4.3.4 Ciphering and deciphering	52
4.4.3.5 NAS COUNT wrap around	52
4.4.4 Integrity protection of NAS signalling messages.....	53
4.4.4.1 General	53
4.4.4.2 Integrity checking of NAS signalling messages in the UE	53
4.4.4.3 Integrity checking of NAS signalling messages in the MME	54
4.4.5 Ciphering of NAS signalling messages	56
4.5 Disabling and re-enabling of UE's E-UTRA capability	56
4.6 Applicability of procedures	59
4.6.1 Relay nodes.....	59
4.7 EPS mobility management and EPS session management in NB-S1 mode	60
4.8 EPS mobility management and EPS session management in WB-S1 mode for IoT.....	60
4.8.1 UE not using satellite E-UTRAN access	60
4.8.2 UE using satellite E-UTRAN access	61
4.9 Disabling and re-enabling of UE's NB-IoT capability	61
4.10 Support of MUSIM features.....	62
4.11 Satellite access for CIoT.....	62
4.11.1 General.....	62
4.11.2 Handling list of "PLMNs not allowed to operate at the present UE location"	62
4.11.3 Handling multiple tracking area codes from the lower layers.....	64

4.11.4	Support for enhanced discontinuous coverage.....	64
5	Elementary procedures for EPS mobility management.....	65
5.1	Overview	65
5.1.1	General.....	65
5.1.2	Types of EMM procedures	66
5.1.3	EMM sublayer states	67
5.1.3.1	General	67
5.1.3.2	EMM sublayer states in the UE.....	67
5.1.3.2.1	General	67
5.1.3.2.2	Main states.....	67
5.1.3.2.2.1	EMM-NULL	67
5.1.3.2.2.2	EMM-DEREGISTERED	67
5.1.3.2.2.3	EMM-REGISTERED-INITIATED	68
5.1.3.2.2.4	EMM-REGISTERED	68
5.1.3.2.2.5	EMM-DEREGISTERED-INITIATED.....	68
5.1.3.2.2.6	EMM-TRACKING-AREA-UPDATING-INITIATED	68
5.1.3.2.2.7	EMM-SERVICE-REQUEST-INITIATED.....	68
5.1.3.2.3	Substates of state EMM-DEREGISTERED	69
5.1.3.2.3.1	General.....	69
5.1.3.2.3.2	EMM-DEREGISTERED.NORMAL-SERVICE	69
5.1.3.2.3.3	EMM-DEREGISTERED.LIMITED-SERVICE.....	69
5.1.3.2.3.4	EMM-DEREGISTERED.ATTEMPTING-TO-ATTACH.....	70
5.1.3.2.3.5	EMM-DEREGISTERED.PLMN-SEARCH.....	70
5.1.3.2.3.6	EMM-DEREGISTERED.NO-IMSI	70
5.1.3.2.3.7	EMM-DEREGISTERED.ATTACH-NEEDED.....	70
5.1.3.2.3.8	EMM-DEREGISTERED.NO-CELL-AVAILABLE	70
5.1.3.2.3.9	EMM-DEREGISTERED.eCALL-INACTIVE	70
5.1.3.2.4	Substates of state EMM-REGISTERED	70
5.1.3.2.4.1	General.....	70
5.1.3.2.4.2	EMM-REGISTERED.NORMAL-SERVICE	70
5.1.3.2.4.3	EMM-REGISTERED.ATTEMPTING-TO-UPDATE	70
5.1.3.2.4.4	EMM-REGISTERED.LIMITED-SERVICE	71
5.1.3.2.4.5	EMM-REGISTERED.PLMN-SEARCH	71
5.1.3.2.4.6	EMM-REGISTERED.UPDATE-NEEDED	71
5.1.3.2.4.7	EMM-REGISTERED.NO-CELL-AVAILABLE	71
5.1.3.2.4.8	EMM-REGISTERED.ATTEMPTING-TO-UPDATE-MM	71
5.1.3.2.4.9	EMM-REGISTERED.IMSI-DETACH-INITIATED	71
5.1.3.3	EPS update status	71
5.1.3.4	EMM sublayer states in the MME	72
5.1.3.4.1	EMM-DEREGISTERED.....	72
5.1.3.4.2	EMM-COMMON-PROCEDURE-INITIATED.....	72
5.1.3.4.3	EMM-REGISTERED.....	72
5.1.3.4.4	EMM-DEREGISTERED-INITIATED	72
5.1.4	Coordination between EMM and GMM.....	73
5.1.5	Coordination between EMM and MM.....	74
5.2	Behaviour of the UE in state EMM-DEREGISTERED and state EMM-REGISTERED	74
5.2.1	General.....	74
5.2.2	UE behaviour in state EMM-DEREGISTERED	74
5.2.2.1	General	74
5.2.2.2	Primary substate selection.....	75
5.2.2.2.1	Selection of the substate after power on.....	75
5.2.2.3	Detailed description of UE behaviour in state EMM-DEREGISTERED	75
5.2.2.3.1	NORMAL-SERVICE.....	75
5.2.2.3.2	LIMITED-SERVICE.....	75
5.2.2.3.3	ATTEMPTING-TO-ATTACH	75
5.2.2.3.4	PLMN-SEARCH.....	76
5.2.2.3.5	NO-IMSI	76
5.2.2.3.6	ATTACH-NEEDED.....	76
5.2.2.3.7	NO-CELL-AVAILABLE	76
5.2.2.3.8	eCALL-INACTIVE.....	77
5.2.2.4	Substate when back to state EMM-DEREGISTERED from another EMM state	77

5.2.3	UE behaviour in state EMM-REGISTERED.....	77
5.2.3.1	General.....	77
5.2.3.2	Detailed description of UE behaviour in state EMM-REGISTERED.....	78
5.2.3.2.1	NORMAL-SERVICE.....	78
5.2.3.2.2	ATTEMPTING-TO-UPDATE.....	78
5.2.3.2.3	LIMITED-SERVICE.....	79
5.2.3.2.4	PLMN-SEARCH.....	79
5.2.3.2.5	UPDATE-NEEDED.....	79
5.2.3.2.6	NO-CELL-AVAILABLE.....	80
5.2.3.2.7	ATTEMPTING-TO-UPDATE-MM.....	80
5.2.3.2.8	IMSI-DETACH-INITIATED.....	80
5.3	General on elementary EMM procedures.....	81
5.3.1	EMM modes and NAS signalling connection.....	81
5.3.1.1	Establishment of the NAS signalling connection.....	81
5.3.1.2	Release of the NAS signalling connection.....	82
5.3.1.2.1	General.....	82
5.3.1.2.2	UE is using EPS services with control plane CIoT EPS optimization.....	85
5.3.1.3	Suspend and resume of the NAS signalling connection.....	85
5.3.2	Lists of forbidden tracking areas.....	86
5.3.3	List of forbidden PLMNs for attach in S101 mode.....	87
5.3.3a	Forbidden PLMNs for EPS services.....	87
5.3.4	Equivalent PLMNs list.....	87
5.3.5	Handling of the periodic tracking area update timer and mobile reachable timer (S1 mode only).....	87
5.3.6	Handling of timer T3402.....	89
5.3.7	Handling of the Local Emergency Numbers List and the Extended Local Emergency Numbers List.....	90
5.3.7a	Specific requirements for UE configured to use timer T3245.....	91
5.3.7b	Specific requirements for UE when receiving non-integrity protected reject messages.....	91
5.3.8	Abnormal cases in the UE.....	94
5.3.9	Handling of NAS level mobility management congestion control.....	95
5.3.9A	Handling of congestion control for transport of user data via the control plane.....	96
5.3.10	Access class control.....	96
5.3.11	Power saving mode.....	96
5.3.12	Extended idle-mode DRX cycle.....	97
5.3.13	Interaction between power saving mode and extended idle mode DRX cycle.....	98
5.3.14	Dedicated core network.....	98
5.3.15	CIoT EPS optimizations.....	98
5.3.16	Restriction on use of enhanced coverage.....	100
5.3.17	Service Gap Control.....	100
5.3.18	Restricted local operator services.....	102
5.3.19	Core Network selection and redirection for UEs using CIoT optimizations.....	102
5.3.19.1	Core network selection.....	102
5.3.19.2	Redirection of the UE by the core network.....	103
5.3.20	UE radio capability signalling optimisation.....	103
5.3.21	Wake-up signal assistance.....	104
5.3.22	Void.....	105
5.4	EMM common procedures.....	105
5.4.1	GUTI reallocation procedure.....	105
5.4.1.1	General.....	105
5.4.1.2	GUTI reallocation initiation by the network.....	106
5.4.1.3	GUTI reallocation completion by the UE.....	106
5.4.1.4	GUTI reallocation completion by the network.....	107
5.4.1.5	Abnormal cases in the UE.....	107
5.4.1.6	Abnormal cases on the network side.....	107
5.4.2	Authentication procedure.....	108
5.4.2.1	General.....	108
5.4.2.2	Authentication initiation by the network.....	109
5.4.2.3	Authentication response by the UE.....	109
5.4.2.4	Authentication completion by the network.....	110
5.4.2.5	Authentication not accepted by the network.....	110
5.4.2.6	Authentication not accepted by the UE.....	111
5.4.2.7	Abnormal cases.....	112
5.4.3	Security mode control procedure.....	116

5.4.3.1	General	116
5.4.3.2	NAS security mode control initiation by the network	117
5.4.3.3	NAS security mode command accepted by the UE	120
5.4.3.4	NAS security mode control completion by the network	121
5.4.3.5	NAS security mode command not accepted by the UE	122
5.4.3.6	Abnormal cases in the UE	122
5.4.3.7	Abnormal cases on the network side	122
5.4.4	Identification procedure	123
5.4.4.1	General	123
5.4.4.2	Identification initiation by the network	123
5.4.4.3	Identification response by the UE	124
5.4.4.4	Identification completion by the network	124
5.4.4.5	Abnormal cases in the UE	124
5.4.4.6	Abnormal cases on the network side	124
5.4.5	EMM information procedure	125
5.4.5.1	General	125
5.4.5.2	EMM information procedure initiation by the network	125
5.4.5.3	EMM information procedure in the UE	126
5.4.5.4	Abnormal cases on the network side	126
5.5	EMM specific procedures	126
5.5.1	Attach procedure	126
5.5.1.1	General	126
5.5.1.2	Attach procedure for EPS services	128
5.5.1.2.1	General	128
5.5.1.2.2	Attach procedure initiation	128
5.5.1.2.3	EMM common procedure initiation	133
5.5.1.2.4	Attach accepted by the network	133
5.5.1.2.4A	Attach successful for EPS services and not accepted for SMS services	140
5.5.1.2.5	Attach not accepted by the network	141
5.5.1.2.5A	Attach for emergency bearer services not accepted by the network	148
5.5.1.2.5B	Attach for initiating a PDN connection for emergency bearer services not accepted by the network	150
5.5.1.2.5B1	Attach by a UE transferring an emergency PDU session using a standalone PDN CONNECTIVITY REQUEST message	151
5.5.1.2.5C	Attach for access to RLOS not accepted by the network	151
5.5.1.2.6	Abnormal cases in the UE	152
5.5.1.2.6A	Abnormal cases in the UE, SMS services not accepted	156
5.5.1.2.7	Abnormal cases on the network side	156
5.5.1.3	Combined attach procedure for EPS services and non-EPS services (S1 mode only)	158
5.5.1.3.1	General	158
5.5.1.3.2	Combined attach procedure initiation	158
5.5.1.3.3	EMM common procedure initiation	158
5.5.1.3.4	Combined attach accepted by the network	158
5.5.1.3.4.1	General	158
5.5.1.3.4.2	Combined attach successful	159
5.5.1.3.4.3	Combined attach successful for EPS services only	160
5.5.1.3.5	Combined attach not accepted by the network	161
5.5.1.3.6	Abnormal cases in the UE	167
5.5.1.3.7	Abnormal cases on the network side	168
5.5.2	Detach procedure	168
5.5.2.1	General	168
5.5.2.2	UE initiated detach procedure	169
5.5.2.2.1	UE initiated detach procedure initiation	169
5.5.2.2.2	UE initiated detach procedure completion for EPS services only	170
5.5.2.2.3	UE initiated combined detach procedure completion	170
5.5.2.2.4	Abnormal cases in the UE	171
5.5.2.2.5	Abnormal cases on the network side	173
5.5.2.3	Network initiated detach procedure	173
5.5.2.3.1	Network initiated detach procedure initiation	173
5.5.2.3.2	Network initiated detach procedure completion by the UE	174
5.5.2.3.3	Network initiated detach procedure completion by the network	179
5.5.2.3.4	Abnormal cases in the UE	179

5.5.2.3.5	Abnormal cases on the network side	180
5.5.3	Tracking area updating procedure (S1 mode only).....	181
5.5.3.1	General	181
5.5.3.2	Normal and periodic tracking area updating procedure	183
5.5.3.2.1	General	183
5.5.3.2.2	Normal and periodic tracking area updating procedure initiation	183
5.5.3.2.3	EMM common procedure initiation	191
5.5.3.2.4	Normal and periodic tracking area updating procedure accepted by the network	192
5.5.3.2.4A	Tracking area updating successful for EPS services and not accepted for SMS services.....	204
5.5.3.2.5	Normal and periodic tracking area updating procedure not accepted by the network	205
5.5.3.2.5A	Tracking area updating procedure for initiating a PDN connection for emergency bearer services not accepted by the network	214
5.5.3.2.5B	Tracking area updating for access to RLOS not accepted by the network	214
5.5.3.2.6	Abnormal cases in the UE	215
5.5.3.2.6A	Abnormal cases in the UE, SMS services not accepted.....	221
5.5.3.2.7	Abnormal cases on the network side	221
5.5.3.3	Combined tracking area updating procedure.....	224
5.5.3.3.1	General	224
5.5.3.3.2	Combined tracking area updating procedure initiation.....	224
5.5.3.3.3	EMM common procedure initiation	227
5.5.3.3.4	Combined tracking area updating procedure accepted by the network	227
5.5.3.3.4.1	General.....	227
5.5.3.3.4.2	Combined tracking area updating successful	227
5.5.3.3.4.3	Combined tracking area updating successful for EPS services only	229
5.5.3.3.5	Combined tracking area updating procedure not accepted by the network	230
5.5.3.3.6	Abnormal cases in the UE	238
5.5.3.3.7	Abnormal cases on the network side	240
5.5.4	eCall inactivity procedure.....	240
5.5.5	Tracking area update request message (for N1 mode only).....	240
5.5.6	Attach request message (for N1 mode only).....	240
5.6	EMM connection management procedures (S1 mode only)	241
5.6.1	Service request procedure	241
5.6.1.1	General	241
5.6.1.2	Service request procedure initiation.....	246
5.6.1.2.1	UE is not using EPS services with control plane CIoT EPS optimization.....	246
5.6.1.2.2	UE is using EPS services with control plane CIoT EPS optimization.....	247
5.6.1.3	EMM common procedure initiation.....	248
5.6.1.4	Service request procedure accepted by the network.....	248
5.6.1.4.1	UE is not using EPS services with control plane CIoT EPS optimization.....	248
5.6.1.4.2	UE is using EPS services with control plane CIoT EPS optimization.....	250
5.6.1.5	Service request procedure not accepted by the network.....	255
5.6.1.5A	Service request procedure for initiating a PDN connection for emergency bearer services not accepted by the network.....	265
5.6.1.5B	Service request procedure for UE attached for access to RLOS not accepted by the network.....	265
5.6.1.6	Abnormal cases in the UE.....	266
5.6.1.7	Abnormal cases on the network side	273
5.6.2	Paging procedure	274
5.6.2.1	General	274
5.6.2.2	Paging for EPS services	274
5.6.2.2.1	Paging for EPS services through E-UTRAN using S-TMSI	274
5.6.2.2.2	Paging for EPS services through E-UTRAN using IMSI.....	277
5.6.2.3	Paging for CS fallback to A/Gb or Iu mode.....	278
5.6.2.3.1	General	278
5.6.2.3.2	Abnormal cases in the UE	279
5.6.2.3.3	Abnormal cases on the network side	279
5.6.2.4	Paging for SMS	280
5.6.3	Transport of NAS messages procedure.....	280
5.6.3.1	General	280
5.6.3.2	UE initiated transport of NAS messages.....	281
5.6.3.3	Network initiated transport of NAS messages	281
5.6.3.4	Abnormal cases in the UE.....	281
5.6.3.5	Abnormal cases on the network side.....	281

5.6.4	Generic transport of NAS messages procedure	282
5.6.4.1	General	282
5.6.4.2	UE initiated generic transport of NAS messages	282
5.6.4.3	Network initiated transport of NAS messages	282
5.6.4.4	Abnormal cases in the UE	282
5.6.4.5	Abnormal cases on the network side	283
5.7	Reception of an EMM STATUS message by an EMM entity	283
6	Elementary procedures for EPS session management	283
6.1	Overview	283
6.1.1	General	283
6.1.2	Types of ESM procedures	284
6.1.3	ESM sublayer states	285
6.1.3.1	General	285
6.1.3.2	ESM sublayer states in the UE	285
6.1.3.2.1	BEARER CONTEXT INACTIVE	285
6.1.3.2.2	BEARER CONTEXT ACTIVE	285
6.1.3.2.3	PROCEDURE TRANSACTION INACTIVE	286
6.1.3.2.4	PROCEDURE TRANSACTION PENDING	286
6.1.3.3	ESM sublayer states in the MME	286
6.1.3.3.1	BEARER CONTEXT INACTIVE	286
6.1.3.3.2	BEARER CONTEXT ACTIVE PENDING	286
6.1.3.3.3	BEARER CONTEXT ACTIVE	286
6.1.3.3.4	BEARER CONTEXT INACTIVE PENDING	286
6.1.3.3.5	BEARER CONTEXT MODIFY PENDING	286
6.1.3.3.6	PROCEDURE TRANSACTION INACTIVE	287
6.1.3.3.7	PROCEDURE TRANSACTION PENDING	287
6.1.4	Coordination between ESM and SM	287
6.1.4A	Coordination between ESM and 5GSM	288
6.1.5	Coordination between ESM and EMM for supporting ISR	288
6.2	IP address allocation	289
6.2.1	General	289
6.2.2	IP address allocation via NAS signalling	289
6.2A	IP header compression	291
6.3	General on elementary ESM procedures	291
6.3.1	Services provided by lower layers	291
6.3.2	Principles of address handling for ESM procedures	291
6.3.3	Abnormal cases in the UE	293
6.3.4	Abnormal cases in the network	294
6.3.5	Handling of APN based congestion control	294
6.3.5A	Handling of group specific session management congestion control	295
6.3.6	Handling of network rejection not due to APN based congestion control	295
6.3.7	Handling of WLAN offload control	296
6.3.8	Handling of serving PLMN rate control	296
6.3.9	Handling of APN rate control	296
6.3.10	Handling of 3GPP PS data off	297
6.3.11	Handling of Reliable Data Service	298
6.3.12	Handling of Ethernet PDN type	298
6.3.13	Handling of Uncrewed aerial vehicle identification, authentication, and authorization	298
6.3.13.1	General	298
6.3.13.2	Authentication and authorization of UAV	298
6.3.13.3	Authorization of C2 communication	299
6.3.13.4	Void	299
6.3.14	Handling of URSP provisioning	299
6.4	Network initiated ESM procedures	300
6.4.1	Default EPS bearer context activation procedure	300
6.4.1.1	General	300
6.4.1.2	Default EPS bearer context activation initiated by the network	300
6.4.1.3	Default EPS bearer context activation accepted by the UE	301
6.4.1.4	Default EPS bearer context activation not accepted by the UE	303
6.4.1.5	Abnormal cases in the UE	303
6.4.1.6	Abnormal cases on the network side	303

6.4.2	Dedicated EPS bearer context activation procedure	304
6.4.2.1	General	304
6.4.2.2	Dedicated EPS bearer context activation initiated by the network.....	304
6.4.2.3	Dedicated EPS bearer context activation accepted by the UE	305
6.4.2.4	Dedicated EPS bearer context activation not accepted by the UE	306
6.4.2.5	Abnormal cases in the UE.....	308
6.4.2.6	Abnormal cases on the network side	308
6.4.3	EPS bearer context modification procedure.....	308
6.4.3.1	General	308
6.4.3.2	EPS bearer context modification initiated by the network	309
6.4.3.3	EPS bearer context modification accepted by the UE	310
6.4.3.4	EPS bearer context modification not accepted by the UE.....	312
6.4.3.5	Abnormal cases in the UE.....	314
6.4.3.6	Abnormal cases on the network side	315
6.4.4	EPS bearer context deactivation procedure.....	315
6.4.4.1	General	315
6.4.4.2	EPS bearer context deactivation initiated by the network.....	316
6.4.4.3	EPS bearer context deactivation accepted by the UE.....	317
6.4.4.4	Abnormal cases in the UE.....	319
6.4.4.5	Abnormal cases on the network side	319
6.4.4.6	Local EPS bearer context deactivation without NAS signalling.....	319
6.5	UE requested ESM procedures.....	321
6.5.0	General.....	321
6.5.1	UE requested PDN connectivity procedure	322
6.5.1.1	General	322
6.5.1.2	UE requested PDN connectivity procedure initiation	322
6.5.1.3	UE requested PDN connectivity procedure accepted by the network.....	326
6.5.1.4	UE requested PDN connectivity procedure not accepted by the network.....	328
6.5.1.4.1	General	328
6.5.1.4.2	Handling of network rejection due to ESM cause #26	330
6.5.1.4.3	Handling of network rejection due to ESM cause other than ESM cause #26	333
6.5.1.4A	Handling the maximum number of active EPS bearer contexts	339
6.5.1.4B	Void.....	339
6.5.1.4C	Handling the maximum number of active user plane radio bearers in NB-S1 mode	339
6.5.1.5	Abnormal cases in the UE.....	339
6.5.1.6	Abnormal cases on the network side	340
6.5.1.7	Handling PDN connectivity request for UE configured for dual priority	341
6.5.2	UE requested PDN disconnect procedure.....	341
6.5.2.1	General	341
6.5.2.2	UE requested PDN disconnection procedure initiation	342
6.5.2.3	UE requested PDN disconnection procedure accepted by the network.....	342
6.5.2.4	UE requested PDN disconnection procedure not accepted by the network	342
6.5.2.5	Abnormal cases in the UE.....	343
6.5.2.6	Abnormal cases on the network side	343
6.5.3	UE requested bearer resource allocation procedure.....	344
6.5.3.1	General	344
6.5.3.2	UE requested bearer resource allocation procedure initiation	344
6.5.3.3	UE requested bearer resource allocation procedure accepted by the network	345
6.5.3.4	UE requested bearer resource allocation procedure not accepted by the network	345
6.5.3.4.1	General	345
6.5.3.4.2	Handling of network rejection due to ESM cause #26	347
6.5.3.4.3	Handling of network rejection due to ESM cause other than ESM cause #26	348
6.5.3.4A	Handling the maximum number of active EPS bearer contexts	350
6.5.3.5	Abnormal cases in the UE.....	351
6.5.3.6	Abnormal cases on the network side	351
6.5.4	UE requested bearer resource modification procedure	351
6.5.4.1	General	351
6.5.4.2	UE requested bearer resource modification procedure initiation	352
6.5.4.3	UE requested bearer resource modification procedure accepted by the network.....	355
6.5.4.4	UE requested bearer resource modification procedure not accepted by the network.....	356
6.5.4.4.1	General	356
6.5.4.4.2	Handling of network rejection due to ESM cause #26	358

6.5.4.4.3	Handling of network rejection due to ESM cause other than ESM cause #26	360
6.5.4.5	Abnormal cases in the UE	362
6.5.4.6	Abnormal cases on the network side	362
6.5.5	Handling session management request for UE configured for dual priority	363
6.6	Miscellaneous procedures	364
6.6.1	Exchange of protocol configuration options	364
6.6.1.1	General	364
6.6.1.2	ESM information request procedure	365
6.6.1.2.1	General	365
6.6.1.2.2	ESM information request initiated by the network	365
6.6.1.2.3	ESM information request completion by the UE	365
6.6.1.2.4	ESM information request completion by the network	365
6.6.1.2.5	Abnormal cases in the UE	365
6.6.1.2.6	Abnormal cases on the network side	366
6.6.1.3	Exchange of protocol configuration options in other messages	366
6.6.2	Notification procedure	366
6.6.2.1	General	366
6.6.2.2	Notification procedure initiation by the network	366
6.6.2.3	Notification procedure in the UE	366
6.6.2.4	Abnormal cases on the network side	367
6.6.3	Remote UE Report procedure	367
6.6.3.1	General	367
6.6.3.2	Remote UE Report initiated by the UE	367
6.6.3.3	Remote UE Report completion by the network	367
6.6.3.4	Remote UE Report completion by the UE	368
6.6.3.5	Abnormal cases in the UE	368
6.6.3.6	Abnormal cases on the network side	368
6.6.4	Transport of user data via the control plane procedure	368
6.6.4.1	General	368
6.6.4.2	UE initiated transport of user data via the control plane	368
6.6.4.3	Network initiated transport of user data via the control plane	369
6.6.4.4	Abnormal cases in the UE	369
6.6.4.5	Abnormal cases on the network side	370
6.7	Reception of an ESM STATUS message by an ESM entity	370
7	Handling of unknown, unforeseen, and erroneous protocol data	371
7.1	General	371
7.2	Message too short	371
7.3	Unknown or unforeseen procedure transaction identity or EPS bearer identity	372
7.3.1	Procedure transaction identity	372
7.3.2	EPS bearer identity	373
7.4	Unknown or unforeseen message type	374
7.5	Non-semantic mandatory information element errors	375
7.5.1	Common procedures	375
7.5.2	EPS mobility management	375
7.5.3	EPS session management	375
7.6	Unknown and unforeseen IEs in the non-imperative message part	376
7.6.1	IEs unknown in the message	376
7.6.2	Out of sequence IEs	376
7.6.3	Repeated IEs	376
7.7	Non-imperative message part errors	377
7.7.1	Syntactically incorrect optional IEs	377
7.7.2	Conditional IE errors	377
7.8	Messages with semantically incorrect contents	377
8	Message functional definitions and contents	377
8.1	Overview	377
8.2	EPS mobility management messages	378
8.2.1	Attach accept	378
8.2.1.1	Message definition	378
8.2.1.2	GUTI	381
8.2.1.3	Location area identification	381

8.2.1.4	MS identity.....	381
8.2.1.5	EMM cause	381
8.2.1.6	T3402 value.....	381
8.2.1.7	T3423 value.....	381
8.2.1.8	Equivalent PLMNs.....	381
8.2.1.9	Emergency number list	381
8.2.1.9A	Extended emergency number list	381
8.2.1.10	EPS network feature support.....	382
8.2.1.11	Additional update result	382
8.2.1.12	T3412 extended value	382
8.2.1.13	T3324 value.....	382
8.2.1.14	Extended DRX parameters.....	382
8.2.1.15	DCN-ID.....	382
8.2.1.16	SMS services status.....	382
8.2.1.17	Non-3GPP NW provided policies	382
8.2.1.18	T3448 value.....	382
8.2.1.19	Network policy.....	382
8.2.1.20	T3447 value.....	383
8.2.1.21	Ciphering key data	383
8.2.1.22	UE radio capability ID	383
8.2.1.23	UE radio capability ID deletion indication.....	383
8.2.1.24	Negotiated WUS assistance information.....	383
8.2.1.25	Negotiated DRX parameter in NB-S1 mode	383
8.2.1.26	Negotiated IMSI offset.....	383
8.2.1.27	Forbidden TAI(s) for the list of "forbidden tracking areas for roaming"	383
8.2.1.28	Forbidden TAI(s) for the list of "forbidden tracking areas for regional provision of service"	383
8.2.1.29	Unavailability configuration	383
8.2.2	Attach complete	384
8.2.3	Attach reject.....	384
8.2.3.1	Message definition	384
8.2.3.2	ESM message container	385
8.2.3.3	T3346 value.....	385
8.2.3.4	T3402 value.....	385
8.2.3.5	Extended EMM cause	385
8.2.3.5A	Lower bound timer value	385
8.2.3.6	Forbidden TAI(s) for the list of "forbidden tracking areas for roaming"	385
8.2.3.7	Forbidden TAI(s) for the list of "forbidden tracking areas for regional provision of service"	385
8.2.4	Attach request	385
8.2.4.1	Message definition	385
8.2.4.2	Old P-TMSI signature	388
8.2.4.3	Additional GUTI	388
8.2.4.4	Last visited registered TAI.....	388
8.2.4.5	DRX parameter	388
8.2.4.6	MS network capability	388
8.2.4.7	Old location area identification.....	388
8.2.4.8	TMSI status	388
8.2.4.9	Mobile station classmark 2.....	388
8.2.4.10	Mobile station classmark 3.....	388
8.2.4.11	Supported Codecs	388
8.2.4.12	Additional update type	388
8.2.4.13	Voice domain preference and UE's usage setting.....	389
8.2.4.14	Device properties	389
8.2.4.15	Old GUTI type	389
8.2.4.16	MS network feature support.....	389
8.2.4.17	TMSI based NRI container	389
8.2.4.18	T3324 value.....	389
8.2.4.19	T3412 extended value	389
8.2.4.20	Extended DRX parameters.....	389
8.2.4.21	UE additional security capability	389
8.2.4.22	UE status	389
8.2.4.23	Additional information requested.....	389
8.2.4.24	N1 UE network capability.....	389

8.2.4.25	UE radio capability ID availability IE.....	389
8.2.4.26	Requested WUS assistance information.....	390
8.2.4.27	DRX parameter in NB-S1 mode	390
8.2.4.28	Requested IMSI offset.....	390
8.2.5	Authentication failure	390
8.2.5.1	Message definition	390
8.2.5.2	Authentication failure parameter.....	390
8.2.6	Authentication reject.....	390
8.2.7	Authentication request	391
8.2.8	Authentication response.....	391
8.2.9	CS service notification.....	392
8.2.9.1	Message definition	392
8.2.9.2	CLI	392
8.2.9.3	SS Code.....	392
8.2.9.4	LCS indicator	392
8.2.9.5	LCS client identity	392
8.2.9.6	Void.....	392
8.2.10	Detach accept.....	393
8.2.10.1	Detach accept (UE originating detach)	393
8.2.10.2	Detach accept (UE terminated detach)	393
8.2.11	Detach request	393
8.2.11.1	Detach request (UE originating detach)	393
8.2.11.2	Detach request (UE terminated detach).....	394
8.2.11.2.1	Message definition.....	394
8.2.11.2.2	EMM cause.....	394
8.2.11.2.3	Forbidden TAI(s) for the list of "forbidden tracking areas for roaming"	394
8.2.11.2.4	Forbidden TAI(s) for the list of "forbidden tracking areas for regional provision of service"	395
8.2.11.2.5	Lower bound timer value.....	395
8.2.12	Downlink NAS Transport.....	395
8.2.13	EMM information	395
8.2.13.1	Message definition	395
8.2.13.2	Full name for network.....	396
8.2.13.3	Short name for network.....	396
8.2.13.4	Local time zone	396
8.2.13.5	Universal time and local time zone	396
8.2.13.6	Network daylight saving time	396
8.2.14	EMM status.....	397
8.2.15	Extended service request	397
8.2.15.1	Message definition	397
8.2.15.2	CSFB response	398
8.2.15.3	EPS bearer context status	398
8.2.15.4	Device properties	398
8.2.15.5	UE request type	398
8.2.15.6	Paging restriction	398
8.2.16	GUTI reallocation command	398
8.2.16.1	Message definition	398
8.2.16.2	TAI list	399
8.2.16.3	DCN-ID.....	399
8.2.16.4	UE radio capability ID	399
8.2.16.5	UE radio capability ID deletion indication.....	399
8.2.17	GUTI reallocation complete	399
8.2.18	Identity request	400
8.2.19	Identity response.....	400
8.2.20	Security mode command	400
8.2.20.1	Message definition	400
8.2.20.2	IMEISV request	401
8.2.20.3	Replayed nonce _{UE}	401
8.2.20.4	Nonce _{MME}	401
8.2.20.5	Hash _{MME}	401
8.2.20.6	Replayed UE additional security capability	401
8.2.20.7	UE radio capability ID request.....	402
8.2.20.8	UE coarse location information request	402

8.2.21	Security mode complete.....	402
8.2.21.1	Message definition	402
8.2.21.2	IMEISV	402
8.2.21.3	Replayed NAS message container	402
8.2.21.4	UE radio capability ID	402
8.2.21.5	UE coarse location information.....	403
8.2.22	Security mode reject	403
8.2.23	Security protected NAS message.....	403
8.2.24	Service reject	403
8.2.24.1	Message definition	403
8.2.24.2	T3442 value.....	404
8.2.24.3	T3346 value.....	404
8.2.24.4	T3448 value.....	404
8.2.24.5	Forbidden TAI(s) for the list of "forbidden tracking areas for roaming"	404
8.2.24.6	Forbidden TAI(s) for the list of "forbidden tracking areas for regional provision of service"	404
8.2.24.7	Lower bound timer value	404
8.2.25	Service request.....	405
8.2.26	Tracking area update accept.....	405
8.2.26.1	Message definition	405
8.2.26.2	T3412 value.....	408
8.2.26.3	GUTI.....	408
8.2.26.4	TAI list	408
8.2.26.5	EPS bearer context status	408
8.2.26.6	Location area identification.....	408
8.2.26.7	MS identity.....	408
8.2.26.8	EMM cause	408
8.2.26.9	T3402 value.....	408
8.2.26.10	T3423 value.....	409
8.2.26.11	Equivalent PLMNs.....	409
8.2.26.12	Emergency number list	409
8.2.26.12A	Extended emergency number list	409
8.2.26.13	EPS network feature support.....	409
8.2.26.14	Additional update result	409
8.2.26.15	T3412 extended value	409
8.2.26.16	T3324 value.....	409
8.2.26.17	Extended DRX parameters.....	409
8.2.26.18	DCN-ID.....	410
8.2.26.19	SMS services status.....	410
8.2.26.20	Non-3GPP NW provided policies	410
8.2.26.21	T3448 value.....	410
8.2.26.22	Network policy.....	410
8.2.26.23	T3447 value.....	410
8.2.26.24	Ciphering key data	410
8.2.26.25	UE radio capability ID	410
8.2.26.26	UE radio capability ID deletion indication.....	410
8.2.26.27	Negotiated WUS assistance information.....	410
8.2.26.28	Negotiated DRX parameter in NB-S1 mode	411
8.2.26.29	Negotiated IMSI offset.....	411
8.2.26.30	EPS additional request result.....	411
8.2.26.31	Forbidden TAI(s) for the list of "forbidden tracking areas for roaming"	411
8.2.26.32	Forbidden TAI(s) for the list of "forbidden tracking areas for regional provision of service"	411
8.2.26.33	Maximum time offset.....	411
8.2.26.34	Unavailability configuration	411
8.2.27	Tracking area update complete	411
8.2.28	Tracking area update reject.....	412
8.2.28.1	Message definition	412
8.2.28.2	T3346 value.....	412
8.2.28.3	Extended EMM cause	412
8.2.28.4	Forbidden TAI(s) for the list of "forbidden tracking areas for roaming"	412
8.2.28.5	Forbidden TAI(s) for the list of "forbidden tracking areas for regional provision of service"	412
8.2.28.6	Lower bound timer value	412
8.2.29	Tracking area update request	413