

---

**Optični spojni elementi in pasivne komponente - Izvedbeni standard - 081-06. del: Električno krmiljeni spremenljivi optični atenuator srednje obsežne naprave 1 x N DWDM brez konektorjev za enorodovna vlakna kategorije OP+ - Razširjeno zunanje zaščiteno okolje**

Fibre optic interconnecting devices and passive components - Performance standard - Part 081-06: Non-connectorized single-mode fibre optic middle-scale 1 x N DWDM devices for category OP+ - Extended outdoor protected environment

(standards.iteh.ai)

oSIST prEN IEC 61753-081-06:2022

Dispositifs d'interconnexion et composants passifs fibroniques – Norme de performance – Partie 081-06: Dispositifs DWDM 1 × N de milieu d'échelle à fibres optiques unimodales, non connectés, pour catégorie OP+ – Environnement extérieur protégé étendu

**Ta slovenski standard je istoveten z: prEN IEC 61753-081-06:2022**

---

**ICS:**

33.180.20	Povezovalne naprave za optična vlakna	Fibre optic interconnecting devices
-----------	---------------------------------------	-------------------------------------

**oSIST prEN IEC 61753-081-06:2022 en**





# 86B/4632/CDV

## COMMITTEE DRAFT FOR VOTE (CDV)

PROJECT NUMBER:

**IEC 61753-081-06 ED1**

DATE OF CIRCULATION:

**2022-08-12**

CLOSING DATE FOR VOTING:

**2022-11-04**

SUPERSEDES DOCUMENTS:

**86B/4547/CD, 86B/4581A/CC**

IEC SC 86B : FIBRE OPTIC INTERCONNECTING DEVICES AND PASSIVE COMPONENTS	
SECRETARIAT: Japan	SECRETARY: Mr Shigeru Tomita
OF INTEREST TO THE FOLLOWING COMMITTEES:	PROPOSED HORIZONTAL STANDARD: <input type="checkbox"/> Other TC/SCs are requested to indicate their interest, if any, in this CDV to the secretary.
FUNCTIONS CONCERNED: <input type="checkbox"/> EMC <input type="checkbox"/> ENVIRONMENT <input type="checkbox"/> QUALITY ASSURANCE <input type="checkbox"/> SAFETY	
<input checked="" type="checkbox"/> SUBMITTED FOR CENELEC PARALLEL VOTING	<input type="checkbox"/> NOT SUBMITTED FOR CENELEC PARALLEL VOTING
<p><b>Attention IEC-CENELEC parallel voting</b></p> <p>The attention of IEC National Committees, members of CENELEC, is drawn to the fact that this Committee Draft for Vote (CDV) is submitted for parallel voting.</p> <p>The CENELEC members are invited to vote through the CENELEC online voting system.</p>	

This document is still under study and subject to change. It should not be used for reference purposes.

Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

TITLE:

**Fibre optic interconnecting devices and passive components – Performance standard – Part 081-06: Non-connectorized single-mode fibre optic middle-scale 1 x N DWDM devices for category OP+ – Extended outdoor protected environment**

PROPOSED STABILITY DATE: 2032

NOTE FROM TC/SC OFFICERS:

## 1 CONTENTS

2	FOREWORD .....	3
3	1 Scope .....	5
4	2 Normative references .....	5
5	3 Terms and definitions .....	7
6	4 Test .....	7
7	5 Test report .....	7
8	6 Performance requirements .....	8
9	6.1 Reference components .....	8
10	6.2 Dimensions .....	8
11	6.3 Test details and requirements .....	8
12	Annex A (normative) Sample size .....	17
13	Bibliography .....	18
14		
15	Table 1 – Single-mode spectral bands .....	7
16	Table 2 – Test details and requirements for type A (Gaussian passband profile) .....	8
17	Table 3 – Test details and requirements for type B (Flat-top passband profile) .....	11
18	Table 4 – Environmental test for all types .....	14
19	Table A.1 – Sample size .....	17

20

21

oSIST prEN IEC 61753-081-06:2022

<https://standards.iteh.ai/catalog/standards/sist/54134bff-6218-4222-bc5a-19886bfla67b/osist-pren-iec-61753-081-06-2022>

## 22 INTERNATIONAL ELECTROTECHNICAL COMMISSION

23

24

25

26

27

28

29

30

31

32

33

**FIBRE OPTIC INTERCONNECTING DEVICES  
 AND PASSIVE COMPONENTS –  
 PERFORMANCE STANDARD –**

**Part 081-06: Non-connectorized single-mode fibre optic middle-scale  
 1 × N DWDM devices for category OP+ – Extended outdoor protected  
 environment**

**FOREWORD**

34

35

36

37

38

39

40

41

42

43

44

45

46

47

48

49

50

51

52

53

54

55

56

57

58

59

60

61

62

63

64

65

66

67

68

69

70

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61753-081-06 has been prepared by subcommittee 86B: Fibre optic interconnecting devices and passive components, of IEC technical committee 86: Fibre optics. The text of this standard is based on the following documents:

FDIS	Report on voting
86B/xx/FDIS	86B/xxx/RVD

71

72

73

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

- 74 This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.
- 75 A list of all parts of IEC 61753 series, published under the general title *Fibre optic*  
76 *interconnecting devices and passive components performance standard*, can be found on the  
77 IEC website.
- 78 The committee has decided that the contents of this publication will remain unchanged until  
79 the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data  
80 related to the specific publication. At this date, the publication will be
- 81 • reconfirmed,
  - 82 • withdrawn,
  - 83 • replaced by a revised edition, or
  - 84 • amended.
- 85

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[oSIST prEN IEC 61753-081-06:2022](https://standards.iteh.ai/catalog/standards/sist/54134bff-6218-4222-bc5a-19886bfla67b/osist-pren-iec-61753-081-06-2022)

<https://standards.iteh.ai/catalog/standards/sist/54134bff-6218-4222-bc5a-19886bfla67b/osist-pren-iec-61753-081-06-2022>

# FIBRE OPTIC INTERCONNECTING DEVICES AND PASSIVE COMPONENTS – PERFORMANCE STANDARD –

## Part 081-06: Non-connectorized single-mode fibre optic middle-scale 1 × N DWDM devices for category OP+ – Extended outdoor protected environment

### 1 Scope

This part of IEC 61753 contains the minimum initial test and measurement requirements and severities which a fibre optic middle-scale 1 × N ( $16 \leq N \leq 64$ ) DWDM (dense wavelength division multiplexing) arrayed waveguide grating device with channel spacing of 50 GHz, 100 GHz or 200 GHz needs to satisfy in order to be categorized as meeting the requirements of category OP+ (extended outdoor protected environment). The requirements are given for the DWDM devices with Gaussian passband profile and flat-top passband profile. The requirements exclude the devices with dynamic electrical temperature control.

### 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60793-2-50, *Optical fibres – Part 2-50: Product specifications – Sectional specification for class B single-mode fibres*

IEC 60794-2-50, *Optical fibre cables – Part 2-50: Indoor cables – Family specification for simplex and duplex cables for use in terminated cable assemblies*

IEC 61300 (all parts), *Fibre optic interconnecting devices and passive components - Basic test and measurement procedures*

IEC 61300-1, *Fibre optic interconnecting devices and passive components - Basic test and measurement procedures - Part 1: General and guidance*

IEC 61300-2-1, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-1: Tests – Vibration (sinusoidal)*

IEC 61300-2-4, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-4: Tests – Fibre or cable retention*

IEC 61300-2-5, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-5: Tests – Torsion*

IEC 61300-2-9, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-9: Tests – Shock*

IEC 61300-2-14, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-14: Tests – High optical power*

- 127 IEC 61300-2-17, *Fibre optic interconnecting devices and passive components – Basic test*  
128 *and measurement procedures – Part 2-17: Tests – Cold*
- 129 IEC 61300-2-18, *Fibre optic interconnecting devices and passive components – Basic test*  
130 *and measurement procedures – Part 2-18: Tests – Dry heat*
- 131 IEC 61300-2-21, *Fibre optic interconnecting devices and passive components – Basic test*  
132 *and measurement procedures – Part 2-21: Tests – Composite temperature/humidity cyclic test*
- 133 IEC 61300-2-22, *Fibre optic interconnecting devices and passive components – Basic test*  
134 *and measurement procedures – Part 2-22: Tests – Change of temperature*
- 135 IEC 61300-2-26, *Fibre optic interconnecting devices and passive components – Basic test*  
136 *and measurement procedures – Part 2-26: Tests – Salt mist*
- 137 IEC 61300-2-27, *Fibre optic interconnecting devices and passive components – Basic test*  
138 *and measurement procedures – Part 2-27: Tests – Dust – Laminar flow*
- 139 IEC 61300-2-42, *Fibre optic interconnecting devices and passive components – Basic test*  
140 *and measurement procedures – Part 2-42: Tests – Static side load for connectors*
- 141 IEC 61300-2-44, *Fibre optic interconnecting devices and passive components - Basic test and*  
142 *measurement procedures - Part 2-44: Tests - Flexing of the strain relief of fibre optic devices*
- 143 IEC 61300-3-2, *Fibre optic interconnecting devices and passive components – Basic test and*  
144 *measurement procedures – Part 3-2: Examinations and measurements – Polarization*  
145 *dependence of attenuation in a single-mode fibre optic device*
- 146 IEC 61300-3-6, *Fibre optic interconnecting devices and passive components – Basic test and*  
147 *measurement procedures – Part 3-6: Examinations and measurements – Return loss*
- 148 IEC 61300-3-20, *Fibre optic interconnecting devices and passive components – Basic test*  
149 *and measurement procedures – Part 3-20: Examinations and measurements – Directivity of*  
150 *fibre optic branching devices*
- 151 IEC 61300-3-28, *Fibre optic interconnecting devices and passive components – Basic test*  
152 *and measurement procedures – Part 3-28: Examinations and measurements – Transient loss*
- 153 IEC 61300-3-29, *Fibre optic interconnecting devices and passive components – Basic test*  
154 *and measurement procedures – Part 3-29: Examinations and measurements – Measurement*  
155 *techniques for characterizing the amplitude of the spectral transfer function of DWDM*  
156 *components*
- 157 IEC 61300-3-32, *Fibre optic interconnecting devices and passive components – Basic test*  
158 *and measurement procedures – Part 3-32: Examinations and measurements – Polarization*  
159 *mode dispersion measurement for passive optical components*
- 160 IEC 61300-3-38, *Fibre optic interconnecting devices and passive components – Basic test*  
161 *and measurement procedures – Part 3-38: Examinations and measurements – Group delay,*  
162 *chromatic dispersion and phase ripple*
- 163 IEC 61753-1, *Fibre optic interconnecting devices and passive components - Performance*  
164 *standard - Part 1: General and guidance*
- 165 IEC 61753-081-02, *Fibre optic interconnecting devices and passive components performance*  
166 *standard – Part 081-02: Non-connectorized single-mode fibre optic middle-scale 1 × N DWDM*  
167 *devices for category C – Controlled environments*



168 IEC 62074-1, *Fibre optic WDM devices – Part 1: Generic specification*

169 IEC TS 62627-09, *Fibre optic interconnecting devices and passive components - Vocabulary*  
170 *for passive optical devices*

### 171 3 Terms and definitions

172 For the purposes of this document, the terms and definitions given in IEC 61753-081-02, IEC  
173 62074-1 and IEC TS 62627-09, apply.

174 ISO and IEC maintain terminological databases for use in standardization at the following  
175 addresses:

- 176 • IEC Electropedia: available at <http://www.electropedia.org/>
- 177 • ISO Online browsing platform: available at <http://www.iso.org/obp>

### 178 4 Test

179 Unless otherwise specified, all test methods shall be in accordance with the IEC 61300 series.  
180 The samples shall be terminated onto single-mode fibres as per IEC 60793-2-50 category B-  
181 652.B, B-652.D or B-657 in either coated fibres (primary and secondary) or reinforced cable  
182 format as per IEC 60794-2-50. DWDM devices used for the test are intended to be previously  
183 unstressed new samples but may also be selected from previously used samples, if desired.  
184 All measurements shall be carried out at the standard atmospheric condition defined in IEC  
185 61300-1, unless otherwise stated. If the device is provided with temperature control, this shall  
186 be set at the set-point specified by the manufacturer.

187 The requirements apply to every combination of input and output port.

188 All tests shall be carried out to validate performance over the required operating wavelength  
189 range. As a result, single or multiple spectral bands may be chosen for the qualification and  
190 differing target specifications may be assigned to each spectral band.

191 The following Table 1 is intended to provide guidance on the wavelength ranges of the  
192 various spectral bands. It is not intended for specification. Values of operating wavelength  
193 used in performance verification shall be defined in the manufacturer's specification.

194  
195

**Table 1 – Single-mode spectral bands**

Band	Descriptor	Range nm
O-band	Original	1 260 to 1 360
E-band	Extended	1 360 to 1 460
S-band	Short wavelength	1 460 to 1 530
C-band	Conventional	1 530 to 1 565
L-band	Long wavelength	1 565 to 1 625
U-band	Ultralong wavelength	1 625 to 1 675
SOURCE ITU-T G-series Recommendations – Supplement 39, Optical system design and engineering considerations		

### 196 5 Test report

197 Fully documented test reports and supporting evidence shall be prepared and be available for  
198 inspection as evidence that the tests have been carried out and complied with.

199 **6 Performance requirements**200 **6.1 Reference components**

201 The testing for these devices does not require the use of reference components.

202 **6.2 Dimensions**203 Dimensions shall comply with either an appropriate IEC interface standard or with those given  
204 in appropriate manufacturers drawings, where the IEC interface standard does not exist or  
205 cannot be used.206 **6.3 Test details and requirements**207 The requirements are given only for pigtailed DWDM devices. For connectorized components,  
208 the connector performances shall be in compliance with IEC 61753-1.209 The minimum length of fibre or cable of 1,0 m per port on each pigtailed side shall be used for  
210 all tests.211 Test details and minimum requirements for category OP+ is shown in Table 2, Table 3 and  
212 Table 4.213 **Table 2 – Test details and requirements for type A (Gaussian passband profile)**

No	Tests	Requirements	Details	
1A	Number of channels: N	$16 \leq N \leq 64$	Operating wavelength: NOTE	ITU-T grid (ITU-T Recommendation G.694.1) or custom design Design information (not test item)
2A	Channel frequency range	Channel central frequency $\pm 0,125 \times \Delta f$ where $\Delta f$ is the channel spacing	Channel central frequency: NOTE	ITU-T grid (ITU-T Recommendation G.694.1) or custom design Design information (not test item)
3A	Attenuation (Insertion loss) IEC 61300-3-29	$\leq 6,0$ dB (channel spacing with 50 GHz) $\leq 4,5$ dB (channel spacing with 100 GHz, 200 GHz) Maximum allowable attenuation (Insertion loss) over the channel frequency range	Launch fibre length: Measurement uncertainty: NOTE	$\geq 2,0$ m 0,2 dB The attenuation (Insertion loss) is determined as the maximum value over all states of polarization
4A	Channel non-uniformity IEC 61300-3-29	$\leq 1,5$ dB Maximum allowable channel non-uniformity of attenuation	Launch fibre length: Measurement uncertainty: NOTE	$\geq 2,0$ m 0,2 dB The channel non-uniformity is determined as the maximum value over all states of polarization
5A	1 dB passband width IEC 61300-3-29	$\geq 0,25 \times \Delta f$ where $\Delta f$ is the channel spacing. Minimum allowable 1 dB passband width (centred at the channel frequency)	Launch fibre length: Measurement uncertainty: NOTE	$\geq 2,0$ m $0,01 \times \Delta f$ The 1 dB passband width is determined as the minimum value over all states of polarization

Table 2 (continued)

No	Tests	Requirements	Details	
6A	3 dB passband width IEC 61300-3-29	$\geq 0,4 \times \Delta f$ where $\Delta f$ is the channel spacing (channel spacing with 200 GHz)  $\geq 0,5 \times \Delta f$ where $\Delta f$ is the channel spacing (channel spacing with 50 GHz, 100 GHz)  Minimum allowable 3 dB passband width (centred at the channel frequency)	Launch fibre length:  Measurement uncertainty:  NOTE	$\geq 2,0$ m  $0,01 \times \Delta f$  The 3 dB passband width is determined as the minimum value over all states of polarization
7A	Passband ripple IEC 61300-3-29	$\leq 1,5$ dB  Maximum attenuation variation within the channel frequency range	Launch fibre length:  Measurement uncertainty:  NOTE	$\geq 2,0$ m  0,2 dB  The passband ripple is determined as the maximum value over all states of polarization.
8A	Adjacent channel crosstalk IEC 61300-3-29	$\leq -25$ dB  Maximum allowable adjacent channel crosstalk over the channel frequency range	Launch fibre length:  Measurement uncertainty:  NOTE	$\geq 2,0$ m  1 dB  The adjacent channel crosstalk is specified only for demultiplexer.  The adjacent channel crosstalk is determined as the maximum value over all states of polarization
9A	Non-adjacent channel crosstalk IEC 61300-3-29	$\leq -30$ dB  Maximum allowable non-adjacent channel crosstalk over the channel frequency range	Launch fibre length:  Measurement uncertainty:  NOTE	$\geq 2,0$ m  1 dB  The non-adjacent channel crosstalk is specified only for demultiplexer.  The non-adjacent channel crosstalk is determined as the maximum value over all states of polarization
10A	Total channel crosstalk IEC 61300-3-29	$\leq -20$ dB  Maximum allowable total channel crosstalk value	Launch fibre length:  Measurement uncertainty:  NOTE	$\geq 2,0$ m  1 dB  The total channel crosstalk is specified only for demultiplexer.  The total channel crosstalk is determined as the maximum value over all states of polarization
11A	Polarization dependent loss (PDL) IEC 61300-3-2	$\leq 0,75$ dB  Maximum allowable PDL over the channel frequency range	Launch fibre length:  Measurement uncertainty:  NOTE	$\geq 2,0$ m  0,10 dB  The allowable PDL combination applies to all combination of input and output ports