SLOVENSKI STANDARD
oSIST prEN IEC 60143-4:2022

01-februar-2022

Zaporedni kondenzatorji za elektroenergetske sisteme - 4. del: Zaporedni kondenzatorji s tiristorskim upravljanjem

Series capacitors for power systems - Part 4: Thyristor controlled series capacitors

Reihenkondensatoren für Starkstromanlagen - Teil 4: Thyristorgesteuerte Reihenkondensatoren

Condensateurs série destinés à être installés sur des réseaux - Partie 4: Condensateurs série commandés par thyristors

Ta slovenski standard je istoveten z: prEN IEC 60143-4:2021

ICS:

29.240.99	Druga oprema v zvezi z omrežji za prenos in distribucijo električne energije	Other equipment related to power transmission and distribution networks
31.060.70	Močnostni kondenzatorji	Power capacitors

oSIST prEN IEC 60143-4:2022 **en**

33/666/CDV

COMMITTEE DRAFT FOR VOTE (CDV)

PROJECT NUMBER:	
IEC 60143-4 ED2	
DATE OF CIRCULATION: **2021-11-26**	CLOSING DATE FOR VOTING: **2022-02-18**
SUPERSEDES DOCUMENTS: **33/652/CD, 33/655A/CC**	

IEC TC 33 : POWER CAPACITORS AND THEIR APPLICATIONS	
SECRETARIAT: Italy	SECRETARY: Mr Stefano Zunino
OF INTEREST TO THE FOLLOWING COMMITTEES: SC 22F	PROPOSED HORIZONTAL STANDARD: ☐
	Other TC/SCs are requested to indicate their interest, if any, in this CDV to the secretary.
FUNCTIONS CONCERNED: ☐ EMC ☐ ENVIRONMENT ☐ QUALITY ASSURANCE ☐ SAFETY	
☒ SUBMITTED FOR CENELEC PARALLEL VOTING	☐ NOT SUBMITTED FOR CENELEC PARALLEL VOTING
Attention IEC-CENELEC parallel voting The attention of IEC National Committees, members of CENELEC, is drawn to the fact that this Committee Draft for Vote (CDV) is submitted for parallel voting. The CENELEC members are invited to vote through the CENELEC online voting system.	

This document is still under study and subject to change. It should not be used for reference purposes.

Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

TITLE:

Series capacitors for power systems - Part 4: Thyristor controlled series capacitors

PROPOSED STABILITY DATE: 2025

NOTE FROM TC/SC OFFICERS:

CONTENTS

FOREWORD 4
1 Scope 6
2 Normative references 6
3 Terms, definitions and abbreviations 7
3.1 Abbreviations 7
3.2 Terms and definitions 7
4 Operating and rating considerations 11
4.1 General 11
4.2 TCSC characteristics 14
4.3 Operating range 15
4.4 Reactive power rating 16
4.5 Power oscillation damping (POD) 16
4.6 SSR mitigation 16
4.7 Harmonics 17
4.8 Control interactions between TCSCs in parallel lines 17
4.9 Operating range, overvoltages and duty cycles 17
4.9.1 Operating range 17
4.9.2 Transient overvoltages 17
4.9.3 Duty cycles 17
5 Valve control 18
5.1 Triggering system 18
5.2 System aspects 19
5.3 Normal operating conditions 19
5.4 Valve firing during system faults 20
5.5 Actions at low line current 20
5.6 Monitoring 20
6 Ratings 20
6.1 Capacitor rating 20
6.2 Reactor rating 21
6.3 Thyristor valve rating 21
6.3.1 Current capability 21
6.3.2 Voltage capability 22
6.4 Varistor rating 24
6.5 Insulation level and creepage distance 24
7 Tests 24
7.1 Test of the capacitor 25
7.1.1 Routine tests 25
7.1.2 Type tests 25
7.1.3 Special test (endurance test) 26
7.2 Tests of the TCSC reactor 26
7.2.1 Routine tests 26
7.2.2 Type tests 26
7.2.3 Special tests 26
7.3 Tests of thyristor valves 27
7.3.1 Routine tests 27
7.3.2 Type tests 27

7.4 Tests of protection and control system 27
7.4.1 Routine tests 28
7.4.2 Type tests 28
7.4.3 Special tests 29
8 Guidance for selection of rating and operation 29
8.1 General 29
8.2 Thyristor controlled series capacitor 31
8.2.1 AC transmission system 31
8.2.2 TCSC operational objectives 31
8.2.3 TCSC ratings 32
8.3 Thyristor valves 33
8.4 Capacitors and reactors 33
8.4.1 Capacitor considerations 34
8.4.2 Reactor considerations 34
8.5 Fault duty cycles for varistor rating 34
8.6 Valve cooling system 35
8.7 TCSC control and protection 36
8.7.1 Control 36
8.7.2 Protection 38
8.7.3 Monitoring and recording 39
8.8 Precommissioning and commissioning tests 39
8.8.1 Introduction 39
8.8.2 Precommissioning tests 40
8.8.3 Station tests 40
8.8.4 Commissioning (field) tests 40
Bibliography 42

Figure 1 – Typical nomenclature of a TCSC installation 12
Figure 2 – TCSC subsegment 13
Figure 3 – TCSC steady state waveforms for control angle α and conduction interval σ 14
Figure 4 – TCSC power frequency steady state reactance characteristics according to Equation (1) with λ = 2,5 15
Figure 5 – Example of TCSC operating range for POD (left) and SSR mitigation (right) 15
Figure 6 – Valve base electronics (VBE) 18
Figure 7 – Valve electronics (VE) 19
Figure 8 – Thyristor valve voltage in a TCSC 23
Figure 9 – Typical block diagram of a real time TCSC protection- and control system simulation environment 29
Figure 10 – Example of operating range diagram for TCSC 32

Table 1 – Peak and RMS voltage relationships 13
Table 2 – Typical external fault duty cycle with unsuccessful high speed auto-reclosing 34
Table 3 – Typical duty cycle for internal fault with successful high speed auto-reclosing 34
Table 4 – Typical duty cycle for internal fault with unsuccessful high speed auto-reclosing 35

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

SERIES CAPACITORS FOR POWER SYSTEMS –

Part 4: Thyristor controlled series capacitors

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.

2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.

3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.

4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.

5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.

6) All users should ensure that they have the latest edition of this publication.

7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.

8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60143-4 has been prepared by IEC technical committee 33: Power capacitors and their applications.

This part of IEC 60143 is to be used in conjunction with the following standards:

– IEC 60143-1:2015, *Series capacitors for power systems – Part 1: General*

– IEC 60143-2:2012, *Series capacitors for power systems – Part 2: Protective equipment for series capacitor banks*

– IEC 60143-3:2015, *Series capacitors for power systems – Part 3: Internal fuses*

This draft was written based on the current standard IEC 60143-4 ED 1.0; changes compared with the aforesaid document are highlighted in red. Further changes compared to 33/652/CD are highlighted in light blue.

A list of all parts of IEC 60143 series, under the general title *Series capacitors for power systems* can be found on the iec website.

NOTE This standard contains excerpts reproduced from IEEE Std 1534-2002. IEEE Std 1534-2002 IEEE Recommended Practice for Specifying Thyristor-Controlled Series Capacitors. Reprinted with permission from IEEE, 3 Park Avenue, New York, NY 10016-5997 USA, Copyright 2002 IEEE.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

SERIES CAPACITORS FOR POWER SYSTEMS –

Part 4: Thyristor controlled series capacitors

1 Scope

This part of IEC 60143 specifies testing of thyristor controlled series capacitor (TCSC) installations used in series with transmission lines. This standard also addresses issues that consider ratings for TCSC thyristor valve assemblies, capacitors, and reactors as well as TCSC control characteristics, protective features, cooling system and system operation.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE If there is a conflict between this part of IEC 60143 and a standard listed below in Clause 2, this standard prevails.

IEC 60050-436, *International Electrotechnical Vocabulary – Chapter 436: Power capacitors*

IEC 60060-1, *High-voltage test techniques – Part 1: General definitions and test requirements*

IEC 60068-1, *Environmental Testing – Part 1: General and guidance*

IEC 60068-2-2, *Basic environmental testing procedures – Part 2-2: Tests – Tests B: Dry heat*

IEC 60068-2-78, *Basic environmental testing procedures – Part 2-78: Tests – Tests C: Damp heat, steady state*

IEC 60071-1, *Insulation co-ordination – Part 1: Definitions, principles and rules*

IEC 60071-2, *Insulation co-ordination – Part 2: Application guide*

IEC 60076-1, *Power transformers – Part 1: General*

IEC 60076-6:2007, *Power transformers – Part 6: Reactors*

IEC 60143-1:2015, *Series capacitors for power systems – Part 1: General*

IEC 60143-2:2012, *Series capacitors for power systems – Part 2: Protective equipment for series capacitor banks*

IEC 60143-3:2015, *Series capacitors for power systems – Part 3: Internal fuses*

IEC 60255-5, *Electrical relays – Part 5: Insulation coordination for measuring relays and protection equipment – Requirements and tests*

IEC 60255-21 (all parts), *Electrical relays – Vibration, shock, bump and seismic tests on measuring relays and protection equipment*

IEC 61000-4-29, *Electromagnetic compatibility (EMC) – Part 4-29: Testing and measurement techniques – Voltage dips, short interruptions and voltage variations on d.c. input port immunity tests*

IEC 62823:2015, *Thyristor valves for thyristor controlled series capacitors (TCSC) – Electrical testing*

NOTE Additional useful references, not explicitly referenced in the text, are listed in the Bibliography.

3 Terms, definitions and abbreviations

For the purposes of this document, the following terms, definitions and abbreviations as well as those given in IEC 60143-1, IEC 60143-2, IEC 60143-3 and some taken from IEC 60050-436 apply.

NOTE In some instances, the IEC definitions may be either too broad or too restrictive. In such a case, an additional definition or note has been included.

3.1 Abbreviations

ETT	Electrically triggered thyristors
FACTS	Flexible ac transmission systems
FSC	Fixed series compensation
LTT	Light-triggered thyristors
MC	Master control
MTBF	Mean time between failure
MTTR	Mean time to repair
POD	Power oscillation damping
RAM	Reliability, availability, and maintainability
RIV	Radio influence voltage
RTU	Remote terminal unit
SCADA	Supervisory control and data acquisition
ER	Events recorder
FR	Fault recorder
RTDS	Real time digital simulation
SSR	Sub synchronous resonance
SVC	Static var compensator
TCR	Thyristor-controlled reactor
RMS	Root-mean-square
BLK	Blocked (mode of operation)
BP	Bypass (mode of operation)
CAP	Capacitive boost (mode of operation)
HMI	Human Machine Interface

3.2 Terms and definitions

3.2.1
thyristor valve
electrically combined assembly of thyristor levels, complete with all connections, auxiliary components and mechanical structures, which can be connected in series with each phase of the reactor or capacitor of a TCSC

3.2.2
bypass current
the current flowing through the bypass switch, protective device, thyristor valve, or other devices, in parallel with the series capacitor, when the series capacitor is bypassed

3.2.3
capacitive range
TCSC operation resulting in an effective increase of the power frequency reactance of the series capacitor (See Figure 5)

3.2.4
temporary overload
short duration (typically 30 min) overload capability of the TCSC at rated frequency and ambient temperature range

3.2.5
dynamic overload
short duration (typically 10 s) overload capability of the TCSC at rated frequency and ambient temperature range. (See Figure 5 and Figure 10)

3.2.6
platform-to-ground cooling/air-handling insulator
an insulator that encloses cooling/air handling paths between platform and ground level

3.2.7
thyristor-controlled series capacitor bank
TCSC
an assembly of thyristor valves, TCSC reactor(s), capacitors, and associated auxiliaries, such as structures, support insulators, switches, and protective devices, with control equipment required for a complete operating installation

3.2.8
valve electronics
VE
electronic circuits at valve potential(s) that perform control functions

3.2.9
TCSC reactor
one or more reactors connected in series with the thyristor valve (see NOTE This figure contains material reproduced from IEEE Std 1534-2002. IEEE Std 1534-2002 IEEE Recommended Practice for Specifying Thyristor-Controlled Series Capacitors, Copyright 2002 IEEE. All rights reserved.

Figure 1, item 12)

3.2.10
valve varistor
an assembly of varistor units that limit overvoltages to a given value. In the context of TCSCs, the valve varistor is typically defined by its ability to limit the voltage across a thyristor valve to a specified protective level while absorbing energy. The valve varistor is designed to withstand the temporary overvoltages and continuous operating voltage across the thyristor valve

3.2.11
valve blocking
an operation to prevent further firing of a thyristor valve by inhibiting triggering

3.2.12
valve deblocking
an operation to permit firing of a thyristor valve by removing valve blocking action

3.2.13
valve base electronics
VBE
an electronic unit, at earth potential, which is the interface between the control system of the TCSC and the thyristor valves

3.2.14
capacitor current
I_C
current through the series capacitor (see Figure 2)

3.2.15
line current
I_L
power frequency line current (see Figure 2)

3.2.16
rated current
I_N
the RMS line current (I_L) at which the TCSC should be capable of continuous operation with rated reactance (X_N) and rated voltage (U_N)

3.2.17
valve current
I_V
current through the thyristor valve (see Figure 2)

3.2.18
capacitor voltage
U_C
voltage across the TCSC (see Figure 2)

3.2.19
protective level
U_{PL}
magnitude of the maximum peak of the power frequency voltage appearing across the overvoltage protector during a power system fault

NOTE The protective level may be expressed in terms of the actual peak voltage across a segment or in terms of the per unit of the peak of the rated voltage across the capacitor.

3.2.20
rated TCSC voltage
U_N
the power frequency voltage across each phase of the TCSC that can be continuously controlled at nominal reactance (X_N), rated current (I_N), frequency, and reference ambient temperature range

3.2.21
apparent reactance
$X(\alpha)$
TCSC apparent power frequency reactance as a function of thyristor control angle (α) (see Figure 4)

3.2.22
rated frequency
f_N
frequency of the system in which the TCSC is intended to be used

3.2.23
rated capacitance
C_N
capacitance value for which the TCSC capacitor has been designed

3.2.24
physical reactance
X_C
the power frequency reactance for each phase of the TCSC bank with thyristors blocked and a capacitor internal dielectric temperature of 20 °C; $X_C = 1/(2\pi f_N \times C_N)$

3.2.25
boostfactor
k_B
the ratio of $X(\alpha)$ divided by X_C; $k_B = X(\alpha) / X_C$

3.2.26
nominal reactance
X_N
the nominal power frequency reactance for each phase of the TCSC with rated line I_N and nominal boost factor

3.2.27
conduction interval
σ
that part of a cycle during which a thyristor valve is in the conducting state, $\sigma = 2\beta$ (see Figure 3)

3.2.28
control angle
α
the time expressed in electrical angular measure from the capacitor voltage (U_C) zero crossing to the starting of current conduction through the thyristor valve. (see Figure 3)

3.2.29
internal fault
an internal fault is a line fault occurring within the protected line section containing the series capacitor bank

3.2.30
external fault
an external fault is a line fault occurring outside the protected line section containing the series capacitor bank