



SLOVENSKI STANDARD

oSIST prEN IEC 61139-2:2021

01-november-2021

Industrijska omrežja - Enožični digitalni komunikacijski vmesnik za male senzorje in dajalnike - 2. del: Funkcijska varnost podaljškov

Industrial networks - Single-drop digital communication interface - Part 2: Functional safety extensions

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: ~~oSIST prEN IEC 61139-2:2021~~ prEN IEC 61139-2:2021
<https://standards.iteh.ai/catalog/standards/sist/c5441fa2-8f26-4bcf-9b71-159d4015150e/osist-pr-en-iec-61139-2-2021>

ICS:

25.040.40	Merjenje in krmiljenje industrijskih postopkov	Industrial process measurement and control
35.110	Omreževanje	Networking

oSIST prEN IEC 61139-2:2021

en,fr,de

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[oSIST prEN IEC 61139-2:2021](https://standards.iteh.ai/catalog/standards/sist/c5441fa2-8f26-4bcf-9b71-159d4015150e/osist-pren-iec-61139-2-2021)

<https://standards.iteh.ai/catalog/standards/sist/c5441fa2-8f26-4bcf-9b71-159d4015150e/osist-pren-iec-61139-2-2021>



PROJECT NUMBER:

IEC 61139-2 ED1

DATE OF CIRCULATION:

2021-09-03

CLOSING DATE FOR VOTING:

2021-11-26

SUPERSEDES DOCUMENTS:

65C/1081/CD, 65C/1094A/CC

IEC SC 65C : INDUSTRIAL NETWORKS	
SECRETARIAT: France	SECRETARY: Ms Valérie DEMASSIEUX
OF INTEREST TO THE FOLLOWING COMMITTEES: SC 65A, SC 65B	PROPOSED HORIZONTAL STANDARD: <input type="checkbox"/> Other TC/SCs are requested to indicate their interest, if any, in this CDV to the secretary.
FUNCTIONS CONCERNED: <input type="checkbox"/> EMC <input type="checkbox"/> ENVIRONMENT <input type="checkbox"/> QUALITY ASSURANCE <input type="checkbox"/> SAFETY	
<input checked="" type="checkbox"/> SUBMITTED FOR CENELEC PARALLEL VOTING <input type="checkbox"/> NOT SUBMITTED FOR CENELEC PARALLEL VOTING Attention IEC-CENELEC parallel voting (standards.iteh.ai) The attention of IEC National Committees, members of CENELEC, is drawn to the fact that this Committee Draft for Vote (CDV) is submitted for parallel voting. https://standards.iteh.ai/catalog/standards/sist/c5441fa2-8f26-4bcf-9b71-590e1f70180a/pr-en-iec-61139-2-2021 The CENELEC members are invited to vote through the CENELEC online voting system.	

This document is still under study and subject to change. It should not be used for reference purposes.

Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

TITLE:

Industrial networks – Single-drop digital communication interface – Part 2: Functional safety extensions

PROPOSED STABILITY DATE: 2025

NOTE FROM TC/SC OFFICERS:

NC comments on this CDV will be resolved during the next SC65C/PT61139-2 meeting currently scheduled as a series of web meetings on November 23rd-25th, 2021. Corresponding meeting notice will be provided in due time by the convenor.

Copyright © 2021 International Electrotechnical Commission, IEC. All rights reserved. It is permitted to download this electronic file, to make a copy and to print out the content for the sole purpose of preparing National Committee positions. You may not copy or "mirror" the file or printed version of the document, or any part of it, for any other purpose without permission in writing from IEC.

CONTENTS

1		
2		
3	FOREWORD	12
4	INTRODUCTION	14
5	1 Scope	16
6	2 Normative references	16
7	3 Terms, definitions, symbols, abbreviated terms, and conventions	17
8	3.1 Common terms and definitions	17
9	3.2 SDCI-FS Safety: Additional terms and definitions	20
10	3.3 Symbols and abbreviated terms	21
11	3.4 Conventions	23
12	3.4.1 Behavioral descriptions	23
13	3.4.2 Memory and transmission octet order	23
14	4 Overview of SDCI-FS	24
15	4.1 Purpose of the technology and feature levels	24
16	4.1.1 Base SDCI-FS technology	24
17	4.1.2 From "analog" and "switching" to communication	24
18	4.1.3 Minimized paradigm shift from FS-DI to FS-Master	25
19	4.1.4 Following the SDCI paradigm (SIO vs. OSSDe)	26
20	4.1.5 Port class B	28
21	4.1.6 "USB-Master" with safety parameterization	28
22	4.1.7 Interoperability matrix of safety devices	29
23	4.2 Positioning within the automation hierarchy	29
24	4.3 Wiring, connectors, and power supply	30
25	4.4 Relationship to SDCI	30
26	4.5 Communication features and interfaces	31
27	4.6 Parameterization	31
28	4.7 Role of FS-Master and FS-Gateway	31
29	4.8 Mapping to upper-level systems	32
30	4.9 Structure of the document	32
31	5 Extensions to the Physical Layer (PL)	32
32	5.1 Overview	32
33	5.2 Extensions to PL services	33
34	5.2.1 PL_SetMode	33
35	5.2.2 PL_Ready	33
36	5.3 Transmitter/receiver	33
37	5.3.1 Assumptions for the expansion to OSSDe	33
38	5.3.2 OSSDe specifics	34
39	5.3.3 Start-up of an FS-Device (Ready pulse)	36
40	5.3.4 Electric characteristics of a receiver in FS-Device and FS-Master	37
41	5.4 Electric and dynamic characteristics of an FS-Device	38
42	5.5 Electric and dynamic characteristics of an FS-Master port (OSSDe)	40
43	5.6 FS-Master port FS-DI interface	41
44	5.7 Wake-up coordination	41
45	5.8 Fast start-up	42
46	5.9 Power supply	42
47	5.10 Medium	42

48	5.10.1	Constraints	42
49	5.10.2	Connectors	42
50	5.10.3	Cable characteristics	42
51	6	Extensions to SIO	43
52	7	Extensions to the data link layer (DL)	43
53	7.1	Overview	43
54	7.2	State machine of the FS-Master DL-mode handler	43
55	7.3	State machine of the FS-Device DL-mode handler	44
56	8	Extensions to the Master Configuration Manager (CM)	46
57	9	Extensions of the FS-Device	47
58	9.1	Principle architecture and models	47
59	9.1.1	FS-Device architecture	47
60	9.1.2	FS-Device model	47
61	9.2	Parameter Manager (PM)	48
62	9.3	Process Data Exchange (PDE)	48
63	9.4	Data Storage (DS)	48
64	9.4.1	General considerations and extensions including safety	48
65	9.4.2	Backup levels	49
66	10	Extensions of the FS-Master	49
67	10.1	Principle architecture	49
68	10.2	SMI service extensions	50
69	10.2.1	Overview	50
70	10.2.2	SMI_FSMasterAccess	52
71	10.2.3	SMI_SPDUIn	53
72	10.2.4	SMI_SPDUOut	53
73	10.3	ArgBlock extensions	53
74	10.3.1	Overview	53
75	10.3.2	FSMasterAccess	54
76	10.3.3	FSCPAuthenticity	54
77	10.3.4	FSPortConfigList	54
78	10.3.5	FSPortStatusList	56
79	10.3.6	SPDUIn	58
80	10.3.7	SPDUOut	58
81	10.4	Safety Layer Manager (SLM)	58
82	10.4.1	Purpose	58
83	10.4.2	FS_PortModes	58
84	10.4.3	FSP parameter	59
85	10.5	Process Data Exchange (PDE)	61
86	10.6	Data Storage (DS)	63
87	11	Safety communication layer (SCL)	63
88	11.1	Functional requirements	63
89	11.2	Communication errors and safety measures	63
90	11.3	SCL services	64
91	11.3.1	Positioning of safety communication layers (SCL)	64
92	11.3.2	FS-Master SCL services	65
93	11.3.3	FS-Device SCL services	66
94	11.4	SCL protocol	68
95	11.4.1	Protocol phases to consider	68

ITEH STANDARD PREVIEW

(standards.iteh.ai)

oSIST prEN IEC 61139-2:2021

[https://standards.iteh.ai/catalog/standards/sist/c5441fa2-8f26-4bcf-9b71-](https://standards.iteh.ai/catalog/standards/sist/c5441fa2-8f26-4bcf-9b71-159d4015150e/osist-pr-en-iec-61139-2-2021)

[159d4015150e/osist-pr-en-iec-61139-2-2021](https://standards.iteh.ai/catalog/standards/sist/c5441fa2-8f26-4bcf-9b71-159d4015150e/osist-pr-en-iec-61139-2-2021)

96	11.4.2	FS-Device faults	69
97	11.4.3	Safety PDU (SPDU).....	69
98	11.4.4	FS-Input and FS-Output data.....	69
99	11.4.5	Port number.....	69
100	11.4.6	Status and control	69
101	11.4.7	CRC signature	70
102	11.4.8	Data types for SDCI-FS	71
103	11.5	SCL behavior	72
104	11.5.1	General	72
105	11.5.2	SCL state machine of the FS-Master	73
106	11.5.3	SCL state machine of the FS-Device	75
107	11.5.4	Sequence charts for several use cases.....	78
108	11.5.5	Monitoring of safety times.....	84
109	11.5.6	Reaction in the event of a malfunction	85
110	11.5.7	Start-up (communication).....	87
111	11.6	SCL management	87
112	11.6.1	Parameter overview (FSP and FST).....	87
113	11.6.2	Parameterization approaches	88
114	11.7	Integrity measures	89
115	11.7.1	IODD integrity.....	89
116	11.7.2	Tool integrity.....	89
117	11.7.3	Transmission integrity.....	89
118	11.7.4	Verification record	89
119	11.7.5	Authentication	90
120	11.7.6	Storage integrity	90
121	11.7.7	FS I/O data structure integrity.....	91
122	11.7.8	Technology parameter (FST) based on IODD	91
123	11.7.9	Technology parameter (FST) based on existing Dedicated Tool (IOPD).....	92
124	11.8	Creation of FSP and FST parameters	93
125	11.9	Integration of Dedicated Tools (IOPD).....	94
126	11.9.1	IOPD interface.....	94
127	11.9.2	Standard interfaces	94
128	11.9.3	Backward channel	95
129	11.10	Validation.....	95
130	11.11	Passivation	95
131	11.11.1	Motivation and means.....	95
132	11.11.2	Port selective (FS-Master)	96
133	11.11.3	Signal selective (FS-Terminal).....	96
134	11.11.4	Qualifier settings in case of communication	96
135	11.11.5	Qualifier handling in case of OSSDe.....	96
136	11.12	SCL diagnosis.....	98
137	12	Functional safe processing (FS-P).....	98
138	12.1	Recommendations for efficient I/O mappings	98
139	12.2	Embedded FS controller	98
140	Annex A (normative, safety-related)	Extensions to parameters	99
141	A.1	Indices and parameters for SDCI-FS.....	99
142	A.2	Parameters in detail.....	100
143	A.2.1	FSP_Authenticity	100
144	A.2.2	FSP_Port.....	100

145	A.2.3	FSP_AuthentCRC	100
146	A.2.4	FSP_ProtVersion	101
147	A.2.5	FSP_ProtMode	101
148	A.2.6	FSP_Watchdog	101
149	A.2.7	FSP_IO_StructCRC	101
150	A.2.8	FSP_TechParCRC	102
151	A.2.9	FSP_ProtParCRC	103
152	A.2.10	FSP_VerifyRecord	103
153	A.2.11	FSP_TimeToReady	103
154	A.2.12	FSP_WCDT	103
155	A.2.13	FSP_OFDT	103
156	A.2.14	FSP_ParamDescCRC	103
157	Annex B (normative, non-safety related) Extensions to EventCodes		105
158	B.1	Additional FS-Device EventCodes	105
159	B.2	Additional Port EventCodes	105
160	Annex C (normative, safety related) Extensions to Data Types		107
161	C.1	Data types for SDCI-FS	107
162	C.2	BooleanT (bit)	107
163	C.3	IntegerT (16)	108
164	C.4	IntegerT (32)	108
165	C.5	Safety Code	109
166	Annex D (normative, safety related) CRC generator polynomials		110
167	D.1	Overview of CRC generator polynomials	110
168	D.2	Residual error probabilities	110
169	D.3	Implementation considerations	112
170	D.3.1	Overview	112
171	D.3.2	Bit shift algorithm (16 bit)	112
172	D.3.3	Lookup table (16 bit)	112
173	D.3.4	Bit shift algorithm (32 bit)	113
174	D.3.5	Lookup table (32 bit)	114
175	D.3.6	Seed values	115
176	Annex E (normative, safety related) IODD extensions		116
177	E.1	General	116
178	E.2	Schema	116
179	E.3	IODD constraints	116
180	E.3.1	General rules	116
181	E.3.2	Description of the IODD structure	116
182	E.3.3	Behavior of "Reset" SystemCommands in SDCI-FS	123
183	E.3.4	Profile Characteristic	123
184	E.3.5	ProcessDataInput and ProcessDataOutput	123
185	E.4	IODD conventions	124
186	E.4.1	Naming	124
187	E.4.2	Process Data (PD)	124
188	E.4.3	IODD conventions for user interface	124
189	E.4.4	Master Tool features	124
190	E.5	Securing	125
191	E.5.1	General	125
192	E.5.2	DefaultValues for FSP	125

193	E.5.3	FSP_Authenticity	126
194	E.5.4	FSP_Protocol	126
195	E.5.5	FSP_IO_Description	126
196	E.5.6	Sample serialization for FSP_ParamDescCRC	126
197	E.5.7	FST and FSP parameters and Data Storage	127
198	E.5.8	Sample IOOD of an FS-Device	128
199	Annex F (normative, non-safety related) Device Tool Interface (DTI) for SDCI		138
200	F.1	Purpose of DTI	138
201	F.2	Base model	138
202	F.3	Invocation interface	139
203	F.3.1	Overview	139
204	F.3.2	Detection of Device Tool	139
205	F.3.3	Program Interface Description – PID	142
206	F.3.4	Temporary Parameter File – TPF	145
207	F.3.5	Temporary Backchannel File – TBF	150
208	F.3.6	Temporary Acknowledgment File – TAF	151
209	F.3.7	Invocation behavior	152
210	F.4	Device data objects (DDO)	152
211	F.4.1	General	152
212	F.4.2	Structure of DDO package	153
213	F.5	Communication Interface	153
214	F.5.1	General	153
215	F.5.2	Principle of DTI communications	154
216	F.5.3	Gateways	155
217	F.5.4	Configuration of the Communication Server	156
218	F.5.5	Definition of the Communication Interface	156
219	F.5.6	Sequence for establishing a communication relation	156
220	F.5.7	Usage of the Communication Server in stand-alone mode	157
221	F.5.8	SDCI specifics	158
222	F.5.9	Changing communication settings	158
223	F.6	Reaction on incorrect Tool behavior	158
224	F.7	Compatibility	159
225	F.7.1	Schema validation	159
226	F.7.2	Version policy	159
227	F.8	Scalability	159
228	F.8.1	Scalability of a Device Tool	159
229	F.8.2	Scalability of a Master Tool	160
230	F.8.3	Interactions at conformance class combinations	160
231	F.9	Schema definitions	161
232	F.9.1	General	161
233	F.9.2	Schema of the PID	161
234	F.9.3	Schema of the TPF	162
235	F.9.4	Schema of the TBF	165
236	F.9.5	Schema of the TAF	166
237	F.9.6	Schema of DTI primitives	166
238	Annex G (normative) Main scenarios of SDCI-FS		168
239	G.1	Overview	168
240	G.2	Sequence chart of commissioning	169
241	G.3	Sequence chart of replacement	170

242	G.4	Sequence chart of misconnection	170
243	Annex H (normative)	System requirements	171
244	H.1	Indicators	171
245	H.1.1	General	171
246	H.1.2	OSSDe	171
247	H.1.3	Safety communication	171
248	H.1.4	Acknowledgment request	171
249	H.2	Installation guidelines, electrical safety, and security	171
250	H.3	Safety function response time	172
251	H.4	Duration of demands	172
252	H.5	Maintenance and repair	172
253	H.6	Safety manual	172
254	Annex I (informative)	Information for test and assessment of the SDCI-FS system of	
255	IEC 61131-9:—	173
256	Bibliography	174
257			
258	Figure 1 –	Positioning of SDCI-FS in functional safety automation	14
259	Figure 2 –	Relationship of this document to standards	15
260	Figure 3 –	Memory and transmission octet order	23
261	Figure 4 –	SDCI-FS communication layer model	24
262	Figure 5 –	Port interface extensions for SDCI-FS	25
263	Figure 6 –	Migration to SDCI-FS	25
264	Figure 7 –	Minimized paradigm shift from FS-DI to FS-Master	26
265	Figure 8 –	FS-Master types and feature levels	26
266	Figure 9 –	Original pin layout of SDCI (port class A)	27
267	Figure 10 –	Optimized OSSDe commissioning with FS-Master	28
268	Figure 11 –	Level "d" of an FS-Master (Class B)	28
269	Figure 12 –	Off-site configuration and parameterization	29
270	Figure 13 –	SDCI-FS within the automation hierarchy	30
271	Figure 14 –	The SDCI physical layer of an FS-Master (class A)	32
272	Figure 15 –	The physical layer of an FS-Device (class A)	33
273	Figure 16 –	Cross compatibility OSSD and OSSDe	33
274	Figure 17 –	Principle OSSDe function	34
275	Figure 18 –	Test pulses to detect cross connection faults	35
276	Figure 19 –	OSSD timings	36
277	Figure 20 –	Typical start-up of an OSSD sensor	36
278	Figure 21 –	Start-up of an FS-Device	37
279	Figure 22 –	Switching thresholds for FS-Device and FS-Master receivers	37
280	Figure 23 –	Reference schematics (one OSSDe channel)	38
281	Figure 24 –	Voltage level definitions	38
282	Figure 25 –	Charge capability at power-up	41
283	Figure 26 –	OSSDe input filter conflict resolution	41
284	Figure 27 –	Start-up of an FS-Device	41
285	Figure 28 –	Required fast start-up timings	42
286	Figure 29 –	State machine of the FS-Master DL-mode handler	43

287	Figure 30 – State machine of the FS-Device DL-mode handler	45
288	Figure 31 – Extension to the Configuration Manager (VerifyRecord)	46
289	Figure 32 – Principle architecture of the FS-Device	47
290	Figure 33 – The FS-Device model.....	48
291	Figure 34 – Principle architecture of the FS-Master	50
292	Figure 35 – SMI service extensions	51
293	Figure 36 – FSP parameter use cases	59
294	Figure 37 – PDE Splitter	62
295	Figure 38 – PDE Composer	63
296	Figure 39 – Positioning of the SDCI-FS Safety Communication Layer (SCL)	65
297	Figure 40 – FS-Master Safety Communication Layer services	65
298	Figure 41 – FS-Device Safety Communication Layer services.....	67
299	Figure 42 – Protocol phases to consider	68
300	Figure 43 – Safety PDUs of FS-Master and FS-Device	69
301	Figure 44 – The 1 % share rule of IEC 61784-3:2021	71
302	Figure 45 – SCL state machine of the FS-Master	73
303	Figure 46 – SCL state machine of the FS-Device	75
304	Figure 47 – FS-Master and FS-Device both with power ON.....	78
305	Figure 48 – FS-Master power OFF → ON	79
306	Figure 49 – FS-Device with delayed SCL start	80
307	Figure 50 – FS-Device with power OFF and ON.....	81
308	Figure 51 – FS-Master detects CRC signature error.....	82
309	Figure 52 – FS-Device detects CRC signature error.....	83
310	Figure 53 – Monitoring of the SCL cycle time	84
311	Figure 54 – Parameter types and assignments.....	88
312	Figure 55 – FSCP-Host-centric system	89
313	Figure 56 – Structure of the FSP_VerifyRecord.....	90
314	Figure 57 – Start-up of SDCI-FS	91
315	Figure 58 – Securing of FST parameters via dedicated tool	92
316	Figure 59 – Modification of FST parameters via Device Tool.....	92
317	Figure 60 – Creation of FSP and FST parameters.....	93
318	Figure 61 – Example of a communication hierarchy	94
319	Figure 62 – Motivation for Port selective passivation.....	95
320	Figure 63 – Qualifier handler (communication).....	96
321	Figure 64 – Qualifier handler (OSSDe).....	97
322	Figure 65 – Qualifier behavior per FS-Master port	97
323	Figure 66 – Mapping efficiency issues	98
324	Figure A.1 – Instance of an FS I/O data description	102
325	Figure A.2 – Example FS I/O data structure with non-safety data.....	102
326	Figure A.3 – Securing of safety parameters	104
327	Figure C.1 – Example of a BooleanT data structure	108
328	Figure C.2 – Safety Code of an output message	109
329	Figure C.3 – Safety Code of an input message	109

330	Figure D.1 – CRC-16 generator polynomial.....	111
331	Figure D.2 – CRC-32 generator polynomial.....	111
332	Figure D.3 – Bit shift algorithm in "C" language (16 bit).....	112
333	Figure D.4 – CRC-16 signature calculation using a lookup table	112
334	Figure D.5 – Bit shift algorithm in "C" language (32 bit).....	114
335	Figure D.6 – CRC-32 signature calculation using a lookup table	114
336	Figure E.1 – Algorithm to build the FSP parameter CRC signatures	125
337	Figure F.1 – Principle of DTI invocation interface	139
338	Figure F.2 – Structure of the registry	140
339	Figure F.3 – Example of a DTI registry.....	140
340	Figure F.4 – Detection of a Device Tool in registry.....	142
341	Figure F.5 – Menu for Device Tool invocation	143
342	Figure F.6 – Purpose of Device data objects (DDO).....	153
343	Figure F.7 – Communication routes between Device Tool and Device.....	154
344	Figure F.8 – Routing across networks and SDCI	155
345	Figure F.9 – Communication Server	155
346	Figure F.10 – Sequence chart for establishing communication	156
347	Figure F.11 – Create Communication Server instance.....	157
348	Figure F.12 – Example of a Connect Request XML document for SDCI.....	158
349	Figure F.13 – XML schema of the PID file.....	161
350	Figure F.14 – XML schema of the TPF	163
351	Figure F.15 – XML schema of a TBF	165
352	Figure G.1 – Commissioning with test and armed operation	169
353	Figure G.2 – FS-Device replacement	170
354	Figure G.3 – FS-Device misconnection	170
355		
356	Table 1 – Operational modes of feature level "a" to "c" (port class A).....	27
357	Table 2 – Interoperability matrix of safety devices.....	29
358	Table 3 – PL_Ready	33
359	Table 4 – OSSD states and conditions	34
360	Table 5 – Cross connection faults	35
361	Table 6 – Electric characteristics of a receiver	37
362	Table 7 – Electric and dynamic characteristics of the FS-Device (OSSDe).....	38
363	Table 8 – Electric and dynamic characteristics of the Port interface	40
364	Table 9 – Cable characteristics.....	42
365	Table 10 – State transition tables of the FS-Master DL-mode handler	44
366	Table 11 – State transition tables of the FS-Device DL-mode handler	45
367	Table 12 – State transition tables of the Configuration Manager	46
368	Table 13 – Extension to Data Storage (DS) state machine	49
369	Table 14 – Data Storage Backup Levels	49
370	Table 15 – SMI services used for FS-Master.....	50
371	Table 16 – SMI_FSMasterAccess	52
372	Table 17 – ArgBlock types and ArgBlockIDs	53

373	Table 18 – FSMasterAccess	54
374	Table 19 – FSCPAAuthenticity	54
375	Table 20 – FSPortConfigList	54
376	Table 21 – FSPortStatusList	56
377	Table 22 – SPDUIIn	58
378	Table 23 – SPDUIOut	58
379	Table 24 – Use case reference table	59
380	Table 25 – Communication errors and safety measures	64
381	Table 26 – SCL services of FS-Master	66
382	Table 27 – SCL services of FS-Device	67
383	Table 28 – Protocol phases to consider	68
384	Table 29 – Control and counting (Control&MCnt)	70
385	Table 30 – Status and counting mirror (Status&DCnt)	70
386	Table 31 – MCount and DCount_i values	70
387	Table 32 – FS process I/O data types	71
388	Table 33 – Rules for the layout of values and qualifiers	72
389	Table 34 – Order of values and qualifier	72
390	Table 35 – Definition of terms used in SCL state machine of the FS-Master	73
391	Table 36 – FS-Master SCL states and transitions	73
392	Table 37 – Definition of terms used in SCL state machine of the FS-Device	75
393	Table 38 – FS-Device SCL states and transitions	76
394	Table 39 – Timing constraints	84
395	Table 40 – Qualifier bits "GOOD/BAD"	96
396	Table 41 – State transition table for the qualifier behavior	97
397	Table A.1 – Indices for SDCI-FS	99
398	Table A.2 – Coding of protocol version	101
399	Table A.3 – Coding of protocol mode	101
400	Table A.4 – Generic FS I/O data structure description	102
401	Table B.1 – FS-Device SCL specific EventCodes	105
402	Table B.2 – FS-Master SCL specific EventCodes	105
403	Table C.1 – Data types for SDCI-FS	107
404	Table C.2 – BooleanT for SDCI-FS	107
405	Table C.3 – Example of BooleanT within a RecordT	107
406	Table C.4 – IntegerT(16)	108
407	Table C.5 – IntegerT(16) coding	108
408	Table C.6 – IntegerT(32)	108
409	Table C.7 – IntegerT(32) coding	109
410	Table D.1 – CRC generator polynomials for SDCI-FS	110
411	Table D.2 – Definition of variables used in Figure D.3	112
412	Table D.3 – Definition of variables used in Figure D.4	112
413	Table D.4 – Lookup table for CRC-16 signature calculation	113
414	Table D.5 – Definition of variables used in Figure D.5	114
415	Table D.6 – Definition of variables used in Figure D.4	114

416	Table D.7 – Lookup table for CRC-32 signature calculation	114
417	Table E.8 – Specific behavior of FS-Device "Reset" SystemCommands	123
418	Table E.9 – User actions to replace DefaultValues	125
419	Table E.10 – RecordItems of FSP_Protocol where allowed values shall be serialized	126
420	Table E.11 – Sample serialization for FSP_ParamDescCRC	126
421	Table F.1 – Description of PID file elements	143
422	Table F.2 – Elements of a TPF	146
423	Table F.3 – Elements of the TBF	150
424	Table F.4 – Elements of the TAF	151
425	Table F.5 – Invocation cases and behaviors	152
426	Table F.6 – Communication Schema mapping	158
427	Table F.7 – Reaction on incorrect Tool behavior	158
428	Table F.8 – DTI conformance classes	160
429	Table F.9 – DTI feature levels of Device Tools	160
430	Table F.10 – Interactions at conformance class combinations	160
431	Table G.1 – Main scenarios of SDCI-FS	168

432

433

iTeh STANDARD PREVIEW (standards.iteh.ai)

[oSIST prEN IEC 61139-2:2021](https://standards.iteh.ai/catalog/standards/sist/c5441fa2-8f26-4bcf-9b71-159d4015150e/osist-pren-iec-61139-2-2021)

<https://standards.iteh.ai/catalog/standards/sist/c5441fa2-8f26-4bcf-9b71-159d4015150e/osist-pren-iec-61139-2-2021>

434

INTERNATIONAL ELECTROTECHNICAL COMMISSION

435

436

437

INDUSTRIAL NETWORKS –

438

SINGLE-DROP DIGITAL COMMUNICATION INTERFACE –

439

Part 2: Functional safety extensions

440

441

442

FOREWORD

443 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising
 444 all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international
 445 co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and
 446 in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports,
 447 Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their
 448 preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with
 449 may participate in this preparatory work. International, governmental and non-governmental organizations liaising
 450 with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for
 451 Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.

452 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international
 453 consensus of opinion on the relevant subjects since each technical committee has representation from all
 454 interested IEC National Committees.

455 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National
 456 Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC
 457 Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any
 458 misinterpretation by any end user.

459 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications
 460 transparently to the maximum extent possible in their national and regional publications. Any divergence between
 461 any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.

462 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity
 463 assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any
 464 services carried out by independent certification bodies.

465 6) All users should ensure that they have the latest edition of this publication.

466 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and
 467 members of its technical committees and IEC National Committees for any personal injury, property damage or
 468 other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and
 469 expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC
 470 Publications.

471 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is
 472 indispensable for the correct application of this publication.

473 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent
 474 rights. IEC shall not be held responsible for identifying any or all such patent rights.

475 IEC 61139-2 has been prepared by subcommittee 65C: Industrial networks, of IEC technical
 476 committee TC65: Industrial-process measurement, control and automation. It is an International
 477 Standard.

478 The text of this International Standard is based on the following documents:

Draft	Report on voting
65C/XX/FDIS	65C/XX/RVD

479

480 Full information on the voting for its approval can be found in the report on voting indicated in
 481 the above table.

482 The language used for the development of this International Standard is English.

483 This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in
 484 accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available
 485 at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are
 486 described in greater detail at www.iec.ch/standardsdev/publications.

487 The committee has decided that the contents of this document will remain unchanged until the
488 stability date indicated on the IEC website under webstore.iec.ch in the data related to the
489 specific document. At this date, the document will be

- 490 • reconfirmed,
- 491 • withdrawn,
- 492 • replaced by a revised edition, or
- 493 • amended.

494

495 **IMPORTANT – The 'color inside' logo on the cover page of this publication indicates**
496 **that it contains colors which are considered to be useful for the correct understanding**
497 **of its contents. Users should therefore print this document using a color printer.**

498

499

500

iTeh STANDARD PREVIEW (standards.iteh.ai)

[oSIST prEN IEC 61139-2:2021](https://standards.iteh.ai/catalog/standards/sist/c5441fa2-8f26-4bcf-9b71-159d4015150e/osist-pren-iec-61139-2-2021)

<https://standards.iteh.ai/catalog/standards/sist/c5441fa2-8f26-4bcf-9b71-159d4015150e/osist-pren-iec-61139-2-2021>