

# ETSI TS 138 104 V18.7.0 (2024-10)



**5G;  
NR;  
Base Station (BS) radio transmission and reception  
(3GPP TS 38.104 version 18.7.0 Release 18)**

[ETSI TS 138 104 V18.7.0 \(2024-10\)](https://standards.iteh.ai/catalog/standards/etsi/b73dd8a2-761b-4908-b21b-20914de24fcd/etsi-ts-138-104-v18-7-0-2024-10)

<https://standards.iteh.ai/catalog/standards/etsi/b73dd8a2-761b-4908-b21b-20914de24fcd/etsi-ts-138-104-v18-7-0-2024-10>



---

**Reference**RTS/TSGR-0438104vi70

---

---

**Keywords**5G

---

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° w061004871

---

**Important notice**

The present document can be downloaded from the  
ETSI [Search & Browse Standards application](#).

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#).

Users should be aware that the present document may be revised or have its status changed,  
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to  
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our  
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

---

**Notice of disclaimer & limitation of liability**

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2024.  
All rights reserved.

---

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

---

# Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables. <https://standards.iteh.ai/catalog/standards/etsi/b73dd8a2-761b-4908-b21b-70914de24fed/etsi-ts-138-104-v18-7-0-2024-10>

The cross reference between 3GPP and ETSI identities can be found under <https://webapp.etsi.org/key/queryform.asp>.

---

# Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# Contents

|                                                                                |    |
|--------------------------------------------------------------------------------|----|
| Intellectual Property Rights .....                                             | 2  |
| Legal Notice .....                                                             | 2  |
| Modal verbs terminology.....                                                   | 2  |
| Foreword.....                                                                  | 14 |
| 1 Scope .....                                                                  | 16 |
| 2 References .....                                                             | 16 |
| 3 Definitions, symbols and abbreviations .....                                 | 17 |
| 3.1 Definitions .....                                                          | 17 |
| 3.2 Symbols.....                                                               | 22 |
| 3.3 Abbreviations .....                                                        | 24 |
| 4 General .....                                                                | 26 |
| 4.1 Relationship with other core specifications.....                           | 26 |
| 4.2 Relationship between minimum requirements and test requirements .....      | 26 |
| 4.3 Conducted and radiated requirement reference points .....                  | 26 |
| 4.3.1 BS type 1-C .....                                                        | 26 |
| 4.3.2 BS type 1-H .....                                                        | 27 |
| 4.3.3 BS type 1-O and BS type 2-O .....                                        | 28 |
| 4.4 Base station classes .....                                                 | 28 |
| 4.5 Regional requirements.....                                                 | 29 |
| 4.6 Applicability of requirements.....                                         | 32 |
| 4.7 Requirements for contiguous and <i>non-contiguous spectrum</i> .....       | 33 |
| 4.8 Requirements for BS capable of multi-band operation .....                  | 33 |
| 4.9 OTA co-location with other base stations .....                             | 34 |
| 5 Operating bands and channel arrangement .....                                | 36 |
| 5.1 General .....                                                              | 36 |
| 5.2 Operating bands .....                                                      | 36 |
| 5.3 BS channel bandwidth .....                                                 | 39 |
| 5.3.1 General.....                                                             | 39 |
| 5.3.2 Transmission bandwidth configuration .....                               | 40 |
| 5.3.3 Minimum guardband and transmission bandwidth configuration .....         | 41 |
| 5.3.4 RB alignment.....                                                        | 42 |
| 5.3.5 BS channel bandwidth per operating band .....                            | 42 |
| 5.3A BS channel bandwidth for CA.....                                          | 47 |
| 5.3A.1 Transmission bandwidth configuration for CA .....                       | 47 |
| 5.3A.2 Minimum guardband and transmission bandwidth configuration for CA ..... | 47 |
| 5.4 Channel arrangement.....                                                   | 50 |
| 5.4.1 Channel spacing.....                                                     | 50 |
| 5.4.1.1 Channel spacing for adjacent NR carriers .....                         | 50 |
| 5.4.1.2 Channel spacing for CA .....                                           | 50 |
| 5.4.2 Channel raster .....                                                     | 51 |
| 5.4.2.1 NR-ARFCN and channel raster.....                                       | 51 |
| 5.4.2.1A NB-IoT carrier frequency numbering.....                               | 52 |
| 5.4.2.2 Channel raster to resource element mapping.....                        | 52 |
| 5.4.2.3 Channel raster entries for each <i>operating band</i> .....            | 52 |
| 5.4.3 Synchronization raster .....                                             | 58 |
| 5.4.3.1 Synchronization raster and numbering.....                              | 58 |
| 5.4.3.3 Synchronization raster entries for each operating band.....            | 59 |
| 6 Conducted transmitter characteristics .....                                  | 64 |
| 6.1 General .....                                                              | 64 |
| 6.2 Base station output power .....                                            | 64 |
| 6.2.1 General.....                                                             | 64 |
| 6.2.2 Minimum requirement for BS type 1-C.....                                 | 65 |

|            |                                                                                                            |     |
|------------|------------------------------------------------------------------------------------------------------------|-----|
| 6.2.3      | Minimum requirement for <i>BS type 1-H</i> .....                                                           | 65  |
| 6.2.4      | Additional requirements (regional).....                                                                    | 65  |
| 6.3        | Output power dynamics.....                                                                                 | 66  |
| 6.3.1      | General.....                                                                                               | 66  |
| 6.3.2      | RE power control dynamic range .....                                                                       | 66  |
| 6.3.2.1    | General .....                                                                                              | 66  |
| 6.3.2.2    | Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i> .....                                    | 66  |
| 6.3.3      | Total power dynamic range .....                                                                            | 66  |
| 6.3.3.1    | General .....                                                                                              | 66  |
| 6.3.3.2    | Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i> .....                                    | 67  |
| 6.3.4      | NB-IoT RB power dynamic range for NB-IoT operation in NR in-band .....                                     | 67  |
| 6.3.4.1    | General .....                                                                                              | 67  |
| 6.3.4.2    | Minimum Requirement .....                                                                                  | 67  |
| 6.4        | Transmit ON/OFF power .....                                                                                | 68  |
| 6.4.1      | Transmitter OFF power .....                                                                                | 68  |
| 6.4.1.1    | General .....                                                                                              | 68  |
| 6.4.1.2    | Minimum requirement for <i>BS type 1-C</i> .....                                                           | 68  |
| 6.4.1.3    | Minimum requirement for <i>BS type 1-H</i> .....                                                           | 68  |
| 6.4.2      | Transmitter transient period .....                                                                         | 68  |
| 6.4.2.1    | General .....                                                                                              | 68  |
| 6.4.2.2    | Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i> .....                                    | 69  |
| 6.4.2.3    | Void.....                                                                                                  | 69  |
| 6.5        | Transmitted signal quality .....                                                                           | 69  |
| 6.5.1      | Frequency error.....                                                                                       | 69  |
| 6.5.1.1    | General .....                                                                                              | 69  |
| 6.5.1.2    | Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i> .....                                    | 70  |
| 6.5.2      | Modulation quality.....                                                                                    | 70  |
| 6.5.2.1    | General .....                                                                                              | 70  |
| 6.5.2.2    | Minimum Requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i> .....                                    | 70  |
| 6.5.2.3    | EVM frame structure for measurement.....                                                                   | 70  |
| 6.5.3      | Time alignment error .....                                                                                 | 71  |
| 6.5.3.1    | General .....                                                                                              | 71  |
| 6.5.3.2    | Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i> .....                                    | 71  |
| 6.6        | Unwanted emissions.....                                                                                    | 71  |
| 6.6.1      | General.....                                                                                               | 71  |
| 6.6.2      | Occupied bandwidth .....                                                                                   | 72  |
| 6.6.2.1    | General .....                                                                                              | 72  |
| 6.6.2.2    | Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i> .....                                    | 72  |
| 6.6.3      | Adjacent Channel Leakage Power Ratio .....                                                                 | 73  |
| 6.6.3.1    | General .....                                                                                              | 73  |
| 6.6.3.2    | Limits and <i>Basic limits</i> .....                                                                       | 73  |
| 6.6.3.3    | Minimum requirement for <i>BS type 1-C</i> .....                                                           | 76  |
| 6.6.3.4    | Minimum requirement for <i>BS type 1-H</i> .....                                                           | 76  |
| 6.6.4      | Operating band unwanted emissions .....                                                                    | 77  |
| 6.6.4.1    | General .....                                                                                              | 77  |
| 6.6.4.2    | <i>Basic limits</i> .....                                                                                  | 78  |
| 6.6.4.2.1  | <i>Basic limits</i> for Wide Area BS (Category A) .....                                                    | 78  |
| 6.6.4.2.2  | <i>Basic limits</i> for Wide Area BS (Category B) .....                                                    | 80  |
| 6.6.4.2.3  | <i>Basic limits</i> for Medium Range BS (Category A and B).....                                            | 84  |
| 6.6.4.2.4  | <i>Basic limits</i> for Local Area BS (Category A and B).....                                              | 87  |
| 6.6.4.2.4A | <i>Basic limits</i> for Local Area and Medium Range BS for bands n46, n96 and n102 (Category A and B)..... | 89  |
| 6.6.4.2.5  | <i>Basic limits</i> for additional requirements .....                                                      | 92  |
| 6.6.4.3    | Minimum requirements for <i>BS type 1-C</i> .....                                                          | 94  |
| 6.6.4.4    | Minimum requirements for <i>BS type 1-H</i> .....                                                          | 94  |
| 6.6.5      | Transmitter spurious emissions.....                                                                        | 95  |
| 6.6.5.1    | General .....                                                                                              | 95  |
| 6.6.5.2    | <i>Basic limits</i> .....                                                                                  | 95  |
| 6.6.5.2.1  | General transmitter spurious emissions requirements .....                                                  | 95  |
| 6.6.5.2.2  | Protection of the BS receiver of own or different BS .....                                                 | 96  |
| 6.6.5.2.3  | Additional spurious emissions requirements .....                                                           | 96  |
| 6.6.5.2.4  | Co-location with other base stations.....                                                                  | 107 |

|         |                                                                                      |     |
|---------|--------------------------------------------------------------------------------------|-----|
| 6.6.5.3 | Minimum requirements for <i>BS type 1-C</i> .....                                    | 113 |
| 6.6.5.4 | Minimum requirements for <i>BS type 1-H</i> .....                                    | 113 |
| 6.7     | Transmitter intermodulation .....                                                    | 113 |
| 6.7.1   | General .....                                                                        | 113 |
| 6.7.2   | Minimum requirements for <i>BS type 1-C</i> .....                                    | 114 |
| 6.7.2.1 | Co-location minimum requirements .....                                               | 114 |
| 6.7.2.2 | Additional requirements .....                                                        | 114 |
| 6.7.3   | Minimum requirements for <i>BS type 1-H</i> .....                                    | 115 |
| 6.7.3.1 | Co-location minimum requirements .....                                               | 115 |
| 6.7.3.2 | Intra-system minimum requirements .....                                              | 116 |
| 6.7.3.3 | Additional requirements .....                                                        | 116 |
| 7       | Conducted receiver characteristics .....                                             | 118 |
| 7.1     | General .....                                                                        | 118 |
| 7.2     | Reference sensitivity level .....                                                    | 118 |
| 7.2.1   | General .....                                                                        | 118 |
| 7.2.2   | Minimum requirements for <i>BS type 1-C</i> and <i>BS type 1-H</i> .....             | 118 |
| 7.3     | Dynamic range .....                                                                  | 124 |
| 7.3.1   | General .....                                                                        | 124 |
| 7.3.2   | Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i> .....              | 124 |
| 7.4     | In-band selectivity and blocking .....                                               | 136 |
| 7.4.1   | Adjacent Channel Selectivity (ACS) .....                                             | 136 |
| 7.4.1.1 | General .....                                                                        | 136 |
| 7.4.1.2 | Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i> .....              | 136 |
| 7.4.1.3 | Void .....                                                                           | 139 |
| 7.4.1.4 | Void .....                                                                           | 139 |
| 7.4.2   | In-band blocking .....                                                               | 139 |
| 7.4.2.1 | General .....                                                                        | 139 |
| 7.4.2.2 | Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i> .....              | 139 |
| 7.4.2.3 | Void .....                                                                           | 143 |
| 7.4.2.4 | Void .....                                                                           | 143 |
| 7.4.2.5 | Additional narrowband blocking requirement for Band n100 .....                       | 143 |
| 7.5     | Out-of-band blocking .....                                                           | 143 |
| 7.5.1   | General .....                                                                        | 143 |
| 7.5.2   | Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i> .....              | 144 |
| 7.5.3   | Co-location minimum requirements for <i>BS type 1-C</i> and <i>BS type 1-H</i> ..... | 145 |
| 7.5.4   | Void .....                                                                           | 146 |
| 7.5.5   | Additional out-of-band blocking requirements for the use of RMR bands .....          | 146 |
| 7.6     | Receiver spurious emissions .....                                                    | 146 |
| 7.6.1   | General .....                                                                        | 146 |
| 7.6.2   | <i>Basic limits</i> .....                                                            | 146 |
| 7.6.3   | Minimum requirement for <i>BS type 1-C</i> .....                                     | 147 |
| 7.6.4   | Minimum requirement for <i>BS type 1-H</i> .....                                     | 147 |
| 7.7     | Receiver intermodulation .....                                                       | 148 |
| 7.7.1   | General .....                                                                        | 148 |
| 7.7.2   | Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i> .....              | 148 |
| 7.7.3   | Additional narrowband intermodulation requirement for Band n100 .....                | 154 |
| 7.8     | In-channel selectivity .....                                                         | 154 |
| 7.8.1   | General .....                                                                        | 154 |
| 7.8.2   | Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i> .....              | 154 |
| 8       | Conducted performance requirements .....                                             | 167 |
| 8.1     | General .....                                                                        | 167 |
| 8.1.1   | Scope and definitions .....                                                          | 167 |
| 8.1.2   | Void .....                                                                           | 167 |
| 8.2     | Performance requirements for PUSCH .....                                             | 167 |
| 8.2.1   | Requirements for PUSCH with transform precoding disabled .....                       | 167 |
| 8.2.1.1 | General .....                                                                        | 167 |
| 8.2.1.2 | Minimum requirements .....                                                           | 168 |
| 8.2.2   | Requirements for PUSCH with transform precoding enabled .....                        | 177 |
| 8.2.2.1 | General .....                                                                        | 177 |
| 8.2.2.2 | Minimum requirements .....                                                           | 178 |

|           |                                                                           |     |
|-----------|---------------------------------------------------------------------------|-----|
| 8.2.3     | Requirements for UCI multiplexed on PUSCH .....                           | 179 |
| 8.2.3.1   | General .....                                                             | 179 |
| 8.2.3.2   | Minimum requirements .....                                                | 180 |
| 8.2.4     | Requirements for PUSCH for high speed train .....                         | 181 |
| 8.2.4.1   | General .....                                                             | 181 |
| 8.2.4.2   | Minimum requirements .....                                                | 182 |
| 8.2.5     | Requirements for UL timing adjustment .....                               | 184 |
| 8.2.5.1   | Minimum requirements for high speed train .....                           | 185 |
| 8.2.5.2   | Minimum requirements for normal mode .....                                | 186 |
| 8.2.6     | Requirements for PUSCH 0.001% BLER .....                                  | 187 |
| 8.2.6.1   | General .....                                                             | 187 |
| 8.2.6.2   | Minimum requirements .....                                                | 187 |
| 8.2.7     | Requirements for PUSCH repetition Type A .....                            | 188 |
| 8.2.7.1   | General .....                                                             | 188 |
| 8.2.7.2   | Minimum requirements .....                                                | 189 |
| 8.2.8     | Requirements for PUSCH mapping Type B with non-slot transmission .....    | 191 |
| 8.2.8.1   | General .....                                                             | 191 |
| 8.2.8.2   | Minimum requirements .....                                                | 191 |
| 8.2.9     | Requirements of PUSCH for 2-step RA type .....                            | 192 |
| 8.2.9.1   | General .....                                                             | 192 |
| 8.2.9.2   | Minimum requirements .....                                                | 193 |
| 8.2.10    | Requirements for interlaced PUSCH .....                                   | 193 |
| 8.2.10.1  | General .....                                                             | 193 |
| 8.2.10.2  | Minimum requirements .....                                                | 194 |
| 8.2.11    | Performance requirements for CG-UCI multiplexed on interlaced PUSCH ..... | 195 |
| 8.2.11.1  | General .....                                                             | 195 |
| 8.2.11.2  | Minimum requirements .....                                                | 196 |
| 8.2.12    | Requirements for TB processing over multi-slot PUSCH (TBOMS) .....        | 197 |
| 8.2.12.1  | General .....                                                             | 197 |
| 8.2.12.2  | Minimum requirements .....                                                | 197 |
| 8.2.13    | Requirements for PUSCH with DM-RS bundling .....                          | 198 |
| 8.2.13.1  | General .....                                                             | 198 |
| 8.2.13.2  | Minimum requirements .....                                                | 199 |
| 8.3       | Performance requirements for PUCCH .....                                  | 204 |
| 8.3.1     | DTX to ACK probability .....                                              | 204 |
| 8.3.1.1   | General .....                                                             | 204 |
| 8.3.1.2   | Minimum requirement .....                                                 | 204 |
| 8.3.2     | Performance requirements for PUCCH format 0 .....                         | 205 |
| 8.3.2.1   | General .....                                                             | 205 |
| 8.3.2.2   | Minimum requirements .....                                                | 205 |
| 8.3.3     | Performance requirements for PUCCH format 1 .....                         | 206 |
| 8.3.3.1   | NACK to ACK requirements .....                                            | 206 |
| 8.3.3.1.1 | General .....                                                             | 206 |
| 8.3.3.1.2 | Minimum requirements .....                                                | 206 |
| 8.3.3.2   | ACK missed detection requirements .....                                   | 207 |
| 8.3.3.2.1 | General .....                                                             | 207 |
| 8.3.3.2.2 | Minimum requirements .....                                                | 207 |
| 8.3.4     | Performance requirements for PUCCH format 2 .....                         | 208 |
| 8.3.4.1   | ACK missed detection requirements .....                                   | 208 |
| 8.3.4.1.1 | General .....                                                             | 208 |
| 8.3.4.1.2 | Minimum requirements .....                                                | 208 |
| 8.3.4.2   | UCI BLER performance requirements .....                                   | 209 |
| 8.3.4.2.1 | General .....                                                             | 209 |
| 8.3.4.2.2 | Minimum requirements .....                                                | 209 |
| 8.3.5     | Performance requirements for PUCCH format 3 .....                         | 210 |
| 8.3.5.1   | General .....                                                             | 210 |
| 8.3.5.2   | Minimum requirements .....                                                | 211 |
| 8.3.6     | Performance requirements for PUCCH format 4 .....                         | 211 |
| 8.3.6.1   | General .....                                                             | 211 |
| 8.3.6.2   | Minimum requirement .....                                                 | 212 |
| 8.3.7     | Performance requirements for multi-slot PUCCH .....                       | 213 |
| 8.3.7.1   | General .....                                                             | 213 |

|             |                                                                          |     |
|-------------|--------------------------------------------------------------------------|-----|
| 8.3.7.2     | Performance requirements for multi-slot PUCCH format 1 .....             | 213 |
| 8.3.7.2.1   | NACK to ACK requirements .....                                           | 213 |
| 8.3.7.2.1.1 | General .....                                                            | 213 |
| 8.3.7.2.1.2 | Minimum requirements .....                                               | 214 |
| 8.3.7.2.2   | ACK missed detection requirements .....                                  | 214 |
| 8.3.8       | Performance requirements for interlaced PUCCH format 0 .....             | 214 |
| 8.3.8.1     | General .....                                                            | 214 |
| 8.3.8.2     | Minimum requirements .....                                               | 215 |
| 8.3.9       | Performance requirements for interlaced PUCCH format 1 .....             | 215 |
| 8.3.9.1     | NACK to ACK requirements .....                                           | 215 |
| 8.3.9.1.1   | General .....                                                            | 215 |
| 8.3.9.1.2   | Minimum requirements .....                                               | 216 |
| 8.3.9.2     | ACK missed detection requirements .....                                  | 216 |
| 8.3.9.2.1   | General .....                                                            | 216 |
| 8.3.9.2.2   | Minimum requirements .....                                               | 216 |
| 8.3.10      | Performance requirements for interlaced PUCCH format 2 .....             | 217 |
| 8.3.10.1    | General .....                                                            | 217 |
| 8.3.10.2    | Minimum requirements .....                                               | 217 |
| 8.3.11      | Performance requirements for interlaced PUCCH format 3 .....             | 218 |
| 8.3.11.1    | General .....                                                            | 218 |
| 8.3.11.2    | Minimum requirements .....                                               | 218 |
| 8.3.12      | Performance requirements for PUCCH format 1 with DM-RS bundling .....    | 219 |
| 8.3.12.1    | NACK to ACK requirements .....                                           | 219 |
| 8.3.12.1.1  | General .....                                                            | 219 |
| 8.3.12.1.2  | Minimum requirements .....                                               | 219 |
| 8.3.12.2    | ACK missed detection requirements .....                                  | 220 |
| 8.3.12.2.1  | General .....                                                            | 220 |
| 8.3.12.2.2  | Minimum requirements .....                                               | 220 |
| 8.3.13      | Performance requirements for PUCCH format 3 with DMRS bundling .....     | 220 |
| 8.3.13.1    | General .....                                                            | 220 |
| 8.3.13.2    | Minimum requirements .....                                               | 221 |
| 8.3.14      | Performance requirements for sub-slot repetition PUCCH format 0 .....    | 222 |
| 8.3.14.1    | General .....                                                            | 222 |
| 8.3.14.2    | Minimum requirements .....                                               | 222 |
| 8.4         | Performance requirements for PRACH .....                                 | 223 |
| 8.4.1       | PRACH False alarm probability .....                                      | 223 |
| 8.4.1.1     | General .....                                                            | 223 |
| 8.4.1.2     | Minimum requirement .....                                                | 223 |
| 8.4.2       | PRACH detection requirements .....                                       | 223 |
| 8.4.2.1     | General .....                                                            | 223 |
| 8.4.2.2     | Minimum requirements for Normal Mode .....                               | 223 |
| 8.4.2.3     | Minimum requirements for high speed train .....                          | 224 |
| 8.4.2.4     | Minimum requirements for PRACH with $L_{RA}=1151$ and $L_{RA}=571$ ..... | 225 |
| 9           | Radiated transmitter characteristics .....                               | 227 |
| 9.1         | General .....                                                            | 227 |
| 9.2         | Radiated transmit power .....                                            | 227 |
| 9.2.1       | General .....                                                            | 227 |
| 9.2.2       | Minimum requirement for <i>BS type 1-H</i> and <i>BS type 1-O</i> .....  | 228 |
| 9.2.3       | Minimum requirement for <i>BS type 2-O</i> .....                         | 228 |
| 9.3         | OTA base station output power .....                                      | 228 |
| 9.3.1       | General .....                                                            | 228 |
| 9.3.2       | Minimum requirement for <i>BS type 1-O</i> .....                         | 229 |
| 9.3.3       | Minimum requirement for <i>BS type 2-O</i> .....                         | 229 |
| 9.3.4       | Additional requirements (regional) .....                                 | 229 |
| 9.4         | OTA output power dynamics .....                                          | 229 |
| 9.4.1       | General .....                                                            | 229 |
| 9.4.2       | OTA RE power control dynamic range .....                                 | 229 |
| 9.4.2.1     | General .....                                                            | 229 |
| 9.4.2.2     | Minimum requirement for <i>BS type 1-O</i> .....                         | 229 |
| 9.4.3       | OTA total power dynamic range .....                                      | 229 |
| 9.4.3.1     | General .....                                                            | 229 |

|             |                                                                         |     |
|-------------|-------------------------------------------------------------------------|-----|
| 9.4.3.2     | Minimum requirement for <i>BS type 1-O</i> .....                        | 230 |
| 9.4.3.3     | Minimum requirement for <i>BS type 2-O</i> .....                        | 230 |
| 9.5         | OTA transmit ON/OFF power.....                                          | 230 |
| 9.5.1       | General.....                                                            | 230 |
| 9.5.2       | OTA transmitter OFF power.....                                          | 230 |
| 9.5.2.1     | General.....                                                            | 230 |
| 9.5.2.2     | Minimum requirement for <i>BS type 1-O</i> .....                        | 230 |
| 9.5.2.3     | Minimum requirement for <i>BS type 2-O</i> .....                        | 231 |
| 9.5.3       | OTA transient period.....                                               | 231 |
| 9.5.3.1     | General.....                                                            | 231 |
| 9.5.3.2     | Minimum requirement for <i>BS type 1-O</i> .....                        | 231 |
| 9.5.3.3     | Minimum requirement for <i>BS type 2-O</i> .....                        | 231 |
| 9.6         | OTA transmitted signal quality.....                                     | 231 |
| 9.6.1       | OTA frequency error.....                                                | 231 |
| 9.6.1.1     | General.....                                                            | 231 |
| 9.6.1.2     | Minimum requirement for <i>BS type 1-O</i> .....                        | 231 |
| 9.6.1.3     | Minimum requirement for <i>BS type 2-O</i> .....                        | 232 |
| 9.6.2       | OTA modulation quality.....                                             | 232 |
| 9.6.2.1     | General.....                                                            | 232 |
| 9.6.2.2     | Minimum Requirement for <i>BS type 1-O</i> .....                        | 232 |
| 9.6.2.3     | Minimum Requirement for <i>BS type 2-O</i> .....                        | 232 |
| 9.6.2.3.1   | EVM frame structure for measurement.....                                | 232 |
| 9.6.3       | OTA time alignment error.....                                           | 232 |
| 9.6.3.1     | General.....                                                            | 232 |
| 9.6.3.2     | Minimum requirement for <i>BS type 1-O</i> .....                        | 233 |
| 9.6.3.3     | Minimum requirement for <i>BS type 2-O</i> .....                        | 233 |
| 9.7         | OTA unwanted emissions.....                                             | 233 |
| 9.7.1       | General.....                                                            | 233 |
| 9.7.2       | OTA occupied bandwidth.....                                             | 234 |
| 9.7.2.1     | General.....                                                            | 234 |
| 9.7.2.2     | Minimum requirement for <i>BS type 1-O</i> and <i>BS type 2-O</i> ..... | 234 |
| 9.7.3       | OTA Adjacent Channel Leakage Power Ratio (ACLR).....                    | 235 |
| 9.7.3.1     | General.....                                                            | 235 |
| 9.7.3.2     | Minimum requirement for <i>BS type 1-O</i> .....                        | 235 |
| 9.7.3.3     | Minimum requirement for <i>BS type 2-O</i> .....                        | 235 |
| 9.7.4       | OTA operating band unwanted emissions.....                              | 237 |
| 9.7.4.1     | General.....                                                            | 237 |
| 9.7.4.2     | Minimum requirement for <i>BS type 1-O</i> .....                        | 237 |
| 9.7.4.2.1   | Additional requirements.....                                            | 238 |
| 9.7.4.2.1.1 | Protection of DTT.....                                                  | 238 |
| 9.7.4.2.1.2 | Limits in FCC Title 47.....                                             | 238 |
| 9.7.4.3     | Minimum requirement for <i>BS type 2-O</i> .....                        | 238 |
| 9.7.4.3.1   | General.....                                                            | 238 |
| 9.7.4.3.2   | OTA operating band unwanted emission limits (Category A).....           | 239 |
| 9.7.4.3.3   | OTA operating band unwanted emission limits (Category B).....           | 240 |
| 9.7.4.3.4   | Additional OTA operating band unwanted emission requirements.....       | 241 |
| 9.7.5       | OTA transmitter spurious emissions.....                                 | 241 |
| 9.7.5.1     | General.....                                                            | 241 |
| 9.7.5.2     | Minimum requirement for <i>BS type 1-O</i> .....                        | 241 |
| 9.7.5.2.1   | General.....                                                            | 241 |
| 9.7.5.2.2   | General OTA transmitter spurious emissions requirements.....            | 242 |
| 9.7.5.2.3   | Protection of the BS receiver of own or different BS.....               | 242 |
| 9.7.5.2.4   | Additional spurious emissions requirements.....                         | 242 |
| 9.7.5.2.5   | Co-location with other base stations.....                               | 242 |
| 9.7.5.3     | Minimum requirement for <i>BS type 2-O</i> .....                        | 242 |
| 9.7.5.3.1   | General.....                                                            | 242 |
| 9.7.5.3.2   | General OTA transmitter spurious emissions requirements.....            | 243 |
| 9.7.5.3.3   | Additional OTA transmitter spurious emissions requirements.....         | 244 |
| 9.8         | OTA transmitter intermodulation.....                                    | 244 |
| 9.8.1       | General.....                                                            | 244 |
| 9.8.2       | Minimum requirement for <i>BS type 1-O</i> .....                        | 244 |
| 9.8.3       | Additional requirements (regional).....                                 | 245 |

|           |                                                                        |     |
|-----------|------------------------------------------------------------------------|-----|
| 10        | Radiated receiver characteristics .....                                | 247 |
| 10.1      | General .....                                                          | 247 |
| 10.2      | OTA sensitivity .....                                                  | 248 |
| 10.2.1    | BS type 1-H and BS type 1-O .....                                      | 248 |
| 10.2.1.1  | General .....                                                          | 248 |
| 10.2.1.2  | Minimum requirement .....                                              | 248 |
| 10.2.2    | BS type 2-O .....                                                      | 248 |
| 10.3      | OTA reference sensitivity level .....                                  | 249 |
| 10.3.1    | General .....                                                          | 249 |
| 10.3.2    | Minimum requirement for BS type 1-O .....                              | 249 |
| 10.3.3    | Minimum requirement for BS type 2-O .....                              | 251 |
| 10.4      | OTA dynamic range .....                                                | 252 |
| 10.4.1    | General .....                                                          | 252 |
| 10.4.2    | Minimum requirement for BS type 1-O .....                              | 252 |
| 10.5      | OTA in-band selectivity and blocking .....                             | 265 |
| 10.5.1    | OTA adjacent channel selectivity .....                                 | 265 |
| 10.5.1.1  | General .....                                                          | 265 |
| 10.5.1.2  | Minimum requirement for BS type 1-O .....                              | 265 |
| 10.5.1.3  | Minimum requirement for BS type 2-O .....                              | 266 |
| 10.5.2    | OTA in-band blocking .....                                             | 267 |
| 10.5.2.1  | General .....                                                          | 267 |
| 10.5.2.2  | Minimum requirement for BS type 1-O .....                              | 267 |
| 10.5.2.3  | Minimum requirement for BS type 2-O .....                              | 270 |
| 10.6      | OTA out-of-band blocking .....                                         | 271 |
| 10.6.1    | General .....                                                          | 271 |
| 10.6.2    | Minimum requirement for BS type 1-O .....                              | 271 |
| 10.6.2.1  | General minimum requirement .....                                      | 271 |
| 10.6.2.2  | Co-location minimum requirement .....                                  | 272 |
| 10.6.3    | Minimum requirement for BS type 2-O .....                              | 272 |
| 10.6.3.1  | General minimum requirement .....                                      | 272 |
| 10.7      | OTA receiver spurious emissions .....                                  | 273 |
| 10.7.1    | General .....                                                          | 273 |
| 10.7.2    | Minimum requirement for BS type 1-O .....                              | 273 |
| 10.7.3    | Minimum requirement for BS type 2-O .....                              | 274 |
| 10.8      | OTA receiver intermodulation .....                                     | 275 |
| 10.8.1    | General .....                                                          | 275 |
| 10.8.2    | Minimum requirement for BS type 1-O .....                              | 275 |
| 10.8.3    | Minimum requirement for BS type 2-O .....                              | 280 |
| 10.9      | OTA in-channel selectivity .....                                       | 281 |
| 10.9.1    | General .....                                                          | 281 |
| 10.9.2    | Minimum requirement for BS type 1-O .....                              | 281 |
| 10.9.3    | Minimum requirement for BS type 2-O .....                              | 285 |
| 11        | Radiated performance requirements .....                                | 287 |
| 11.1      | General .....                                                          | 287 |
| 11.1.1    | Scope and definitions .....                                            | 287 |
| 11.1.2    | OTA demodulation branches .....                                        | 287 |
| 11.1.3    | Void .....                                                             | 288 |
| 11.2      | Performance requirements for PUSCH .....                               | 288 |
| 11.2.1    | Requirements for BS type 1-O .....                                     | 288 |
| 11.2.1.1  | Requirements for PUSCH with transform precoding disabled .....         | 288 |
| 11.2.1.2  | Requirements for PUSCH with transform precoding enabled .....          | 288 |
| 11.2.1.3  | Requirements for UCI multiplexed on PUSCH .....                        | 288 |
| 11.2.1.4  | Requirements for PUSCH for high speed train .....                      | 288 |
| 11.2.1.5  | Requirements for UL timing adjustment .....                            | 288 |
| 11.2.1.6  | Requirements for PUSCH 0.001% BLER .....                               | 288 |
| 11.2.1.7  | Requirements for PUSCH repetition Type A .....                         | 288 |
| 11.2.1.8  | Requirements for PUSCH mapping Type B with non-slot transmission ..... | 288 |
| 11.2.1.9  | Requirements for PUSCH for 2-step RA type .....                        | 288 |
| 11.2.1.10 | Requirements for interlaced PUSCH .....                                | 288 |
| 11.2.1.11 | Requirements for CG-UCI multiplexed on interlaced PUSCH .....          | 288 |
| 11.2.1.12 | Requirements for TB processing over multi-slot PUSCH (TBoMS) .....     | 288 |

|              |                                                                        |     |
|--------------|------------------------------------------------------------------------|-----|
| 11.2.1.13    | Requirements for PUSCH with DM-RS bundling .....                       | 289 |
| 11.2.2       | Requirements for <i>BS type 2-O</i> .....                              | 289 |
| 11.2.2.1     | Requirements for PUSCH with transform precoding disabled .....         | 289 |
| 11.2.2.1.1   | General .....                                                          | 289 |
| 11.2.2.1.2   | Minimum requirements .....                                             | 289 |
| 11.2.2.2     | Requirements for PUSCH with transform precoding enabled .....          | 294 |
| 11.2.2.2.1   | General .....                                                          | 294 |
| 11.2.2.2.2   | Minimum requirements .....                                             | 294 |
| 11.2.2.3     | Requirements for UCI multiplexed on PUSCH .....                        | 295 |
| 11.2.2.3.1   | General .....                                                          | 295 |
| 11.2.2.3.2   | Minimum requirements .....                                             | 296 |
| 11.2.2.4     | Requirements for PUSCH for 2-step RA type .....                        | 298 |
| 11.2.2.4.1   | General .....                                                          | 298 |
| 11.2.2.4.2   | Minimum requirements .....                                             | 299 |
| 11.2.2.5     | Requirements for PUSCH repetition Type A.....                          | 299 |
| 11.2.2.5.1   | General .....                                                          | 299 |
| 11.2.2.5.2   | Minimum requirements .....                                             | 300 |
| 11.2.2.6     | Requirements for PUSCH mapping Type B with non-slot transmission ..... | 301 |
| 11.2.2.6.1   | General .....                                                          | 301 |
| 11.2.2.6.2   | Minimum requirements .....                                             | 301 |
| 11.2.2.7     | Requirements for PUSCH for high speed train .....                      | 302 |
| 11.2.2.7.1   | General .....                                                          | 302 |
| 11.2.2.7.2   | Minimum requirements .....                                             | 302 |
| 11.2.2.8     | Requirements for UL timing adjustment.....                             | 303 |
| 11.2.2.8.1   | General .....                                                          | 303 |
| 11.2.2.8.2   | Minimum requirements for high speed train .....                        | 304 |
| 11.2.2.9     | Requirements for TB processing over multi-slot PUSCH (TBoMS) .....     | 305 |
| 11.2.2.9.1   | General .....                                                          | 305 |
| 11.2.2.9.2   | Minimum requirements .....                                             | 305 |
| 11.2.2.10    | Requirements for PUSCH with DM-RS bundling .....                       | 306 |
| 11.2.2.10.1  | General .....                                                          | 306 |
| 11.2.2.10.2  | Minimum requirements .....                                             | 306 |
| 11.3         | Performance requirements for PUCCH .....                               | 307 |
| 11.3.1       | Requirements for <i>BS type 1-O</i> .....                              | 307 |
| 11.3.1.1     | DTX to ACK probability .....                                           | 307 |
| 11.3.1.2     | Performance requirements for PUCCH format 0 .....                      | 307 |
| 11.3.1.3     | Performance requirements for PUCCH format 1 .....                      | 307 |
| 11.3.1.4     | Performance requirements for PUCCH format 2 .....                      | 307 |
| 11.3.1.5     | Performance requirements for PUCCH format 3 .....                      | 307 |
| 11.3.1.6     | Performance requirements for PUCCH format 4 .....                      | 307 |
| 11.3.1.7     | Performance requirements for multi-slot PUCCH .....                    | 307 |
| 11.3.1.8     | Performance requirements for PUCCH format 1 with DMRS bundling.....    | 307 |
| 11.3.1.9     | Performance requirements for PUCCH format 3 with DMRS bundling.....    | 308 |
| 11.3.1.10    | Performance requirements for sub-slot repetition PUCCH format 0 .....  | 308 |
| 11.3.2       | Requirements for <i>BS type 2-O</i> .....                              | 308 |
| 11.3.2.1     | DTX to ACK probability .....                                           | 308 |
| 11.3.2.2     | Performance requirements for PUCCH format 0. ....                      | 308 |
| 11.3.2.2.1   | General .....                                                          | 308 |
| 11.3.2.2.2   | Minimum requirements .....                                             | 308 |
| 11.3.2.3     | Performance requirements for PUCCH format 1. ....                      | 309 |
| 11.3.2.3.1   | NACK to ACK requirements .....                                         | 309 |
| 11.3.2.3.1.1 | General.....                                                           | 309 |
| 11.3.2.3.1.2 | Minimum requirements.....                                              | 310 |
| 11.3.2.3.2   | ACK missed detection requirements .....                                | 311 |
| 11.3.2.3.2.1 | General.....                                                           | 311 |
| 11.3.2.3.2.2 | Minimum requirements.....                                              | 311 |
| 11.3.2.4     | Performance requirements for PUCCH format 2 .....                      | 312 |
| 11.3.2.4.1   | ACK missed detection requirements .....                                | 312 |
| 11.3.2.4.1.1 | General.....                                                           | 312 |
| 11.3.2.4.1.2 | Minimum requirements.....                                              | 312 |
| 11.3.2.4.2   | UCI BLER performance requirements .....                                | 313 |
| 11.3.2.4.2.1 | Genera.....                                                            | 313 |

|              |                                                                          |     |
|--------------|--------------------------------------------------------------------------|-----|
| 11.3.2.4.2.2 | Minimum requirements.....                                                | 313 |
| 11.3.2.5     | Performance requirements for PUCCH format 3 .....                        | 314 |
| 11.3.2.5.1   | General .....                                                            | 314 |
| 11.3.2.5.2   | Minimum requirements .....                                               | 314 |
| 11.3.2.6     | Performance requirements for PUCCH format 4 .....                        | 315 |
| 11.3.2.6.1   | General .....                                                            | 315 |
| 11.3.2.6.2   | Minimum requirements .....                                               | 316 |
| 11.3.2.7     | Performance requirements for PUCCH format 1 with DMRS bundling.....      | 317 |
| 11.3.2.7.1   | NACK to ACK requirements .....                                           | 317 |
| 11.3.2.7.1.1 | General.....                                                             | 317 |
| 11.3.2.7.1.2 | Minimum requirements.....                                                | 318 |
| 11.3.2.7.2   | ACK missed detection requirements .....                                  | 318 |
| 11.3.2.7.2.1 | General.....                                                             | 318 |
| 11.3.2.7.2.2 | Minimum requirements.....                                                | 319 |
| 11.3.2.8     | Performance requirements for PUCCH format 3 with DMRS bundling.....      | 319 |
| 11.3.2.8.1   | General .....                                                            | 319 |
| 11.3.2.8.2   | Minimum requirements .....                                               | 320 |
| 11.4         | Performance requirements for PRACH.....                                  | 320 |
| 11.4.1       | Requirements for <i>BS type 1-O</i> .....                                | 320 |
| 11.4.1.1     | PRACH False alarm probability .....                                      | 320 |
| 11.4.1.2     | PRACH detection requirements .....                                       | 320 |
| 11.4.2       | Requirements for <i>BS type 2-O</i> .....                                | 320 |
| 11.4.2.1     | PRACH False alarm probability .....                                      | 320 |
| 11.4.2.1.1   | General .....                                                            | 320 |
| 11.4.2.1.2   | Minimum requirement.....                                                 | 320 |
| 11.4.2.2     | PRACH detection requirements .....                                       | 321 |
| 11.4.2.2.1   | General .....                                                            | 321 |
| 11.4.2.2.2   | Minimum requirements for Normal mode.....                                | 321 |
| 11.4.2.2.3   | Minimum requirements for high speed train .....                          | 322 |
| 11.4.2.2.4   | Minimum requirements for PRACH with $L_{RA}=1151$ and $L_{RA}=571$ ..... | 322 |
| 11.4.2.2.5   | Minimum requirements for multiple PRACH transmission .....               | 323 |

## **Annex A (normative): Reference measurement channels .....324**

|      |                                                                                                                                                                                  |     |
|------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| A.1  | Fixed Reference Channels for reference sensitivity level, ACS, in-band blocking, out-of-band blocking, receiver intermodulation and in-channel selectivity (QPSK, $R=1/3$ )..... | 324 |
| A.2  | Fixed Reference Channels for dynamic range (16QAM, $R=2/3$ ).....                                                                                                                | 327 |
| A.3  | Fixed Reference Channels for performance requirements (QPSK, $R=193/1024$ ) .....                                                                                                | 329 |
| A.3A | Fixed Reference Channels for performance requirements (QPSK, $R=99/1024$ ) .....                                                                                                 | 336 |
| A.3B | Fixed Reference Channels for performance requirements (QPSK, $R=308/1024$ ) .....                                                                                                | 338 |
| A.4  | Fixed Reference Channels for performance requirements (16QAM, $R=658/1024$ ) .....                                                                                               | 342 |
| A.5  | Fixed Reference Channels for performance requirements (64QAM, $R=567/1024$ ) .....                                                                                               | 347 |
| A.6  | PRACH Test preambles .....                                                                                                                                                       | 350 |
| A.7  | Fixed Reference Channels for performance requirements (16QAM, $R=434/1024$ ) .....                                                                                               | 351 |
| A.8  | Fixed Reference Channels for performance requirements (QPSK, $R=157/1024$ ) .....                                                                                                | 353 |
| A.9  | Fixed Reference Channels for performance requirements (256QAM, $R=682.5/1024$ ) .....                                                                                            | 354 |
| A.10 | Fixed Reference Channels for performance requirements (64QAM, $R=517/1024$ ) .....                                                                                               | 356 |
| A.11 | Fixed Reference Channels for performance requirements (64QAM, $R=438/1024$ ) .....                                                                                               | 360 |
| A.12 | Void.....                                                                                                                                                                        | 361 |

## **Annex B (normative): Error Vector Magnitude (FR1).....363**

|     |                                      |     |
|-----|--------------------------------------|-----|
| B.1 | Reference point for measurement..... | 363 |
| B.2 | Basic unit of measurement .....      | 363 |

|                                                                                                                |                                                                                         |            |
|----------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|------------|
| B.3                                                                                                            | Modified signal under test .....                                                        | 364        |
| B.4                                                                                                            | Estimation of frequency offset .....                                                    | 364        |
| B.5                                                                                                            | Estimation of time offset .....                                                         | 364        |
| B.5.1                                                                                                          | General .....                                                                           | 364        |
| B.5.2                                                                                                          | Window length .....                                                                     | 365        |
| B.6                                                                                                            | Estimation of TX chain amplitude and frequency response parameters .....                | 366        |
| B.7                                                                                                            | Averaged EVM .....                                                                      | 368        |
| <b>Annex C (normative): Error Vector Magnitude (FR2).....</b>                                                  |                                                                                         | <b>370</b> |
| C.1                                                                                                            | Reference point for measurement.....                                                    | 370        |
| C.2                                                                                                            | Basic unit of measurement .....                                                         | 370        |
| C.3                                                                                                            | Modified signal under test.....                                                         | 371        |
| C.4                                                                                                            | Estimation of frequency offset .....                                                    | 371        |
| C.5                                                                                                            | Estimation of time offset .....                                                         | 371        |
| C.5.1                                                                                                          | General .....                                                                           | 371        |
| C.5.2                                                                                                          | Window length .....                                                                     | 372        |
| C.6                                                                                                            | Estimation of TX chain amplitude and frequency response parameters .....                | 373        |
| C.7                                                                                                            | Averaged EVM .....                                                                      | 375        |
| <b>Annex D (normative): Characteristics of the interfering signals .....</b>                                   |                                                                                         | <b>377</b> |
| <b>Annex E: Void</b>                                                                                           |                                                                                         | <b>378</b> |
| <b>Annex F (normative): Relationship between EIRP based regulatory requirements and 3GPP requirements.....</b> |                                                                                         | <b>379</b> |
| F.1                                                                                                            | General .....                                                                           | 379        |
| F.2                                                                                                            | Relationship between EIRP based regulatory requirements and conducted requirements..... | 379        |
| F.3                                                                                                            | Relationship between EIRP based regulatory requirements and OTA requirements.....       | 380        |
| <b>Annex G (Normative): Propagation conditions .....</b>                                                       |                                                                                         | <b>381</b> |
| G.1                                                                                                            | Static propagation condition.....                                                       | 381        |
| G.2                                                                                                            | Multi-path fading propagation conditions .....                                          | 381        |
| G.2.1                                                                                                          | Delay profiles .....                                                                    | 381        |
| G.2.1.1                                                                                                        | Delay profiles for FR1 .....                                                            | 382        |
| G.2.1.2                                                                                                        | Delay profiles for FR2 .....                                                            | 383        |
| G.2.2                                                                                                          | Combinations of channel model parameters .....                                          | 385        |
| G.2.3                                                                                                          | MIMO Channel Correlation Matrices .....                                                 | 386        |
| G.2.3.1                                                                                                        | MIMO Correlation Matrices using Uniform Linear Array (ULA) .....                        | 386        |
| G.2.3.1.1                                                                                                      | Definition of MIMO Correlation Matrices.....                                            | 386        |
| G.2.3.1.2                                                                                                      | MIMO Correlation Matrices at High, Medium and Low Level .....                           | 390        |
| G.2.3.2                                                                                                        | Multi-Antenna channel models using cross polarized antennas .....                       | 392        |
| G.2.3.2.1                                                                                                      | Definition of MIMO Correlation Matrices using cross polarized antennas .....            | 393        |
| G.2.3.2.2                                                                                                      | Spatial Correlation Matrices at UE and gNB sides .....                                  | 393        |
| G.2.3.2.2.1                                                                                                    | Spatial Correlation Matrices at UE side .....                                           | 393        |
| G.2.3.2.2.2                                                                                                    | Spatial Correlation Matrices at gNB side .....                                          | 394        |
| G.2.3.2.3                                                                                                      | MIMO Correlation Matrices using cross polarized antennas .....                          | 394        |
| G.3                                                                                                            | High speed train condition .....                                                        | 394        |
| G.4                                                                                                            | Moving propagation conditions.....                                                      | 399        |
| <b>Annex H (informative): Change history .....</b>                                                             |                                                                                         | <b>401</b> |

History .....415

iTeh Standards

(<https://standards.iteh.ai>)

Document Preview

[ETSI TS 138 104 V18.7.0 \(2024-10\)](https://standards.iteh.ai/catalog/standards/etsi/b73dd8a2-761b-4908-b21b-20914de24fed/etsi-ts-138-104-v18-7-0-2024-10)

<https://standards.iteh.ai/catalog/standards/etsi/b73dd8a2-761b-4908-b21b-20914de24fed/etsi-ts-138-104-v18-7-0-2024-10>