

ETSI TS 138 141-1 V18.7.0 (2024-09)



5G;
NR;

**Base Station (BS) conformance testing
Part 1: Conducted conformance testing
(3GPP TS 38.141-1 version 18.7.0 Release 18)**

[ETSI TS 138 141-1 V18.7.0 \(2024-10\)](https://standards.iteh.ai/catalog/standards/etsi/acf29ef1-bec1-49e6-b99b-334b576e8b62/etsi-ts-138-141-1-v18-7-0-2024-10)

<https://standards.iteh.ai/catalog/standards/etsi/acf29ef1-bec1-49e6-b99b-334b576e8b62/etsi-ts-138-141-1-v18-7-0-2024-10>



Reference

RTS/TSGR-0438141-1v170

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<https://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our

Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2024.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables. (2024-10)

The cross reference between 3GPP and ETSI identities can be found under <https://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	17
1 Scope	19
2 References	19
3 Definitions, symbols and abbreviations	21
3.1 Definitions	21
3.2 Symbols.....	23
3.3 Abbreviations	25
4 General conducted test conditions and declarations.....	27
4.1 Measurement uncertainties and test requirements	27
4.1.1 General.....	27
4.1.2 Acceptable uncertainty of Test System.....	27
4.1.2.1 General	27
4.1.2.2 Measurement of transmitter	28
4.1.2.3 Measurement of receiver	31
4.1.2.4 Measurement of performance requirements.....	35
4.1.3 Interpretation of measurement results.....	35
4.2 Conducted requirement reference points	36
4.2.1 BS type 1-C	36
4.2.2 BS type 1-H	36
4.3 Base station classes	37
4.4 Regional requirements.....	38
4.5 BS configurations	40
4.5.1 BS type 1-C	40
4.5.1.1 Transmit configurations	40
4.5.1.1.1 General	40
4.5.1.1.2 Transmission with multiple transmitter antenna connectors.....	40
4.5.1.2 Receive configurations.....	40
4.5.1.2.1 General	40
4.5.1.2.2 Reception with multiple receiver antenna connectors, receiver diversity.....	41
4.5.1.3 Duplexers	41
4.5.1.4 Power supply options	41
4.5.1.5 Ancillary RF amplifiers.....	41
4.5.2 BS type 1-H	42
4.5.2.1 Transmit configurations	42
4.5.2.2 Receive configurations.....	43
4.5.2.3 Power supply options	43
4.5.3 BS with integrated Luant BS modem	44
4.6 Manufacturer declarations	44
4.7 Test configurations	50
4.7.1 General.....	50
4.7.2 Test signal used to build Test Configurations.....	51
4.7.3 NRTC1: Contiguous spectrum operation.....	51
4.7.3.1 NRTC1 generation	51
4.7.3.2 NRTC1 power allocation	51
4.7.4 NRTC2: Contiguous CA occupied bandwidth.....	51
4.7.4.1 NRTC2 generation	52
4.7.4.2 NRTC2 power allocation	52
4.7.5 NRTC3: Non-contiguous spectrum operation	52
4.7.5.1 NRTC3 generation	52
4.7.5.2 NRTC3 power allocation	53
4.7.6 NRTC4: Multi-band test configuration for full carrier allocation.....	53

4.7.6.1	NRTC4 generation	53
4.7.6.2	NRTC4 power allocation	53
4.7.7	NRTC5: Multi-band test configuration with high PSD per carrier	54
4.7.7.1	NRTC5 generation	54
4.7.7.2	NRTC5 power allocation	54
4.7.8	NRTC6: Non-contiguous spectrum operation in band n46, n96 and n102	54
4.7.8.1	NRTC6 generation	54
4.7.8.2	NRTC6 power allocation	55
4.8	Applicability of requirements	55
4.8.1	General	55
4.8.2	Requirement set applicability	55
4.8.3	Applicability of test configurations for single-band operation	56
4.8.4	Applicability of test configurations for multi-band operation	57
4.8.5	Additional conformance	58
4.9	RF channels and test models	59
4.9.1	RF channels	59
4.9.2	Test models	60
4.9.2.1	General	60
4.9.2.2	FR1 test models	60
4.9.2.2.1	FR1 test model 1.1 (NR-FR1-TM1.1)	62
4.9.2.2.2	FR1 test model 1.2 (NR-FR1-TM1.2)	63
4.9.2.2.3	FR1 test model 2 (NR-FR1-TM2)	63
4.9.2.2.4	FR1 test model 2a (NR-FR1-TM2a)	64
4.9.2.2.4A	FR1 test model 2b (NR-FR1-TM2b)	64
4.9.2.2.5	FR1 test model 3.1 (NR-FR1-TM3.1)	64
4.9.2.2.6	FR1 test model 3.1a (NR-FR1-TM3.1a)	65
4.9.2.2.6A	FR1 test model 3.1b (NR-FR1-TM3.1b)	65
4.9.2.2.7	FR1 test model 3.2 (NR-FR1-TM3.2)	65
4.9.2.2.8	FR1 test model 3.3 (NR-FR1-TM3.3)	66
4.9.2.2.9	NB-IoT operation in NR in-band test model (NR-N-TM)	67
4.9.2.3	Data content of Physical channels and Signals for NR-FR1-TM	67
4.9.2.3.1	PDCCH	67
4.9.2.3.2	PDSCH	68
4.9.2.4	Data content of Physical channels and Signals for NR-N-TM	69
4.9.3	NB-IoT testing	69
4.10	Requirements for contiguous and non-contiguous spectrum	69
4.11	Requirements for BS capable of multi-band operation	70
4.12	Format and interpretation of tests	71
5	Operating bands and channel arrangement	72
6	Conducted transmitter characteristics	73
6.1	General	73
6.1.1	BS type 1-C	73
6.1.2	BS type 1-H	73
6.2	Base station output power	73
6.2.1	Definition and applicability	73
6.2.2	Minimum requirement	74
6.2.3	Test purpose	75
6.2.4	Method of test	75
6.2.4.1	Initial conditions	75
6.2.4.2	Procedure	75
6.2.5	Test requirement	75
6.3	Output power dynamics	76
6.3.1	General	76
6.3.2	RE power control dynamic range	76
6.3.2.1	Definition and applicability	76
6.3.2.2	Minimum requirement	76
6.3.2.3	Test purpose	76
6.3.3	Total power dynamic range	76
6.3.3.1	Definition and applicability	76
6.3.3.2	Minimum requirement	77

6.3.3.3	Test purpose	77
6.3.3.4	Method of test	77
6.3.3.4.1	Initial conditions	77
6.3.3.4.2	Procedure	77
6.3.3.5	Test requirements	77
6.3.4	NB-IoT RB power dynamic range	78
6.3.4.1	Definition and applicability	78
6.3.4.2	Minimum requirement	78
6.3.4.3	Test purpose	78
6.3.4.4	Method of test	78
6.3.4.5	Test requirements	78
6.4	Transmit ON/OFF power	79
6.4.1	Transmitter OFF power	79
6.4.1.1	Definition and applicability	79
6.4.1.2	Minimum requirement	79
6.4.1.3	Test purpose	79
6.4.1.4	Method of test	79
6.4.1.5	Test requirements	79
6.4.2	Transmitter transient period	80
6.4.2.1	Definition and applicability	80
6.4.2.2	Minimum requirement	80
6.4.2.3	Test purpose	80
6.4.2.4	Method of test	80
6.4.2.4.1	Initial conditions	80
6.4.2.4.2	Procedure	81
6.4.2.5	Test requirements	81
6.5	Transmitted signal quality	81
6.5.1	General	81
6.5.2	Frequency error	82
6.5.2.1	Definition and applicability	82
6.5.2.2	Minimum Requirement	82
6.5.2.3	Test purpose	82
6.5.2.4	Method of test	82
6.5.2.5	Test Requirements	82
6.5.3	Modulation quality	82
6.5.3.1	Definition and applicability	82
6.5.3.2	Minimum Requirement	82
6.5.3.3	Test purpose	83
6.5.3.4	Method of test	83
6.5.3.4.1	Initial conditions	83
6.5.3.4.2	Procedure	83
6.5.3.5	Test requirements	84
6.5.4	Time alignment error	86
6.5.4.1	Definition and applicability	86
6.5.4.2	Minimum requirement	86
6.5.4.3	Test purpose	86
6.5.4.4	Method of test	86
6.5.4.4.1	Initial conditions	86
6.5.4.4.2	Procedure	86
6.5.4.5	Test requirement	87
6.6	Unwanted emissions	87
6.6.1	General	87
6.6.2	Occupied bandwidth	88
6.6.2.1	Definition and applicability	88
6.6.2.2	Minimum Requirements	88
6.6.2.3	Test purpose	88
6.6.2.4	Method of test	89
6.6.2.4.1	Initial conditions	89
6.6.2.4.2	Procedure	89
6.6.2.5	Test requirements	90
6.6.3	Adjacent Channel Leakage Power Ratio (ACLR)	90
6.6.3.1	Definition and applicability	90

6.6.3.2	Minimum requirement	90
6.6.3.3	Test purpose	90
6.6.3.4	Method of test	90
6.6.3.4.1	Initial conditions	90
6.6.3.4.2	Procedure	91
6.6.3.5	Test requirements	91
6.6.3.5.1	General requirements	91
6.6.3.5.2	Limits and <i>basic limits</i>	91
6.6.3.5.3	<i>BS type 1-C</i>	95
6.6.3.5.4	<i>BS type 1-H</i>	95
6.6.4	Operating band unwanted emissions	96
6.6.4.1	Definition and applicability	96
6.6.4.2	Minimum requirement	97
6.6.4.3	Test purpose	97
6.6.4.4	Method of test	98
6.6.4.4.1	Initial conditions	98
6.6.4.4.2	Procedure	98
6.6.4.5	Test requirements	99
6.6.4.5.1	General requirements	99
6.6.4.5.2	Basic limits for Wide Area BS (Category A)	99
6.6.4.5.3	Basic limits for Wide Area BS (Category B)	100
6.6.4.5.3.1	Category B requirements (Option 1)	100
6.6.4.5.3.2	Category B requirements (Option 2)	103
6.6.4.5.4	Basic limits for Medium Range BS (Category A and B)	105
6.6.4.5.5	Basic limits for Local Area BS (Category A and B)	109
6.6.4.5.5A	Basic limits for Local Area and Medium Range BS for band n46, n96 and n102 (Category A and B)	111
6.6.4.5.6	Basic limits for additional requirements	114
6.6.4.5.6.1	Limits in FCC Title 47	114
6.6.4.5.6.2	Protection of DTT	114
6.6.4.5.6.3	Additional operating band unwanted emissions limits for Band n48	114
6.6.4.5.6.4	Additional operating band unwanted emissions limits for Band n53	114
6.6.4.5.6.5	Protection of GPS	115
6.6.4.5.7	<i>BS type 1-C</i>	116
6.6.4.5.8	<i>BS type 1-H</i>	116
6.6.5	Transmitter spurious emissions	116
6.6.5.1	Definition and applicability	116
6.6.5.2	Minimum requirement	116
6.6.5.3	Test purpose	117
6.6.5.4	Method of test	117
6.6.5.4.1	Initial conditions	117
6.6.5.4.2	Procedure	117
6.6.5.5	Test requirements	118
6.6.5.5.1	Basic limits	118
6.6.5.5.1.1	Tx spurious emissions	118
6.6.5.5.1.2	Protection of the BS receiver of own or different BS	118
6.6.5.5.1.3	Additional spurious emissions requirements	119
6.6.5.5.1.4	Co-location with other base stations	130
6.6.5.5.2	(void)	136
6.6.5.5.3	<i>BS type 1-C</i>	136
6.6.5.5.4	<i>BS type 1-H</i>	136
6.7	Transmitter intermodulation	136
6.7.1	Definition and applicability	136
6.7.2	Minimum requirement	137
6.7.3	Test purpose	137
6.7.4	Method of test	137
6.7.4.1	Initial conditions	137
6.7.4.2	Procedure	137
6.7.5	Test requirements	138
6.7.5.1	<i>BS type 1-C</i>	138
6.7.5.1.1	Co-location minimum requirements	138
6.7.5.1.2	Additional requirements	139

6.7.5.2	BS type 1-H	140
6.7.5.2.1	Co-location minimum requirements	140
6.7.5.2.2	Intra-system minimum requirements	141
6.7.5.2.3	Additional requirements	141
7	Conducted receiver characteristics	143
7.1	General	143
7.2	Reference sensitivity level	143
7.2.1	Definition and applicability	143
7.2.2	Minimum requirement	143
7.2.3	Test purpose	144
7.2.4	Method of test	144
7.2.4.1	Initial conditions	144
7.2.4.2	Procedure	144
7.2.5	Test requirements	144
7.3	Dynamic range	150
7.3.1	Definition and applicability	150
7.3.2	Minimum requirement	150
7.3.3	Test purpose	150
7.3.4	Method of test	150
7.3.4.1	Initial conditions	150
7.3.4.2	Procedure	150
7.3.5	Test requirements	151
7.4	In-band selectivity and blocking	163
7.4.1	Adjacent Channel Selectivity (ACS)	163
7.4.1.1	Definition and applicability	163
7.4.1.2	Minimum requirement	163
7.4.1.3	Test purpose	163
7.4.1.4	Method of test	164
7.4.1.4.1	Initial conditions	164
7.4.1.4.2	Procedure	164
7.4.1.5	Test requirements	164
7.4.2	In-band blocking	167
7.4.2.1	Definition and applicability	167
7.4.2.2	Minimum requirement	167
7.4.2.3	Test purpose	167
7.4.2.4	Method of test	167
7.4.2.4.1	Initial conditions	167
7.4.2.4.2	Procedure for general blocking	167
7.4.2.4.3	Procedure for narrowband blocking	168
7.4.2.5	Test requirements	168
7.4.2.5.1	Additional narrowband blocking requirement for Band n100	172
7.5	Out-of-band blocking	173
7.5.1	Definition and applicability	173
7.5.2	Minimum requirement	173
7.5.3	Test purpose	173
7.5.4	Method of test	173
7.5.4.1	Initial conditions	173
7.5.4.2	Procedure	173
7.5.5	Test requirements	174
7.5.5.1	General requirements	174
7.5.5.2	Co-location requirements	175
7.5.5.3	Additional requirement	176
7.5.5.3.1	Additional requirement for Band n101	176
7.6	Receiver spurious emissions	176
7.6.1	Definition and applicability	176
7.6.2	Minimum requirement	177
7.6.3	Test purpose	177
7.6.4	Method of test	177
7.6.4.1	Initial conditions	177
7.6.4.2	Procedure	177
7.6.5	Test requirements	178

7.6.5.1	Basic limits.....	178
7.6.5.2	BS type 1-C	179
7.6.5.3	BS type 1-H.....	179
7.7	Receiver intermodulation	179
7.7.1	Definition and applicability	179
7.7.2	Minimum requirement	179
7.7.3	Test purpose.....	179
7.7.4	Method of test	179
7.7.4.1	Initial conditions	179
7.7.4.2	Procedure	180
7.7.5	Test requirements.....	180
7.7.5.1	Additional narrowband intermodulation requirement for Band n100	187
7.8	In-channel selectivity	187
7.8.1	Definition and applicability	187
7.8.2	Minimum requirement	187
7.8.3	Test purpose.....	188
7.8.4	Method of test	188
7.8.4.1	Initial conditions	188
7.8.4.2	Procedure	188
7.8.5	Test requirements.....	188
8	Conducted performance characteristics.....	199
8.1	General	199
8.1.1	Scope and definitions.....	199
8.1.2	Applicability rule	200
8.1.2.0	General	200
8.1.2.1	Applicability of PUSCH performance requirements.....	200
8.1.2.1.1	Applicability of requirements for different subcarrier spacings	200
8.1.2.1.2	Applicability of requirements for different channel bandwidths	200
8.1.2.1.3	Applicability of requirements for different configurations.....	200
8.1.2.1.7	Applicability of 2-step RA type requirements for different subcarrier spacings	201
8.1.2.1.8	Applicability of PUSCH with 0.001% BLER requirements.....	201
8.1.2.1.9	Applicability of PUSCH repetition type A requirements	201
8.1.2.1.10	Applicability of PUSCH with enhanced DM-RS	201
8.1.2.2	Applicability of PUCCH performance requirements	201
8.1.2.2.1	Applicability of requirements for different formats.....	201
8.1.2.2.2	Applicability of requirements for different subcarrier spacings	201
8.1.2.2.3	Applicability of requirements for different channel bandwidths	201
8.1.2.2.4	Applicability of requirements for different configurations.....	202
8.1.2.2.5	Applicability of requirements for multi-slot PUCCH.....	202
8.1.2.2.6	Applicability of requirements for PUCCH sub-slot based repetition	202
8.1.2.3	Applicability of PRACH performance requirements	202
8.1.2.3.1	Applicability of requirements for different formats.....	202
8.1.2.3.2	Applicability of requirements for different subcarrier spacings	202
8.1.2.3.3	Applicability of requirements for different channel bandwidths	202
8.1.2.3.4	Applicability of requirements for different restricted set types of long PRACH format 0	202
8.1.2.4	Applicability of PUSCH for high speed train performance requirements.....	203
8.1.2.4.1	Applicability of requirements for different speeds	203
8.1.2.4.2	Applicability of requirements for 1T1R	203
8.1.2.5	Applicability of interlaced PUSCH performance requirements	203
8.1.2.5.1	General applicability of interlaced PUSCH performance requirements	203
8.1.2.5.2	Applicability of requirements for different subcarrier spacings	203
8.1.2.5.3	Applicability of requirements for different channel bandwidths	203
8.1.2.5.4	Applicability of requirements for different configurations.....	203
8.1.2.5.5	Applicability of CG-UCI multiplexed on PUSCH requirements.....	203
8.1.2.6	Applicability of interlaced PUCCH performance requirements.....	204
8.1.2.6.1	General applicability of interlaced PUCCH performance requirements.....	204
8.1.2.6.2	Applicability of requirements for different formats.....	204
8.1.2.6.3	Applicability of requirements for different subcarrier spacings	204
8.1.2.6.4	Applicability of requirements for different channel bandwidths	204
8.1.2.7	Applicability of performance requirements for PRACH with $L_{RA}=1151$ and $L_{RA}=571$	204
8.1.2.7.1	Applicability of requirements for different formats.....	204

8.1.2.7.2	Applicability of requirements for different subcarrier spacings	204
8.1.2.7.3	Applicability of requirements for different channel bandwidths	204
8.1.2.8	Applicability of performance requirements for PUSCH with TB over Multi-Slots	204
8.1.2.8.1	Applicability of requirements for different UL-DL patterns	204
8.1.2.9	Applicability of performance requirements for PUSCH with DM-RS bundling	205
8.1.2.9.1	Applicability of requirements for TDD with different subcarrier spacings	205
8.1.2.9.2	Applicability of requirements for TDD with different UL-DL patterns	205
8.1.2.9.3	Applicability of requirements for different receiver antenna connectors	205
8.1.2.10	Applicability of performance requirements for PUCCH with DM-RS bundling	205
8.1.2.10.1	Applicability of requirements for TDD with different subcarrier spacings	205
8.1.2.10.2	Applicability of requirements for TDD with different UL-DL patterns	205
8.1.2.11	Applicability of PUSCH performance requirements for ATG scenario	205
8.1.2.11.1	Applicability of requirements with different UL-DL patterns	205
8.1.2.11.2	Applicability of requirements for different MCSs	205
8.1.2.12	Applicability of PUCCH performance requirements for ATG scenario	206
8.1.2.13	Applicability of PRACH performance requirements for ATG scenario	206
8.2	Performance requirements for PUSCH	206
8.2.1	Performance requirements for PUSCH with transform precoding disabled	206
8.2.1.1	Definition and applicability	206
8.2.1.2	Minimum Requirement	206
8.2.1.3	Test Purpose	206
8.2.1.4	Method of test	206
8.2.1.4.1	Initial Conditions	206
8.2.1.4.2	Procedure	206
8.2.1.5	Test Requirement	207
8.2.2	Performance requirements for PUSCH with transform precoding enabled	216
8.2.2.1	Definition and applicability	216
8.2.2.2	Minimum Requirement	216
8.2.2.3	Test Purpose	216
8.2.2.4	Method of test	216
8.2.2.4.1	Initial Conditions	216
8.2.2.4.2	Procedure	216
8.2.2.5	Test Requirement	217
8.2.3	Performance requirements for UCI multiplexed on PUSCH	218
8.2.3.1	Definition and applicability	218
8.2.3.2	Minimum Requirements	219
8.2.3.3	Test purpose	219
8.2.3.4	Method of test	219
8.2.3.4.1	Initial conditions	219
8.2.3.4.2	Procedure	219
8.2.3.5	Test Requirement	220
8.2.4	Performance requirements for PUSCH for high speed train	221
8.2.4.1	Definition and applicability	221
8.2.4.2	Minimum Requirement	221
8.2.4.3	Test Purpose	221
8.2.4.4	Method of test	222
8.2.4.4.1	Initial Conditions	222
8.2.4.4.2	Procedure	222
8.2.4.5	Test Requirement	223
8.2.5	Performance requirements for UL timing adjustment	226
8.2.5.1	Definition and applicability	226
8.2.5.2	Minimum Requirement	226
8.2.5.3	Test Purpose	226
8.2.5.4	Method of test	226
8.2.5.4.1	Initial Conditions	226
8.2.5.4.2	Procedure	226
8.2.5.5	Test Requirement for High Speed Train	229
8.2.6	Performance requirements for PUSCH with 0.001% BLER	230
8.2.6.1	Definition and applicability	230
8.2.6.2	Minimum Requirement	230
8.2.6.3	Test Purpose	230
8.2.6.4	Method of test	230

8.2.6.4.1	Initial Conditions	230
8.2.6.4.2	Procedure	230
8.2.6.5	Test Requirement	231
8.2.7	Performance requirements for PUSCH repetition Type A	232
8.2.7.1	Definition and applicability	232
8.2.7.2	Minimum Requirement	233
8.2.7.3	Test Purpose	233
8.2.7.4	Method of test	233
8.2.7.4.1	Initial Conditions	233
8.2.7.4.2	Procedure	233
8.2.7.5	Test Requirement	234
8.2.8	Performance requirements for PUSCH Mapping Type B with non-slot transmission	236
8.2.8.1	Definition and applicability	236
8.2.8.2	Minimum Requirement	236
8.2.8.3	Test Purpose	236
8.2.8.4	Method of test	236
8.2.8.4.1	Initial Conditions	236
8.2.8.4.2	Procedure	236
8.2.8.5	Test Requirement	237
8.2.9	Performance requirements for PUSCH msgA for 2-step RA type	238
8.2.9.1	Definition and applicability	238
8.2.9.2	Minimum Requirement	238
8.2.9.3	Test Purpose	238
8.2.9.4	Method of test	238
8.2.9.4.1	Initial Conditions	238
8.2.9.4.2	Procedure	238
8.2.9.5	Test Requirement	240
8.2.10	Requirements for interlaced PUSCH	241
8.2.10.1	Definition and applicability	241
8.2.10.2	Minimum Requirement	241
8.2.10.3	Test Purpose	242
8.2.10.4	Method of test	242
8.2.10.4.1	Initial Conditions	242
8.2.10.4.2	Procedure	242
8.2.10.5	Test Requirement	243
8.2.11	Performance requirements for CG-UCI multiplexed on interlaced PUSCH	244
8.2.11.1	Definition and applicability	244
8.2.11.2	Minimum Requirements	244
8.2.11.3	Test purpose	245
8.2.11.4	Method of test	245
8.2.11.4.1	Initial conditions	245
8.2.11.4.2	Procedure	245
8.2.11.5	Test Requirement	246
8.2.12	Performance requirements for TB processing over multi-slot PUSCH (TBoMS)	247
8.2.12.1	Definition and applicability	247
8.2.12.2	Minimum Requirement	247
8.2.12.3	Test Purpose	247
8.2.12.4	Method of test	247
8.2.12.4.1	Initial Conditions	247
8.2.12.4.2	Procedure	248
8.2.12.5	Test Requirement	249
8.2.13	Performance requirements for PUSCH with DMRS bundling	250
8.2.13.1	Definition and applicability	250
8.2.13.2	Minimum Requirement	250
8.2.13.3	Test Purpose	250
8.2.13.4	Method of test	250
8.2.13.4.1	Initial Conditions	250
8.2.13.4.2	Procedure	250
8.2.13.5	Test Requirement	251
8.2.14	Performance requirements for PUSCH for ATG	253
8.2.14.1	Definition and applicability	253
8.2.14.2	Minimum Requirement	253

8.2.14.3	Test Purpose	254
8.2.14.4	Method of test	254
8.2.14.4.1	Initial Conditions	254
8.2.14.4.2	Procedure	254
8.2.14.5	Test Requirement	255
8.2.15	Performance requirements for PUSCH with enhanced DM-RS	256
8.2.15.1	Definition and applicability	256
8.2.15.2	Minimum Requirement	256
8.2.15.3	Test Purpose	256
8.2.15.4	Method of test	256
8.2.15.4.1	Initial Conditions	256
8.2.15.4.2	Procedure	256
8.2.15.5	Test Requirement	257
8.3	Performance requirements for PUCCH	258
8.3.1	Performance requirements for PUCCH format 0	258
8.3.1.1	Definition and applicability	258
8.3.1.2	Minimum Requirement	259
8.3.1.3	Test purpose	259
8.3.1.4	Method of test	259
8.3.1.4.1	Initial conditions	259
8.3.1.4.2	Procedure	259
8.3.1.5	Test Requirement	260
8.3.2	Performance requirements for PUCCH format 1	261
8.3.2.1	NACK to ACK detection	261
8.3.2.1.1	Definition and applicability	261
8.3.2.1.2	Minimum Requirement	261
8.3.2.1.3	Test purpose	261
8.3.2.1.4	Method of test	261
8.3.2.1.4.1	Initial Conditions	261
8.3.2.1.4.2	Procedure	261
8.3.2.1.5	Test Requirement	262
8.3.2.2	ACK missed detection	263
8.3.2.2.1	Definition and applicability	263
8.3.2.2.2	Minimum Requirement	263
8.3.2.2.3	Test purpose	263
8.3.2.2.4	Method of test	264
8.3.2.2.4.1	Initial Conditions	264
8.3.2.2.4.2	Procedure	264
8.3.2.2.5	Test Requirement	265
8.3.3	Performance requirements for PUCCH format 2	265
8.3.3.1	ACK missed detection	265
8.3.3.1.1	Definition and applicability	265
8.3.3.1.2	Minimum requirements	265
8.3.3.1.3	Test purpose	266
8.3.3.1.4	Method of test	266
8.3.3.1.4.1	Initial Condition	266
8.3.3.1.4.2	Procedure	266
8.3.3.1.5	Test requirements	267
8.3.3.2	UCI BLER performance requirements	267
8.3.3.2.1	Definition and applicability	267
8.3.3.2.2	Minimum Requirement	267
8.3.3.2.3	Test purpose	267
8.3.3.2.4	Method of test	268
8.3.3.2.4.1	Initial Condition	268
8.3.3.2.4.2	Procedure	268
8.3.3.2.5	Test requirements	269
8.3.4	Performance requirements for PUCCH format 3	269
8.3.4.1	Definition and applicability	269
8.3.4.2	Minimum requirement	269
8.3.4.3	Test purpose	269
8.3.4.4	Method of test	270
8.3.4.4.1	Initial conditions	270

8.3.4.4.2	Procedure.....	270
8.3.4.5	Test requirement	271
8.3.5	Performance requirements for PUCCH format 4.....	272
8.3.5.1	Definition and applicability.....	272
8.3.5.2	Minimum requirement	272
8.3.5.3	Test purpose	272
8.3.5.4	Method of test	272
8.3.5.4.1	Initial conditions.....	272
8.3.5.4.2	Procedure.....	272
8.3.5.5	Test requirement	273
8.3.6	Performance requirements for multi-slot PUCCH.....	274
8.3.6.1	Performance requirements for multi-slot PUCCH format 1.....	274
8.3.6.1.1	NACK to ACK detection.....	274
8.3.6.1.1.1	Definition and applicability	274
8.3.6.1.1.2	Minimum Requirement.....	274
8.3.6.1.1.3	Test purpose.....	274
8.3.6.1.1.4	Method of test	274
8.3.6.1.1.4.1	Initial conditions.....	274
8.3.6.1.1.4.2	Procedure.....	275
8.3.6.1.1.5	Test Requirement	275
8.3.6.1.2	ACK missed detection.....	276
8.3.6.1.2.1	Definition and applicability	276
8.3.6.1.2.2	Minimum Requirement.....	276
8.3.6.1.2.3	Test purpose.....	276
8.3.6.1.2.4	Method of test	276
8.3.6.1.2.4.1	Initial conditions.....	276
8.3.6.1.2.4.2	Procedure.....	276
8.3.6.1.2.5	Test Requirement.....	277
8.3.7	Performance requirements for interlaced PUCCH format 0.....	278
8.3.7.1	Definition and applicability.....	278
8.3.7.2	Minimum Requirement	278
8.3.7.3	Test purpose	278
8.3.7.4	Method of test	278
8.3.7.4.1	Initial conditions.....	278
8.3.7.4.2	Procedure.....	278
8.3.7.5	Test Requirement	279
8.3.8	Performance requirements for interlaced PUCCH format 1.....	280
8.3.8.1	NACK to ACK detection.....	280
8.3.8.1.1	Definition and applicability.....	280
8.3.8.1.2	Minimum Requirement	280
8.3.8.1.3	Test purpose	280
8.3.8.1.4	Method of test.....	280
8.3.8.1.4.1	Initial Conditions	280
8.3.8.1.4.2	Procedure	280
8.3.8.1.5	Test Requirement.....	281
8.3.8.2	ACK missed detection.....	282
8.3.8.2.1	Definition and applicability.....	282
8.3.8.2.2	Minimum Requirement	282
8.3.8.2.3	Test purpose	282
8.3.8.2.4	Method of test.....	282
8.3.8.2.4.1	Initial Conditions	282
8.3.8.2.4.2	Procedure	282
8.3.8.2.5	Test Requirement.....	283
8.3.9	Performance requirements for interlaced PUCCH format 2.....	283
8.3.9.1	Definition and applicability.....	283
8.3.9.2	Minimum requirement	284
8.3.9.3	Test purpose	284
8.3.9.4	Method of test	284
8.3.9.4.1	Initial conditions.....	284
8.3.9.4.2	Procedure.....	284
8.3.9.5	Test requirement	285
8.3.10	Performance requirements for interlaced PUCCH format 3.....	285

8.3.10.1	Definition and applicability.....	285
8.3.10.2	Minimum requirement	286
8.3.10.3	Test purpose	286
8.3.10.4	Method of test	286
8.3.10.4.1	Initial conditions.....	286
8.3.10.4.2	Procedure.....	286
8.3.10.5	Test requirement	287
8.3.11	Performance requirements for PUCCH sub-slot based repetition format 0	287
8.3.11.1	Definition and applicability.....	287
8.3.11.2	Minimum Requirement	288
8.3.11.3	Test purpose	288
8.3.11.4	Method of test	288
8.3.11.4.1	Initial conditions.....	288
8.3.11.4.2	Procedure.....	288
8.3.11.5	Test Requirement	289
8.3.12	Performance requirements PUCCH format 1 with DM-RS bundling.....	289
8.3.12.1	NACK to ACK detection	289
8.3.12.1.1	Definition and applicability	289
8.3.12.1.2	Minimum Requirement	289
8.3.12.1.3	Test purpose	289
8.3.12.1.4	Method of test.....	290
8.3.12.1.4.1	Initial conditions	290
8.3.12.1.4.2	Procedure	290
8.3.12.1.5	Test Requirement.....	291
8.3.12.2	ACK missed detection.....	291
8.3.12.2.1	Definition and applicability	291
8.3.12.2.2	Minimum Requirement	291
8.3.12.2.3	Test purpose	291
8.3.12.2.4	Method of test.....	291
8.3.12.2.4.1	Initial conditions	291
8.3.12.2.4.2	Procedure	292
8.3.12.2.5	Test Requirement.....	293
8.3.13	Performance requirements for PUCCH format 3 with DM-RS bundling	293
8.3.13.1	Definition and applicability.....	293
8.3.13.2	Minimum requirement	293
8.3.13.3	Test purpose	293
8.3.13.4	Method of test	293
8.3.13.4.1	Initial conditions.....	293
8.3.13.4.2	Procedure.....	293
8.3.13.5	Test requirement	294
8.4	Performance requirements for PRACH	295
8.4.1	PRACH false alarm probability and missed detection.....	295
8.4.1.1	Definition and applicability.....	295
8.4.1.2	Minimum requirement	296
8.4.1.3	Test purpose	296
8.4.1.4	Method of test	296
8.4.1.4.1	Initial conditions.....	296
8.4.1.4.2	Procedure.....	296
8.4.1.5	Test requirement for Normal Mode.....	297
8.4.1.6	Test requirement for high speed train.....	298
8.4.1.7	Test requirement for PRACH with $L_{RA}=1151$ and $L_{RA}=571$	299

Annex A (normative): Reference measurement channels301

A.1	Fixed Reference Channels for reference sensitivity level, ACS, in-band blocking, out-of-band blocking, receiver intermodulation and in-channel selectivity (QPSK, $R=1/3$).....	301
A.2	Fixed Reference Channels for dynamic range (16QAM, $R=2/3$).....	302
A.3	Fixed Reference Channels for performance requirements (QPSK, $R=193/1024$)	304
A.3A	Fixed Reference Channels for performance requirements (QPSK, $R=99/1024$)	307
A.3B	Fixed Reference Channels for performance requirements (QPSK, $R=308/1024$)	308