TECHNICAL SPECIFICATION

ISO/TS 9241-126

First edition 2019-12

Ergonomics of human-system interaction —

Part 126: **Guidance on the presentation of auditory information**

iTeh Standards (https://standards.iteh.ai) Document Preview

ISO/TS 9241-126:2019

https://standards.iteh.ai/catalog/standards/iso/f80127af-9cc4-401c-b3b3-ccbb5d0c725a/iso-ts-9241-126-2019



iTeh Standards (https://standards.iteh.ai) Document Preview

ISO/TS 9241-126:2019

https://standards.iteh.ai/catalog/standards/iso/f80127af-9cc4-401c-b3b3-ccbb5d0c725a/iso-ts-9241-126-2019



COPYRIGHT PROTECTED DOCUMENT

© ISO 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Fax: +41 22 749 09 47 Email: copyright@iso.org

Website: www.iso.org Published in Switzerland

г					
Intr					
1	Scope				
2	Normative reference	es	1		
3	Terms and definitions				
4	Application		5		
-	4.1 Accessibility				
	4.2 Applying the r	ecommendations in this document			
5					
3		unavailability			
		excessive light			
		intain visual attention			
		ty and simplicity			
	5.5 Event-based n	nessages	5		
		uiring immediate action			
		uiring verbal response			
		f message relevance			
	5.9 Attention capt	ure	5		
	5.10 Muting sound	iTeli Standards			
6	Auditory presentation				
	6.1 General	na.//atandauda itah ai\	5		
	6.1.1 Audit	ory channel overload	5		
	6.1.2 Inform	nation conciseness			
	6.1.3 Avoid	extreme dimensions	5		
		ural option			
	6.1.5 Ease	of learning	(
	6.1.6 Signa	invariance 8012/a1-9cc4-401c-b3b3-ccbb3d0c725a/iso-ts-			
	6.1.7 Signa	similarity similarity	7241-120-2016		
		stage signal usage			
		al sequencing			
		orting short term memory			
		-cultural sounds			
		sentative sounds			
		sentative sound usagen noisy environments			
		distinctiveness			
	0	ge signal frequency			
		duration in noisy environments			
7	Auditory dimensions				
	-				
		ute pitch identification			
		oral proximity for pitch comparison			
		rity for pitch comparison			
		num difference for pitch comparison			
		ency range for pitch identification			
		ency range for most accurate pitch discrimination			
		onicity for pitch identification			
		onic tones for pitch discrimination tasks			
		distance sound			
		ucted sound			
	5	distortion	کک ر		

ISO/TS 9241-126:2019(E)

		7.2.2	Separate signal control	
		7.2.3	Loudness cues about the environment	
		7.2.4	Minimal signal intensity	9
		7.2.5	Signal intensity for rapid response	9
		7.2.6	Relative maximal signal intensity	9
		7.2.7	Absolute maximal signal loudness	9
	7.3	Timbr	re	
		7.3.1	Timbre discrimination	9
		7.3.2	Musical instrument timbres	
	7.4	Locali	zation	
		7.4.1	Guidance related to lateral sound localization	
		7.4.2	Minimum angle for position discrimination	
		7.4.3	Frequency selection for sound localization	
		7.4.4	Minimum distance for front/back position identification	
		7.4.5	Guidance related to distance judgment	
		7.4.6	Doppler effect	
		7.4.7	Guidance related to elevation angle judgment	10
	7.5			
	7.5		Minimum cignal duration	
		7.5.1	Minimum signal duration	
	7.6	7.5.2	Adjustable signal duration	
	7.6	-	m and accent usage	
	7.7	,	g	
		7.7.1	Event-based sounds	
		7.7.2	Sounds to guide rhythmic movements	
		7.7.3	Concurrent auditory streams	11
R	Spee	ch		11
	8.1		priate usage	
	0.1	8.1.1	Complex messages	
		8.1.2	Source identification	
		8.1.3	Untrained users	
		8.1.4	Stressful context of use	
		8.1.5	Rapid information exchange 9241-126-2019	
	//02 1		al speech presentation	12
	0.2	8.2.1	Climinate non relevent anged) <u>12</u> 0-201
			Eliminate non-relevant speech	
		8.2.2	Audio volume consistency	
		8.2.3	Monophonic speech presentation	
		8.2.4	Present messages serially	
		8.2.5	Information brevity	
		8.2.6	Message replay	
		8.2.7	Option phrase sequencing	
		8.2.8	Grouping information	
	8.3	Langu	age	
		8.3.1	Language and dialect control	13
		8.3.2	Avoid dialect-specific expressions	
		8.3.3	Vocabulary used in prompts	13
		8.3.4	Consistency of terminology use	13
		8.3.5	Unambiguous prompts	13
		8.3.6	Simple linguistic forms	13
		8.3.7	Minimum syllable count	13
		8.3.8	Sentence usage	
	8.4			
		8.4.1	Use of synthetic speech	
		8.4.2	Source voice identification	
		8.4.3	Dialects and accents	
		8.4.4	Speech output rate	
		8.4.5	Intonation and prosody	
			-	
9	Earc	ons		14

ISO/TS 9241-126:2019(E)

	9.1	Meaningful earcons	14	
	9.2	Sound organization Earcon usage		
	9.3			
	9.4	Earcon construction		
	9.5 Earcon duration			
	9.6	Consistency across earcons	15	
	9.7	Reversing earcons	15	
10	Codir	Coding		
	10.1	General		
		10.1.1 Meaningfulness of codes	15	
		10.1.2 Access to meaning of code		
		10.1.3 Rules of code construction	15	
		10.1.4 Distinctiveness of codes	15	
		10.1.5 Consistent coding	15	
		10.1.6 Coding relative values	15	
		10.1.7 Ordered coding	16	
		10.1.8 Change of state		
		10.1.9 Combination codes		
		10.1.10 User training in codes	16	
		10.1.11 Counting simultaneous tones	16	
	10.2	Dimension-specific coding	16	
		10.2.1 Number of frequencies for pitch coding		
		10.2.2 Frequency selection for pitch coding	16	
		10.2.3 Need for redundant coding when coding based on frequency		
		10.2.4 Coding based on timbre		
		10.2.5 Coding based on intensity	17	
		10.2.6 Number of levels for loudness coding		
		10.2.7 Intensity spacing for loudness coding		
		10.2.8 Number of levels for pitch and loudness coding	17	
		10.2.9 Coding by position and distance	17	
		10.2.10 Coding position and distance with rhythm		
		10.2.11 Number of levels for duration coding		
D:LI:	agranh	ai/catalog/standards/iso/f80127af-9cc4-401c-b3b3-ccbb5d0c725a/iso-ts-924	1-126-2018	

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 159, *Ergonomics*, Subcommittee SC 4, *Ergonomics of human-system interaction*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

https://standards.iteh.ai/catalog/standards/iso/f80127af-9cc4-401c-b3b3-ccbb5d0c725a/iso-ts-9241-126-2019

Introduction

Interactive systems have used auditory information as primary sources and, more commonly, to enhance interactions in primarily visual systems since about the time the digital computer was invented. Even before that, one can consider telephone conversations to be a type of interactive system where information is presented aurally. The way participants in a telephone conversation present information to one another is largely based on learned and subconscious conventions. In the digital realm, sound has been used in increasingly symbolic ways, straying out of necessity from the realistic representations of objects and actions in the physical world.

Unlike visual displays, the information conveyed through sound is typically sparse, and it seems more difficult to intuitively understand what makes a sound scheme usable, whether in its design or its presentation. Since the main communication medium of modern interactive software is the visual display, it is not surprising that a need was first identified for guidelines relating to presentation of visual information. However, designers developing for both visual and auditory information would benefit from guidelines rooted in scientific discovery, that lead to clear and usable communication of information, while not inhibiting the creative process.

This document focuses on guidelines for presentation of information in the auditory modality.

The success of this document will depend on its positive impact on usability of future systems presenting auditory information using these guidelines. However, this document is not necessarily designed to be used by the direct beneficiaries of this desired usability increase. Instead, it serves the following types of users:

- a) the user interface designer, who will apply these guidelines during the development process;
- b) the buyer, who will reference this document during the product procurement process, and whose end users will gain from the potential benefits provided by the guidelines;
- c) those responsible for ensuring products meet the recommendations in this document;
- d) designers of auditory interface development tools to be used by auditory interface designers;
- e) writers of software industry standard guides to be used by auditory interface designers. 126-2019

iTeh Standards (https://standards.iteh.ai) Document Preview

ISO/TS 9241-126:2019

https://standards.iteh.ai/catalog/standards/iso/f80127af-9cc4-401c-b3b3-ccbb5d0c725a/iso-ts-9241-126-2019

Ergonomics of human-system interaction —

Part 126:

Guidance on the presentation of auditory information

1 Scope

This document provides guidance for the auditory presentation of information controlled by software, irrespective of the device. It includes specific properties such as the syntactic or semantic aspects of information, e.g. coding techniques, and gives provisions for the organization of information taking account of human perception and memory capabilities.

This document does not address the hardware issues of the transmission and the production of auditory information.

NOTE 1 Volume is dependent on hardware and thus cannot always be absolutely controlled by software. Environmental conditions can also affect the ability for sounds to be perceived, which can be beyond the ability of the software to take into account.

This document does not apply to auditory alarms, warnings or other safety-related uses of auditory information.

NOTE 2 Safety-related uses of auditory presentation of information are covered in various domain specific standards, such as ISO 7731:2003 which deals with auditory danger signals for public and work areas, and IEC 60601-1-8:2006 which provides very specific requirements for auditory alarms for medical devices.

While this document applies to the presentation of all non-safety-related information, it does not include application domain specific guidance (e.g., audio instructions for consumer products).

This document can be utilized throughout the design process (e.g. as specification and guidance for designers during design or as a basis for heuristic evaluation). Its provisions for the presentation of information depend on the auditory design approach, the task, the user, the environment and the single or multiple technologies that can be used for presenting the information. Consequently, this document cannot be applied without knowledge of the context of use. It is not intended to be used as a prescriptive set of rules to be applied in its entirety but rather assumes that the designer has proper information available concerning task and user requirements and understands the use of available technology.

This document does not address visual or tactile/haptic presentation of information or modality shifting for the presentation of auditory information in other modalities.

NOTE 3 ISO 9241-112 provides high-level ergonomic guidance that applies to all modalities.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 9241-171, Ergonomics of human-system interaction — Part 171: Guidance on software accessibility

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO/TS 9241-126:2019(E)

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at https://www.iso.org/obp
- IEC Electropedia: available at http://www.electropedia.org/

3.1

pitch

perception of the highness or lowness of a sound's frequency (3.2)

3.2

frequency

number of complete oscillations per unit time of a periodic waveform

3.3

fundamental frequency

lowest frequency (3.2) component of a periodic waveform

3.4

overtone

higher *tone* (3.18) produced simultaneously with a *fundamental frequency* (3.3) and that, with the fundamental frequency, comprise a complex tone

3.5

harmonic

overtone (3.4) that is an integer multiple of the fundamental frequency (3.3)

3.6

harmonicity

degree to which a sound's *overtones* (3.4) are composed of integer multiples of its *fundamental* frequency (3.3)

Note 1 to entry: A sound with high harmonicity is called "harmonic" while a sound with low harmonicity is called "inharmonic".

Note 2 to entry: The degree to which a sound's overtones depart from being integer multiples of its fundamental 6–20 | 9 frequency is called "inharmonicity".

3.7

pure tone

tone (3.18) composed of a single frequency (3.2) with no harmonics (3.5)

3.8

intensity

power per unit area of a sound wave in a direction perpendicular to that area

3.9

loudness

perception of a sound's intensity (3.8)

3.10

masking threshold

sound pressure level below which a signal is not audible when in the presence of another specified sound (i.e. a masking signal or masker)

Note 1 to entry: The masking threshold depends on the sound's *frequency* (3.2), the type of masker, and the kind of sound being masked.

3.11

timbre

quality given to a sound by its overtones (3.4)

3.12

reverberation

resonance

echo

prolongation of a sound through reflection off objects or structures in the sound environment

3.13

interaural

relating to sound reception and perception by each ear considered separately

3.14

monaural

relating to sound emanating from a single sound source or presented equally from all sound sources

3.15

rhythm

strong, regular, repeated pattern of sound

3.16

accent

increased stress or emphasis on a particular sound within a sequence, usually by increasing its *intensity* (3.8) or duration relative to other sounds in the sequence

3.17

earcon

auditory icon

brief, distinctive sound used to represent a specific object or event

3.18

tone

discrete musical sound

3.19

prosody

10Sudy 180/18 9241-126:2019

 $rhy thmic \ and \ into national \ aspect \ of \ language \ a_{f-9cc4-401c-b3b3-ccbb5d0c725a/iso-ts-9241-126-2019}$

3.20

lateral sound localization

ability of a user to approximate the location where a sound originated

3.21

accessibility

extent to which products, systems, services, environments and facilities can be used by people from a population with the widest range of user needs, characteristics and capabilities to achieve identified goals in identified contexts of use

Note 1 to entry: Context of use includes direct use or use supported by assistive technologies.

[SOURCE: ISO 9241-112:2017, 3.15]

4 Application

4.1 Accessibility

Auditory presentation of information shall be in accordance with ISO 9241-171, which gives specific requirements and recommendations for the presentation of information in the auditory modality and the presentation of the same information in different modalities.

NOTE ISO 9241-171:2008, 10.6, contains significant guidance on the controllability and accessibility of audio output.