

SLOVENSKI STANDARD SIST EN 480-15:2023

01-oktober-2023

Nadomešča:

SIST EN 480-15:2013

Kemijski dodatki za beton, malto in injekcijsko maso - Metode preskušanja - 15. del: Referenčni beton in metode za preskušanje spreminjanja viskoznosti dodatkov

Admixtures for concrete, mortar and grout - Test methods - Part 15: Reference concrete and method for testing viscosity modifying admixtures

Zusatzmittel für Beton, Mörtel und Einpressmörtel - Prüfverfahren - Teil 15: Referenzbeton und Prüfverfahren zur Prüfung von viskositätsmodifizierenden Zusatzmitteln

Adjuvants pour béton, mortier et coulis - Méthodes d'essai - Partie 15 : Béton de référence et méthode d'essai des adjuvants modificateurs de viscosité

Ta slovenski standard je istoveten z: EN 480-15:2023

ICS:

91.100.30 Beton in betonski izdelki Concrete and concrete

products

SIST EN 480-15:2023 en,fr,de

SIST EN 480-15:2023

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 480-15:2023

https://standards.iteh.ai/catalog/standards/sist/bab6ef1f-01b3-4943-8cc9-9e84ac36835f/sist-en-480-15-2023

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM EN 480-15

July 2023

ICS 91.100.30

Supersedes EN 480-15:2013

English Version

Admixtures for concrete, mortar and grout - Test methods - Part 15: Reference concrete and method for testing viscosity modifying admixtures

Adjuvants pour béton, mortier et coulis - Méthodes d'essai - Partie 15 : Béton de référence et méthode d'essai des adjuvants modificateurs de viscosité

Zusatzmittel für Beton, Mörtel und Einpressmörtel -Prüfverfahren - Teil 15: Referenzbeton und Prüfverfahren zur Prüfung von viskositätsmodifizierenden Zusatzmitteln

This European Standard was approved by CEN on 28 May 2023.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

EN 480-15:2023 (E)

Contents		Page
European foreword		
1	Scope	5
2	Normative references	5
3	Terms and definitions	5
4	Constituent materials	6
4.1	Cement	6
4.2	Aggregate	6
4.3	Mixing water	6
5	Reference concrete	6
6	Preparation of reference concrete	7
6.1	Mix proportions	7
6.2	Mix proportions Mixing and testing	7
7	Test report	8

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 480-15:2023

https://standards.iteh.ai/catalog/standards/sist/bab6ef1f-01b3-4943-8cc9-9e84ac36835f/sisten-480-15-2023

European foreword

This document (EN 480-15:2023) has been prepared by Technical Committee CEN/TC 104 "Concrete and related products", the secretariat of which is held by SN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by January 2024, and conflicting national standards shall be withdrawn at the latest by January 2024.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 480-15:2013.

This document has been drafted by Subcommittee 3 (SC 3) of CEN/TC 104 "Admixtures for concrete, mortar and grout".

This document is part of the EN 480 series, with the title *Admixtures for concrete, mortar and grout* — *Test methods,* which comprises the following parts:

- Part 1: Reference concrete and reference mortar for testing
- Part 2: Determination of setting time
- Part 4: Determination of bleeding of concrete
- Part 5: Determination of capillary absorption
- Part 6: Infrared analysis
- Part 8: Determination of the conventional dry material content
- Part 10: Determination of water soluble chloride content
- Part 11: Determination of air void characteristics in hardened concrete
- Part 12: Determination of the alkali content of admixtures
- Part 13: Reference masonry mortar for testing mortar admixtures
- Part 14: Determination of the effect on corrosion susceptibility of reinforcing steel by potentiostatic electro-chemical test
- Part 15: Reference concrete and method for testing viscosity modifying admixtures (the present document)

This document is intended to be used together with the other standards of the EN 480 series and for testing admixtures in accordance with the EN 934 series of standards.

EN 480-15:2023 (E)

The main changes compared with the previous edition are listed below:

- a) identification of the relevant test method standard for the determination of the density of fresh concrete in Table 2;
- b) editorial changes.

Any feedback and questions on this document should be directed to the users' national standards body. A complete listing of these bodies can be found on the CEN website.

According to the CEN-CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and the United Kingdom.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 480-15:2023</u> https://standards.iteh.ai/catalog/standards/sist/bab6ef1f-01b3-4943-8cc9-9e84ac36835f/sist en-480-15-2023

1 Scope

This document specifies the constituent materials, the composition and the mix procedure to produce a reference concrete with a prescribed consistency and segregated portion for testing viscosity modifying admixtures as defined in EN 934-2. It also describes how to determine the requirements for the test mix in comparison with the control mix.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 196-2, Method of testing cement - Part 2: Chemical analysis of cement

EN 196-6, Methods of testing cement - Part 6: Determination of fineness

EN 197-1, Cement - Part 1: Composition, specifications and conformity criteria for common cements

EN 934-2, Admixtures for concrete, mortar and grout - Part 2: Concrete admixtures - Definitions, requirements, conformity, marking and labelling

EN 1008, Mixing water for concrete - Specification for sampling, testing and assessing the suitability of water, including water recovered from processes in the concrete industry, as mixing water for concrete

EN 12350-6, Testing fresh concrete - Part 6: Density

EN 12350-7, Testing fresh concrete - Part 7: Air content - Pressure methods

EN 12350-8, Testing fresh concrete - Part 8: Self-compacting concrete - Slump-flow test

EN 12350-11, Testing fresh concrete - Part 11: Self-compacting concrete - Sieve segregation test

EN 12390-1, Testing hardened concrete - Part 1: Shape, dimensions and other requirements for specimens and moulds

EN 12390-2, Testing hardened concrete - Part 2: Making and curing specimens for strength tests

EN 12620, Aggregates for concrete

3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at https://www.iso.org/obp
- IEC Electropedia: available at https://www.electropedia.org/

4 Constituent materials

4.1 Cement

The reference concrete shall be made with a CEM l cement of strength class 42,5 or 52,5 conforming to EN 197-1.

The cement used shall have a C_3A content of 7 % to 11 % by mass calculated from chemical analysis according to EN 196-2 and a specific surface of 3 200 cm²/g to 4 600 cm²/g determined according to EN 196-6.

4.2 Aggregate

A natural normal weight aggregate conforming to EN 12620 with low water absorption (\leq 2 % by mass) shall be used. The grading shall conform to Table 1.

Percentage by mass passing the test sieve Aperture size - mm 95 to 100 16 12 85 to 100 8 62 to 74 4 42 to 52 2 28 to 38 1 19 to 29 0,500 11 to 21 https://standar0,250 4 to 14 0.125 2 to 6 0 to 2 0,063

Table 1 — Aggregate for reference concrete

4.3 Mixing water

Water according to EN 1008, or distilled or de-ionized water shall be used as mixing water.

Wash water from concrete production shall not be used.

5 Reference concrete

Unless otherwise specified, tests on the reference concrete are performed as comparative tests. That is, the performance of the admixtures is determined by comparing the reference concrete containing the viscosity modifying admixture (test mix) with the reference concrete made without the viscosity modifying admixture (control mix) but otherwise with the same aggregate/cement ratio and constituents from the same delivery.

The requirements for the reference concrete are given in Table 2. The fresh concrete shall be fully compacted. The air content of the control mix shall not exceed 2 % by volume.

Constituent / test	Requirement	
Reference cement	$(400 \pm 10) \text{ kg/m}^3$	
Aggregate	According to 4.2. The aggregate: cement ratio shall be recorded.	
Superplasticizer or plasticizer to EN 934-2	Within manufacturers normal range	
Water	$\leq 230 \text{ kg/m}^3$	
Slump flow (SF) to EN 12350-8	Control mix 660 mm to 750 mm Test mix ≥ control mix	
Sieve segregation (SR) to EN 12350-11	Control mix 15 % ≤ SR ≤ 30 %	
Air content to EN 12350-7	Control mix ≤ 2 %	
Fresh density to EN 12350-6	According to 6.2 the fresh density shall be recorded.	

6 Preparation of reference concrete

6.1 Mix proportions

The mix proportions shall be in accordance with Table 2.

The aggregate shall be used in an oven dry condition (≥105 °C) to remove doubts on moisture content variation. If the aggregate is not oven dry, its moisture content shall be determined and the aggregate and water content shall be corrected accordingly. In the case of dispute, oven dry aggregates shall be used.

The dosage of the superplasticizer and the quantity of water in the control mix shall be such as to obtain an initial slump flow (SF) and sieve segregation (SR) in accordance with Table 2.

The test mix containing the viscosity modifying admixture shall have the same water content, cement content and the same aggregate: cement ratio as the control mix but the dosage of superplasticizer shall be adjusted if necessary to give a consistence not less than that of the control mix.

6.2 Mixing and testing

Prior to mixing, each of the constituents shall be conditioned to a temperature of (20 ± 2) °C.

The following mixing technique shall be adopted to ensure repeatability of results and eliminate initial moisture absorption effects on consistence.

- Use a forced action pan mixer to a minimum of 50 % and a maximum 90 % of capacity.
- Wipe the inside with a damp cloth if dry.
- Add all the aggregates to the pan mixer with half the mixing water. Mix for 2 min then stand for 2 min. Cover the pan mixer during the standing period to minimize evaporation effects.
- Restart the mixer for 30 s after or while adding the cement. Over the next 30 s, add the remaining water and admixtures as appropriate to the mix (noting any manufacturer's recommendations with respect to the order and timing). Mix for a further 2 min.

EN 480-15:2023 (E)

- Determine the slump flow (SF) and start the sieve segregation test (SR) within 10 min of completion of mixing.
- If the slump flow and sieve segregation of the control mix are outside the limits in Table 2, discard the mix and repeat at a revised water or superplasticiser content. If the slump flow of the test mix is not equal to or greater than the slump flow of the control mix, discard the mix and repeat at a revised superplasticiser content.
- Determine the fresh density and air content within 30 min from completion of mixing (if necessary the concrete may be remixed for 10 s).
- If the air content and/or cement content of the control mix calculated from the fresh density are outside the limits in Table 2, discard the mix and test a new mix.
- Take three specimens from each mix for compressive strength testing. The control mix should be held for 60 min to 90 min then remixed for 1 min before taking the specimens to prevent segregation in the cube or cylinder mould. The test mix specimens should not be remixed but be made within 60 min from completion of initial mixing. Prepare and cure the specimens in accordance with EN 12390-2 using moulds conforming to EN 12390-1. If the compressive strength of one of the specimens varies from the average of the set by more than 10 % it shall be discarded and the average recalculated from the remaining two specimens.

Test report 7

The test report shall include the following information for the control and test mixes:

- a reference to this document, including its year of publication;
- identification of the sample; b)
- aggregate:
- c)
 - 1) source and type;
 - 2) crushed / uncrushed;
 - 3) grading;
 - 4) moisture content if not oven dry;
- cement:
 - 1) source;
 - 2) notation to EN 197-1 including strength class;
 - 3) C₃A content;
 - 4) specific surface;