

ETSI TS 138 101-2 V17.15.0 (2024-10)



**5G;
NR;
User Equipment (UE) radio transmission and reception;
Part 2: Range 2 Standalone
(3GPP TS 38.101-2 version 17.15.0 Release 17)**

[ETSI TS 138 101-2 V17.15.0 \(2024-10\)](https://standards.iteh.ai/catalog/standards/etsi/ce30be43-85a0-421e-9965-487122537c7b/etsi-ts-138-101-2-v17-15-0-2024-10)

<https://standards.iteh.ai/catalog/standards/etsi/ce30be43-85a0-421e-9965-487122537c7b/etsi-ts-138-101-2-v17-15-0-2024-10>



Reference

RTS/TSGR-0438101-2vhf0

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
ETSI [Search & Browse Standards application](#).

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#).

Users should be aware that the present document may be revised or have its status changed,
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2024.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <https://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document **"shall"**, **"shall not"**, **"should"**, **"should not"**, **"may"**, **"need not"**, **"will"**, **"will not"**, **"can"** and **"cannot"** are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and **"must not"** are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	12
1 Scope	14
2 References	14
3 Definitions, symbols and abbreviations	15
3.1 Definitions	15
3.2 Symbols.....	16
3.3 Abbreviations	18
4 General	20
4.1 Relationship between minimum requirements and test requirements	20
4.2 Applicability of minimum requirements	20
4.3 Specification suffix information.....	20
5 Operating bands and channel arrangement.....	22
5.1 General	22
5.2 Operating bands.....	22
5.2A Operating bands for CA	22
5.2A.1 Intra-band CA	22
5.2A.2 Inter-band CA	23
5.2D Operating bands for UL MIMO	23
5.3 UE Channel bandwidth	23
5.3.1 General.....	23
5.3.2 Maximum transmission bandwidth configuration	24
5.3.3 Minimum guardband and transmission bandwidth configuration.....	24
5.3.4 RB alignment	26
5.3A UE channel bandwidth for CA	27
5.3A.1 General.....	27
5.3A.2 Minimum guardband and transmission bandwidth configuration for CA	27
5.3A.3 RB alignment with different numerologies for CA.....	28
5.3A.4 UE channel bandwidth per operating band for CA.....	28
5.3D Channel bandwidth for UL MIMO.....	31
5.4 Channel arrangement.....	31
5.4.1 Channel spacing.....	31
5.4.1.1 Channel spacing for adjacent NR carriers	31
5.4.2 Channel raster	32
5.4.2.1 NR-ARFCN and channel raster.....	32
5.4.2.2 Channel raster to resource element mapping.....	32
5.4.2.3 Channel raster entries for each operating band	32
5.4.3 Synchronization raster	33
5.4.3.1 Synchronization raster and numbering.....	33
5.4.3.2 Synchronization raster to synchronization block resource element mapping.....	33
5.4.3.3 Synchronization raster entries for each operating band.....	34
5.4A Channel arrangement for CA.....	34
5.4A.1 Channel spacing for CA.....	34
5.5 Configurations	36
5.5A Configurations for CA.....	36
5.5A.1 Configurations for intra-band contiguous CA.....	36
5.5A.2 Configurations for intra-band non-contiguous CA	43
5.5A.3 Configurations for inter-band CA.....	52
5.5D Configurations for UL MIMO.....	56
6 Transmitter characteristics	57

6.1	General	57
6.2	Transmitter power	57
6.2.1	UE maximum output power	57
6.2.1.0	General	57
6.2.1.1	UE maximum output power for power class 1	57
6.2.1.2	UE maximum output power for power class 2	58
6.2.1.3	UE maximum output power for power class 3	59
6.2.1.4	UE maximum output power for power class 4	61
6.2.1.5	UE maximum output power for power class 5	62
6.2.1.6	UE maximum output power for power class 6	63
6.2.1.7	UE maximum output power for power class 7	64
6.2.2	UE maximum output power reduction	65
6.2.2.0	General	65
6.2.2.1	UE maximum output power reduction for power class 1	65
6.2.2.2	UE maximum output power reduction for power class 2	67
6.2.2.3	UE maximum output power reduction for power class 3	67
6.2.2.4	UE maximum output power reduction for power class 4	69
6.2.2.5	UE maximum output power reduction for power class 5	69
6.2.2.6	UE maximum output power reduction for power class 6	69
6.2.2.7	UE maximum output power reduction for power class 7	69
6.2.3	UE maximum output power with additional requirements	69
6.2.3.1	General	69
6.2.3.2	Void	71
6.2.3.2.1	Void	71
6.2.3.2.2	Void	71
6.2.3.2.3	Void	71
6.2.3.2.4	Void	71
6.2.3.2.5	Void	71
6.2.3.3	A-MPR for NS_202	71
6.2.3.3.1	A-MPR for NS_202 for power class 1	71
6.2.3.3.2	A-MPR for NS_202 for power class 2	71
6.2.3.3.3	A-MPR for NS_202 for power class 3	71
6.2.3.3.4	A-MPR for NS_202 for power class 4	71
6.2.3.3.5	A-MPR for NS_202 for power class 5	71
6.2.3.3.6	A-MPR for NS_202 for power class 6	71
6.2.3.3.7	A-MPR for NS_202 for power class 7	71
6.2.3.4	A-MPR for NS_203	71
6.2.3.4.1	A-MPR for NS_203 for power class 1	71
6.2.3.4.2	A-MPR for NS_203 for power class 2	72
6.2.3.4.3	A-MPR for NS_203 for power class 3	72
6.2.3.4.4	A-MPR for NS_203 for power class 4	72
6.2.3.4.5	A-MPR for NS_203 for power class 5	72
6.2.3.4.6	A-MPR for NS_203 for power class 6	72
6.2.3.4.7	A-MPR for NS_203 for power class 7	72
6.2.4	Configured transmitted power	72
6.2.5	Requirements for UL gap (<i>ul-GapFR2-r17</i>) for TX power management	73
6.2A	Transmitter power for CA	74
6.2A.1	UE maximum output power for CA	74
6.2A.2	UE maximum output power reduction for CA	75
6.2A.2.1	General	75
6.2A.2.2	Maximum output power reduction for power class 1	75
6.2A.2.2.1	Maximum output power reduction for power class 1 intra-band contiguous UL CA	75
6.2A.2.2.2	Maximum output power reduction for power class 1 intra-band non-contiguous UL CA	77
6.2A.2.2.3	Maximum output power reduction for power class 1 inter-band CA	77
6.2A.2.3	Maximum output power reduction for power class 2	78
6.2A.2.4	Maximum output power reduction for power class 3	78
6.2A.2.4.1	Maximum output power reduction for power class 3 intra-band contiguous CA	78
6.2A.2.4.2	Maximum output power reduction for power class 3 intra-band non-contiguous CA	79
6.2A.2.4.3	Maximum output power reduction for power class 3 inter-band CA	80
6.2A.2.5	Maximum output power reduction for power class 4	80
6.2A.2.6	Maximum output power reduction for power class 5	80
6.2A.3	UE maximum output power with additional requirements for CA	81

6.2A.3.1	General	81
6.2A.3.2	Void	82
6.2A.3.2.1	Void	82
6.2A.3.2.2	Void	82
6.2A.3.2.3	Void	82
6.2A.3.2.4	Void	82
6.2A.3.2.5	Void	82
6.2A.3.3	A-MPR for CA_NS_202	82
6.2A.3.3.1	A-MPR for CA_NS_202 for power class 1	82
6.2A.3.3.2	A-MPR for CA_NS_202 for power class 2	82
6.2A.3.3.3	A-MPR for CA_NS_202 for power class 3	82
6.2A.3.3.4	A-MPR for CA_NS_202 for power class 4	82
6.2A.3.3.5	A-MPR for CA_NS_202 for power class 5	82
6.2A.3.4	A-MPR for CA_NS_203	82
6.2A.3.4.1	A-MPR for CA_NS_203 for power class 1	82
6.2A.3.4.2	A-MPR for CA_NS_203 for power class 2	82
6.2A.3.4.3	A-MPR for CA_NS_203 for power class 3	82
6.2A.3.4.4	A-MPR for CA_NS_203 for power class 4	83
6.2A.3.4.5	A-MPR for CA_NS_203 for power class 5	83
6.2A.4	Configured transmitted power for CA	83
6.2A.4.1	Configured transmitted power for intra-band UL CA	83
6.2A.4.2	Configured transmitted power for inter-band UL CA	84
6.2A.5	Requirements for UL gap (<i>ul-GapFR2-r17</i>) for TX power management in CA	85
6.2D	Transmitter power for UL MIMO	85
6.2D.1	UE maximum output power for UL MIMO	85
6.2D.1.0	General	85
6.2D.1.1	UE maximum output power for UL MIMO for power class 1	86
6.2D.1.2	UE maximum output power for UL MIMO for power class 2	87
6.2D.1.3	UE maximum output power for UL MIMO for power class 3	88
6.2D.1.4	UE maximum output power for UL MIMO for power class 4	89
6.2D.1.5	UE maximum output power for UL MIMO for power class 5	90
6.2D.1.6	UE maximum output power for UL MIMO for power class 6	90
6.2D.2	UE maximum output power reduction for modulation / channel bandwidth for UL MIMO	91
6.2D.2.1	UE maximum output power reduction for modulation / channel bandwidth for UL MIMO for power class 1	91
6.2D.2.2	UE maximum output power reduction for modulation / channel bandwidth for UL MIMO for power class 2	92
6.2D.2.3	UE maximum output power reduction for modulation / channel bandwidth for UL MIMO for power class 3	92
6.2D.2.4	UE maximum output power reduction for modulation / channel bandwidth for UL MIMO for power class 4	92
6.2D.2.5	UE maximum output power reduction for modulation / channel bandwidth for UL MIMO for power class 5	92
6.2D.2.6	UE maximum output power reduction for modulation / channel bandwidth for UL MIMO for power class 6	92
6.2D.3	UE maximum output power reduction with additional requirements for UL MIMO	92
6.2D.3.1	UE maximum output power reduction with additional requirements for UL MIMO for power class 1	92
6.2D.3.2	UE maximum output power reduction with additional requirements for UL MIMO for power class 2	93
6.2D.3.3	UE maximum output power reduction with additional requirements for UL MIMO for power class 3	93
6.2D.3.4	UE maximum output power reduction with additional requirements for UL MIMO for power class 4	93
6.2D.3.5	UE maximum output power reduction with additional requirements for UL MIMO for power class 5	93
6.2D.3.6	UE maximum output power reduction with additional requirements for UL MIMO for power class 6	93
6.2D.4	Configured transmitted power for UL MIMO	93
6.3	Output power dynamics	93
6.3.1	Minimum output power	93
6.3.1.0	General	93

6.3.1.1	Minimum output power for power class 1	94
6.3.1.2	Minimum output power for power class 2, 3, and 4.....	94
6.3.1.3	Minimum output power for power class 5 and 6.....	94
6.3.1.4	Minimum output power for power class 7	95
6.3.2	Transmit OFF power.....	95
6.3.3	Transmit ON/OFF time mask	95
6.3.3.1	General	95
6.3.3.2	General ON/OFF time mask	96
6.3.3.3	Transmit power time mask for slot and short or long subslot boundaries.....	96
6.3.3.4	PRACH time mask.....	96
6.3.3.5	Void.....	98
6.3.3.6	SRS time mask	98
6.3.3.7	PUSCH-PUCCH and PUSCH-SRS time masks	99
6.3.3.8	Transmit power time mask for consecutive slot or long subslot transmission and short subslot transmission boundaries	99
6.3.3.9	Transmit power time mask for consecutive short subslot transmissions boundaries	100
6.3.4	Power control.....	101
6.3.4.1	General	101
6.3.4.2	Absolute power tolerance.....	101
6.3.4.3	Relative power tolerance	101
6.3.4.4	Aggregate power tolerance.....	102
6.3A	Output power dynamics for CA	102
6.3A.1	Minimum output power for CA	102
6.3A.1.0	General	102
6.3A.1.1	Minimum output power for power class 1	103
6.3A.1.2	Minimum output power for power class 2, 3, and 4.....	103
6.3A.1.3	Minimum output power for power class 5	104
6.3A.2	Transmit OFF power for CA.....	104
6.3A.3	Transmit ON/OFF time mask for CA	104
6.3A.4	Power control for CA.....	105
6.3A.4.1	General	105
6.3A.4.2	Absolute power tolerance.....	105
6.3A.4.3	Relative power tolerance	105
6.3A.4.4	Aggregate power tolerance.....	105
6.3D	Output power dynamics for UL MIMO	106
6.3D.0	General.....	106
6.3D.1	Minimum output power for UL MIMO	106
6.3D.1.1	Minimum output power for UL MIMO for power class 1	106
6.3D.1.2	Minimum output power for UL MIMO for power class 2, 3 and 4.....	106
6.3D.1.3	Minimum output power for UL MIMO for power class 5 and 6.....	106
6.3D.2	Transmit OFF power for UL MIMO.....	106
6.3D.3	Transmit ON/OFF time mask for UL MIMO	106
6.4	Transmit signal quality	106
6.4.1	Frequency Error	106
6.4.2	Transmit modulation quality.....	107
6.4.2.0	General	107
6.4.2.1	Error vector magnitude	107
6.4.2.2	Carrier leakage	109
6.4.2.2.1	General	109
6.4.2.2.2	Carrier leakage for power class 1	109
6.4.2.2.3	Carrier leakage for power class 2	109
6.4.2.2.4	Carrier leakage for power class 3	110
6.4.2.2.5	Carrier leakage for power class 4	110
6.4.2.2.6	Carrier leakage for power class 5	110
6.4.2.2.7	Carrier leakage for power class 6	110
6.4.2.2.8	Carrier leakage for power class 7	110
6.4.2.3	In-band emissions	111
6.4.2.3.1	General	111
6.4.2.3.2	In-band emissions for power class 1.....	111
6.4.2.3.3	In-band emissions for power class 2.....	112
6.4.2.3.4	In-band emissions for power class 3.....	112
6.4.2.3.5	In-band emissions for power class 4.....	113

6.4.2.3.6	In-band emissions for power class 5	114
6.4.2.3.7	In-band emissions for power class 6	115
6.4.2.3.8	In-band emissions for power class 7	115
6.4.2.4	EVM equalizer spectrum flatness	115
6.4.2.5	EVM spectral flatness for Pi/2 BPSK modulation	116
6.4.2.6	Phase continuity requirements for DMRS bundling	117
6.4A	Transmit signal quality for CA	118
6.4A.0	General	118
6.4A.1	Frequency error	119
6.4A.2	Transmit modulation quality	119
6.4A.2.0	General	119
6.4A.2.1	Error Vector magnitude	119
6.4A.2.2	Carrier leakage	119
6.4A.2.2.1	General	119
6.4A.2.2.2	Carrier leakage for power class 1	120
6.4A.2.2.3	Carrier leakage for power class 2	120
6.4A.2.2.4	Carrier leakage for power class 3	120
6.4A.2.2.5	Carrier leakage for power class 4	121
6.4A.2.2.6	Carrier leakage for power class 5	121
6.4A.2.3	Inband emissions	121
6.4A.2.3.1	General	121
6.4A.2.3.2	Inband emissions for power class 1	122
6.4A.2.3.3	Inband emissions for power class 2	122
6.4A.2.3.4	Inband emissions for power class 3	123
6.4A.2.3.5	Inband emissions for power class 4	124
6.4A.2.3.6	Inband emissions for power class 5	125
6.4A.2.4	EVM equalizer spectrum flatness	126
6.4D	Transmit signal quality for UL MIMO	126
6.4D.0	General	126
6.4D.1	Frequency error for UL MIMO	126
6.4D.2	Transmit modulation quality for UL MIMO	126
6.4D.3	Time alignment error for UL MIMO	127
6.4D.4	Requirements for coherent UL MIMO	127
6.5	Output RF spectrum emissions	128
6.5.1	Occupied bandwidth	128
6.5.2	Out of band emissions	128
6.5.2.0	General	128
6.5.2.1	Spectrum emission mask	128
6.5.2.2	Void	129
6.5.2.3	Adjacent channel leakage ratio	129
6.5.3	Spurious emissions	130
6.5.3.1	Spurious emission band UE co-existence	130
6.5.3.2	Additional spurious emissions	131
6.5.3.2.1	General	131
6.5.3.2.2	Void	132
6.5.3.2.3	Additional spurious emission requirements for NS_202	132
6.5.3.2.4	Additional spurious emission requirements for NS_203	132
6.5.3.2.5	Additional spurious emission requirements for NS_204	132
6.5A	Output RF spectrum emissions for CA	133
6.5A.1	Occupied bandwidth for CA	133
6.5A.1.0	General	133
6.5A.1.1	Occupied bandwidth for intra-band contiguous UL CA	133
6.5A.1.2	Occupied bandwidth for intra-band non-contiguous UL CA	133
6.5A.1.3	Occupied bandwidth for inter-band UL CA	133
6.5A.2	Out of band emissions	133
6.5A.2.1	Spectrum emission mask for CA	133
6.5A.2.1.0	General	133
6.5A.2.1.1	Spectrum emission mask for intra-band contiguous UL CA	133
6.5A.2.1.2	Spectrum emission mask for intra-band non-contiguous UL CA	134
6.5A.2.1.3	Spectrum emission mask for inter-band UL CA	134
6.5A.2.2	Void	134
6.5A.2.3	Adjacent channel leakage ratio for CA	134

6.5A.2.3.1	Adjacent channel leakage ratio for CA intra-band contiguous UL CA	134
6.5A.2.3.2	Adjacent channel leakage ratio for CA intra-band non-contiguous UL CA	135
6.5A.2.3.3	Adjacent channel leakage ratio for CA inter-band UL CA	135
6.5A.3	Spurious emissions for CA	135
6.5A.3.0	General spurious emissions for CA	135
6.5A.3.0.0	General	135
6.5A.3.0.1	Spurious emissions for intra-band contiguous UL CA	136
6.5A.3.0.2	Spurious emissions for intra-band non-contiguous UL CA	136
6.5A.3.0.3	Spurious emissions for inter-band UL CA	136
6.5A.3.1	Spurious emission band UE co-existence for UL CA	136
6.5A.3.2	Additional spurious emissions	137
6.5A.3.2.1	General	137
6.5A.3.2.2	Void	137
6.5A.3.2.3	Additional spurious emission requirements for CA_NS_202	137
6.5A.3.2.4	Additional spurious emission requirements for CA_NS_203	137
6.5D	Output RF spectrum emissions for UL MIMO	138
6.5D.1	Occupied bandwidth for UL MIMO	138
6.5D.2	Out of band emissions for UL MIMO	138
6.5D.3	Spurious emissions for UL MIMO	138
6.6	Beam correspondence	138
6.6.1	General	138
6.6.2	(Void)	138
6.6.3	(Void)	138
6.6.4	Beam correspondence for power class 3	138
6.6.4.1	General	138
6.6.4.2	Beam correspondence tolerance for power class 3	139
6.6.4.3	Side Conditions	139
6.6.4.3.1	Side Condition for beam correspondence based on SSB and CSI-RS	139
6.6.4.3.2	Side Condition for SSB based enhanced Beam Correspondence requirements	140
6.6.4.3.3	Side Condition for CSI-RS based enhanced Beam Correspondence requirements	140
6.6.4.4	Applicability	141
6.6.5	(Void)	141
6.6.6	Beam correspondence for power class 5	141
6.6.6.1	General	141
6.6.6.2	(Reserved)	142
6.6.6.3	Side Conditions	142
6.6.6.3.1	Side Condition for beam correspondence based on SSB and CSI-RS	142
6.6.6.3.2	Side Condition for SSB based enhanced Beam Correspondence requirements	143
6.6.6.3.3	Side Condition for CSI-RS based enhanced Beam Correspondence requirements	143
6.6.6.4	Applicability	143
6.6.7	Beam correspondence for power class 6	144
6.6.7.1	General	144
6.6.7.2	(Void)	144
6.6.7.3	Side Conditions	144
6.6.7.3.1	(Void)	144
6.6.7.3.2	Side Condition for SSB based enhanced Beam Correspondence requirements	144
6.6.7.3.3	Side Condition for CSI-RS based enhanced Beam Correspondence requirements	144
6.6.7.4	Applicability	145
6.6.8	Beam correspondence for power class 7	146
6.6.8.1	General	146
6.6.8.2	Void	146
6.6.8.3	Side Conditions	146
6.6.8.3.1	Side Condition for beam correspondence based on SSB and CSI-RS	146
6.6.8.3.2	Side Condition for SSB based enhanced Beam Correspondence requirements	147
6.6.8.3.3	Side Condition for CSI-RS based enhanced Beam Correspondence requirements	147
6.6.8.4	Applicability	147
6.6A	Beam correspondence for CA	148
7	Receiver characteristics	149
7.1	General	149
7.2	Diversity characteristics	149
7.3	Reference sensitivity	149

7.3.1	General.....	149
7.3.2	Reference sensitivity power level	149
7.3.2.1	Reference sensitivity power level for power class 1	149
7.3.2.2	Reference sensitivity power level for power class 2	150
7.3.2.3	Reference sensitivity power level for power class 3	150
7.3.2.4	Reference sensitivity power level for power class 4	151
7.3.2.5	Reference sensitivity power level for power class 5	151
7.3.2.6	Reference sensitivity power level for power class 6	152
7.3.2.7	Reference sensitivity power level for power class 7	152
7.3.3	Void	153
7.3.4	EIS spherical coverage.....	153
7.3.4.1	EIS spherical coverage for power class 1.....	153
7.3.4.2	EIS spherical coverage for power class 2.....	153
7.3.4.3	EIS spherical coverage for power class 3.....	154
7.3.4.4	EIS spherical coverage for power class 4.....	154
7.3.4.5	EIS spherical coverage for power class 5.....	155
7.3.4.6	EIS spherical coverage for power class 6.....	155
7.3.4.7	EIS spherical coverage for power class 7.....	155
7.3A	Reference sensitivity for DL CA.....	156
7.3A.1	General.....	156
7.3A.2	Reference sensitivity power level for CA	156
7.3A.2.1	Intra-band contiguous CA	156
7.3A.2.3	Inter-band CA	157
7.3A.3	EIS spherical coverage for DL CA	157
7.3A.3.1	Void.....	157
7.3A.3.2	Void.....	157
7.3A.3.3	EIS spherical coverage for inter-band CA	157
7.3D	Void.....	158
7.4	Maximum input level	158
7.4A	Maximum input level for DL CA	159
7.4A.1	Maximum input level for Intra-band contiguous CA.....	159
7.4A.2	Maximum input level for Intra-band non-contiguous CA	159
7.4A.3	Maximum input level for Inter-band CA	159
7.4D	Void.....	159
7.5	Adjacent channel selectivity.....	159
7.5A	Adjacent channel selectivity for DL CA	161
7.5A.1	Adjacent channel selectivity for Intra-band contiguous CA	161
7.5A.2	Adjacent channel selectivity for Intra-band non-contiguous CA.....	163
7.5A.3	Adjacent channel selectivity for Inter-band CA.....	163
7.5D	Void.....	163
7.6	Blocking characteristics	163
7.6.1	General.....	163
7.6.2	In-band blocking.....	164
7.6.3	Void	165
7.6A	Blocking characteristics for DL CA	165
7.6A.1	General.....	165
7.6A.2	In-band blocking.....	165
7.6A.2.2	In-band blocking for Intra-band non-contiguous CA.....	165
7.6A.2.3	In-band blocking for Inter-band CA.....	166
7.6D	Void.....	166
7.7	Void.....	166
7.8	Void.....	166
7.9	Spurious emissions	166
7.10	Void.....	167

Annex A (normative): Measurement channels.....168

A.1	General	168
A.2	UL reference measurement channels	168
A.2.1	General	168
A.2.2	Void.....	168
A.2.3	Reference measurement channels for TDD.....	169

A.2.3.1	DFT-s-OFDM Pi/2-BPSK	169
A.2.3.2	DFT-s-OFDM QPSK.....	170
A.2.3.3	DFT-s-OFDM 16QAM.....	170
A.2.3.4	DFT-s-OFDM 64QAM.....	171
A.2.3.5	CP-OFDM QPSK	171
A.2.3.6	CP-OFDM 16QAM	172
A.2.3.7	CP-OFDM 64QAM	173
A.3	DL reference measurement channels	174
A.3.1	General	174
A.3.2	Void.....	177
A.3.3	DL reference measurement channels for TDD.....	177
A.3.3.1	General	177
A.3.3.2	FRC for receiver requirements for QPSK	178
A.3.3.3	FRC for receiver requirements for 16QAM.....	181
A.3.3.4	FRC for receiver requirements for 64QAM.....	182
A.3.3.5	FRC for receiver requirements for 256QAM.....	186
A.4	Void.....	190
A.5	OFDMA Channel Noise Generator (OCNG)	190
A.5.1	OCNG Patterns for FDD.....	190
A.5.2	OCNG Patterns for TDD	190
A.5.2.1	OCNG TDD pattern 1: Generic OCNG TDD Pattern for all unused REs	190
Annex B (informative):	Void	191
Annex C (normative):	Downlink physical channels.....	192
C.1	General	192
C.2	Setup.....	192
C.3	Connection	192
C.3.1	Measurement of Receiver Characteristics	192
Annex D (normative):	Characteristics of the interfering signal	193
D.1	General	193
D.2	Interference signals.....	193
Annex E (normative):	Environmental conditions	194
E.1	General	194
E.2	Environmental	194
E.2.1	Temperature	194
E.2.2	Voltage	194
E.2.3	Void.....	195
Annex F (normative):	Transmit modulation.....	196
F.1	Measurement Point.....	196
F.2	Basic Error Vector Magnitude measurement	196
F.3	Basic in-band emissions measurement.....	197
F.4	Modified signal under test.....	197
F.5	Window length	199
F.5.1	Timing offset	199
F.5.2	Window length	199
F.5.3	Window length for normal CP	200
F.5.4	Window length for Extended CP.....	200
F.5.5	Window length for PRACH	200
F.6	Averaged EVM	201
F.7	Spectrum Flatness	202

F.8	Phase offset measurement for DMRS bundling	202
F.8.1	Measurement point	202
F.8.2	Symbols used	203
F.8.3	Modified test signal	203
F.8.4	Phase offset measurement	203
F.9	Reserved	203
F.10	EVM for dual transmit polarizations	203
F.10.1	General	203
F.10.2	MIMO Equalization (UL MIMO transmission)	204
F.10.3	Maximum Ratio combining (Tx diversity transmission)	205
F.10.4	Layer processing	205
Annex G (normative):	Difference of relative phase and power errors	207
G.0	General	207
G.1	Measurement Point	207
G.2	Relative Phase Error Measurement	207
G.2.1	Symbols and subcarriers used	208
G.2.2	CFO (carrier frequency offset) correction	208
G.2.3	Steps of the measurement method	208
Annex H (Normative):	Modified MPR behavior	210
H.1	Indication of modified MPR behavior	210
Annex I (informative):	Void	211
Annex J (normative):	UE coordinate system	212
J.1	Reference coordinate system	212
J.2	Test conditions and angle definitions	213
J.3	DUT positioning guidelines	217
Annex K (informative):	Void	219
Annex L (informative):	Change history	220
History		231

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

In the present document, modal verbs have the following meanings:

- shall** indicates a mandatory requirement to do something
- shall not** indicates an interdiction (prohibition) to do something

The constructions "shall" and "shall not" are confined to the context of normative provisions, and do not appear in Technical Reports.

The constructions "must" and "must not" are not used as substitutes for "shall" and "shall not". Their use is avoided insofar as possible, and they are not used in a normative context except in a direct citation from an external, referenced, non-3GPP document, or so as to maintain continuity of style when extending or modifying the provisions of such a referenced document.

- should** indicates a recommendation to do something
- should not** indicates a recommendation not to do something
- may** indicates permission to do something
- need not** indicates permission not to do something

The construction "may not" is ambiguous and is not used in normative elements. The unambiguous constructions "might not" or "shall not" are used instead, depending upon the meaning intended.

- can** indicates that something is possible
- cannot** indicates that something is impossible

The constructions "can" and "cannot" are not substitutes for "may" and "need not".

- will** indicates that something is certain or expected to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document
- will not** indicates that something is certain or expected not to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document
- might** indicates a likelihood that something will happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

might not indicates a likelihood that something will not happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

In addition:

is (or any other verb in the indicative mood) indicates a statement of fact

is not (or any other negative verb in the indicative mood) indicates a statement of fact

The constructions "is" and "is not" do not indicate requirements.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ETSI TS 138 101-2 V17.15.0 (2024-10)

[https://standards.iteh.ai/catalog/standards/etsi/ce30be43-85a0-421e-9965-487122537c7b/etsi-ts-138-101-2-v17-15-0-2024-](https://standards.iteh.ai/catalog/standards/etsi/ce30be43-85a0-421e-9965-487122537c7b/etsi-ts-138-101-2-v17-15-0-2024-10)

10