

---

**INTERNATIONAL STANDARD**



**2462**

---

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

---

**Sodium chlorate for industrial use — Determination of  
moisture content — Gravimetric method**

First edition — 1973-04-01

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO 2462:1973](https://standards.iteh.ai/catalog/standards/sist/c8ba0c0d-cb2c-402e-87b0-0b5e53597481/iso-2462-1973)

<https://standards.iteh.ai/catalog/standards/sist/c8ba0c0d-cb2c-402e-87b0-0b5e53597481/iso-2462-1973>

---

UDC 661.833.322.5 : 543.71 : 543.21

Ref. No. ISO 2462-1973 (E)

**Descriptors** : sodium chlorate, chemical analysis, determination of content, moisture content, gravimetric analysis.

## FOREWORD

ISO (the International Organization for Standardization) is a worldwide federation of national standards institutes (ISO Member Bodies). The work of developing International Standards is carried out through ISO Technical Committees. Every Member Body interested in a subject for which a Technical Committee has been set up has the right to be represented on that Committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the Technical Committees are circulated to the Member Bodies for approval before their acceptance as International Standards by the ISO Council.

International Standard ISO 2462 was drawn up by Technical Committee ISO/TC 47, *Chemistry*.

**STANDARD PREVIEW**  
**(standards.iteh.ai)**

It was approved in January 1972 by the Member Bodies of the following countries :

[ISO 2462:1973](#)

Austria	<a href="https://standards.iteh.ai/catalog/standards/sist/0b5e5355-324f-4001-cb2c-402e-87b0-0b5e5355-324f/iso-2462-1973">https://standards.iteh.ai/catalog/standards/sist/0b5e5355-324f-4001-cb2c-402e-87b0-0b5e5355-324f/iso-2462-1973</a>	India	South Africa, Rep. of
Belgium		Ireland	Spain
Chile		Korea, Dem.P.Rep. of	Sweden
Czechoslovakia		Netherlands	Switzerland
Egypt, Arab Rep. of		New Zealand	Thailand
France		Poland	United Kingdom
Germany		Portugal	U.S.S.R.
Hungary		Romania	

No Member Body expressed disapproval of the document.

# Sodium chlorate for industrial use – Determination of moisture content – Gravimetric method

## 1 SCOPE

This International Standard specifies a method for the determination of the moisture content of sodium chlorate for industrial use.

## 2 FIELD OF APPLICATION

The method is applicable to products with moisture content greater than 0,02 % (*m/m*). The method is not applicable to the analysis of mixtures based on sodium chlorate, such as herbicides, insecticides, etc.

## 3 PRINCIPLE

Heating a test portion, spread in the form of a thin layer, at 105 °C for 2 h. The loss of mass represents the moisture content of the test portion.

## 4 APPARATUS

Ordinary laboratory apparatus and

**4.1 Weighing bottle**, approximately 50 mm in diameter, with ground glass lid.

**4.2 Electric oven**, capable of being controlled at 105 ± 2 °C. Check this temperature by means of a thermometer placed so that its bulb is close to the weighing bottle used during the test.

NOTE – Ensure that the maximum temperature of the oven used can never exceed 250 °C so as to avoid risk of an explosion in case of failure of the regulator.

## 5 PROCEDURE

### 5.1 Warning

**Sodium chlorate induces combustion. Avoid storage or handling close to a source of heat. Avoid all contact of the salt or its solutions with combustible materials (clothes, wood, straw, rags, fatty substances, etc.) which are likely to catch fire or give rise to an explosive mixture. Wash copiously with water any materials accidentally impregnated with sodium chlorate.**

### 5.2 Test portion

Weigh, to the nearest 0,000 2 g, 5 ± 0,1 g of the test sample.

### 5.3 Determination

Weigh the empty weighing bottle (4.1), to the nearest 0,000 2 g after leaving it for 30 min in the oven (4.2) controlled at 105 ± 2 °C and cooling it in a desiccator.

Spread the test portion in a thin layer in the weighing bottle (4.1) and weigh the whole to the nearest 0,000 2 g.

Place the weighing bottle and its contents, with the cover tilted, in the oven (4.2) controlled at 105 ± 2 °C, and leave it there for 2 h.

Remove the weighing bottle, and place it in the desiccator to cool, then close it and weigh it again to the nearest 0,000 2 g.

## 6 EXPRESSION OF RESULTS

Moisture content is given, as a percentage by mass, by the formula :

$$(m_1 - m_2) \times \frac{100}{m_0}$$

where

$m_0$  is the mass, in grams, of the test portion (5.2);

$m_1$  is the mass, in grams, of the weighing bottle and test portion before heating;

$m_2$  is the mass, in grams, of the weighing bottle and test portion after heating.

## 7 TEST REPORT

The test report shall include the following particulars :

- the reference of the method used;
- the results and the method of expression used;
- any unusual features noted during the determination;
- any operation not included in this International Standard, or regarded as optional.

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

ISO 2462:1973

<https://standards.iteh.ai/catalog/standards/sist/c8ba0c0d-cb2c-402e-87b0-0b5e53597481/iso-2462-1973>

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

This page intentionally left blank

[ISO 2462:1973](#)

<https://standards.iteh.ai/catalog/standards/sist/c8ba0c0d-cb2c-402e-87b0-0b5e53597481/iso-2462-1973>