

---

---

**Road vehicles — Clock extension  
peripheral interface (CXPI) —**

**Part 5:  
Application layer conformance test  
plan**

**iTeh STANDARD PREVIEW**  
*Véhicules routiers — Interface périphérique d'extension d'horloge  
(CXPI) —  
Partie 5: Plan de test de conformité de la couche application*  
(standards.iteh.ai)

ISO 20794-5:2020

<https://standards.iteh.ai/catalog/standards/sist/3bb53d97-63d7-446d-9cc7-857313b51ab0/iso-20794-5-2020>



## iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 20794-5:2020

<https://standards.iteh.ai/catalog/standards/sist/3bb53d97-63d7-446d-9cc7-857313b51ab0/iso-20794-5-2020>



### **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

|  | Page      |
|--|-----------|
| Foreword .....   | v         |
| Introduction .....   | vi        |
| <b>1 Scope .....</b>   | <b>1</b>  |
| <b>2 Normative references .....</b>                                  | <b>1</b>  |
| <b>3 Terms and definitions .....</b>                                 | <b>1</b>  |
| <b>4 Symbols and abbreviated terms .....</b>                         | <b>3</b>  |
| 4.1 Symbols .....  | 3         |
| 4.2 Abbreviated terms .....  | 3         |
| <b>5 Conventions .....</b>   | <b>4</b>  |
| <b>6 General test specification considerations .....</b>             | <b>4</b>  |
| 6.1 General .....  | 4         |
| 6.2 Test conditions .....  | 4         |
| 6.3 IUT requirements .....   | 4         |
| 6.4 CTC definition .....   | 4         |
| 6.5 Test system set-up .....   | 5         |
| 6.6 Configuration of test system and IUT .....                       | 6         |
| 6.6.1 General .....  | 6         |
| 6.6.2 IUT-specific set-up parameters .....                           | 7         |
| 6.6.3 User Specific configurations .....                             | 8         |
| 6.6.4 W/S_Init configurations .....                                  | 8         |
| 6.6.5 W/S_Passive configurations .....                               | 8         |
| 6.6.6 W/S_RdySleep configurations .....                              | 8         |
| 6.6.7 W/S_NotRdySleep configurations .....                           | 8         |
| 6.6.8 A_WSSup configurations .....                                   | 9         |
| 6.6.9 NonW/S configurations .....                                    | 9         |
| 6.6.10 ErrDet configurations .....                                   | 9         |
| 6.6.11 Event configurations .....                                    | 9         |
| 6.6.12 Polling configurations .....                                  | 9         |
| 6.7 SUT initialisation .....   | 10        |
| 6.7.1 General .....  | 10        |
| 6.7.2 Default initialisation .....                                   | 10        |
| 6.7.3 Sleep initialisation .....                                     | 10        |
| 6.7.4 Power-off initialisation .....                                 | 10        |
| 6.7.5 Transmission prohibition initialisation .....                  | 10        |
| 6.7.6 Clock supply of secondary clock master initialisation .....    | 10        |
| <b>7 Application conformance test plan .....</b>                     | <b>10</b> |
| 7.1 General .....  | 10        |
| 7.2 Network management .....   | 10        |
| 7.2.1 General .....  | 10        |
| 7.2.2 State transition definition .....                              | 11        |
| 7.2.3 State transition CTCs .....                                    | 11        |
| 7.2.4 Wake-up request/notification of master node trigger CTCs ..... | 15        |
| 7.2.5 Wake-up request/notification of slave node trigger CTCs .....  | 18        |
| 7.2.6 Sleep request/notification CTCs .....                          | 25        |
| 7.2.7 Network Management multi clock master processing CTCs .....    | 31        |
| 7.3 Fault management .....   | 34        |
| 7.3.1 Error detection/recovery CTCs .....                            | 34        |
| 7.3.2 CXPI network error CTCs .....                                  | 41        |
| 7.3.3 SCT error CTCs .....   | 42        |
| 7.3.4 Error notification between CXPI nodes CTCs .....               | 43        |
| <b>8 Application layer conformance test plan .....</b>               | <b>45</b> |

|                           |  |           |
|---------------------------|--|-----------|
| 8.1                       | General.....   | 45        |
| 8.2                       | Transfer management CTCs.....                                      | 45        |
| 8.2.1                     | General.....   | 45        |
| 8.2.2                     | 7.CTC_10.1 – Master node event-triggered method.....               | 45        |
| 8.2.3                     | 7.CTC_10.2 – Slave node event-triggered method.....                | 46        |
| 8.2.4                     | 7.CTC_10.3 – Master node polling method.....                       | 46        |
| 8.2.5                     | 7.CTC_10.4 – Slave node polling method.....                        | 47        |
| 8.2.6                     | 7.CTC_10.5 – Behaviour of unknown or invalid ReqId reception.....  | 48        |
| 8.2.7                     | 7.CTC_10.6 – Master node sets unused bits in response message..... | 48        |
| 8.2.8                     | 7.CTC_10.7 – Slave node sets unused bits in response message.....  | 49        |
| <b>Bibliography .....</b> |  | <b>51</b> |

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ISO 20794-5:2020

<https://standards.iteh.ai/catalog/standards/sist/3bb53d97-63d7-446d-9cc7-857313b51ab0/iso-20794-5-2020>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 31, *Data communication*.

A list of all parts in the ISO 20794 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

## Introduction

ISO 20794 (all parts) specifies the application (partly), application layer, transport layer, network layer, data link layer, and physical layer requirements of an in-vehicle network called "clock extension peripheral interface (CXPI)".

CXPI is an automotive low-speed single wire network. It is an enabler for reducing vehicle weight and fuel consumption by reducing wire counts to simple devices like switches and sensors.

CXPI serves as and is designed for automotive control applications, for example door control group, light switch, and HVAC (Heating Ventilation and Air Condition) systems.

The CXPI services, protocols, and their key characteristics are specified in different parts according to the OSI layers.

- Application and application layer:
  - application measurement and control data communication to exchange information between applications in different nodes based on message communication;
  - wake-up and sleep functionality;
  - two kinds of communication methods can be selected at system design by each node:
    - i) the event-triggered method, which supports application measurement- and control-based (event-driven) slave node communication; and
    - ii) the polling method, which supports slave node communication based on a periodic master schedule;
  - performs error detection and reports the result to the application;
  - application error management.
- Transport layer and network layer:
  - transforms a message into a single packet;
  - adds protocol control information for diagnostic and node configuration into each packet;
  - adds packet identifier for diagnostic and node configuration into each packet;
  - performs error detection and reports the result to higher OSI layers.
- Data link layer and physical layer:
  - provides long and short data frames;
  - adds a frame identifier into the frame;
  - adds frame information into the frame;
  - adds a cyclic redundancy check into the frame;
  - performs byte-wise arbitration and reports the arbitration result to higher OSI layers;
  - performs frame type detection in reception function;
  - performs error detection and reports the result to higher OSI layers;
  - performs Carrier Sense Multiple Access (CSMA);
  - performs Collision Resolution (CR);

- generates a clock, which is transmitted with each bit to synchronise the connected nodes on the CXPI network;
- supports bit rates up to 20 kbit/s.

To achieve this, it is based on the Open Systems Interconnection (OSI) Basic Reference Model specified in ISO/IEC 7498-1 and ISO/IEC 10731<sup>[2]</sup>, which structures communication systems into seven layers.

Figure 1 illustrates an overview of communication frameworks beyond the scope of this document including related standards:

- vehicle normal communication framework, which is composed of ISO 20794-2 and this document;
- vehicle diagnostic communication framework, which is composed of ISO 14229-1<sup>[3]</sup>, ISO 14229-2<sup>[4]</sup> and ISO 14229-8<sup>[5]</sup>;
- presentation layer standards, e.g. vehicle manufacturer specific or ISO 22901-1 ODX<sup>[10]</sup>;
- lower OSI layers framework, which is composed of ISO 20794-3<sup>[6]</sup>, ISO 20794-4<sup>[7]</sup>, ISO 20794-6<sup>[8]</sup> and ISO 20794-7<sup>[9]</sup>.

ISO 20794 (all parts) and ISO 14229-8<sup>[5]</sup> are based on the conventions specified in the OSI Service Conventions (ISO/IEC 10731<sup>[2]</sup>) as they apply for all layers and the diagnostic services.




Figure 1 — ISO 20794 documents reference according to OSI model

## **iTeh STANDARD PREVIEW** **(standards.iteh.ai)**

ISO 20794-5:2020

<https://standards.iteh.ai/catalog/standards/sist/3bb53d97-63d7-446d-9cc7-857313b51ab0/iso-20794-5-2020>



# Road vehicles — Clock extension peripheral interface (CXPI) —

## Part 5: Application layer conformance test plan

### 1 Scope

This document specifies the conformance test plan for ISO 20794-2:2020 implementations.

It specifies conformance test cases related to:

- concept of operation;
- network management;
- transfer management; and
- error management.

**STANDARD PREVIEW**  
**(standards.iteh.ai)**

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 7498-1, *Information processing systems — Open systems interconnection — Basic reference model*

ISO 20794-2:2020, *Road vehicles — Clock extension peripheral interface (CXPI) — Part 2: Application layer*

### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 20794-2, ISO/IEC 7498-1 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

#### 3.1

##### clock master

node that transmits *clock* (3.4) to the *lower OSI layers* (3.2)

#### 3.2

##### lower OSI layer

OSI layer lower than application layer

#### 3.3

##### master node

node that provides the *schedule* (3.10) master management (include ReqTypeId transmission), the *primary clock* (3.7) and optionally the sleep message transmission management

**3.4**

**clock**

function that synchronises all nodes on the CXPI network

**3.5**

**initiator**

node that transmits messages

**3.6**

**passive**

node that receives messages

**3.7**

**primary clock**

clock (3.4) that is provided by the *master node* (3.3)

**3.8**

**REPEAT**

pseudo code command for an iteration

**3.9**

**REPEAT END**

pseudo code command for ending an iteration

**3.10**

**schedule**

origin of periodic frame transmission

**3.11**

**secondary clock**

clock (3.4) that is provided by one dedicated *slave node* (3.13)

**3.12**

**sequence**

transmission and reception procedure of messages among two or more nodes

**3.13**

**slave node**

node other than *master node* (3.3) connected to the CXPI network

**3.14**

**slave initiator node**

node that is woken up by its own *slave node* (3.13)

**3.15**

**slave passive node**

node that is woken up by another *slave node* (3.13)

**3.16**

**wake-up pulse**

stimulus initiated by a node used for wake-up of other nodes on the CXPI network

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

ISO 20794-5:2020  
<https://standards.iteh.ai/catalog/standards/sist/3bb53d97-63d7-446d-9cc7-857313b51ab0/iso-20794-5-2020>

## 4 Symbols and abbreviated terms

### 4.1 Symbols

|                                  |  |
|----------------------------------|--|
| ---                              | empty cell/undefined                   |
| kbit/s                           | kilobit per second                     |
| $t_{\text{clock\_start\_m}}$     | master node clock start time           |
| $t_{\text{clock\_stop\_m}}$      | master node clock stop time            |
| $t_{\text{sleep\_s}}$            | slave node sleep state transition time |
| $t_{\text{wakeup\_m}}$           | master node wake-up time               |
| $t_{\text{wakeup\_recovery\_s}}$ | slave node wake-up recovery time       |
| $t_{\text{wakeup\_s}}$           | slave node wake-up time                |
| $t_{\text{wakeup\_schedule\_m}}$ | master node wake-up schedule time      |

## iTeh STANDARD PREVIEW

### 4.2 Abbreviated terms (standards.iteh.ai)

|        |                                  |
|--------|----------------------------------|
| ASP    | abstract service primitive       |
| AL     | application layer                |
| APP    | application                      |
| CRC    | cyclic redundancy check          |
| DLC    | data length code                 |
| ECU    | electronic control unit          |
| EMI    | electro-magnetic interference    |
| ErrDet | error detection                  |
| ETS    | enhanced testability service     |
| IUT    | implementation under test        |
| OSI    | open systems interconnection     |
| PDU    | protocol data unit               |
| PID    | protected identifier             |
| PCO    | point of control and observation |
| ReqId  | request identifier               |

|           |                         |
|-----------|-------------------------|
| ReqTypeId | request type identifier |
| SCT       | sequence count          |
| SUT       | system under test       |

## 5 Conventions

This document is based on OSI service conventions as specified in ISO/IEC 10731<sup>[2]</sup> and ISO/IEC 9646-1<sup>[1]</sup> for conformance test system setup.

## 6 General test specification considerations

### 6.1 General

This document covers the conformance test cases (CTC) to verify the requirements described in ISO 20794-2 application layer document.

### 6.2 Test conditions

Tests can be performed at room temperature, if the temperature is in the range of 15° C to 35° C. Also, the tests shall be performed under room EMI (electro-magnetic interference) conditions.

### 6.3 IUT requirements

The occurrence of the error specified in ISO 20794-2:2020, 9.6.8 shall be notified to the application.

The IUT shall be initialised in the test case respectively.

### 6.4 CTC definition

The definition of each test case specifies, whether the IUT is a master or slave node. Each CTC is defined in the structure as defined in [Table 1](#).

**Table 1 — CTC definition example**

| Item                 | Content  |
|----------------------|--|
| <b>CTC # – Title</b> | [OSI layer #].CTC_[number_name]<br>E.g. 8.CTC_1.4 – State machine – Slave node – Sleep permission  |
| <b>Purpose</b>       | This CTC shall verify ...<br>E.g. This CTC verifies the test for the slave node to transit into the sleep state with sleep permission. This CTC is applicable only to an IUT, which supports the wake-up/sleep feature.  |
| <b>Reference</b>     | REQ document, REQ number – REQ name<br>E.g. ISO 20794-2:2020, REQ 8.3 APP – NM – Normal, standby, and sleep states;  |
| <b>Prerequisite</b>  | The test system set-up shall be in accordance with <a href="#">Figure 2</a> .<br>The clock master is implemented in the LT of the test system.   |
| <b>Set-up</b>        | <ul style="list-style-type: none"> <li>— The IUT shall be configured as a slave node.</li> <li>— The IUT shall be configured to default (see <a href="#">6.6</a>) and in addition support W/S_RdySleep configurations (see <a href="#">6.6.6</a>).</li> <li>— The bit rate shall be set to the default value (see <a href="#">6.6</a>).</li> <li>— The SUT shall be initialised to the sleep state (see <a href="#">6.7.3</a>).</li> </ul> |

Table 1 (continued)

| Item                     | Content   |
|--------------------------|---|
| <b>Step</b>              | <ol style="list-style-type: none"> <li>1. A short description of the test step e.g. LT shall transmit the wake-up pulse.</li> <li>2. A short description of the test step e.g. LT shall observe any messages on the CXPI network and shall report to the UT.</li> </ol>   |
| <b>Iteration</b>         | Definition of repetitions of test procedure steps.<br>Example:<br>REPEAT step 1 to step 2, 5 times;<br>...;<br>REPEAT END.  |
| <b>Expected response</b> | Define the expected behaviour of IUT by checking on the CXPI network when the test step is executed. Example:<br>After step 1: the IUT shall receive a wake-up notification pulse, waits $t_{\text{cxpi\_network\_error}}$ time from the wake-up pulse.<br>After step 2: the LT shall report the observation on the CXPI network to the UT. |
| <b>Remark</b>            | E.g. either "---" if no remark or "Observation of $t_{\text{wakeup\_schedule\_m}}$ time and $t_{\text{wakeup\_m}}$ time starts from second rising edge of clock."   |

## 6.5 Test system set-up

The test system set-up follows ISO/IEC 9646-1 and consists of a test system and a system under test (SUT) connected via the physical medium. The test system implements an upper tester (UT) and a lower tester (LT). The test system uses set-up parameters (see [Figure 2](#), key 1) for testing the communication with the IUT.


The UT uses the test control protocol (see [Figure 2](#), key 2) to control the LT.

The point of control and observation (PCO) functionality between the UT of the test system and the UT App test stub in the SUT is provided by direct logical access to the abstract service primitive interface [ASPs (ETs), PCO, see dashed line in [Figure 2](#), key 3] and the associated parameters of the OSI layer as specified in the ISO 20794 series.

The UT App test stub in the SUT (see [Figure 2](#), key 4) supports an equivalent part of the ASP (see [Figure 2](#), key 3) and the associated parameters to control and measure the state(s) of the IUT.

The UT App in the test system, which represents the conformance test controller, manipulates the service primitive interface parameters in the IUT App test stub via the ASPs (ETs) and PCO of the OSI layers to fulfil the purpose of each CTC.

If the IUT is a master node then the LT functions as a slave node. If the IUT is a slave node then the LT functions as a master node. The test system ensures the precision of the bit time and bit synchronisation of the master node as specified in ISO 20794-4:2020, 9.3.7.



- Key**
- 1 set-up parameters (CXPI node's electronic data sheet)
  - 2 test control protocol
  - 3 abstract service primitives (ASPs) based on enhanced testability services (ETS) and points of control and observation (PCO)
  - 4 upper tester application test stub

Figure 2 — Test system set-up

## 6.6 Configuration of test system and IUT

### 6.6.1 General

The test system requires set-up parameters (see [Figure 2](#) key 1), which specify OSI layer properties of the IUT. The IUT-specific data sheet (see [Figure 2](#) key 1) includes set-up parameters, which the test system requires for the conformance test cases.

[Table 2](#) defines the configurations of the test system and the IUT.

**Table 2 — Configuration of test system and IUT**

| Configuration item                        | Configuration of test system and IUT |                 |                      |                          |                     |                |                     |       |         |
|---|--------------------------------------|-----------------|----------------------|--------------------------|---------------------|----------------|---------------------|-------|---------|
|   | W/S<br>_Init                         | W/S<br>_passive | W/S<br>_Rdy<br>Sleep | W/S<br>_Not Rdy<br>Sleep | A_WSSup             | Non<br>W/S     | ErrDet              | Event | Polling |
| Internal condition of wake-up             | 1 <sub>2</sub>                       | 0 <sub>2</sub>  | 1 <sub>2</sub>       | 1 <sub>2</sub>           | ---                 | ---            | ---                 | ---   | ---     |
| Transmission method                       | ---                                  | ---             | ---                  | ---                      | ---                 | ---            | ---                 | event | polling |
| Wake-up/sleep                             | 1 <sub>2</sub>                       | 1 <sub>2</sub>  | 1 <sub>2</sub>       | 1 <sub>2</sub>           | 0 <sub>2</sub>      | ---            | ---                 | ---   | ---     |
| TST_FRM_05_REQ_PID_ERRBIT                 | ---                                  | ---             | ---                  | ---                      | supported<br>by IUT | ---            | supported<br>by IUT | ---   | ---     |
| Condition of sleep permission (sleep_ind) | 1 <sub>2</sub>                       | 1 <sub>2</sub>  | 1 <sub>2</sub>       | 0 <sub>2</sub>           | ---                 | 0 <sub>2</sub> | 0 <sub>2</sub>      | ---   | ---     |

[Table 3](#) specifies test message names which are used by the IUT and the test system in the CTCs. In each CTC description, the message setting is specified in the 'Definition' column. If there is no reference to [Table 3](#), the settings are specified in the CTC.

**Table 3 — Configuration of test messages used by IUT and test system**

| Name                        | Definition   |
|-----------------------------|--|
| TST_MSG_00_REQ_PTYPE        | Test message 00 <sub>16</sub> of master node including a ReqTypeId value (00 <sub>16</sub> ) of A_ReqId.   |
| TST_MSG_01_REQ_PID          | Test message 01 <sub>16</sub> of master or slave node including an A_PID value (01 <sub>16</sub> to 7F <sub>16</sub> ) of A_ReqId.   |
| TST_MSG_02_REQ_PID_SLEEP    | Test message 02 <sub>16</sub> for master node including an A_PID value (1F <sub>16</sub> ) of A_ReqId for diagnostic and node configuration requests or sleep message.   |
| TST_MSG_03_REQ_PID_UNKNOWN  | Test message 03 <sub>16</sub> for master or slave node including a not defined A_PID value of A_ReqId (not defined for reception/transmission by IUT).   |
| TST_MSG_04_REQ_PID_INVALID  | Test message 04 <sub>16</sub> for master or slave node including an A_PID value of A_ReqId (not defined for reception/transmission by IUT with an incorrect parity bit) determined by A_Length = 01 <sub>16</sub> .  |
| TST_MSG_05_REQ_PID_ERRBIT   | Test message 05 <sub>16</sub> of master or slave node including an error bit A_PID value (01 <sub>16</sub> to 7F <sub>16</sub> ) of L_ReqId.<br>The value of this PID can use a supplier-specific ReqId.   |
| TST_MSG_10_RESP_0-12        | Test message 10 <sub>16</sub> for master or slave node including FI field, DATA field and CRC field determined by 00 <sub>16</sub> ≤ A_Length ≤ 0C <sub>16</sub> .   |
| TST_MSG_11_RESP_12          | Test message 11 <sub>16</sub> for master or slave node including FI field, DATA field and CRC field determined by A_Length = 0C <sub>16</sub> .  |
| TST_MSG_14_RESP_LONG_0-255  | Test message 14 <sub>16</sub> of master or slave node including FI field, DATA field and CRC field determined by 00 <sub>16</sub> ≤ A_Length ≤ FF <sub>16</sub> .  |
| TST_MSG_17_RESP_SLEEP_8     | Test message 17 <sub>16</sub> of master node including FI field, fixed byte pattern of DATA field and CRC field fixed byte pattern is (00 <sub>16</sub> , FF <sub>16</sub> , FF <sub>16</sub> , FF <sub>16</sub> , FF <sub>16</sub> , FF <sub>16</sub> , FF <sub>16</sub> , FF <sub>16</sub> ) determined by A_Length = 08 <sub>16</sub> . |
| TST_MSG_18_RESP_ERRBIT_0-12 | Test message 18 <sub>16</sub> of master node including FI field, DATA field with an error bit and CRC field determined by 00 <sub>16</sub> ≤ A_Length ≤ 0C <sub>16</sub> .   |

### 6.6.2 IUT-specific set-up parameters

The set-up parameters include at least the following information.

- The request identifier uses 01<sub>16</sub> to 7F<sub>16</sub> and uses 00<sub>16</sub> in the request protected type identifier field.
- The CXPI node wake-up uses a wake-up trigger based on the parameter wakeup\_ind value 0<sub>2</sub> or 1<sub>2</sub>.