

DRAFT INTERNATIONAL STANDARD

ISO/DIS 20794-6

ISO/TC 22/SC 31

Secretariat: DIN

Voting begins on:
2019-11-13

Voting terminates on:
2020-02-05

Road vehicles — Clock extension peripheral interface (CXPI) —

Part 6:

Transport and network layer conformance test plan

Véhicules routiers — Interface périphérique d'extension d'horloge (CXPI) —

Partie 6: Plan de test de conformité des couches transport et réseau

ICS: 43.040.15

ITeH STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/32bd2adf-a703-4e3e-8656-8e63a6418cf7/iso-dis-20794-6>

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

This document is circulated as received from the committee secretariat.



Reference number
ISO/DIS 20794-6:2019(E)

© ISO 2019

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/32bd2adf-a703-4e3e-8656-8e63a6418cf7/iso-dis-20794-6>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Symbols and abbreviated terms	3
4.1 Symbols.....	3
4.2 Abbreviated terms.....	3
5 Conventions	4
6 General test specification considerations	4
6.1 General	4
6.2 Test conditions.....	4
6.3 IUT requirements.....	4
6.4 CTC definition.....	5
6.5 Test system set-up.....	5
6.6 Configuration of test system and IUT	6
6.7 SUT initialisation.....	9
7 Transport layer conformance test plan	10
7.1 General	10
7.2 4.CTC_1.2 – T_PDU and T_PCI data handling (T_PCItype and T_PCI_DLext)	11
7.3 4.CTC_1.3 – T_PDU and T_PCI data handling (T_PCItype and T_PCI_DLext with short data field)	12
7.4 4.CTC_2.1 – TL Error detection test (T_PCItype).....	13
7.5 4.CTC_2.2 – TL Error detection test (T_PCI_DL)	14
7.6 4.CTC_2.3 – TL Error detection test(T_PCI_DLext)	15
8 Network layer conformance test	16
8.1 General	16
8.2 3.CTC_3.1 – N_PDU specification test (N_NAD)	16
8.3 3.CTC_3.2 – N_PDU specification test (N_SLEEP field)	17
8.4 3.CTC_3.3 – NL error detection (N_As timeout)	18
Bibliography	19

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 22, Road vehicles, Subcommittee SC 31, Data communication.

A list of all parts in the ISO 20794 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

ISO 20794 (all parts) specifies the application (partly), application layer, transport layer, network layer, data link layer, and physical layer requirements of an in-vehicle network called "clock extension peripheral interface (CXPI)". CXPI is an automotive low-speed single-wire network. It is an enabler for reducing vehicle weight and fuel consumption by reducing wire counts to simple devices like switches and sensors.

CXPI serves as and is designed for automotive control applications for example, door control group, light switch, and HVAC (Heating Ventilation and Air Conditioning) systems.

The CXPI services, protocols, and their key characteristics are specified in different parts according to the OSI layers.

- Application and application layer
 - — application measurement and control data communication to exchange information between applications in different nodes based on message communication;
 - — wake-up and sleep functionality;
 - — two kinds of communication methods can be selected at system design by each node:
 - i) i) the event-triggered method, which supports application measurement- and control-based (event-driven) slave node communication, and
 - ii) ii) the polling method, which supports slave node communication based on a periodic master schedule;
 - — performs error detection and reports the result to the application;
 - — application error management;
- Transport layer and network layer
 - — transforms a message into a single packet;
 - — adds protocol control information for diagnostic and node configuration into each packet;
 - — adds packet identifier for diagnostic and node configuration into each packet;
 - — performs error detection and reports the result to higher OSI layers.
- Data link layer and physical layer
 - — provides long and short data frames;
 - — adds a frame identifier into the frame;
 - — adds frame information into the frame;
 - — adds a cyclic redundancy check into the frame;
 - — performs byte-wise arbitration and reports the arbitration result to higher OSI layers;
 - — performs frame type detection in reception function;

ISO/DIS 20794-6:2019(E)

- — performs error detection and reports the result to higher OSI layers.
- — performs Carrier Sense Multiple Access (CSMA);
- — performs Collision Resolution (CR);
- — generates a clock, which is transmitted with each bit to synchronise the connected nodes on the CXPI network;
- — supports bit rates up to 20 kbit/s;

To achieve this, it is based on the Open Systems Interconnection (OSI) Basic Reference Model specified in ISO/IEC 7498-1 and ISO/IEC 10731^[1], which structures communication systems into seven layers.

Figure 1 illustrates an overview of communication frameworks beyond the scope of this document including related standards:

- vehicle normal communication framework, which is composed of this document, and ISO 20794-5;
- vehicle diagnostic communication framework, which is composed of ISO 14229-1, ISO 14229-2^[2], and ISO 14229-8^[4];
- presentation layer standards, e.g. vehicle manufacturer specific or ISO 22901-1 ODX^[6];
- lower OSI layers framework, which is composed of ISO 20794-3, ISO 20794-4, ISO 20794-6, and ISO 20794-7 conformance testing.

ISO 20794 (all parts) and ISO 14229-8^[4] are based on the conventions specified in the OSI Service Conventions (ISO/IEC 10731)^[1] as they apply for all layers and the diagnostic services.




Figure 1 — ISO 20794 document reference according to OSI model

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/32bd2adf-a703-4e3e-8656-8e63a6418cf7/iso-dis-20794-6>

Road vehicles — Clock extension peripheral interface (CXPI) — Part 6: Transport and network layers conformance test plan

1 Scope

This document specifies the transport and network layer conformance test plan, which tests the transportation of diagnostic communication and node configuration data and network layer services using the service interface parameters reported by lower layers and submitted to higher OSI layers.

The transport and network layer conformance test plan contains the following descriptions:

- concept of operation conformance test plan;
- transport layer protocol conformance test plan;
- network layer services conformance test plan; and
- error detection conformance test plan.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 10731:1994 (Ed. 1), *Information technology — Open Systems Interconnection — Basic Reference Model — Conventions for the definition of OSI services*

ISO 20794-2, *Road vehicles – Clock extension peripheral interface (CXPI) — Part 2: Application layer*

ISO 14229-1, *Road vehicles — Unified diagnostic services (UDS) — Part 1: Application layer*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 20794-2, ISO/IEC 7498-1 [1], and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1 lower OSI layers

OSI layers lower than transport layer and network layer

3.2 master node

node that provides the schedule master management (include ReqTypeId transmission), the primary clock, and optionally the sleep message transmission management

3.3 slave node

node other than master node connected to the CXPI network

3.4 protocol data unit

data byte array that is contain data and the other information to establish communication

3.5 protocol control information

information contains frame type and data length

3.6 protocol control information type

information that identifies the frame type

3.7 single frame data length

information that identifies the data length

3.8 single frame data length extension

information that identifies data length beyond single frame data length

3.9 node address

address information that identifies target node

3.10 result

transmission or reception status to report to upper OSI layers