

SLOVENSKI STANDARD kSIST-TS FprCEN/TS 17782:2021

01-december-2021

[Not translated]

Fertilizing products - Determination of the stability of fertilizing products containing micronutrient chelates at different pHs

Düngeprodukte - Bestimmung der Stabilität von Spurennährstoffchelaten bei verschiedenen pH-Werten

iTeh STANDARD PREVIEW (standards.iteh.ai)

Ta slovenski standard je istoveten z. FprCFprCEN/TS217782 https://standards.iteh.ai/catalog/standards/sist/beca06b4-160f-48ed

https://standards.iteh.ai/catalog/standards/sist/beca06b4-160f-48ec-a38fb04ffa8062e3/ksist-ts-fprcen-ts-17782-2021

<u>ICS:</u>

65.080 Gnojila

Fertilizers

en,fr,de

kSIST-TS FprCEN/TS 17782:2021

2003-01. Slovenski inštitut za standardizacijo. Razmnoževanje celote ali delov tega standarda ni dovoljeno.

kSIST-TS FprCEN/TS 17782:2021

iTeh STANDARD PREVIEW (standards.iteh.ai)

kSIST-TS FprCEN/TS 17782:2021 https://standards.iteh.ai/catalog/standards/sist/beca06b4-160f-48ec-a38fb04ffa8062e3/ksist-ts-fprcen-ts-17782-2021

kSIST-TS FprCEN/TS 17782:2021

TECHNICAL SPECIFICATION SPÉCIFICATION TECHNIQUE TECHNISCHE SPEZIFIKATION

FINAL DRAFT FprCEN/TS 17782

October 2021

ICS 65.080

English Version

Fertilizing products - Determination of the stability of fertilizing products containing micronutrient chelates at different pHs

Düngeprodukte - Bestimmung der Stabilität von Spurennährstoffchelaten in Düngeprodukten bei verschiedenen pH Werten

This draft Technical Specification is submitted to CEN members for Vote. It has been drawn up by the Technical Committee CEN/TC 260.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom. (standards.iteh.ai)

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation TS ForCEN/TS 17782:2021

Warning : This document is not a Technical Specification. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a Technical Specification.⁷⁸²⁻²⁰²¹



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

kSIST-TS FprCEN/TS 17782:2021

FprCEN/TS 17782:2021 (E)

Contents

	ean foreword		
Introduction			
1	Scope	5	
2	Normative references	5	
3	Terms and definitions	5	
4	Principle	5	
5	Interferences	5	
6	Reagents	5	
7	Apparatus	7	
8	Sampling and sample preparation	7	
9	Procedure	3	
9.1	Preparation of the test sample solution	3	
9.2	Preparation of fertilizer solution in reference tap water	3	
9.3	Preparation of fertilizer solution in reference tap water)	
9.4	Metal chelated content quantification artis.iteli.ar))	
10	Calculation and expression of results	9	
10.1	Mass concentration of the micronutrient (i) in the reference tap water at a specific		
	pHhttps://standarda.itab.ai/ataba/standarda/siat/haca06b4.160f.48ac.a38f		
10.2	Stability of fertilizing products containing micronutrient chelates at a specific pH		
11	Test report10)	
Biblio	graphy11	L	

European foreword

This document (FprCEN/TS 17782:2021) has been prepared by Technical Committee CEN/TC 260 "Fertilizers and liming materials", the secretariat of which is held by DIN.

This document is currently submitted to the Vote on TS.

This document has been prepared under a Standardization Request given to CEN by the European Commission and the European Free Trade Association.

iTeh STANDARD PREVIEW (standards.iteh.ai)

kSIST-TS FprCEN/TS 17782:2021 https://standards.iteh.ai/catalog/standards/sist/beca06b4-160f-48ec-a38fb04ffa8062e3/ksist-ts-fprcen-ts-17782-2021

Introduction

Micronutrients are considered to be, in plant nutrition, a number of elements known to be needed in small amounts for proper plant growth and development. The most common micronutrient metals are Iron (Fe), Manganese (Mn), Cobalt (Co), Copper (Cu) and Zinc (Zn).

An EU fertilizing product consists solely of component materials complying with the requirements for one or more of the component material categories (CMCs). CMC 1 corresponds with the virgin material substances and mixtures.

If a micronutrient fertilizing product contains a substance, or one of the substances in the mixture, which is intended to enhance the long term availability to plants of micronutrients in the EU fertilizing product, that substance is either a chelating agent or a complexing agent. The EU fertilizing products containing chelates remain stable for at least three days in a solution having any pH within the range declared as guaranteeing acceptable stability. Metal chelates can be used in agriculture directly to soils, in nutrient solution in fertirigation or soilless culture and in solution for foliar application. Tap water is a good model for interaction with chelates since it contains calcium and magnesium that may react chemically with the metal chelates. Composition described for CIPAC (Collaborative International Pesticides Analytical Council) standard tap water D is a good representative of a tap water of medium hardness and will be used in this standard to determine the stability of micronutrient chelates at any specific pHs, in a reference tap water for three days.

This document defines a test method to check the chelate stability in solution, using as a model the interaction in a reference tap water similar to the CIPAC D.

(standards.iteh.ai)

kSIST-TS FprCEN/TS 17782:2021 https://standards.iteh.ai/catalog/standards/sist/beca06b4-160f-48ec-a38fb04ffa8062e3/ksist-ts-fprcen-ts-17782-2021

1 Scope

This document specifies a method for the determination of the soluble metal that remains in solution at different pHs after the application of a solution of the fertilizer substance containing micronutrient chelates in a tap water solution used as a reference.

The method applies to fertilizing products containing chelated micronutrients.

2 Normative references

The following documents are referred in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 12944-1, Fertilizers and liming materials and soil improvers - Vocabulary - Part 1: General terms

EN 12944-2, Fertilizers and liming materials and soil improvers - Vocabulary - Part 2: Terms relating to fertilizers

EN 16963, Fertilizers - Determination of boron, cobalt, copper, iron, manganese, molybdenum and zinc using ICP-AES

EN 16965, Fertilizers - Determination of cobalt, copper, iron, manganese and zinc using flame atomic absorption spectrometry (FAAS)

EN ISO 3696, Water for analytical laboratory use Specification and test methods (ISO 3696)

FprCEN/TS 17786-1, Inorganic micronutrient fertilizers-Determination of the chelated micronutrient content and the chelated fraction of micronutrients Freatment with a cation exchange resin b04ffa8062e3/ksist-ts-fprcen-ts-17782-2021

FprCEN/TS 17786-2, Inorganic micronutrient fertilizers - Determination of the chelated micronutrient content and the chelated fraction of micronutrients - Determination of EDTA, DTPA, HEEDTA, IDHA or EDDS

3 Terms and definitions

For the purposes of this document, the terms and definitions given in EN 12944-1 and EN 12944-2 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at <u>https://www.iso.org/obp</u>

— IEC Electropedia: available at <u>https://www.electropedia.org/</u>

3.1

ChSt

stability of the metal chelate

micronutrient present in a fertilizer product that is soluble in the reference tap water after three days of interaction at a specific pH, divided by its metal chelated content

Note 1 to entry: ChSt is expressed as a percentage.

4 Principle

The sample is dissolved in water and then let to interact for three days in a reference tap water at a specific pH. After filtration, the amount of each metal remaining in solution, determined as in EN 16963 or EN 16965, are compared with the chelated metal extracted by FprCEN/TS 17786-1 or FprCEN/TS 17786-2.

5 Interferences

Any substance (chelating or complexing agent) combining with a micronutrient to form a stable compound at the specific working pH may account for a certain degree of ChSt. This is the case for many complexing agents, e.g. lignosulfonates, heptagluconates and for chelating agents other than those declared for the fertilizer substance.

6 Reagents

All reagents shall be of recognized analytical grade.

6.1 Water

All water used shall conform to EN ISO 3696 and be degassed.

6.2 Potassium hydroxide solution, substance concentration *c*(KOH) = 1,0 mol/l.

Carefully dissolve 28,05 g of KOH in water (6.1) in a 500 ml volumetric flask and make up the volume.

The incorporation of CO_2 from the atmosphere should be carefully avoided.

6.3 Potassium hydroxide solution, *c*(KOH) = 0,1 mol/l <u>kSIST-TS FprCEN/TS 17782:2021</u>

Dilute 50 ml of the potasitium hydroxide solution (6.2) in water (6.1) in a 500 ml volumetric flask and make up to volume.

6.4 Nitric acid solution, *c*(HNO₃) = 0,1 mol/l

Carefully dilute 6,9 ml of nitric acid (65 % HNO₃, ρ = 1,40 g/ml) in water (6.1) in a 1 000 ml volumetric flask and make up to volume.

6.5 Nitric acid solution, $c(HNO_3) = 0.01 \text{ mol/l}$

Dilute 50 ml of the nitric acid solution (6.4) in water (6.1) in a 500 ml volumetric flask and make up to volume.

6.6 Stock solutions for buffered reference tap water preparation.

6.6.1 Solution A, *c*(CaCl₂) = 0,054 8 mol/l.

Dissolve 4,028 g of $CaCl_2 \cdot 2H_2O$ in water (6.1) in a beaker, transfer quantitatively to a 500 ml volumetric flask and make up to volume.

6.6.2 Solution B, *c*(MgSO₄) = 0,013 7 mol/l.

Dissolve 1,668 g of $MgSO_4$ ·7H₂O in water (6.1) in a beaker, transfer quantitatively to a 500 ml volumetric flask and make up to volume.

6.6.3 Solution C, c(NaAc) = 0,010 mol/l + c(HEPES) = 0,010 mol/l + c(MES) = 0,010 mol/l + c(AMPSO) = 0,010 mol/l + c(CAPS) = 0,010 mol/l + c(KOH) = 0,010 mol/l.

Dissolve 0,082 g of NaAc (sodium acetate, CAS 127-09-3), 0,238 g of HEPES (4-(2-Hydroxyethyl)piperazine-1-ethanesulfonic acid, CAS 7365-45-9), 0,195 g of MES (2-(N-morpholino)ethanesulfonic acid, CAS 4432-31-9), 0,227 g of AMPSO (N-(1,1-Dimethyl-2-hydroxyethyl)-3-amino-2-hydroxypropanesulfonic acid, CAS 68399-79-1) and 0,221 g of CAPS (3-(Cyclohexylamine)-1-propanesulfonic acid, CAS 1135-40-6) in water (6.1) in a beaker, add 10,0 ml of potassium hydroxide solution (6.2) and transfer quantitatively to a 100 ml volumetric flask and make up to volume.

7 Apparatus

All glassware, filters, and equipment parts coming in contact with samples and solutions, shall be appropriate for micronutrient analysis, be very clean and free from contamination.

Usual laboratory equipment and, in particular, the following:

- 7.1 Graduated flasks, capacity 1 000 ml, 500 ml, 250 ml and 100 ml volumetric flasks.
- 7.2 Shaker, horizontal eccentric shaker.

7.3 Thermostatic bath or chamber

Incubator or thermostatic bath able to maintain 25 ± 1°CREVIEW

7.4 Shaking flasks (standards.iteh.ai)

Polyethylene flasks each having a capacity of 50 ml and a stopper.

7.5 pH-meter https://standards.iteh.ai/catalog/standards/sist/beca06b4-160f-48ec-a38fb04ffa8062e3/ksist-ts-fprcen-ts-17782-2021

pH-meter, equipped with a glass electrode; the system shall be calibrated with pH 7 and pH 10 calibration buffers.

7.6 Membrane filter

Micromembrane filters resistant to aqueous solutions, with porosity of 0,45 μ m.

7.7 Filter paper, ash free and of recognized and tested quality.

8 Sampling and sample preparation

Sampling is not part of the method specified in this document. Recommended sampling methods are given in EN 1482-1.

For the size reduction of samples with a high amount of chelating agent, it is not recommended to use a high-speed laboratory mill. It is more convenient to grind the sample in a mortar to a particle size less than 1 mm.

9 Procedure

9.1 Preparation of the test sample solution

Test samples can have one micronutrient chelated. They can be straight inorganic micronutrient fertilizers, inorganic macronutrients containing one chelated micronutrient or organo-mineral fertilizers containing one chelated micronutrient. Since the range of concentrations is very large, preparation of sample solutions should be done considering the soluble micronutrient content.

Test samples can also have several micronutrient chelated. They can be compound inorganic micronutrient fertilizers, inorganic macronutrients containing several chelated micronutrient or organo-mineral fertilizers containing several chelated micronutrients. Sample solutions should be done considering the sum of all the soluble micronutrient content.

Weigh an amount of sample according to Table 1, depending on the sum of the declared content of soluble metal micronutrients Fe, Mn, Cu, Zn and Co to within 1 mg, into a 500 ml Erlenmeyer flask. Add 200 ml of water (6.1). Place the flask in the shaker (7.2) and shake in the dark for 60 min. Filter the extract with filter paper (7.7), if necessary, into a 250 ml volumetric flask and make up to volume with water (6.1).

	Mass of sample AND ^m ARD andards.it	Volume of the extract PREV _e IEW eh ai)	Aliquot to add to 100 ml reference tap water V
[%] <u>ks</u>	IST-TS F [B] EN/TS 17	<u>7782:2021</u> [ml]	/ _a [ml]
	ai/catalog/standards/sist 062e3/ksist-ts-fprcen-1	/beca06b4-260f-48ec-a38 s-17782-2021	20
2 to ≤ 10	5	250	10
> 10	1	250	20

Table 1 — Sample mass and volume

9.2 Preparation of fertilizer solution in reference tap water

Add approximately 50 ml of water (6.1) in a 100 ml beaker.

Add, following this sequence and stirring after each addition: 5,00 ml solution A (6.6.1), 5,00 ml solution B (6.6.2) and 1,00 ml solution C (6.6.3). Adjust to the desired pH (7.5), to the nearest 0,1 unit with the aid of potassium hydroxide (6.3) and/or nitric acid solutions (6.5). Then add an aliquot of the test sample solution (9.1) as indicated in Table 1.

Stir vigorously. Adjust the pH again to the desired value with the aid of potassium hydroxide (6.3) and/or nitric acid solutions (6.5). Make up to volume (100 ml) in a volumetric flask with water (6.1).

Repeat the same procedure with the same components and quantities but adjusting the solution pH to all the desired pHs.

Fill polyethylene shaking flasks (7.4) with these solutions and keep them stand in the dark at 25 °C in the incubator (7.3) for three days. After this time, filter an aliquot of each solution using 0,45 μ m membrane filters (7.6).