



SLOVENSKI STANDARD
SIST-TS CEN/TS 17790:2023

01-februar-2023

Organsko-mineralna gnojila - Določanje vsebnosti kelatiranih mikrohranil in deleža kelatiranih mikrohranil z obdelavo s kationsko izmenjalno smolo

Organo-mineral fertilizers - Determination of the chelated micronutrient content and the chelated fraction of micronutrients by treatment with a cation exchange resin

Organisch-mineralische Düngemittel - Bestimmung des Gehalts an chelatisierten Spurennährstoffen und des chelatisierten Anteils an Spurennährstoffen durch Behandlung mit einem Kationenaustauscherharz

Engrais organo-minéraux - Détermination de la teneur en oligo-éléments chélatés et de la fraction chélatée d'oligo-éléments par traitement avec une résine échangeuse de cations

Ta slovenski standard je istoveten z: CEN/TS 17790:2022

ICS:

65.080 Gnojila Fertilizers

SIST-TS CEN/TS 17790:2023 en,fr,de

TECHNICAL SPECIFICATION
SPÉCIFICATION TECHNIQUE
TECHNISCHE SPEZIFIKATION

CEN/TS 17790

April 2022

ICS 65.080

English Version

**Organo-mineral fertilizers - Determination of the chelated
micronutrient content and the chelated fraction of
micronutrients by treatment with a cation exchange resin**

Engrais organo-minéraux - Détermination de la teneur
en oligo-éléments chélatés et de la fraction chélatée
d'oligo-éléments par traitement avec une résine
échangeuse de cations

Organisch-mineralische Düngemittel - Bestimmung des
Gehalts an chelatisierten Spurennährstoffen und des
chelatisierten Anteils an Spurennährstoffen durch
Behandlung mit einem Kationenaustauscherharz

This Technical Specification (CEN/TS) was approved by CEN on 21 February 2022 for provisional application.

The period of validity of this CEN/TS is limited initially to three years. After two years the members of CEN will be requested to submit their comments, particularly on the question whether the CEN/TS can be converted into a European Standard.

CEN members are required to announce the existence of this CEN/TS in the same way as for an EN and to make the CEN/TS available promptly at national level in an appropriate form. It is permissible to keep conflicting national standards in force (in parallel to the CEN/TS) until the final decision about the possible conversion of the CEN/TS into an EN is reached.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents	Page
European foreword	3
Introduction	4
1 Scope	5
2 Normative references	5
3 Terms and definitions	5
4 Principle	6
5 Interferences	6
6 Reagents	6
7 Apparatus	8
8 Sampling and sample preparation	8
9 Procedure	8
9.1 Extraction of the sample	8
9.2 pH adjustment	9
9.3 Ion exchange separation	9
9.4 Spectrometric determination	10
9.5 Water soluble micronutrient content determination	10
10 Expression of results	10
10.1 Chelated micronutrient content in the fertilizer	10
10.2 Chelated fraction of a micronutrient in the fertilizer	11
11 Test report	11
Annex A (informative) Complete names of chelating agents	12
Bibliography	13

European foreword

This document (CEN/TS 17790:2022) has been prepared by Technical Committee CEN/TC 260 “Fertilizers and liming materials”, the secretariat of which is held by DIN.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a Standardization Request given to CEN by the European Commission and the European Free Trade Association.

Any feedback and questions on this document should be directed to the users’ national standards body. A complete listing of these bodies can be found on the CEN website.

According to the CEN/CENELEC Internal Regulations, the national standards organisations of the following countries are bound to announce this Technical Specification: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST-TS CEN/TS 17790:2023](https://standards.iteh.ai/catalog/standards/sist/72ad145c-f41a-4454-b370-f59f7458b56a/sist-ts-cen-ts-17790-2023)

<https://standards.iteh.ai/catalog/standards/sist/72ad145c-f41a-4454-b370-f59f7458b56a/sist-ts-cen-ts-17790-2023>

CEN/TS 17790:2022 (E)**Introduction**

Micronutrients are considered to be, in plant nutrition, a number of elements known to be needed in small amounts for proper plant growth and development. The most common are Iron (Fe), Manganese (Mn), Molybdenum (Mo), Copper (Cu), Zinc (Zn) and Boron (B).

If an organo-mineral fertilizer contains a substance, or one of the substances in the mixture, which is intended to enhance the long-term availability to plants of micronutrients in the EU fertilizing product, that substance is either a chelating agent or a complexing agent.

The chelating agents are divided into two groups¹:

- Group 1: EDTA, DTPA, HEEDTA, IDHA and [S,S]-EDDS;
- Group 2: Chelating agents present in UVCB (unknown or variable composition, complex reaction products and biological materials) chelates including [o,o] EDDHA, [o,p] EDDHA, [o,o] EDDHMA, HBED and EDDHSA.

This document defines the test method to be used in order to measure the compliance with the chelated fraction of a micronutrient in product function category (PFC) 1(B) (classified according to Regulation (EU) 2019/1009 [9]) for organo-mineral fertilizers containing one or more chelating agents of Group 2.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST-TS CEN/TS 17790:2023](https://standards.iteh.ai/catalog/standards/sist/72ad145c-f41a-4454-b370-f59f7458b56a/sist-ts-cen-ts-17790-2023)

<https://standards.iteh.ai/catalog/standards/sist/72ad145c-f41a-4454-b370-f59f7458b56a/sist-ts-cen-ts-17790-2023>

¹ Abbreviated terms are described in Annex A.

1 Scope

This document specifies a method for the determination of the chelated micronutrient content and the chelated fraction of a micronutrient, in organo-mineral fertilizers, having an organic matrix based on vegetal residues (cocoa shells, grape residue, soybean residue, etc), algae extract, and animal meal (feather, bones, blood, etc) and containing UVCB, EDDHA, EDDHMA, HBED, EDDHSA micronutrients by the treatment with a cation exchange resin.

The limit of determination of the chelated micronutrient content highly depends on the specific electrical conductivity of the sample, on the amount of nutrient present, and varies between 0,005 % in simple matrices with high amounts of micronutrient, and 0,5 % in more complex cases (see 9.1).

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 12944-1, *Fertilizers and liming materials — Vocabulary — Part 1: General terms*

EN 12944-2, *Fertilizers and liming materials — Vocabulary — Part 2: Terms relating to fertilizers*

EN 16962, *Fertilizers — Extraction of water soluble micro-nutrients in fertilizers and removal of organic compounds from fertilizer extracts*

EN 16963, *Fertilizers — Determination of boron, cobalt, copper, iron, manganese, molybdenum and zinc using ICP-AES*

EN 16965, *Fertilizers — Determination of cobalt, copper, iron, manganese and zinc using flame atomic absorption spectrometry (FAAS)*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in EN 12944-1 and EN 12944-2 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1

chelated fraction of a micronutrient

ratio of chelated micronutrient content compared to the total water-soluble micronutrient content

Note 1 to entry: The chelated fraction is expressed as a percentage.

CEN/TS 17790:2022 (E)

4 Principle

The sample is extracted with water and the extract adjusted to a neutral pH. The chelated forms of an element thus having a negative and/or neutral charge are not retained by an ion exchange resin of the strong sulfonated cationic type, and are separated from the non-chelated forms, having a cationic nature. The chelated forms are collected and their content determined by spectrometry, as well as the water-soluble content.

5 Interferences

Any substance combining with a micronutrient to form a stable, negative or uncharged compound (chelate or complex) at neutral pH, will prevent the retention by the resin, and account for a certain degree of chelation. This is the case for many complexing agents, e.g. amino acids, citrate, and for chelating agents other than ethylenediaminetetraacetic acid (EDTA), hydroxyethylethylenediaminetetraacetic acid (HEEDTA), diethylenetriaminepentaacetic acid (DTPA), ethylenediamine-di-(o-hydroxyphenyl)acetic acid ([o,o] EDDHA), ethylenediamine-N,N'-di[(2-hydroxy-5-sulfophenyl)acetic acid] (EDDHSA) and ethylenediamine-di-(o-hydroxy-p-methylphenyl)acetic acid ([o,o] EDDHMA).

In order to determine the presence of the statutory chelating agents in the sample, EN 13368-1 [4] and EN 13368-2 [5] should be applied.

In some cases, especially where complex fertilizer matrices with high amounts of phosphate are handled, or where micronutrients with a low chelated fraction are present, slow precipitation reactions can occur during the contact with the resin, causing equilibrium shifts, adsorption, decreasing the exchange capacity and leading to inaccurate and imprecise results. It is advised to proceed as soon as possible with all steps. Highly unstable solutions cannot be considered.

6 Reagents

All reagents shall be of recognized analytical grade.

6.1 Water

All water used should conform to EN ISO 3696 and be degassed.

6.2 Sulfonated cationic exchange resin

Polystyrene divinylbenzene (PS-DVB) copolymer, slightly crosslinked (mass fraction of DVB less than or equal to 8 %), in sodic or protonic form, free from Co, Cu, Fe, Mn, and Zn².

6.2.1 Preparation and determination of exchange capacity

Protonate the resin prior to use, transform to the sodic form, to eliminate any contamination and measure the cationic exchange capacity (CEC) of the sodic resin in wet form as follows:

Transfer 50 g of resin to a 500 ml beaker and add 250 ml of hydrochloric acid solution (6.4).

Place on a magnetic stirrer. After 1 h of moderate stirring, the suspension is transferred onto the sieve (6.1). The resin is recovered and transferred back to the beaker. The acidification and separation operations are repeated as described. At the end of the second operation, the protonated resin present on the sieve is washed thoroughly with water until the rinsing water is free from chloride when tested with silver nitrate.

² Dowex 50 x 4-400, Amberlite IR 120 or equivalent are examples of suitable products available commercially. This information is given for the convenience of users of this document and does not constitute an endorsement by CEN of these products.

Transfer the wet protonated resin into a 500 ml beaker and add 250 ml of sodium chloride solution (6.5). While stirring on a magnetic stirrer and using a pH meter, titrate the resin using the sodium hydroxide solution (6.6) until a stable pH of 7,0 is obtained.

Transfer quantitatively the resin which is now in sodic form onto the sieve (7.1). Rinse thoroughly with water until the rinsing water is free from chloride (silver nitrate test). Once rinsing is complete, allow the resin to drain. Weigh the drained wet resin to within 0,01 g. The wet sodic resin may be stored in a stoppered opaque flask at ambient temperature for 2 years.

The cationic exchange capacity of the resin is given by the following Formula (1):

$$Z = 2 \times \frac{V_0}{m} \quad (1)$$

where

Z is the cationic exchange capacity (CEC), in mmol/g of wet resin;

V_0 is the required volume of NaOH (6.6), needed for obtaining a stable pH 7, in ml;

m is the mass of the drained wet resin, in g.

6.3 Hydrochloric acid 1 + 1, substance concentration $c(\text{HCl}) \approx 6 \text{ mol/l}$

Hydrochloric acid, diluted 1 + 1 with water.

6.4 Hydrochloric acid solution, $c(\text{HCl}) = 1 \text{ mol/l}$

Dilute 165 ml of hydrochloric acid 1:1 (6.3) to 1 000 ml.

6.5 Sodium chloride solution, $c(\text{NaCl}) = 1 \text{ mol/l}$

Dissolve 58,4 g of NaCl in water and dilute to 1 000 ml.

6.6 Sodium hydroxide solution, $c(\text{NaOH}) = 2 \text{ mol/l}$

Carefully dissolve 80,0 g of NaOH in water and dilute to 1 000 ml.

6.7 Sodium hydroxide solution, $c(\text{NaOH}) = 0,1 \text{ mol/l}$

Dilute 25 ml of the sodium hydroxide solution (6.6) to 500 ml.

6.8 Nitric acid solution, $c(\text{HNO}_3) = 0,1 \text{ mol/l}$

Carefully dilute 6,9 ml of nitric acid (65 % HNO_3 , $\rho = 1,40 \text{ g/ml}$) to 1 000 ml.

6.9 Sodium hydroxide solution, $c(\text{NaOH}) = 0,01 \text{ mol/l}$

Dilute 50 ml of the sodium hydroxide solution (6.7) to 500 ml.

6.10 Nitric acid solution, $c(\text{HNO}_3) = 0,01 \text{ mol/l}$

Dilute 50 ml of the nitric acid solution (6.8) to 500 ml.

CEN/TS 17790:2022 (E)**7 Apparatus**

All glassware, filters, and equipment parts coming in contact with samples and solutions, should be appropriate for micronutrient analysis, be very clean and free from contamination, especially by the element Fe.

Usual laboratory equipment and in particular the following:

7.1 Sieve

Sieve having a plastic body and a nylon mesh of aperture size less than the minimum diameter of the resin particles. The mass of the dry sieve shall be determined to within 0,01 g.

7.2 Tumbling shaker

Tumbling or rotary shaker operating at a rotational speed between 30 min⁻¹ and 40 min⁻¹, at a temperature of 18 °C to 22 °C.

7.3 Conductivity meter

Equipped with a conductivity cell and a temperature controller. The cell shall be rinsed and dried before immersion, and calibrated with a 0,01 mol/l potassium chloride solution, having a specific conductivity at 20 °C of 1,28 mS/cm.

7.4 Shaking flasks

Polyethylene flasks each having a capacity of 50 ml and a stopper.

7.5 Membrane filter

Micromembrane filters resistant to aqueous solutions, with porosity of 0,45 µm.

7.6 pH-meter

pH-meter, equipped with a glass electrode; the system shall be calibrated with pH 7 and pH 10 calibration buffers.

7.7 Graduated flasks, capacity 500 ml, 250 ml and 100 ml volumetric flasks.

8 Sampling and sample preparation

Sampling and sample preparation are not part of the method specified in this document. Recommended sampling methods are given in EN 1482-1 and, for sample preparation, in EN 1482-2.

For the size reduction of samples with a high amount of chelating agents, it is not recommended to use a high speed laboratory mill. It is more convenient to grind the sample to a particle size less than 1 mm with a mortar.

9 Procedure**9.1 Extraction of the sample**

Weigh an amount of sample, depending on the declared content of water-soluble micronutrient, to within 1 mg, into a volumetric flask of 250 ml or 500 ml, according to Table 1: