



SLOVENSKI STANDARD oSIST prEN 16603-20:2021

01-november-2021

Nadomešča:
SIST EN 16603-20:2020

Vesoljska tehnika - Električna in elektronska

Space engineering - Electrical and electronic

Raumfahrttechnik - Elektrik und Elektronik

Ingénierie spatiale - Électrique et électronique

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: prEN 16603-20

<https://standards.iteh.ai/catalog/standards/sist/0a1fd51b-e077-4a4e-997b-24a2d903bc8f/sist-pr-en-16603-20-2021>

ICS:

49.060	Letalska in vesoljska električna oprema in sistemi	Aerospace electric equipment and systems
49.140	Vesoljski sistemi in operacije	Space systems and operations

oSIST prEN 16603-20:2021

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[oSIST prEN 16603-20:2021](#)

<https://standards.iteh.ai/catalog/standards/sist/0a1fd51b-e077-4a4e-997b-24a2d903be8f/osist-pren-16603-20-2021>

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

DRAFT
prEN 16603-20

October 2021

ICS 49.140

Will supersede EN 16603-20:2020

English version

Space engineering - Electrical and electronic

Ingénierie spatiale - Électrique et électronique

Raumfahrttechnik - Elektrik und Elektronik

This draft European Standard is submitted to CEN members for enquiry. It has been drawn up by the Technical Committee CEN/CLC/JTC 5.


If this draft becomes a European Standard, CEN and CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

This draft European Standard was established by CEN and CENELEC in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN and CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN and CENELEC members are the national standards bodies and national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation. Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Warning : This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.



CEN-CENELEC Management Centre:
Rue de la Science 23, B-1040 Brussels

Table of contents

European Foreword	6
1 Scope	7
2 Normative references	8
3 Terms, definitions and abbreviated terms	9
3.1 Terms from other standards	9
3.2 Terms specific to the present standard	9
3.3 Abbreviated terms	16
3.4 Nomenclature	18
4 General requirements	19
4.1 Interface requirements	19
4.1.1 Overview	19
4.1.2 Signals interfaces	19
4.1.3 Commands	19
4.1.4 Telemetry	21
4.2 Design	21
4.2.1 Failure containment and redundancy	21
4.2.2 Data processing	30
4.2.3 Electrical connectors	31
4.2.4 Testing	32
4.2.5 Mechanical: Wired electrical connections	33
4.2.6 Miscellaneous	33
4.3 Verification	34
4.3.1 Provisions	34
4.3.2 Documentation	34
5 Electrical power	35
5.1 Functional description	35
5.2 Power subsystem and budgets	35
5.2.1 General	35
5.2.2 Provisions	35

5.3	Failure containment and redundancy.....	36
5.4	Electrical power interfaces.....	37
5.5	Power generation	38
5.5.1	Solar cell, coverglass, SCA and PVA qualification	38
5.5.2	Solar array specification and design	38
5.5.3	Solar array power computation	40
5.5.4	Solar array drive mechanisms.....	43
5.6	Electrochemical Energy Storage	43
5.6.1	Applicability.....	43
5.6.2	Batteries	43
5.6.3	Battery cell.....	45
5.6.4	Battery use and storage.....	46
5.6.5	Battery safety.....	46
5.7	Power conditioning and control.....	47
5.7.1	Applicability.....	47
5.7.2	Spacecraft bus.....	47
5.7.3	Battery Charge and Discharge Management	51
5.7.4	Bus under-voltage or over-voltage.....	52
5.7.5	Power converters and regulators	53
5.7.6	Payload interaction.....	54
5.8	Power distribution and protection.....	55
5.8.1	General.....	55
5.8.2	Harness	58
5.9	Safety.....	59
5.10	High voltage engineering.....	59
5.11	Verification	60
5.11.1	Provisions.....	60
5.11.2	<<deleted>>	60
6	Electromagnetic compatibility (EMC).....	61
6.1	Overview	61
6.2	Policy	61
6.2.1	Overall EMC programme	61
6.2.2	EMC control plan	61
6.2.3	Electromagnetic compatibility advisory board (EMCAB).....	62
6.3	System level.....	62
6.3.1	Electromagnetic interference safety margin (EMISM)	62
6.3.2	Inter-element EMC and EMC with environment	63

prEN 16603-20:2021 (E)

6.3.3	Hazards of electromagnetic radiation.....	63
6.3.4	Spacecraft charging protection program	64
6.3.5	Intrasystem EMC	65
6.3.6	Radio frequency compatibility	65
6.3.7	Spacecraft DC magnetic field emission.....	65
6.3.8	Design provisions for EMC control.....	66
6.3.9	Detailed design requirements	66
6.4	Verification	66
6.4.1	Verification plan and report	66
6.4.2	Safety margin demonstration for critical or EED circuit	67
6.4.3	Detailed verification requirements.....	67
7	Radio frequency systems.....	68
7.1	Functional description	68
7.2	Antennas.....	69
7.2.1	General.....	69
7.2.2	Antenna structure	70
7.2.3	Antenna interfaces.....	75
7.2.4	Antennas Verification.....	76
7.3	RF Power	76
7.3.1	Overview.....	76
7.3.2	RF Power handling (thermal).....	77
7.3.3	Corona or Gas Discharge	77
7.3.4	Qualification for power handling and gas discharge	78
7.4	Passive intermodulation	78
7.4.1	Overview	78
7.4.2	General requirements	78
7.4.3	Identification of potentially critical intermodulation products	78
7.4.4	Verification.....	79
7.4.5	Qualification for passive intermodulation.....	79
7.5	Verification	79
8	Pre-tailoring matrix per space product and feature types.....	80
8.1	Introduction	80
8.2	Use of the inclusive and exclusive requirement categories.....	81
	Annex A (normative) EMC control plan - DRD	128
	Annex B (normative) Electromagnetic effects verification plan (EMEVP) - DRD	131

Annex C (normative) Electromagnetic effects verification report (EMEVR) - DRD	133
Annex D (normative) Battery user manual - DRD	135
Bibliography	136

Figures

Figure 5-1: Output impedance mask (Ohm)	50
Figure 5-2: Source and load impedance characterisation.....	56
Figure 5-3: Thevenin equivalent model	56
Figure 5-4: Norton equivalent model	57

Tables

Table 4-1: List of rigid and non-rigid materials.....	28
Table 5-1: Parameters for BOL worst and best case power calculations	42
Table 5-2: Additional power parameters for EOL worst and best case calculations....	42
Table 5-3: <<deleted, merged with new Table 8-3>>	60
Table 7-1: <<deleted, merged with new Table 8-3>>	76
Table 7-2: <<deleted, merged with new Table 8-3>>	79
Table 8-1: Definition of pre-tailoring matrix applicability statuses	83
Table 8-2: Definition of features for exclusive requirements	83
Table 8-3: Pre-tailoring matrix per "Space product and feature types".....	84

European Foreword

This document (prEN 16603-20:2021) has been prepared by Technical Committee CEN/CLC/TC 5 "Space", the secretariat of which is held by DIN (Germany).

This document (prEN 16603-20:2021) originates from ECSS-E-ST-20C Rev.2 DIR1.

This document is currently submitted to the Enquiry.

This document will supersede EN 16603-20:2020.

The main changes with respect to EN 16603-20:2020 are listed below:

- Clause 4.2.1.1 added due to addition of new clause 4.2.1.2
- Addition of requirements in new clause 4.2.1.2 "Reliable insulation"
- The addition of the new clause 4.2.1.2 made it necessary to add the new header 4.2.1.1 "General requirements" to separate the requirement from the former clause 4.2.1 "Failure containment and redundancy" from the new requirements for "Reliable insulation".
- Update to cover the aspects of "reliable insulation" also known as "double insulation"
- Addition of several terms in clause 3.2 related to the added subject of "Reliable insulation"

This document has been developed to cover specifically space systems and will therefore have precedence over any EN covering the same scope but with a wider do-main of applicability (e.g. : aerospace).

1

Scope

This Standard establishes the basic rules and general principles applicable to the electrical, electronic, electromagnetic, microwave and engineering processes. It specifies the tasks of these engineering processes and the basic performance and design requirements in each discipline.

It defines the terminology for the activities within these areas.

It defines the specific requirements for electrical subsystems and payloads, deriving from the system engineering requirements laid out in ECSS-E-ST-10 “Space engineering – System engineering general requirements”.

This standard may be tailored for the specific characteristic and constraints of a space project in conformance with ECSS-S-ST-00.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[oSIST prEN 16603-20:2021](https://standards.iteh.ai/catalog/standards/sist/0a1fd51b-e077-4a4e-997b-24a2d903be8f/osist-pren-16603-20-2021)

<https://standards.iteh.ai/catalog/standards/sist/0a1fd51b-e077-4a4e-997b-24a2d903be8f/osist-pren-16603-20-2021>

Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this ECSS Standard. For dated references, subsequent amendments to, or revision of any of these publications do not apply, However, parties to agreements based on this ECSS Standard are encouraged to investigate the possibility of applying the more recent editions of the normative documents indicated below. For undated references, the latest edition of the publication referred to applies.

EN reference	Reference in text	Title
EN 16601-00-01	ECSS-S-ST-00-01	ECSS system – Glossary of terms
EN 16603-10	ECSS-E-ST-10	Space engineering – System engineering general requirements
EN 16603-20-06	ECSS-E-ST-20-06	Space engineering – Spacecraft charging
EN 16603-20-07	ECSS-E-ST-20-07	Space engineering – Electromagnetic compatibility
EN 16603-20-08	ECSS-E-ST-20-08	Space engineering – Photovoltaic assemblies and components
EN 16603-20-20	ECSS-E-ST-20-20	Space engineering – Electrical design and interface requirements for power supply
EN 16603-33-11	ECSS-E-ST-33-11	Space engineering – Explosive systems and devices
EN 16603-50-05	ECSS-E-ST-50-05	Space engineering – Radio frequency and modulation
EN 16603-50-14	ECSS-E-ST-50-14	Space engineering – Spacecraft discrete interfaces
EN 16602-30-11	ECSS-Q-ST-30-11	Space product assurance – Derating – EEE components
EN 16602-40	ECSS-Q-ST-40	Space product assurance – Safety
EN 16602-70-12	ECSS-Q-ST-70-12	Space product assurance – Design rules for printed circuit boards
	IEEE 145-1993	Antenna terms
	Impedance Specifications for Stable DC Distributed Power Systems, EEE transactions on power electronics, Vol. 17, no. 2, March 2002	Impedance Specifications for Stable DC Distributed Power Systems, X. Feng, J. Liu, F.C. Lee, IEEE Transactions on power electronics, Vol. 17, no. 2, March 2002

Terms, definitions and abbreviated terms

3.1 Terms from other standards

- a. For the purpose of this Standard, the terms and definitions from ECSS-S-ST-00-01 apply.
- b. For the purpose of this Standard, the following terms and definitions from ECSS-E-ST-20-20 apply:
 1. latching current limiter (LCL)
 2. retriggerable latching current limiter (RLCL)

3.2 Terms specific to the present standard

3.2.1 antenna farm

ensemble of all antennas accommodated on the spacecraft and provides for all the transmission and reception of RF signals

3.2.2 antenna port

abstraction of the physical connection among the antenna and its feeding lines, realised by means of connectors or waveguide flanges

3.2.3 antenna RF chain

sequence of microwave components inserted between an antenna input port or a BFN output port and a corresponding individual radiating element

NOTE Examples of microwave components are: ortho-mode transducers, polarisers, transformers as well as filters.

3.2.4 antenna support structure

part of an antenna having no electrical function, which can however impact its electrical performances, either directly due to scattering or indirectly

NOTE Example of indirect effect is induced thermo-elastic deformations.

3.2.5 array antenna

antenna composed by a number of, possibly different, elements that radiate RF signals directly into free space operating in combination, such that all or a part of them radiate the same signals

3.2.6 array-fed reflector antenna

antenna composed by a feed array, which can include or not a beam forming network, and one or more optical elements like reflectors and lenses

3.2.7 battery bus

primary power bus directly connected to the battery

NOTE Battery bus is sometimes called unregulated bus (although the battery charge is regulated).

3.2.8 beam forming network (BFN)

wave-guiding structure composed a chain of microwave components and devices aimed at distributing the RF power injected at the input ports to a number of output ports; in a transmitting antenna the RF power injected from the transmitter is routed to the radiating elements, in a receiving antenna the RF power coming from the radiating elements is routed to the antenna ports connected to the receiver

NOTE Examples of microwave components and devices are lines, phase shifters, couplers, loads.

3.2.9 conducted emission (CE)

desired or undesired electromagnetic energy that is propagated along a conductor

3.2.10 critical line

[CONTEXT: reliable insulation] line that is part of a critical net

NOTE As an example, limited to a solar array, typically a **critical line** is a line that carries the current of a section downstream from the electrical node collecting the current from the different strings that constitute the section (but not at the node itself). However, in case a short between strings within a section can cause a catastrophic effect then correspondingly a string is considered as a critical line (this can be relevant, for example, for high voltage solar arrays for which there is limited heritage)."

3.2.11 critical net

[CONTEXT: reliable insulation] electrical net that if short circuited with another critical net or another conductor including satellite and launcher structure can cause critical effects

NOTE For "critical effects" see Table 4-1 of ECSS-Q-ST-30-02.

3.2.12 critical pressure

pressure at which corona or partial discharge can occur in an equipment

3.2.13 diffusivity

ability of a body to generate incoherent diffuse scattering due to local roughness, inhomogeneity or anisotropy when illuminated by RF waves

3.2.14 depth of discharge (DOD)

ampere-hour removed from a battery expressed as a percentage of the nameplate capacity

3.2.15 double insulation

see "reliable insulation"

3.2.16 electrical bonding

process of connecting conductive parts to each other so that a low impedance path is established for grounding and shielding purposes

3.2.17 electromagnetic compatibility (EMC)

ability of equipment or an element to function satisfactorily in its electromagnetic environment without introducing intolerable electromagnetic disturbances to anything in that environment

3.2.18 electromagnetic compatibility control

set of techniques to effectively regulate the electromagnetic interference environment or susceptibility of individual space system components or both

NOTE They include, among others, the design, placement of components, shielding, and employment of rejection filters.

3.2.19 electromagnetic interference (EMI)

undesired electrical phenomenon that is created by, or adversely affects any device whose normal functioning is predicated upon the utilization of electrical phenomena

NOTE It is characterized by the manifestation of degradation of the performance of an equipment, transmission channel, or element caused by an electromagnetic disturbance.

3.2.20 electromagnetic interference safety margin (EMISM)

ratio between the susceptibility threshold and the interference present on a test point

3.2.21 emission

electromagnetic energy propagated by radiation or conduction

3.2.22 energy balance

situation in which the spacecraft energy budget is positive when elaborated over a considered period of time

NOTE 1 Energy budget is generation minus consumption and losses.

NOTE 2 The considered period of time can be one orbit, several orbits or any relevant mission period.

3.2.23 energy reserve

energy that remains available from the energy storage assembly at the worst-case, most depleted, point of nominal operations

NOTE It is important that the energy reserve is sufficient to permit reaching a safe operating mode upon occurrence of an anomaly

3.2.24 essential function

function without which the spacecraft cannot be recovered following any conceivable on-board or ground-based failure

NOTE Examples of unrecoverable spacecraft is when spacecraft cannot be commanded, or permanently losses attitude and control, or the energy balance is no longer ensured, or the spacecraft consumables (e.g. hydrazine or Xenon) are depleted to such an extent that more than 10% of its lifetime is affected, or the safety of the crew is threatened.

3.2.25 faulty signal

signal generated by a circuit, appearing at its interface to another circuit, going out of its nominal range because of a failure

3.2.26 foldback current limiter (FCL)

non latching current-limiting function where the current limit decreases with the output voltage

NOTE This function is used for power distribution and protection typically for essential loads.

3.2.27 fully regulated bus

bus providing power during sunlight and eclipse periods with a regulated voltage

3.2.28 grounding

process of establishing intentional electrical conductive paths between an electrical circuit reference or a conductive part and equipment chassis or space vehicle structure

NOTE grounding is typically performed for safety, functionality, signal integrity, EMI control or charge bleeding purpose.

3.2.29 high Priority telecommand (HPC)

command originated from ground and issued by the telecommand decoder for essential spacecraft functions without main on board software intervention

3.2.30 high voltage

AC or DC voltage at which partial discharges, corona, arcing or high electrical fields can occur

3.2.31 insulation

separation of elements either by material or by a distance

NOTE Etymologically, insulation is the act of protecting something with a material that prevents heat, sound, electricity, etc. from passing through. To insulate will then correspond to the action to protect by adding a material, an insulation (materials or device used for this protection). But in this document, to avoid heavy requirement formulations, the term 'insulation' (and their derivatives) includes both notions of separation of elements either by a material or by a distance.

3.2.32 invariable gap

physical distance among electrically conductive elements respecting the specified minimum limits independent from the stresses applied to the unit or part of the unit

NOTE Changes of the gap can result from effects of mechanical, thermomechanical or other nature, applied to the unit or part of the unit.

NOTE Stresses include the impacts of AIT operations, environmental tests, ageing and the use of insulation materials.

3.2.33 isolation

separation of elements put far from each other, with the notion of distance

NOTE To isolate is the action to separate by adding distance and to be isolated means protected by a distance.

3.2.34 lens antenna

antenna composed by a number of RF lenses and reflecting surfaces illuminated by a primary source, the feed

3.2.35 lightning indirect effects

electrical transients induced by lightning in electrical circuits due to coupling of electromagnetic fields