

SLOVENSKI STANDARD SIST EN 16603-20:2024

01-februar-2024

Vesoljska tehnika - Električna in elektronska

Space engineering - Electrical and electronic

Raumfahrttechnik - Elektrik und Elektronik

Ingénierie spatiale - Électrique et électronique

Ta slovenski standard je istoveten z: EN 16603-20:2023

ICS:

49.060 ds itch a Letalska in vesoljska 0a i fd5 i b Aerospace electric 2d903be8f/sist-en-16603-20-2024

električna oprema in sistemi equipment and systems

49.140 Vesoljski sistemi in operacije Space systems and

operations

SIST EN 16603-20:2024 sl,en,fr

iTeh Standards (https://standards.iteh.ai) Document Preview

SIST EN 16603-20:2024

https://standards.iteh.ai/catalog/standards/sist/0a1fd51b-e077-4a4e-997b-24a2d903be8f/sist-en-16603-20-2024

EUROPEAN STANDARD

EN 16603-20

NORME EUROPÉENNE

EUROPÄISCHE NORM

November 2023

ICS 49.140

Supersedes EN 16603-20:2020

English version

Space engineering - Electrical and electronic

Ingénierie spatiale - Électrique et électronique

Raumfahrttechnik - Elektrik und Elektronik

This European Standard was approved by CEN on 20 November 2023.

CEN and CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN and CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN and CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN and CENELEC members are the national standards bodies and national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and United Kingdom.





CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Table of contents

European Foreword6			6	
1 Scope7				
2 Normative references8				
3 Term	s, defin	itions and abbreviated terms	9	
3.1	Terms fi	om other standards	9	
3.2	Terms specific to the present standard			
3.3	Abbreviated terms16			
3.4	Nomeno	slature1	18	
4 Gene	ral requ	iirements1	9	
4.1	Interface	e requirements1	19	
	4.1.1	Overview		
	4.1.2	Signals interfaces	19	
	4.1.3	Commands1		
	4.1.4	Telemetry Document Preview 2	21	
4.2	Design.	SIST EN 16603-2022024	21	
	4.2.1 ai/	Failure containment and redundancy	21	
	4.2.2	Data processing	30	
	4.2.3	Electrical connectors	32	
	4.2.4	Testing	33	
	4.2.5	Mechanical: Wired electrical connections	34	
	4.2.6	Miscellaneous	34	
4.3	Verificat	ion3	35	
	4.3.1	Provisions	35	
	4.3.2	Documentation	35	
5 Elect	rical po	wer3	36	
5.1	Function	nal description3	36	
5.2	Power s	ubsystem and budgets3	36	
	5.2.1	General3	36	
	5.2.2	Provisions	36	

EN 16603-20:2023 (E)

	5.3	Failure containment and redundancy		37
	5.4	Electric	al power interfaces	38
	5.5	Power g	generation	39
		5.5.1	Solar cell, coverglass, SCA and PVA qualification	39
		5.5.2	Solar array specification and design	39
		5.5.3	Solar array power computation	42
		5.5.4	Solar array drive mechanisms	44
	5.6	Electrod	chemical Energy Storage	44
		5.6.1	Applicability	44
		5.6.2	Batteries	45
		5.6.3	Battery cell	47
		5.6.4	Battery use and storage	47
		5.6.5	Battery safety	48
	5.7	Power of	conditioning and control	49
		5.7.1	Applicability	49
		5.7.2	Spacecraft bus	49
		5.7.3	Battery Charge and Discharge Management	53
		5.7.4	Bus under-voltage or over-voltage	
		5.7.5	Power converters and regulators	54
		5.7.6	Payload interaction	55
	5.8	Power of	distribution and protection	
		5.8.1	General Bocument Preview	56
		5.8.2	Harness	59
	5.9	Safety	0005-20.2024 cutalog/standards/sist/0u1fd51b-c077-4a4c-997b-24u2d903bc8f/sis	60 -16603-20-2024
	5.10	High vo	ltage engineering	60
	5.11	Verifica	tion	61
		5.11.1	Provisions	61
		5.11.2	< <deleted>></deleted>	61
6	Elect	romagr	netic compatibility (EMC)	62
	6.1	•	ew	
	6.2			
		6.2.1	Overall EMC programme	
		6.2.2	EMC control plan	
		6.2.3	Electromagnetic compatibility advisory board (EMCAB)	
	6.3	System	level	
		6.3.1	Electromagnetic interference safety margin (EMISM)	
		6.3.2	Inter-element EMC and EMC with environment	

EN 16603-20:2023 (E)

	6.3.3	Hazards of electromagnetic radiation	64
	6.3.4	Spacecraft charging protection program	65
	6.3.5	Intrasystem EMC	66
	6.3.6	Radio frequency compatibility	66
	6.3.7	Spacecraft DC magnetic field emission	66
	6.3.8	Design provisions for EMC control	67
	6.3.9	Detailed design requirements	67
6.4	Verific	ation	67
	6.4.1	Verification plan and report	67
	6.4.2	Safety margin demonstration for critical or EED circuit	68
	6.4.3	Detailed verification requirements	68
7 Radi	io frequ	iency systems	69
7.1	Function	onal description	69
7.2	Antenr	nas	70
	7.2.1	General	70
	7.2.2	Antenna structure	71
	7.2.3	Antenna interfaces	76
	7.2.4	Antennas Verification	77
7.3	RF Po	wer	77
	7.3.1	Overview	77
	7.3.2	RF Power handling (thermal)	78
	7.3.3	Corona or Gas Discharge	
	7.3.4	Qualification for power handling and gas discharge	
sta7.41	Passiv	e intermodulation sist/0a1fd51b-e077-4a4e-997b-24a2d903be8f	sist- 79 -16603-20-2024
	7.4.1	Overview	79
	7.4.2	General requirements	79
	7.4.3	Identification of potentially critical intermodulation products	79
	7.4.4	Verification	80
	7.4.5	Qualification for passive intermodulation	80
7.5	Verifica	ation	80
8 Pre-	tailorin	g matrix per space product and feature types	81
8.1	Introdu	81	
8.2	Use of	the inclusive and exclusive requirement categories	82
Annex	A (nor	mative) EMC control plan - DRD	125
Annex	B (nor	mative) Electromagnetic effects verification plan (EME\	/P) -
DRI)		128

Annex C (normative) Electromagnetic effects verification report (EMEV DRD	-
Annex D (normative) Battery user manual - DRD	133
Bibliography	.135
Figures	
Figure 5-1: Output impedance mask (Ohm)	51
Figure 5-2: Source and load impedance characterisation	57
Figure 5-3: Thevenin equivalent model	58
Figure 5-4: Norton equivalent model	58
Tables	
Table 4-1: List of rigid and non-rigid materials	28
Table 5-1: Parameters for BOL worst and best case power calculations	43
Table 5-2: Additional power parameters for EOL worst and best case calculations.	44
Table 8-1: Definition of pre-tailoring matrix applicability statuses	84
Table 8-2: Definition of features for exclusive requirements	84
Table 8-3: Pre-tailoring matrix per "Space product and feature types"	85

SIST EN 16603-20:2024

https://standards.iteh.ai/catalog/standards/sist/0a1fd51b-e077-4a4e-997b-24a2d903be8f/sist-en-16603-20-202

European Foreword

This document (EN 16603-20:2023) has been prepared by Technical Committee CEN-CENELEC/TC 5 "Space", the secretariat of which is held by DIN.

This standard (EN 16603-20:2023) originates from ECSS-E-ST-20C Rev.2.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by May 2024, and conflicting national standards shall be withdrawn at the latest by May 2024.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 16603-20:2020.

The main changes with respect to EN 16603-20:2020 are listed below:

- clause 4.2.1.1 added due to addition of new clause 4.2.1.2;
- addition of requirements in new clause 4.2.1.2 "Reliable insulation";
- the addition of the new clause 4.2.1.2 made it necessary to add the new header 4.2.1.1 "General requirements" to separate the requirement from the former clause 4.2.1 "Failure containment and redundancy" from the new requirements for "Reliable insulation";
- update to cover the aspects of "reliable insulation" also known as "double insulation";
- addition of several terms in clause 3.2 related to the added subject of https://standards.iteh.ai/catalog/stan "Reliable insulation". 077-4a4e-997b-24a2d903be8l/sist-en-1660

This document has been prepared under a standardization request given to CEN by the European Commission and the European Free Trade Association.

This document has been developed to cover specifically space systems and has therefore precedence over any EN covering the same scope but with a wider domain of applicability (e.g. : aerospace).

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

1 Scope

This Standard establishes the basic rules and general principles applicable to the electrical, electronic, electromagnetic, microwave and engineering processes. It specifies the tasks of these engineering processes and the basic performance and design requirements in each discipline.

It defines the terminology for the activities within these areas.

It defines the specific requirements for electrical subsystems and payloads, deriving from the system engineering requirements laid out in ECSS-E-ST-10 "Space engineering – System engineering general requirements".

This standard may be tailored for the specific characteristics and constrains of a space project in conformance with ECSS-S-ST-00.

iTeh Standards (https://standards.iteh.ai) Document Preview

SIST EN 16603-20:2024

https://standards.iteh.ai/catalog/standards/sist/0a1fd51b-e077-4a4e-997b-24a2d903be8f/sist-en-16603-20-202

2

Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this ECSS Standard. For dated references, subsequent amendments to, or revision of any of these publications do not apply. However, parties to agreements based on this ECSS Standard are encouraged to investigate the possibility of applying the more recent editions of the normative documents indicated below. For undated references, the latest edition of the publication referred to applies.

EN reference	Reference in text	Title
EN 16601-00-01	ECSS-S-ST-00-01	ECSS system – Glossary of terms
EN 16603-10	ECSS-E-ST-10	Space engineering – System engineering general requirements
EN 16603-20-06	ECSS-E-ST-20-06	Space engineering – Spacecraft charging
EN 16603-20-07	ECSS-E-ST-20-07	Space engineering – Electromagnetic compatibility
EN 16603-20-08	ECSS-E-ST-20-08 C1 Sta	Space engineering - Photovoltaic assemblies and components
EN 16603-20-20	ECSS-E-ST-20-20	Space engineering - Electrical design and interface requirements for power supply
EN 16603-33-11	ECSS-E-ST-33-11	Space engineering – Explosive systems and devices
EN 16603-50-05	ECSS-E-ST-50-05	Space engineering – Radio frequency and modulation
EN 16603-50-14	ECSS-E-ST-50-14	Space engineering – Spacecraft discrete interfaces
EN 16602-30-02	ECSS-Q-ST-30-02	Space product assurance – Failure modes, effects (and criticality) analysis (FMEA/FMECA)
EN 16602-30-11	ECSS-Q-ST-30-11	Space product assurance – Derating – EEE components
EN 16602-40	ECSS-Q-ST-40	Space product assurance – Safety
EN 16602-70-12	ECSS-Q-ST-70-12	Space product assurance – Design rules for printed circuit boards
	IEEE 145-1993	Antenna Terms
	Impedance Specifications for Stable DC Distributed Power Systems, EEE transactions on power electronics, Vol. 17, no. 2, March 2002	Impedance Specifications for Stable DC Distributed Power Systems, X. Feng, J. Liu, F.C. Lee, IEEE Transactions on power electronics, Vol. 17, no. 2, March 2002

3

Terms, definitions and abbreviated terms

3.1 Terms from other standards

- a. For the purpose of this Standard, the terms and definitions from ECSS-S-ST-00-01 apply.
- b. For the purpose of this Standard, the following terms and definitions from ECSS-E-ST-20-20 apply:
 - 1. latching current limiter (LCL);
 - 2. retriggerable latching current limiter (RLCL).

3.2 Terms specific to the present standard

3.2.1 antenna farm

ensemble of all antennas accommodated on the spacecraft and provides for all the transmission and reception of RF signals

3.2.2 antenna port

abstraction of the physical connection among the antenna and its feeding lines, realised by means of connectors or waveguide flanges

3.2.3 antenna RF chain

sequence of microwave components inserted between an antenna input port or a BFN output port and a corresponding individual radiating element

NOTE Examples of microwave components are: orthomode transducers, polarisers, transformers as well as filters.

3.2.4 antenna support structure

part of an antenna having no electrical function, which can however impact its electrical performances, either directly due to scattering or indirectly

NOTE Example of indirect effect is induced thermoelastic deformations.

3.2.5 array antenna

antenna composed by a number of, possibly different, elements that radiate RF signals directly into free space operating in combination, such that all or a part of them radiate the same signals

3.2.6 array-fed reflector antenna

antenna composed by a feed array, which can include or not a beam forming network, and one or more optical elements like reflectors and lenses

3.2.7 battery bus

primary power bus directly connected to the battery

NOTE Battery bus is sometimes called unregulated bus (although the battery charge is regulated).

3.2.8 beam forming network (BFN)

wave-guiding structure composed a chain of microwave components and devices aimed at distributing the RF power injected at the input ports to a number of output ports; in a transmitting antenna the RF power injected from the transmitter is routed to the radiating elements, in a receiving antenna the RF power coming from the radiating elements is routed to the antenna ports connected to the receiver

NOTE Examples of microwave components and devices are lines, phase shifters, couplers, loads.

3.2.9 conducted emission (CE)

desired or undesired electromagnetic energy that is propagated along a conductor

3.2.10 i Teh Standards

[CONTEXT: reliable insulation] line that is part of a critical net

NOTE As an example, limited to a solar array, typically

a critical line is a line that carries the current of a section downstream from the electrical node collecting the current from the different strings that constitute the section. However, in case a short between strings within a section leads to a failure propagation, then correspondingly a string is considered as a critical line.

3.2.11 critical net

[CONTEXT: reliable insulation] electrical net that if short circuited with another electrical net or another conductor including satellite and launcher structure can cause critical effects

NOTE For "critical effects" see Table 4-1 of ECSS-Q-ST-30-02.

3.2.12 critical pressure

pressure at which corona or partial discharge can occur in an equipment

3.2.13 diffusivity

ability of a body to generate incoherent diffuse scattering due to local roughness, inhomogeneity or anysotropy when illuminated by RF waves

3.2.14 depth of discharge (DOD)

ampere-hour removed from a battery expressed as a percentage of the nameplate capacity

3.2.15 double insulation

see "reliable insulation"

3.2.16 electrical bonding

process of connecting conductive parts to each other so that a low impedance path is established for grounding and shielding purposes

3.2.17 electromagnetic compatibility (EMC)

ability of equipment or an element to function satisfactorily in its electromagnetic environment without introducing intolerable electromagnetic disturbances to anything in that environment

3.2.18 electromagnetic compatibility control

set of techniques to effectively regulate the electromagnetic interference environment or susceptibility of individual space system components or both

NOTE They include, among others, the design, placement of components, shielding, and employment of rejection filters.

3.2.19 electromagnetic interference (EMI)

undesired electrical phenomenon that is created by, or adversely affects any device whose normal functioning is predicated upon the utilization of electrical phenomena

NOTE It is characterized by the manifestation of degradation of the performance of an equipment, transmission channel, or element caused by an electromagnetic disturbance.

3.2.20 electromagnetic interference safety margin (EMISM)

ratio between the susceptibility threshold and the interference present on a test point

3.2.21 emission

electromagnetic energy propagated by radiation or conduction

3.2.22 energy balance

situation in which the spacecraft energy budget is positive when elaborated over a considered period of time

NOTE 1 Energy budget is generation minus consumption and losses.

NOTE 2 The considered period of time can be one orbit, several orbits or any relevant mission period.

EN 16603-20:2023 (E)

3.2.23 energy reserve

energy that remains available from the energy storage assembly at the worstcase, most depleted, point of nominal operations

NOTE

It is important that the energy reserve is sufficient to permit reaching a safe operating mode upon occurrence of an anomaly.

3.2.24 essential function

function without which the spacecraft cannot be recovered following any conceivable on-board or ground-based failure

NOTE

Examples of unrecoverable spacecraft is when spacecraft commanded, cannot be permanently losses attitude and control, or the energy balance is no longer ensured, or the spacecraft consumables (e.g. hydrazine or Xenon) are depleted to such an extent that more than 10 % of its lifetime is affected, or the safety of the crew is threatened.

3.2.25 faulty signal

signal generated by a circuit, appearing at its interface to another circuit, going out of its nominal range because of a failure

3.2.26 foldback current limiter (FCL)

non latching current-limiting function where the current limit decreases with the output voltage

NOTE This function is used for power distribution and protection typically for essential loads.

3.2.27 fully regulated bus

bus providing power during sunlight and eclipse periods with a regulated voltage

3.2.28 grounding

process of establishing intentional electrical conductive paths between an electrical circuit reference or a conductive part and equipment chassis or space vehicle structure

NOTE

Grounding is typically performed for safety, functionality, signal integrity, EMI control or charge bleeding purpose.

3.2.29 high Priority telecommand (HPC)

command originated from ground and issued by the telecommand decoder for essential spacecraft functions without main on board software intervention